

## Xenon Electronics Limited

Workshop 719, Workdwide Industrial Centre, 43-47 Shan Mei Street, Fo Tan, Hong Kong Tel: 852-35682854 Email: <a href="mailto:internal@xenon-tech.com">internal@xenon-tech.com</a>

## Modular Approval Request Letter

Date: 16 July, 2019

Dear Application Examiner,

[Xenon Electronics Limited], FCC ID: 2ATBKDSMPSDR would like to have your authorization as a modular approval. The requirements of Public Notice DA00-1407 have been met and shown on the following statements.

Items to be covered	Answer from applicant
The modular transmitter must have its own RF shielding.	The RF portions of the module
1. The modular transmitter must have its own the smilling.	are completely contained within
	a metal shielding can. The
	module does not depend on any
	other shielding.
2. The modular transmitter must have buffered modulation/data	All inputs to the module are
inputs (if such inputs are provided) to ensure that the module will	buffered through logic or
comply with Part 15 requirements under conditions of excessive data	microprocessor inputs.
rates or over-modulation.	microprocessor inputs.
rates of over-modulation.	
The modular transmitter must have its own power supply	The modular transmitter has its
regulation.	own power supply regulation.
Togulation.	own power supply regulation.
4. The modular transmitter must comply with the antenna	The module and antenna design
requirements of Section 15.203 and 15.204(c). The antenna must	is not user serviceable. It utilizes
either be permanently attached or employ a "unique" antenna coupler	non-standard micro-coaxial
(at all connections between the module and the antenna, including	connectors and antennas with
the cable).	approximate gain of 1.5 dBi.
	approximate gain or 110 azii
5. The modular transmitter must be tested in a stand-alone	The EUT was tested stand-alone
configuration, i.e., the module must not be inside another device	with a test-jig. Please refer to
during testing. This is intended to demonstrate that the module is	setup configuration photos.
capable of complying with Part 15 emission limits regardless of the	
device into which it is eventually installed.	
, in the second of the second	
6. The modular transmitter must be labeled with its own FCC ID	The FCC ID label format is
number, and, if the FCC ID is not visible when the module is	included in the filing. The product
installed inside another device, then the outside of the device into	will always be inside another
which the module is installed must also display a label referring to	enclosure during actual use. A
the enclosed module. This exterior label can use wording such as	label will be placed on the
the following: "Contains Transmitter Module FCC ID: XYZMODEL1"	outside of the product if the FCC
or "Contains FCC ID: XYZMODEL1." Any similar wording that	ID is not visible.
expresses the same meaning may be used. The Grantee may	
either provide such a label, an example of which must be included	

-		
	in the application for equipment authorization, or, must provide adequate instructions along with the module which explain this requirement. In the latter case, a copy of these instructions must be included in the application for equipment authorization.	
=	7. The modular transmitter must comply with any specific rule or operating requirements applicable to the transmitter and the manufacturer must provide adequate instructions along with the module to explain any such requirements. A copy of these instructions must be included in the application for equipment authorization. For example, there are very strict operational and timing requirements that must be met before a transmitter is authorized for operation under Section 15.231. For instance, data transmission is prohibited, except for operation under Section 15.231(e), in which case there are separate field strength level and timing requirements. Compliance with these requirements must be assured.	The module complies with all specific rules applicable to the transmitter including all the conditions provided in the integration instructions by the grantee. Please refer to report and user manual.
	8. The modular transmitter must comply with any applicable RF exposure requirements. For example, FCC Rules in Sections 2.1091, 2.1093 and specific Sections of Part 15, including 15.319(i), 15.407(f), 15.253(f) and 15.255(g), require that Unlicensed PCS, UNII and millimeter wave devices perform routine environmental evaluation for RF Exposure to demonstrate compliance. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF Exposure compliance in accordance with Section 15.247(b)(4). Modular transmitters approved under other Sections of Part 15, when necessary, may also need to address certain RF Exposure concerns, typically by providing specific installation and operating instructions for users, installers and other interested parties to ensure compliance.	The transmitter meets the requirements.

