

ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No. : OT-195-RWD-010

AGR No. : A194A-177

Applicant : UbeesLab

Address : 14F Saman Bldg., 520, Teheran-ro, Gangnam-gu, Seoul, Republic of Korea

Manufacturer : FALINUX

Address : B-1001 Indeokwon-IT-Valley, 40, Imi-ro, Uiwang-si, Gyeonggi-do, Republic of Korea

Type of Equipment : SOCCERBEE POD

FCC ID. : 2ATBU-UBLAB01

Model Name : UBLAB01

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : April 17, 2019

Date of issue : May 09, 2019

SUMMARY

The equipment complies with the regulation; *FCC PART 15 SUBPART C Section 15.247*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by:



Ha-Ram Lee / Assistant Manager
ONETECH Corp.

Approved by:



Jae-Ho Lee / Chief Engineer
ONETECH Corp.

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. RF EXPOSURE EVALUATION	6
4.1 STANDARD APPLICABLE	6
4.2 EUT DESCRIPTION.....	6
4.3 TEST RESULT OF SAR EXCLUSION FOR PORTABLE DEVICES	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-195-RWD-010	May 09, 2019	Initial Issue	All

1. VERIFICATION OF COMPLIANCE

Applicant : UbeesLab
Address : 14F Saman Bldg., 520, Teheran-ro, Gangnam-gu, Seoul, Republic of Korea
Contact Person : Joonhyup, Seo/Director
Telephone No. : +82-2-511-5461
FCC ID : 2ATBU-UBLAB01
Model Name : UBLAB01
Serial Number : N/A
Date : May 09, 2019

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
KIND OF EQUIPMENT	SOCCERBEE POD
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
Modifications on the Equipment to Achieve Compliance	None
Final Test was Conducted On	3 m, Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The UbeesLab, Model UBLAB01 (referred to as the EUT in this report) is a SOCCERBEE POD. The product specification described herein was obtained from product data sheet or user's manual.

Device Type	SOCCERBEE POD
Operating Frequency	2 402 MHz ~ 2 480 MHz
RF Output Power	-4.87 dBm
Number of Channel	40 Channel
Modulation Type	GFSK
Antenna Type	PCB Antenna
Antenna Gain	0.006 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	32 MHz, 32.768 kHz
Rated Supply Voltage	DC 3.7 V

Note: GPS / GNSS is Rx only. Therefore, GPS / GNSS does not affect BLE Tx.

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. RF Exposure Evaluation

4.1 Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to the procedure, KDB 447498 D01, the standalone SAR test exclusion threshold is

$$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}] < 3$$

4.2 EUT Description

Kind of EUT	SOC CERBEE POD
Operating Frequency Band	☐ Wireless Microphone: 494.000 MHz ~ 501.000 MHz and 498.200 MHz ~ 505.200 MHz ☐ WLAN: 2 412 MHz ~ 2 462 MHz ☐ WLAN: 5 180 MHz ~ 5 240 MHz ☐ WLAN: 5 745 MHz ~ 5 825 MHz ☐ Bluetooth: 2 402 MHz ~ 2 480 MHz ☒ Bluetooth BLE: 2 402 MHz ~ 2 480 MHz
MAX. RF OUTPUT POWER	-4.87 dBm
Antenna Gain	0.006 dBi
Exposure Evaluation Applied	☐ MPE ☐ SAR ☒ N/A

4.3 Test Result of SAR Exclusion for Portable Devices

$[(\text{Max. Power of channel, including tune-up tolerance, mW})/(\text{Min. test separation distance, mm})] \times [\sqrt{f(\text{GHz})}]$

$= (0.37/5) \times \sqrt{2.480} = 0.12 < 3$

Conclusion: The SAR test exclusion threshold is less than 3, so the device meets the RF Exposure Requirement and excluded SAR Test.

Frequency (MHz)	Target Power W/tolerance (dBm)	Max tune up power (dBm)	Max tune up power (mW)	Separation distance (mm)	RF exposure
2 480	-4.87 ± 0.5	-4.37	0.37	5	0.12



Tested by: Yu-Seog Sim / Assistant Manager