



TEST REPORT

FCC ID:2ATCA-L10KPB

Applicant: ALOGIC Corporation Pty Ltd.
Address: Level 40,140 William Street, Melbourne VIC 3000
Manufacturer: ALOGIC Corporation Pty Ltd.
Address: Level 40,140 William Street, Melbourne VIC 3000
EUT: ALOGIC Lift 4 in 1 Wireless Charging 10000mAh Power Bank
Trade Mark: ALOGIC
Model Number: L10KPBWH, L10KPBXX (XX represents colors)
Date of Receipt: Oct. 25, 2023
Test Date: Oct. 25, 2023 - Nov. 01, 2023
Date of Report: Nov. 01, 2023
Prepared By: Shenzhen DL Testing Technology Co., Ltd.
Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone, Baolong Street, Longgang District, Shenzhen, Guangdong, China
Applicable Standards: FCC PART 15 Subpart C
ANSI C63.10:2013
Test Result: Pass
Report Number: DL-20231101058E

Prepared (Engineer): Alisa Song

Reviewer (Supervisor): Jack Bu

Approved (Manager): Jade Yang



This test report is based on a single evaluation of one sample of above mentioned products. It is not permitted to be duplicated in extracts without written approval of Shenzhen DL Testing Technology Co., Ltd.



TABLE OF CONTENT

	Page
Test Report Declaration	
1. VERSION	3
2. TEST SUMMARY	3
3. GENERAL INFORMATION	4
4. TEST INSTRUMENT USED.....	6
5. CONDUCTED EMISSION TEST.....	7
6. RADIATION EMISSION TEST.....	11
7. BANDWIDTH TEST	16
8. SETUP PHOTOGRAPHS	18
9. EUT PHOTOGRAPHS	19

**1. VERSION**

Version No.	Date	Description
00	Nov. 01, 2023	Original

2. TEST SUMMARY

EMC Emission			
Test Item	Section in CFR 47	Result	Remark
AC Power Line Conducted Emission	15.207	PASS	
Spurious Emission	15.209(a)(f)	PASS	
20dB Bandwidth	15.215	PASS	
Antenna requirement	15.203	PASS	

NOTE:

(1) "N/A" denotes test is not applicable in this Test Report

(2) Test Facility: Shenzhen DL Testing Technology Co., Ltd.

Address: 101-201, Building C, Shuanghuan, No.8, Baoqing Road, Baolong Industrial Zone,
Baolong Street, Longgang District, Shenzhen, Guangdong, China



3. GENERAL INFORMATION

3.1 Description of Device (EUT)


Product Name: ALOGIC Lift 4 in 1 Wireless Charging 10000mAh Power Bank
 Trade Mark: ALOGIC
 Model No.: L10KPBWH
 L10KPBXX (XX represents colors)
 Model Difference: The product's different for model number and appearance color.
 Serial No.: N/A
 Hardware version: V1.2
 Software version: 8D15
 Operation Frequency: 115kHz ~ 205kHz, 325kHz
 Modulation type: MSK
 Antenna Type: Inductive loop coil Antenna
 Antenna gain: 0dBi
 Battery Capacity: 3.8V, 10000mAh, 38Wh
 Input:USB-C: DC5V---3A DC9V---2A
 Power supply: Output: USB-C: DC5V---3A DC9V---2A DC12V---1.5A
 USB-A:DC5V---3A DC9V---2A DC12V---1.5A
 Wireless charger: 5W, 7.5W, 10W, 15W

3.2 Tested System Details


None.

3.3 Block Diagram of Test Set-up

AC Mode



DC Mode





3.4 Test Mode Description

- Mode1. Type-C Input+Wireless charger Output Mode(Watch+ Mobile phone)(Full Load)
- Mode2. Type-C Input+Wireless charger Output Mode(Watch+ Mobile phone) (Half Load)
- Mode3. Type-C Input+Wireless charger Output Mode(Watch+ Mobile phone) (No Load)
- Mode4. Type-C Output+Wireless charger Output Mode(Watch+ Mobile phone) (Full Load)
- Mode5. Type-C Output+Wireless charger Output Mode(Watch+ Mobile phone) (Half Load)
- Mode6. Type-C Output+Wireless charger Output Mode(Watch+ Mobile phone) (No Load)
- Mode7. USB-A Output+Wireless charger Output Mode(Watch+ Mobile phone) (Full Load)
- Mode8. USB-A Output+Wireless charger Output Mode(Watch+ Mobile phone) (Half Load)
- Mode9. USB-A Output+Wireless charger Output Mode(Watch+ Mobile phone) (No Load)
- Mode10. Wireless charger Output Mode(Watch+ Mobile phone) (Full Load)
- Mode11. Wireless charger Output Mode(Watch+ Mobile phone) (Half Load)
- Mode12. Wireless charger Output Mode(Watch+ Mobile phone) (No Load)

Note: 1. We have evaluated 1%, 50% and 99% battery level charging mode, and the worst mode (99%) is showed in this report.

2. All modes have been tested, and the report only shows the results of the worst mode1 and mode10.

3: When the product was in wireless charging mode, we tested charging both the phone and watch simultaneously and separately. The worst mode was simultaneous charging and the data was recorded in the report.

4: No load condition = Phone(or watch) battery 99% Full load condition = Phone(or watch) battery 1%
Half load condition = Phone(or watch) battery 1%

3.5 Test Auxiliary Equipment

Adapter (Provide by test lab):

Manufacturer: XIAOMI

Model: AD65G

I/P: AC 100-240V 50/60Hz

O/P: DC 5V/3A, DC 9V/3A, DC 10V/5A, DC 12V/3A,

DC 15V/3A, DC 20V/3.25A

Mobile phone (Provide by test lab):

Manufacturer: SAMSUNG

Model: Galaxy S21 5G

Watch (Provide by test lab):

Manufacturer: Apple

Model: Watch Series 6

3.6 Test Uncertainty

Conducted Emission Uncertainty(150kHz-30MHz)	:	±2.56dB
20dB Bandwidth	:	±0.5kHz
Radiated Emission Uncertainty(9kHz-1GHz)	:	±3.24dB



4. TEST INSTRUMENT USED

For Conducted Emission Test (843 Shielded Room)

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
843 Shielded Room	ChengYu	843 Room	843	Sep. 20, 2022	Sep. 19, 2025
EMI Receiver	R&S	ESR	101421	Nov. 05, 2022	Nov. 04, 2023
LISN	R&S	ENV216	102417	Nov. 05, 2022	Nov. 04, 2023
Clamp	COM-POWER	CLA-050	431071	Nov. 05, 2022	Nov. 04, 2023
3-Loop Antenna	DAZE	ZN30401	13021	Nov. 05, 2022	Nov. 04, 2023
ISN T8	Schwarzbeck	NTFM 8158	101135	Nov. 05, 2022	Nov. 04, 2023
ISN T5	Schwarzbeck	NTFM 8158	101136	Nov. 05, 2022	Nov. 04, 2023
843 Cable 1#	ChengYu	CE Cable	001	Nov. 05, 2022	Nov. 04, 2023
843 Cable 1#	ChengYu	CE Cable	002	Nov. 05, 2022	Nov. 04, 2023


For Radiated Emission Test (966 chamber)

Equipment	Manufacturer	Model	Serial	Last Cal.	Next Cal.
966 Chamber	ChengYu	966 Room	966	Sep. 20, 2022	Sep. 19, 2025
Spectrum Analyzer	Agilent	E4408B	MY50140780	Nov. 05, 2022	Nov. 04, 2023
EMI Receiver	R&S	ESRP7	101393	Nov. 05, 2022	Nov. 04, 2023
Amplifier	Schwarzbeck	BBV9743B	00153	Nov. 05, 2022	Nov. 04, 2023
Amplifier	EMEC	EM01G8GA	00270	Nov. 05, 2022	Nov. 04, 2023
Broadband Trilog Antenna	Schwarzbeck	VULB9162	00306	Nov. 05, 2022	Nov. 04, 2023
Horn Antenna	Schwarzbeck	BBHA9120D	02139	Nov. 05, 2022	Nov. 04, 2023
Loop Antenna	ZHINAN	ZN30900A	/	Nov. 05, 2022	Nov. 04, 2023
966 Cable 1#	ChengYu	966	004	Nov. 05, 2022	Nov. 04, 2023
966 Cable 2#	ChengYu	966	003	Nov. 05, 2022	Nov. 04, 2023

5. CONDUCTED EMISSION TEST

5.1 Block Diagram of Test Setup

For Mains Terminals Test



5.2 Test Standard and Limit

FCC Part 15 Subpart C

Frequency MHz	Limits dB(μ V)	
	Quasi-peak Level	Average Level
0.15~0.50	66 ~ 56*	55 ~ 46*
0.50~5.00	56	46
5.00~30.00	60	50

Notes: 1. *Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

5.3 EUT Configuration on Test

The following equipment's are installed on conducted emission test to meet FCC Part 15 Subpart C requirement and operating in a manner which tends to maximize its emission characteristics in a normal application.

5.4 Operating Condition of EUT

5.4.1 Setup the EUT and simulators as shown in Section 5.1.

5.4.2 Turn on the power of all equipments.

5.4.3 Let the EUT work in test modes and test it.



5.5 Test Procedure

The EUT is put on the table and connected to the AC mains through a Artificial Mains Network (AMN) or ISN. This provided a 50ohm coupling impedance for the tested equipments. Both sides of AC line are checked to find out the maximum conducted emission levels according to the **ANSI C63.10** regulations during conducted emission test.

The bandwidth of the test receiver (R&S Test Receiver ESR) is set at 10kHz.

The frequency range from 150 kHz to 30 MHz is investigated.

Notes:

- 1.An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3.Mesurement Level = Reading level + Correct Factor


5.6 Test Result

PASS

Please refer to the following page.




Conducted Emission Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase:	Line
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.154500	35.58	10.46	46.04	65.75	-19.71	QP	P	
2	0.154500	17.05	10.46	27.51	55.75	-28.24	AVG	P	
3	0.384000	25.93	9.17	35.10	58.19	-23.09	QP	P	
4	0.384000	17.24	9.17	26.41	48.19	-21.78	AVG	P	
5	0.465000	32.04	9.24	41.28	56.60	-15.32	QP	P	
6 *	0.465000	24.11	9.24	33.35	46.60	-13.25	AVG	P	
7	0.955500	29.35	9.34	38.69	56.00	-17.31	QP	P	
8	0.955500	19.89	9.34	29.23	46.00	-16.77	AVG	P	
9	3.385500	22.92	9.77	32.69	56.00	-23.31	QP	P	
10	3.385500	11.30	9.77	21.07	46.00	-24.93	AVG	P	
11	18.195000	29.27	10.34	39.61	60.00	-20.39	QP	P	
12	18.195000	13.60	10.34	23.94	50.00	-26.06	AVG	P	



Conducted Emission Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Phase:	Neutral
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1




No.	Frequency (MHz)	Reading (dBUV)	Factor (dB)	Level (dBUV)	Limit (dBUV)	Margin (dB)	Detector	P/F	Remark
1	0.154400	34.77	10.27	45.04	65.76	-20.72	QP	P	
2	0.154400	17.01	10.27	27.28	55.76	-28.48	AVG	P	
3	0.231000	29.65	8.96	38.61	62.41	-23.80	QP	P	
4	0.231000	13.90	8.96	22.86	52.41	-29.55	AVG	P	
5	0.465000	30.94	9.40	40.34	56.60	-16.26	QP	P	
6 *	0.465000	28.84	9.40	38.24	46.60	-8.36	AVG	P	
7	2.089500	20.82	9.94	30.76	56.00	-25.24	QP	P	
8	2.089500	13.21	9.94	23.15	46.00	-22.85	AVG	P	
9	3.304400	20.89	10.00	30.89	56.00	-25.11	QP	P	
10	3.304400	12.93	10.00	22.93	46.00	-23.07	AVG	P	
11	17.254500	25.28	10.39	35.67	60.00	-24.33	QP	P	
12	17.254500	8.27	10.39	18.66	50.00	-31.34	AVG	P	


6. RADIATION EMISSION TEST

6.1 Block Diagram of Test Setup

Radiated Emission Test-Up Frequency Below 30MHz



Below 1GHz



6.2 Test Standard and Limit

FCC Part 15 Subpart C



Limits for frequency below 30MHz

Frequency	Limit (uV/m)	Measurement Distance(m)	Remark
0.009-0.090	2400/F(kHz)	300	AVERAGE
0.090-0.110	2400/F(kHz)	300	Quasi-peak Value
0.110-0.490	2400/F(kHz)	300	AVERAGE
0.490-1.705	24000/F(kHz)	30	Quasi-peak Value
1.705-30	30	30	Quasi-peak Value

Above 30MHz

Frequency (MHz)	Distance (Meters)	Field Strengths Limits (dBμV/m)	Remark
30 ~ 88	3	40.0	Quasi-peak Value
88 ~ 216	3	43.5	Quasi-peak Value
216 ~ 960	3	46.0	Quasi-peak Value
960 ~ 1000	3	54.0	Quasi-peak Value
Above 1000	3	74.0	PEAK
		54.0	AVERAGE

Remark:

(1) The smaller limit shall apply at the cross point between two frequency bands.

(2) Distance refers to the distance in meters between the measuring instrument, antenna and the closed point of any part of the device or system.

6.3 EUT Configuration on Test

The FCC Part 15 Subpart C regulations test method must be used to find the maximum emission during radiated emission test.

The configuration of EUT is the same as used in conducted emission test.

Please refer to Section 5.3.

6.4 Operating Condition of EUT

Same as conducted emission test, which is listed in Section 5.4 except the test set up replaced as Section 6.2.

6.5 Test Procedure

1) The radiated emissions test was conducted in a semi-anechoic chamber.

2) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane, but separated from metallic contact with the ground reference plane by 0.1m of insulation.

3) Before final measurements of radiated emissions, a pre-scan was performed in the spectrum mode with the peak detector to find out the maximum emissions spectrum plots of the EUT.

4) The frequencies of maximum emission were determined in the final radiated emissions measurement. At each frequency, the EUT was rotated 360°, and the antenna was raised and lowered from 1 to 4 meters in order to determine the maximum disturbance. Measurements were performed for both horizontal and vertical antenna polarization.

5) The bandwidth setting on the field strength meter (R&S Test Receiver ESCI) is set at 120kHz.


6) The frequency range from 30MHz to 1000MHz is checked.



6.6 Test Result

PASS, Please refer to the following page.

Radiation Emission Test Data 9 kHz~30 MHz			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	/
Test Voltage:	AC 120V/60Hz	Test Mode:	Mode 1



Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Detector Type
0.1385	54.67	10.22	64.89	105.06	-40.17	Peak
0.2584	27.47	10.47	37.94	99.60	-61.66	Peak
0.3250	51.86	10.88	62.74	97.60	-34.86	Peak
2.2015	31.60	10.23	41.83	70	-28.17	Peak
3.7301	31.60	10.18	41.78	70	-28.22	Peak
5.5506	29.96	10.69	40.65	70	-29.35	Peak
13.9946	38.32	9.06	47.38	70	-22.62	Peak

Note:


Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level(Meter Reading+ Factor) - Limit.




Radiation Emission Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Horizontal
Test Voltage:	DC 3.8V	Test Mode:	Mode 10



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV/m	Limit dB/m	Margin dB	Detector
1	57.9992	32.90	-11.23	21.67	40.00	-18.33	QP
2	98.8324	40.50	-15.17	25.33	43.50	-18.17	QP
3 *	162.6105	42.71	-15.57	27.14	43.50	-16.36	QP
4	275.1569	40.82	-11.22	29.60	46.00	-16.40	QP
5	437.1200	33.21	-8.36	24.85	46.00	-21.15	QP
6	638.3686	30.18	-4.97	25.21	46.00	-20.79	QP



Radiation Emission Test Data			
Temperature:	24.5 °C	Relative Humidity:	54%
Pressure:	1009hPa	Polarization:	Vertical
Test Voltage:	DC 3.8V	Test Mode:	Mode 10



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Margin	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		58.4074	31.88	-11.83	20.05	40.00	-19.95	QP
2	*	87.4175	40.05	-15.52	24.53	40.00	-15.47	QP
3		162.6105	42.94	-15.64	27.30	43.50	-16.20	QP
4		254.7281	36.99	-10.83	26.16	46.00	-19.84	QP
5		386.6338	35.40	-8.48	26.92	46.00	-19.08	QP
6		627.2735	28.95	-4.13	24.82	46.00	-21.18	QP

Remarks:

1. Final Level = Receiver Read level + Correct factor (Antenna Factor + Cable Loss – Pre-amplifier Factor)
2. The emission levels of other frequencies are very lower than the limit and not show in test report.



7. BANDWIDTH TEST

7.1 TEST SETUP


1. Set RBW = 3kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.


7.2 TEST SETUP



7.3 TEST Result


Frequency (kHz)	20dB bandwidth (kHz)	Result
138	8.125	Pass
325	8.312	Pass







8. SETUP PHOTOGRAPHS





9. EUT PHOTOGRAPHS





***** END OF REPORT *****