



FCC ID: 2ATCUHT19-01150

According to KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1

At 100 MHz to 6 GHz and for test separation distances  $\leq 50\text{mm}$ , the SAR test exclusion threshold is determined according to the following  
[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)]  
 $\times [\sqrt{f(\text{GHz})}] \leq 3.0$

#### 1. SAR test exclusion threshold

**Frequency: 2 480 MHz (min. separation distances = 5 mm)**

SAR test exclusion thresholds (5 mm) =  $3 \times 5 / (\sqrt{2.480}) = 9.525 \text{ mW}$

| Test mode | Max. Tune-up Tolerance (mW) | SAR Test Exclusion Thresholds (5mm) (mW) |
|-----------|-----------------------------|------------------------------------------|
| BT        | 0.79                        | 9.525                                    |

Calculation value :  $1.0 \text{ (mW)} / 5 \text{ (mm)} \times \sqrt{2.480} = 0.315$

So, Calculation value  $\leq 3.0$

Remark:

-For BT Max. conducted power is 1.0 (mW) closet 0.79 (mW), so 1.0 (mW) was calculated.  
-When the minimum test separation distance is  $< 5 \text{ mm}$ , a distance of 5 mm is applied to determine SAR test exclusion.

#### 2. Conclusion: No SAR is required.