

TEST REPORT

For WiFi-2.4GHz Band

Report No.	CHTEW22080267	Report Verification:
Project No.	SHT2206030501EW	 ReportNo: CHTEW22080267
FCC ID	2ATDI-C2000	
Applicant's name	NRadio Technologies, Co., Ltd.	
Address.....	Room 408, Ziyun Building, No.211, Xin'an 2nd Rd., Bao'an District, Shenzhen, P.R.C.	
Product Name	Dual-Band 4G LTE Router	
Trade Mark	NRadio	
Model No.	C2000	
Listed Model(s)	N5,N6,C6,N8,C8,N9,C9,B5,B8,C4800,C5800	
Standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247	
Date of receipt of test sample.....	Jun. 15, 2022	
Date of testing.....	Jun. 16, 2022- Aug. 16, 2022	
Date of issue.....	Aug. 17, 2022	
Result.....	PASS	

Compiled by
(Position+Printed name+Signature): File administrator Silvia Li



Supervised by
(Position+Printed name+Signature): Project Engineer David Chen



Approved by
(Position+Printed name+Signature): RF Manager Hans Hu



Testing Laboratory Name

Shenzhen Huatongwei International Inspection Co., Ltd.

Address.....

1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

The test report merely correspond to the test sample.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	3
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	4
<u>3.</u>	<u>SUMMARY</u>	5
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	7
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test mode	7
4.4.	Test sample information	8
4.5.	Support unit used in test configuration and system	8
4.6.	Testing environmental condition	8
4.7.	Statement of the measurement uncertainty	8
4.8.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	10
5.1.	Antenna Requirement	10
5.2.	AC Conducted Emission	11
5.3.	Peak Output Power	13
5.4.	Power Spectral Density	14
5.5.	6dB bandwidth	15
5.6.	99% Occupied Bandwidth	16
5.7.	Duty Cycle	17
5.8.	Conducted Band edge and Spurious Emission	18
5.9.	Radiated Band edge Emission	20
5.10.	Radiated Spurious Emission	27
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	37
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS</u>	39
<u>8.</u>	<u>APPENDIX REPORT</u>	46

1. **TEST STANDARDS AND REPORT VERSION**

1.1. **Test Standards**

The tests were performed according to following standards:

- [FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz
- [ANSI C63.10:2013](#): American National Standard for Testing Unlicensed Wireless Devices
- [KDB 558074 D01 15.247 Meas Guidance v05r02](#): Guidance for Compliance Measurements on Digital Transmission System, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating under Section 15.247 of The FCC Rules
- [KDB662911 D01 Multiple Transmitter Output v02r01](#): Emissions Testing of Transmitters with Multiple Outputs in the Same Band (e.g., MIMO, Smart Antenna, etc)
- [KDB662911 D02 MIMO with Cross-Polarized Antennas v01](#): MIMO with Cross-Polarized Antenna

1.2. **Report version**

Revision No.	Date of issue	Description
N/A	2022-08-17	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203/15.247(c)	PASS	Xiaoqin Li
5.2	AC Conducted Emission	15.207	PASS	Xiaoqin Li
5.3	Peak Output Power	15.247(b)(3)	PASS	Xiaoqin Li
5.4	Power Spectral Density	15.247(e)	PASS	Xiaoqin Li
5.5	6dB Bandwidth	15.247(a)(2)	PASS	Xiaoqin Li
5.6	99% Occupied Bandwidth	-	PASS ^{*1}	Xiaoqin Li
5.7	Duty cycle	-	PASS ^{*1}	Xiaoqin Li
5.8	Conducted Band Edge and Spurious Emission	15.247(d)/15.205	PASS	Xiaoqin Li
5.9	Radiated Band Edge Emission	15.205/15.209	PASS	Pan Xie
5.10	Radiated Spurious Emission	15.247(d)/15.205/15.209	PASS	Pan Xie

Note:

- The measurement uncertainty is not included in the test result.
- *1: No requirement on standard, only report these test data.

3. SUMMARY

3.1. Client Information

Applicant:	NRadio Technologies, Co., Ltd.
Address:	Room 408, Ziyun Building, No.211, Xin'an 2nd Rd., Bao'an District, Shenzhen, P.R.C.
Manufacturer:	NRadio Technologies, Co., Ltd.
Address:	Room 408, Ziyun Building, No.211, Xin'an 2nd Rd., Bao'an District, Shenzhen, P.R.C.

3.2. Product Description

Main unit information:	
Product Name:	Dual-Band 4G LTE Router
Trade Mark:	NRadio
Model No.:	C2000
Listed Model(s):	N5,N6,C6,N8,C8,N9,C9,B5,B8,C4800,C5800
Power supply:	DC 5V from adapter
Hardware version:	V1
Software version:	1.9
Accessory unit information:	
Adapter information:	Model:JZB310-050200UU Input: AC100-240V, 50/60Hz, 0.35A Output: 5.0Vdc, 2000mA

3.3. Radio Specification Description

Support type ² :	<input checked="" type="checkbox"/> 802.11b	<input checked="" type="checkbox"/> 802.11g	<input checked="" type="checkbox"/> 802.11n
Support bandwidth:	<input checked="" type="checkbox"/> 20MHz	<input checked="" type="checkbox"/> 40MHz	
Modulation:	802.11b: 802.11g/n:	DBPSK, DQPSK, BPSK, QPSK BPSK, QPSK, 16QAM, 64QAM	
Operation frequency:	802.11b/g/n(HT20): 802.11n(HT40)	2412MHz~2462MHz 2422MHz~2452MHz	
Channel number:	802.11b/g/n(HT20): 802.11n(HT40)	11 7	
Channel separation:	5MHz		
Antenna technology:	<input type="checkbox"/> SISO	<input checked="" type="checkbox"/> MIMO	
Antenna Delivery:	<input type="checkbox"/> 1*TX+1*RX	<input checked="" type="checkbox"/> 2*TX+2*RX	<input type="checkbox"/> 3*TX+3*RX
Antenna type:	internal PCB antenna		
Antenna gain:	ANT1:2.61dBi; ANT2:3.93dBi;		

Note:

*2: only show the RF function associated with this report.

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	1/F, Bldg 3, Hongfa Hi-tech Industrial Park, Genyu Road, Tianliao, Gongming, Shenzhen, China	
Connect information:	<p>Phone: 86-755-26715499</p> <p>E-mail: cs@szhtw.com.cn</p> <p>http://www.szhtw.com.cn</p>	
Qualifications	Type	Accreditation Number
	FCC	762235

4. TEST CONFIGURATION

4.1. Test frequency list

According to section 15.31(m), regards to the operating frequency range over 10 MHz, must select three channels which were tested. The Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, please see the below blue front.

802.11b/802.11g/802.11n(HT20)		802.11n(HT40)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	03	2422
02	2417	04	2427
.. :	.. :	.. :	.. :
06	2437	06	2437
.. :	.. :	.. :	.. :
10	2457	08	2447
11	2462	09	2452

4.2. Descriptions of Test mode

Preliminary tests were performed in different data rates, final test modes are considering the modulation and worse data rates as below table.

Modulation	Data rate
802.11b	1Mbps
802.11g	6Mbps
802.11n(HT20)	MCS0
802.11n(HT40)	MCS0

4.3. Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For AC power line conducted emissions:
The EUT was set to connect with the WLAN AP under large package sizes transmission.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.4. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT22060305002
EMI test items	YPHT22060305002

Note:

RF Conducted test items: Peak Output Power, Power Spectral Density, 6dB Bandwidth, 99% Occupied Bandwidth, Duty cycle, Conducted Band Edge and Spurious Emission

RF Radiated test items: Radiated Band Edge Emission, Radiated Spurious Emission

EMI test items: AC Conducted Emission

4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
<input checked="" type="checkbox"/> No			
Item	Equipment	Trade Name	Model No.
1			
2			

4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.7. Statement of the measurement uncertainty

Test Item	Measurement Uncertainty
AC Conducted Emission (150kHz~30MHz)	3.00 dB
Radiated Emission (30MHz~1000MHz)	4.36 dB
Radiated Emissions (1GHz~25GHz)	5.10 dB
Peak Output Power	0.77dB
Power Spectral Density	0.77dB
Conducted Spurious Emission	0.77dB
6dB Bandwidth	70Hz for <1GHz 130Hz for >1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.8. Equipment Used during the Test

● Conducted Emission							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Shielded Room	Albatross projects	HTWE0114	N/A	N/A	2018/09/28	2023/09/27
●	EMI Test Receiver	R&S	HTWE0111	ESCI	101247	2021/09/14	2022/09/13
●	Artificial Mains	SCHWARZBECK	HTWE0113	NNLK 8121	573	2021/09/17	2022/09/16
●	Pulse Limiter	R&S	HTWE0193	ESH3-Z2	101447	2021/09/16	2022/09/15
●	RF Connection Cable	HUBER+SUHNER	HTWE0113-02	ENVIROFLE_X_142	EF-NM-BNCM-2M	2021/09/17	2022/09/16
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-6th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2018/09/30	2022/09/29
●	EMI Test Receiver	R&S	HTWE0099	ESCI	100900	2021/09/14	2022/09/13
●	Loop Antenna	R&S	HTWE0170	HFH2-Z2	100020	2021/04/06	2024/04/05
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0123	VULB9163	538	2021/04/06	2024/04/05
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	N/A	2021/11/05	2022/11/04
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-01	N/A	N/A	2022/02/25	2023/02/24
●	RF Connection Cable	HUBER+SUHNER	HTWE0062-02	SUCOFLEX104	501184/4	2022/02/25	2023/02/24
●	Test Software	R&S	N/A	ES-K1	N/A	N/A	N/A

● Radiated emission-7th test site							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11121	2018/09/27	2022/09/26
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2021/09/13	2022/09/12
●	Horn Antenna	SCHWARZBECK	HTWE0126	9120D	1011	2020/04/01	2023/03/31
●	Broadband Horn Antenna	SCHWARZBECK	HTWE0103	BBHA9170	BBHA9170472	2020/04/27	2023/04/26
●	Pre-amplifier	CD	HTWE0071	PAP-0102	12004	2021/11/05	2022/11/04
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0201	BBV 9718	9718-248	2022/02/28	2023/02/27
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-01	6m 18GHz S Serisa	N/A	2022/02/25	2023/02/24
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-02	6m 3GHz RG Serisa	N/A	2022/02/25	2023/02/24
●	RF Connection Cable	HUBER+SUHNER	HTWE0119-05	6m 3GHz RG Serisa	N/A	2022/02/25	2023/02/24
●	RF Connection Cable	HUBER+SUHNER	HTWE0120-04	6m 3GHz RG Serisa	N/A	2022/02/25	2023/02/24
●	Test Software	Audix	N/A	E3	N/A	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

FCC CFR Title 47 Part 15 Subpart C Section 15.247(c) (1)(i):

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

TEST RESULT

Passed

Not Applicable

The product has two internal antennas, the gain of ANT1 is 2.61dBi, the gain of ANT2 is 3.93dBi, and the product is a CDD device with different gain, according to KDB 662911 D01 section F, the Directional gain=G_{ANTMAX} + Array gain

For power spectral density measurements on all devices,


Array gain=10log(N_{ANT}/N_{ss}) dB, the worst case directional gain will occur when N_{ss}=1.

So the Directional gain=3.93+10log(2/1)=6.94dBi which exceeds 6 dBi requirement, that the PSD limit should be 8-(6.94-6)=7.06dBm

For power measurements on IEEE 802.11 devices,

Array gain=0 dB for N_{ant}≤4

So the Directional gain=3.93+0 =3.93 dBi which is less than 6 dBi requirement, please refer to the below antenna photo.



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.


TEST MODE:

Please refer to the clause 4.2

TEST RESULT


Passed

Not Applicable



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150000	48.53	---	66.00	17.47	L1	10.1
0.155500	49.04	---	65.70	16.66	L1	10.1
0.259500	38.62	---	61.45	22.83	L1	10.1
0.439500	---	27.12	47.07	19.95	L1	10.1
0.540500	---	35.92	46.00	10.08	L1	10.1
0.563500	46.38	---	56.00	9.62	L1	10.1
0.567500	---	38.10	46.00	7.90	L1	10.1
0.587500	36.26	---	56.00	19.74	L1	10.1
0.619500	33.00	---	56.00	23.00	L1	10.1
0.623500	---	24.69	46.00	21.31	L1	10.1
0.695500	---	23.66	46.00	22.34	L1	10.2
0.859500	---	25.46	46.00	20.54	L1	10.1



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.155500	47.42	---	65.70	18.28	N	10.1
0.179500	44.56	---	64.51	19.95	N	10.1
0.231500	40.21	---	62.40	22.18	N	10.1
0.307500	36.49	---	60.04	23.55	N	10.1
0.352500	31.54	---	58.90	27.36	N	10.1
0.443500	---	26.63	47.00	20.37	N	10.1
0.471500	---	27.23	46.49	19.26	N	10.1
0.536500	---	32.80	46.00	13.20	N	10.1
0.547500	42.37	---	56.00	13.63	N	10.1
0.547500	---	36.05	46.00	9.95	N	10.1
0.567500	---	37.32	46.00	8.68	N	10.1
0.891500	---	21.93	46.00	24.07	N	10.1

5.3. Peak Output Power

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (b)(3): 30dBm

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was tested according to ANSI C63.10 and KDB 558074 D01 requirements.
2. The maximum peak conducted output power may be measured using a broadband peak RF power meter.
3. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.
4. Record the measurement data.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA

Please refer to appendix A on the appendix report


5.4. Power Spectral Density

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (e):

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input,
2. Configure the spectrum analyzer as shown below:
Center frequency=DTS channel center frequency
Span =1.5 times the DTS bandwidth
 $RBW = 3 \text{ kHz} \leq RBW \leq 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time = auto couple
Detector = peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter wave form on the spectrum analyzer.
4. Use the peak marker function to determine the maximum amplitude level within the RBW.
5. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA

Please refer to appendix B on the appendix report


5.5. 6dB bandwidth

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (a)(2):

For digital modulation systems, the minimum 6 dB bandwidth shall be at least 500 kHz.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = DTS channel center frequency
Span=2 x DTS bandwidth
 $RBW = 100 \text{ kHz}$, $VBW \geq 3 \times RBW$
Sweep time= auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA


Please refer to appendix C on the appendix report

5.6. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed Not Applicable

TEST DATA


Please refer to appendix D on the appendix report

5.7. Duty Cycle

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 1 MHz, VBW \geq RBW
Sweep=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST DATA


Please refer to appendix E on the appendix report

5.8. Conducted Band edge and Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d): In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Establish a reference level by using the following procedure

Center frequency=DTS channel center frequency
 The span = 1.5 times the DTS bandwidth.
 RBW = 100 kHz, VBW \geq 3 x RBW
 Detector = peak, Sweep time = auto couple, Trace mode = max hold
 Allow trace to fully stabilize
 Use the peak marker function to determine the maximum PSD level

Note that the channel found to contain the maximum PSD level can be used to establish the reference level.
3. Emission level measurement

Set the center frequency and span to encompass frequency range to be measured
 RBW = 100 kHz, VBW \geq 3 x RBW
 Detector = peak, Sweep time = auto couple, Trace mode = max hold
 Allow trace to fully stabilize
 Use the peak marker function to determine the maximum amplitude level.
4. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
5. Ensure that the amplitude of all unwanted emission outside of the authorized frequency band excluding restricted frequency bands) are attenuated by at least the minimum requirements specified (at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz). Report the three highest emission relative to the limit.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed **Not Applicable**

TEST DATA

Please refer to appendix F on the appendix report


5.9. Radiated Band edge Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.247 (d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, Radiated Emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the Radiated Emissions limits specified in §15.209(a) (see §15.205(c)).

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10 .
2. The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT waspositioned such that the distance from antenna to the EUT was 3 meters.
4. The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find themaximum emission, all of the interface cables were manipulated according to ANSI C63.10 on radiated measurement.
5. Use the following spectrum analyzer settings:
 - a) Span shall wide enough to fully capture the emission being measured
 - b) Set RBW=100kHz for <1GHz, VBW=3*RBW, Sweep time=auto, Detector=peak, Trace=max hold
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
 For average measurement:
 - VBW=10Hz, When duty cycle is no less than 98 percent
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clasue 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed

Not Applicable

Note:

- 1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m).
- 4) Pre-scan all modulation mode and antenna. 802.11b/g/n in the report only displays the worst antenna information.

ANT0

Type	802.11b		Test channel		CH01			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	37.46	27.96	5.95	37.56	20.00	53.81	74.00	-20.19	Peak	
2	2390.01	37.51	27.72	6.19	37.45	20.00	53.97	74.00	-20.03	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	31.45	27.96	5.95	37.56	20.00	47.80	54.00	-6.20	Average	
2	2390.01	30.32	27.72	6.19	37.45	20.00	46.78	54.00	-7.22	Average	

Type	802.11b		Test channel		CH01			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	37.57	27.96	5.95	37.56	20.00	53.92	74.00	-20.08	Peak	
2	2390.01	37.56	27.72	6.19	37.45	20.00	54.02	74.00	-19.98	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	30.65	27.96	5.95	37.56	20.00	47.00	54.00	-7.00	Average	
2	2390.01	30.39	27.72	6.19	37.45	20.00	46.85	54.00	-7.15	Average	

Type	802.11b		Test channel		CH11			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	37.90	27.43	6.16	37.26	20.00	54.23	74.00	-19.77	Peak	
2	2500.00	36.98	27.40	6.15	37.26	20.00	53.27	74.00	-20.73	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	31.12	27.43	6.16	37.26	20.00	47.45	54.00	-6.55	Average	
2	2500.00	29.71	27.40	6.15	37.26	20.00	46.00	54.00	-8.00	Average	

Type	802.11b		Test channel		CH11			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	36.92	27.43	6.16	37.26	20.00	53.25	74.00	-20.75	Peak	
2	2500.00	38.07	27.40	6.15	37.26	20.00	54.36	74.00	-19.64	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	29.76	27.43	6.16	37.26	20.00	46.09	54.00	-7.91	Average	
2	2500.00	29.67	27.40	6.15	37.26	20.00	45.96	54.00	-8.04	Average	

ANT1

Type	802.11b		Test channel		CH01			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.91	27.96	5.95	37.56	20.00	53.26	74.00	-20.74	Peak	
2	2390.01	38.99	27.72	6.19	37.45	20.00	55.45	74.00	-18.55	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	30.76	27.96	5.95	37.56	20.00	47.11	54.00	-6.89	Average	
2	2390.01	32.52	27.72	6.19	37.45	20.00	48.98	54.00	-5.02	Average	

Type	802.11b		Test channel		CH01			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.78	27.96	5.95	37.56	20.00	53.13	74.00	-20.87	Peak	
2	2390.01	37.08	27.72	6.19	37.45	20.00	53.54	74.00	-20.46	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	30.37	27.96	5.95	37.56	20.00	46.72	54.00	-7.28	Average	
2	2390.01	29.93	27.72	6.19	37.45	20.00	46.39	54.00	-7.61	Average	

Type	802.11b		Test channel		CH11			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	37.96	27.43	6.16	37.26	20.00	54.29	74.00	-19.71	Peak	
2	2500.00	37.39	27.40	6.15	37.26	20.00	53.68	74.00	-20.32	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	30.52	27.43	6.16	37.26	20.00	46.85	54.00	-7.15	Average	
2	2500.00	30.90	27.40	6.15	37.26	20.00	47.19	54.00	-6.81	Average	

Type	802.11b		Test channel		CH11			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	36.28	27.43	6.16	37.26	20.00	52.61	74.00	-21.39	Peak	
2	2500.00	36.96	27.40	6.15	37.26	20.00	53.25	74.00	-20.75	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	30.90	27.43	6.16	37.26	20.00	47.23	54.00	-6.77	Average	
2	2500.00	29.66	27.40	6.15	37.26	20.00	45.95	54.00	-8.05	Average	

ANT0

Type	802.11g		Test channel		CH01			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	37.88	27.96	5.95	37.56	20.00	54.23	74.00	-19.77	Peak	
2	2390.01	38.14	27.72	6.19	37.45	20.00	54.60	74.00	-19.40	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	26.10	27.96	5.95	37.56	20.00	42.45	54.00	-11.55	Average	
2	2390.01	27.09	27.72	6.19	37.45	20.00	43.55	54.00	-10.45	Average	

Type	802.11g		Test channel		CH01			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	36.72	27.96	5.95	37.56	20.00	53.07	74.00	-20.93	Peak	
2	2390.01	38.04	27.72	6.19	37.45	20.00	54.50	74.00	-19.50	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	25.94	27.96	5.95	37.56	20.00	42.29	54.00	-11.71	Average	
2	2390.01	26.15	27.72	6.19	37.45	20.00	42.61	54.00	-11.39	Average	

Type	802.11g		Test channel		CH11			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	37.45	27.43	6.16	37.26	20.00	53.78	74.00	-20.22	Peak	
2	2500.00	37.81	27.40	6.15	37.26	20.00	54.10	74.00	-19.90	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	26.48	27.43	6.16	37.26	20.00	42.81	54.00	-11.19	Average	
2	2500.00	26.44	27.40	6.15	37.26	20.00	42.73	54.00	-11.27	Average	

Type	802.11g		Test channel		CH11			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	36.34	27.43	6.16	37.26	20.00	52.67	74.00	-21.33	Peak	
2	2500.00	36.88	27.40	6.15	37.26	20.00	53.17	74.00	-20.83	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	25.52	27.43	6.16	37.26	20.00	41.85	54.00	-12.15	Average	
2	2500.00	25.57	27.40	6.15	37.26	20.00	41.86	54.00	-12.14	Average	

ANT1

Type	802.11g		Test channel		CH01			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	38.04	27.96	5.95	37.56	20.00	54.39	74.00	-19.61	Peak	
2	2390.01	39.21	27.72	6.19	37.45	20.00	55.67	74.00	-18.33	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	26.04	27.96	5.95	37.56	20.00	42.39	54.00	-11.61	Average	
2	2390.01	27.06	27.72	6.19	37.45	20.00	43.52	54.00	-10.48	Average	

Type	802.11g		Test channel		CH01			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	38.44	27.96	5.95	37.56	20.00	54.79	74.00	-19.21	Peak	
2	2390.01	38.67	27.72	6.19	37.45	20.00	55.13	74.00	-18.87	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	25.92	27.96	5.95	37.56	20.00	42.27	54.00	-11.73	Average	
2	2390.01	26.10	27.72	6.19	37.45	20.00	42.56	54.00	-11.44	Average	

Type	802.11g		Test channel		CH11			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	38.00	27.43	6.16	37.26	20.00	54.33	74.00	-19.67	Peak	
2	2500.00	37.29	27.40	6.15	37.26	20.00	53.58	74.00	-20.42	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	26.56	27.43	6.16	37.26	20.00	42.89	54.00	-11.11	Average	
2	2500.00	26.21	27.40	6.15	37.26	20.00	42.50	54.00	-11.50	Average	

Type	802.11g		Test channel		CH11			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	37.38	27.43	6.16	37.26	20.00	53.71	74.00	-20.29	Peak	
2	2500.00	37.10	27.40	6.15	37.26	20.00	53.39	74.00	-20.61	Peak	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	25.64	27.43	6.16	37.26	20.00	41.97	54.00	-12.03	Average	
2	2500.00	25.55	27.40	6.15	37.26	20.00	41.84	54.00	-12.16	Average	

MIMO

Type	802.11n(HT20)		Test channel		CH01			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	37.79	27.96	5.95	37.56	20.00	54.14	74.00	-19.86	Peak	
2	2390.01	38.76	27.72	6.19	37.45	20.00	55.22	74.00	-18.78	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	26.05	27.96	5.95	37.56	20.00	42.40	54.00	-11.60	Average	
2	2390.01	26.87	27.72	6.19	37.45	20.00	43.33	54.00	-10.67	Average	

Type	802.11n(HT20)		Test channel		CH01			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	37.97	27.96	5.95	37.56	20.00	54.32	74.00	-19.68	Peak	
2	2390.01	37.15	27.72	6.19	37.45	20.00	53.61	74.00	-20.39	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2310.00	26.03	27.96	5.95	37.56	20.00	42.38	54.00	-11.62	Average	
2	2390.01	26.19	27.72	6.19	37.45	20.00	42.65	54.00	-11.35	Average	

Type	802.11n(HT20)		Test channel		CH11			Polarity		Horizontal	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	37.41	27.43	6.16	37.26	20.00	53.74	74.00	-20.26	Peak	
2	2500.00	38.58	27.40	6.15	37.26	20.00	54.87	74.00	-19.13	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	26.30	27.43	6.16	37.26	20.00	42.63	54.00	-11.37	Average	
2	2500.00	26.14	27.40	6.15	37.26	20.00	42.43	54.00	-11.57	Average	

Type	802.11n(HT20)		Test channel		CH11			Polarity		Vertical	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	36.28	27.43	6.16	37.26	20.00	52.61	74.00	-21.39	Peak	
2	2500.00	37.72	27.40	6.15	37.26	20.00	54.01	74.00	-19.99	Peak	
<hr/>											
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2483.49	25.58	27.43	6.16	37.26	20.00	41.91	54.00	-12.09	Average	
2	2500.00	25.64	27.40	6.15	37.26	20.00	41.93	54.00	-12.07	Average	

MIMO

Type	802.11n(HT40)		Test channel		CH03		Polarity		Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	37.48	27.96	5.95	37.56	20.00	53.83	74.00	-20.17	Peak
2	2389.99	37.97	27.72	6.19	37.45	20.00	54.43	74.00	-19.57	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	26.04	27.96	5.95	37.56	20.00	42.39	54.00	-11.61	Average
2	2389.99	27.09	27.72	6.19	37.45	20.00	43.55	54.00	-10.45	Average

Type	802.11n(HT40)		Test channel		CH03		Polarity		Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	37.11	27.96	5.95	37.56	20.00	53.46	74.00	-20.54	Peak
2	2389.99	37.82	27.72	6.19	37.45	20.00	54.28	74.00	-19.72	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2310.00	25.94	27.96	5.95	37.56	20.00	42.29	54.00	-11.71	Average
2	2389.99	25.92	27.72	6.19	37.45	20.00	42.38	54.00	-11.62	Average

Type	802.11n(HT40)		Test channel		CH09		Polarity		Horizontal	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	36.94	27.43	6.16	37.26	20.00	53.27	74.00	-20.73	Peak
2	2500.00	37.36	27.40	6.15	37.26	20.00	53.65	74.00	-20.35	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	26.51	27.43	6.16	37.26	20.00	42.84	54.00	-11.16	Average
2	2500.00	26.08	27.40	6.15	37.26	20.00	42.37	54.00	-11.63	Average

Type	802.11n(HT40)		Test channel		CH09		Polarity		Vertical	
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	36.89	27.43	6.16	37.26	20.00	53.22	74.00	-20.78	Peak
2	2500.00	36.78	27.40	6.15	37.26	20.00	53.07	74.00	-20.93	Peak
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Aux dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2483.50	25.71	27.43	6.16	37.26	20.00	42.04	54.00	-11.96	Average
2	2500.00	25.51	27.40	6.15	37.26	20.00	41.80	54.00	-12.20	Average

5.10. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:
RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;
If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement
For average measurement:
 - VBW=10Hz, When duty cycle is no less than 98 percent
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation, so refer to this clause 5.6 duty cycle.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

Passed Not Applicable

Note:


- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Over Limit = Level- Limit
- 3) Average measurement was not performed if peak level is lower than average limit(54 dBuV/m) for above 1GHz.


FOR 9 kHz ~ 30 MHz

The EUT was pre-scanned this frequency band, found the radiated level 20dB lower than the limit, so don't show data on this report.

FOR 30 MHz ~ 1000 MHz

Have pre-scan all test channel, found CH06 of 802.11B which it was worst case, so only show the worst case's data on this report.





FOR 1 GHz ~ 25 GHz

The EUT was pre-scanned all modulation mode and antenna. 802.11b/g/n in the report only displays the worst antenna information.

ANT0

Type	802.11b		Test channel		CH01		Polarity		Horizontal	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1217.32	51.50	25.71	4.15	36.62	44.74	74.00	-29.26	Peak	
2	2655.59	50.43	27.73	6.45	37.01	47.60	74.00	-26.40	Peak	
3	4825.23	36.66	31.40	9.01	35.23	41.84	74.00	-32.16	Peak	
4	8062.71	33.40	37.20	12.19	33.32	49.47	74.00	-24.53	Peak	
Type	802.11b		Test channel		CH01		Polarity		Vertical	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1333.54	49.63	26.20	4.40	36.38	43.85	74.00	-30.15	Peak	
2	2667.28	45.21	27.80	6.46	37.03	42.44	74.00	-31.56	Peak	
3	4825.23	38.19	31.40	9.01	35.23	43.37	74.00	-30.63	Peak	
4	7231.75	35.26	36.44	11.31	34.04	48.97	74.00	-25.03	Peak	
Type	802.11b		Test channel		CH06		Polarity		Horizontal	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1217.32	51.50	25.71	4.15	36.62	44.74	74.00	-29.26	Peak	
2	2655.59	50.43	27.73	6.45	37.01	47.60	74.00	-26.40	Peak	
3	5256.28	37.67	31.40	9.36	35.34	43.09	74.00	-30.91	Peak	
4	7316.14	34.09	36.43	11.40	34.10	47.82	74.00	-26.18	Peak	
Type	802.11b		Test channel		CH06		Polarity		Vertical	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1333.54	49.63	26.20	4.40	36.38	43.85	74.00	-30.15	Peak	
2	2667.28	45.21	27.80	6.46	37.03	42.44	74.00	-31.56	Peak	
3	4874.47	38.09	31.40	9.09	35.16	43.42	74.00	-30.58	Peak	
4	7316.14	36.38	36.43	11.40	34.10	50.11	74.00	-23.89	Peak	
Type	802.11b		Test channel		CH11		Polarity		Horizontal	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1217.32	51.50	25.71	4.15	36.62	44.74	74.00	-29.26	Peak	
2	2655.59	50.43	27.73	6.45	37.01	47.60	74.00	-26.40	Peak	
3	4981.67	36.79	31.75	9.29	35.21	42.62	74.00	-31.38	Peak	
4	7390.79	34.28	36.58	11.47	34.02	48.31	74.00	-25.69	Peak	
Type	802.11b		Test channel		CH11		Polarity		Vertical	

Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1333.54	49.63	26.20	4.40	36.38	43.85	74.00	-30.15	Peak	
2	2667.28	45.21	27.80	6.46	37.03	42.44	74.00	-31.56	Peak	
3	4996.14	41.24	31.87	9.32	35.24	47.19	74.00	-26.81	Peak	
4	7390.79	36.75	36.58	11.47	34.02	50.78	74.00	-23.22	Peak	

ANT1

Type	802.11b		Test channel		CH01		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2374.08	48.94	27.75	6.14	37.49	45.34	74.00	-28.66	Peak	
2	2655.59	51.42	27.73	6.45	37.01	48.59	74.00	-25.41	Peak	
3	4825.23	37.69	31.40	9.01	35.23	42.87	74.00	-31.13	Peak	
4	7221.27	34.18	36.46	11.29	34.03	47.90	74.00	-26.10	Peak	
Type	802.11b		Test channel		CH01		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1330.61	50.92	26.19	4.40	36.37	45.14	74.00	-28.86	Peak	
2	1711.25	53.86	25.12	5.13	37.11	47.00	74.00	-27.00	Peak	
3	4825.23	36.65	31.40	9.01	35.23	41.83	74.00	-32.17	Peak	
4	4996.14	41.63	31.87	9.32	35.24	47.58	74.00	-26.42	Peak	
Type	802.11b		Test channel		CH06		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2374.08	48.94	27.75	6.14	37.49	45.34	74.00	-28.66	Peak	
2	2655.59	51.42	27.73	6.45	37.01	48.59	74.00	-25.41	Peak	
3	4874.47	37.36	31.40	9.09	35.16	42.69	74.00	-31.31	Peak	
4	6600.29	36.10	34.30	10.69	34.59	46.50	74.00	-27.50	Peak	
Type	802.11b		Test channel		CH06		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1330.61	50.92	26.19	4.40	36.37	45.14	74.00	-28.86	Peak	
2	1711.25	53.86	25.12	5.13	37.11	47.00	74.00	-27.00	Peak	
3	4981.67	38.53	31.75	9.29	35.21	44.36	74.00	-29.64	Peak	
4	7992.86	34.48	37.07	12.20	33.31	50.44	74.00	-23.56	Peak	
Type	802.11g		Test channel		CH11		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2374.08	48.94	27.75	6.14	37.49	45.34	74.00	-28.66	Peak	
2	2655.59	51.42	27.73	6.45	37.01	48.59	74.00	-25.41	Peak	
3	4996.14	37.41	31.87	9.32	35.24	43.36	74.00	-30.64	Peak	
4	8016.07	33.16	37.13	12.21	33.31	49.19	74.00	-24.81	Peak	
Type	802.11b		Test channel		CH11		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1330.61	50.92	26.19	4.40	36.37	45.14	74.00	-28.86	Peak	
2	1711.25	53.86	25.12	5.13	37.11	47.00	74.00	-27.00	Peak	
3	4996.14	40.39	31.87	9.32	35.24	46.34	74.00	-27.66	Peak	
4	7390.79	34.75	36.58	11.47	34.02	48.78	74.00	-25.22	Peak	

ANT0

Type	802.11g		Test channel		CH01		Polarity		Horizontal	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1096.68	50.59	25.39	4.04	36.90	43.12	74.00	-30.88	Peak	
2	2661.43	49.28	27.77	6.46	37.01	46.50	74.00	-27.50	Peak	
3	5792.66	35.17	31.99	9.99	34.86	42.29	74.00	-31.71	Peak	
4	8027.71	34.01	37.16	12.21	33.31	50.07	74.00	-23.93	Peak	
Type	802.11g		Test channel		CH01		Polarity		Vertical	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1200.06	55.14	25.60	4.10	36.64	48.20	74.00	-25.80	Peak	
2	1993.57	49.91	26.07	5.56	37.06	44.48	74.00	-29.52	Peak	
3	4996.14	43.01	31.87	9.32	35.24	48.96	74.00	-25.04	Peak	
4	6994.50	36.54	35.37	11.14	34.05	49.00	74.00	-25.00	Peak	
Type	802.11g		Test channel		CH06		Polarity		Horizontal	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1096.68	50.59	25.39	4.04	36.90	43.12	74.00	-30.88	Peak	
2	2661.43	49.28	27.77	6.46	37.01	46.50	74.00	-27.50	Peak	
3	5076.48	35.37	32.20	9.35	35.44	41.48	74.00	-32.52	Peak	
4	7969.71	33.50	36.98	12.12	33.32	49.28	74.00	-24.72	Peak	
Type	802.11g		Test channel		CH06		Polarity		Vertical	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1200.06	55.14	25.60	4.10	36.64	48.20	74.00	-25.80	Peak	
2	1993.57	49.91	26.07	5.56	37.06	44.48	74.00	-29.52	Peak	
3	4974.45	41.52	31.70	9.28	35.21	47.29	74.00	-26.71	Peak	
4	7981.27	33.49	37.03	12.16	33.31	49.37	74.00	-24.63	Peak	
Type	802.11g		Test channel		CH11		Polarity		Horizontal	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1096.68	50.59	25.39	4.04	36.90	43.12	74.00	-30.88	Peak	
2	2661.43	49.28	27.77	6.46	37.01	46.50	74.00	-27.50	Peak	
3	5054.44	35.95	32.20	9.35	35.39	42.11	74.00	-31.89	Peak	
4	8144.98	33.54	37.02	12.21	33.40	49.37	74.00	-24.63	Peak	
Type	802.11g		Test channel		CH11		Polarity		Vertical	
Mark Frequency Reading Antenna Cable Preamp Level Limit Over Remark										
1	1200.06	55.14	25.60	4.10	36.64	48.20	74.00	-25.80	Peak	
2	1993.57	49.91	26.07	5.56	37.06	44.48	74.00	-29.52	Peak	
3	4988.90	42.18	31.81	9.31	35.23	48.07	74.00	-25.93	Peak	
4	7444.58	34.60	36.60	11.48	33.97	48.71	74.00	-25.29	Peak	

ANT1

Type	802.11g		Test channel		CH01			Polarity		Horizontal
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2371.47	49.98	27.76	6.14	37.49	46.39	74.00	-27.61	Peak	
2	2667.28	47.50	27.80	6.46	37.03	44.73	74.00	-29.27	Peak	
3	4996.14	37.26	31.87	9.32	35.24	43.21	74.00	-30.79	Peak	
4	8027.71	33.03	37.16	12.21	33.31	49.09	74.00	-24.91	Peak	
Type	802.11g		Test channel		CH01			Polarity		Vertical
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1666.72	49.29	25.10	5.01	37.18	42.22	74.00	-31.78	Peak	
2	2658.51	47.51	27.75	6.45	37.01	44.70	74.00	-29.30	Peak	
3	4981.67	41.31	31.75	9.29	35.21	47.14	74.00	-26.86	Peak	
4	8109.62	32.81	37.16	12.19	33.34	48.82	74.00	-25.18	Peak	
Type	802.11g		Test channel		CH06			Polarity		Horizontal
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2371.47	49.98	27.76	6.14	37.49	46.39	74.00	-27.61	Peak	
2	2667.28	47.50	27.80	6.46	37.03	44.73	74.00	-29.27	Peak	
3	5106.01	35.35	32.18	9.35	35.48	41.40	74.00	-32.60	Peak	
4	7401.51	34.41	36.60	11.48	34.01	48.48	74.00	-25.52	Peak	
Type	802.11g		Test channel		CH06			Polarity		Vertical
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1666.72	49.29	25.10	5.01	37.18	42.22	74.00	-31.78	Peak	
2	2658.51	47.51	27.75	6.45	37.01	44.70	74.00	-29.30	Peak	
3	4996.14	41.06	31.87	9.32	35.24	47.01	74.00	-26.99	Peak	
4	8016.07	34.05	37.13	12.21	33.31	50.08	74.00	-23.92	Peak	
Type	802.11g		Test channel		CH11			Polarity		Horizontal
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	2371.47	49.98	27.76	6.14	37.49	46.39	74.00	-27.61	Peak	
2	2667.28	47.50	27.80	6.46	37.03	44.73	74.00	-29.27	Peak	
3	4996.14	36.31	31.87	9.32	35.24	42.26	74.00	-31.74	Peak	
4	8027.71	33.58	37.16	12.21	33.31	49.64	74.00	-24.36	Peak	
Type	802.11g		Test channel		CH11			Polarity		Vertical
<hr/>										
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1666.72	49.29	25.10	5.01	37.18	42.22	74.00	-31.78	Peak	
2	2658.51	47.51	27.75	6.45	37.01	44.70	74.00	-29.30	Peak	
3	3990.33	45.01	29.90	8.23	36.38	46.76	74.00	-27.24	Peak	
4	6974.25	36.94	35.25	11.11	34.07	49.23	74.00	-24.77	Peak	

MIMO

Type	802.11n(HT20)		Test channel		CH01			Polarity		Horizontal
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1095.47	52.76	25.38	4.04	36.90	45.28	74.00	-28.72	Peak	
2	2366.26	46.99	27.77	6.12	37.50	43.38	74.00	-30.62	Peak	
3	5069.12	34.77	32.20	9.35	35.43	40.89	74.00	-33.11	Peak	
4	8027.71	32.73	37.16	12.21	33.31	48.79	74.00	-25.21	Peak	
Type	802.11n(HT20)		Test channel		CH01			Polarity		Vertical
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1488.39	54.35	25.95	4.67	36.81	48.16	74.00	-25.84	Peak	
2	2664.36	49.27	27.79	6.46	37.02	46.50	74.00	-27.50	Peak	
3	4996.14	37.00	31.87	9.32	35.24	42.95	74.00	-31.05	Peak	
4	8062.71	32.40	37.20	12.19	33.32	48.47	74.00	-25.53	Peak	
Type	802.11n(HT20)		Test channel		CH06			Polarity		Horizontal
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1095.47	52.76	25.38	4.04	36.90	45.28	74.00	-28.72	Peak	
2	2366.26	46.99	27.77	6.12	37.50	43.38	74.00	-30.62	Peak	
3	5792.66	34.82	31.99	9.99	34.86	41.94	74.00	-32.06	Peak	
4	8618.94	32.15	37.44	14.15	35.25	48.49	74.00	-25.51	Peak	
Type	802.11n(HT20)		Test channel		CH06			Polarity		Vertical
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1488.39	54.35	25.95	4.67	36.81	48.16	74.00	-25.84	Peak	
2	2664.36	49.27	27.79	6.46	37.02	46.50	74.00	-27.50	Peak	
3	4996.14	35.92	31.87	9.32	35.24	41.87	74.00	-32.13	Peak	
4	8004.46	32.46	37.11	12.22	33.31	48.48	74.00	-25.52	Peak	
Type	802.11n(HT20)		Test channel		CH11			Polarity		Horizontal
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1095.47	52.76	25.38	4.04	36.90	45.28	74.00	-28.72	Peak	
2	2366.26	46.99	27.77	6.12	37.50	43.38	74.00	-30.62	Peak	
3	4981.67	35.68	31.75	9.29	35.21	41.51	74.00	-32.49	Peak	
4	8581.52	33.44	37.29	13.90	35.38	49.25	74.00	-24.75	Peak	
Type	802.11n(HT20)		Test channel		CH11			Polarity		Vertical
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1488.39	54.35	25.95	4.67	36.81	48.16	74.00	-25.84	Peak	
2	2664.36	49.27	27.79	6.46	37.02	46.50	74.00	-27.50	Peak	
3	4687.28	36.85	31.35	9.37	35.81	41.76	74.00	-32.24	Peak	
4	8470.24	34.23	36.88	12.55	34.88	48.78	74.00	-25.22	Peak	

MIMO

Type	802.11n(HT40)		Test channel		CH03		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1097.88	52.53	25.39	4.04	36.89	45.07	74.00	-28.93	Peak	
2	2368.86	46.98	27.76	6.13	37.49	43.38	74.00	-30.62	Peak	
3	5054.44	35.15	32.20	9.35	35.39	41.31	74.00	-32.69	Peak	
4	8074.41	32.44	37.20	12.19	33.32	48.51	74.00	-25.49	Peak	
Type	802.11n(HT40)		Test channel		CH03		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1332.08	51.45	26.19	4.40	36.38	45.66	74.00	-28.34	Peak	
2	2664.36	45.66	27.79	6.46	37.02	42.89	74.00	-31.11	Peak	
3	6974.25	36.24	35.25	11.11	34.07	48.53	74.00	-25.47	Peak	
4	8027.71	32.64	37.16	12.21	33.31	48.70	74.00	-25.30	Peak	
Type	802.11n(HT40)		Test channel		CH06		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1097.88	52.53	25.39	4.04	36.89	45.07	74.00	-28.93	Peak	
2	2368.86	46.98	27.76	6.13	37.49	43.38	74.00	-30.62	Peak	
3	6974.25	35.10	35.25	11.11	34.07	47.39	74.00	-26.61	Peak	
4	8039.36	32.86	37.18	12.20	33.31	48.93	74.00	-25.07	Peak	
Type	802.11n(HT40)		Test channel		CH06		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1332.08	51.45	26.19	4.40	36.38	45.66	74.00	-28.34	Peak	
2	2664.36	45.66	27.79	6.46	37.02	42.89	74.00	-31.11	Peak	
3	6994.50	35.93	35.37	11.14	34.05	48.39	74.00	-25.61	Peak	
4	8581.52	33.20	37.29	13.90	35.38	49.01	74.00	-24.99	Peak	
Type	802.11n(HT40)		Test channel		CH09		Polarity		Horizontal	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1097.88	52.53	25.39	4.04	36.89	45.07	74.00	-28.93	Peak	
2	2368.86	46.98	27.76	6.13	37.49	43.38	74.00	-30.62	Peak	
3	5767.51	35.71	31.94	9.95	34.86	42.74	74.00	-31.26	Peak	
4	8109.62	32.25	37.16	12.19	33.34	48.26	74.00	-25.74	Peak	
Type	802.11n(HT40)		Test channel		CH09		Polarity		Vertical	
Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark	
1	1332.08	51.45	26.19	4.40	36.38	45.66	74.00	-28.34	Peak	
2	2664.36	45.66	27.79	6.46	37.02	42.89	74.00	-31.11	Peak	
3	4996.14	35.31	31.87	9.32	35.24	41.26	74.00	-32.74	Peak	
4	6984.37	37.52	35.31	11.13	34.06	49.90	74.00	-24.10	Peak	

6. TEST SETUP PHOTOS

Radiated Emission





AC Conducted Emission





7. EXTERNAL AND INTERNAL PHOTOS

EXTERNAL PHOTOS












INTERNAL PHOTOS









8. APPENDIX REPORT