

# TEST REPORT

Reference No..... : WTX22X12249978W001  
FCC ID ..... : 2ATDU-9531-9532  
Applicant ..... : FERMAX ELECTRONICA, S.A.U  
Address..... : AV. TRES CRUCES, 133, VALENCIA 46017, Spain  
Manufacturer ..... : FERMAX ELECTRONICA, S.A.U  
Address..... : AV. TRES CRUCES, 133, VALENCIA 46017, Spain  
Product Name ..... : MILO DIGITAL VIDEO PANEL MEET, MILO TOUCH DIGITAL VIDEO  
PANEL MEET  
Model No..... : 9531, 9532  
Standards ..... : FCC Part 15.225  
Date of Receipt sample .... : 2022-12-12  
Date of Test..... : 2022-12-12 to 2023-02-02  
Date of Issue ..... : 2023-02-02  
Test Report Form No. .... : WTX\_Part 15\_225W  
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

*Jack Huang*

---

Jack Huang

Approved by:

*Silin Chen*

---

Silin Chen

## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....	4
1.2 TEST STANDARDS.....	5
1.3 TEST METHODOLOGY .....	5
1.4 TEST FACILITY .....	5
1.5 EUT SETUP AND TEST MODE .....	6
1.6 MEASUREMENT UNCERTAINTY.....	7
1.7 TEST EQUIPMENT LIST AND DETAILS .....	8
<b>2. SUMMARY OF TEST RESULTS.....</b>	<b>11</b>
<b>3. ANTENNA REQUIREMENT .....</b>	<b>12</b>
3.1 STANDARD APPLICABLE .....	12
3.2 TEST RESULT.....	12
<b>4. RADIATED EMISSIONS .....</b>	<b>13</b>
4.1 STANDARD APPLICABLE .....	13
4.2 TEST PROCEDURE .....	13
4.3 CORRECTED AMPLITUDE & MARGIN CALCULATION.....	15
4.4 SUMMARY OF TEST RESULTS/PLOTS.....	16
<b>5. OUT OF BAND EMISSIONS .....</b>	<b>21</b>
5.1 STANDARD APPLICABLE .....	21
5.2 TEST PROCEDURE .....	21
5.3 SUMMARY OF TEST RESULTS/PLOTS.....	21
<b>6. FREQUENCY STABILITY .....</b>	<b>23</b>
6.1 STANDARD APPLICABLE .....	23
6.2 TEST PROCEDURE .....	23
6.3 SUMMARY OF TEST RESULTS/PLOTS.....	23
<b>7. EMISSION BANDWIDTH.....</b>	<b>24</b>
7.1 APPLICABLE STANDARD .....	24
7.2 TEST PROCEDURE .....	24
7.3 SUMMARY OF TEST RESULTS/PLOTS.....	24
<b>8. CONDUCTED EMISSIONS .....</b>	<b>26</b>
8.1 TEST PROCEDURE .....	26
8.2 BASIC TEST SETUP BLOCK DIAGRAM .....	26
8.3 TEST RECEIVER SETUP .....	26
8.4 SUMMARY OF TEST RESULTS/PLOTS.....	26
<b>APPENDIX PHOTOGRAPHS.....</b>	<b>31</b>

**Report version**

Version No.	Date of issue	Description
Rev.00	2023-02-02	Original
/	/	/

## 1. GENERAL INFORMATION

---

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	MILO DIGITAL VIDEO PANEL MEET, MILO TOUCH DIGITAL VIDEO PANEL MEET
Trade Name:	/
Model No.:	9531
Adding Model(s):	9532
Rated Voltage:	DC12V
Power Adapter Model:	/
<p><i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model 9531, but the circuit and the electronic construction do not change, declared by the manufacturer.</i></p>	

Technical Characteristics of EUT	
Support Standards:	NFC
Frequency Range:	13.56MHz
Max. Field Strength:	44.10dBuV/m (at 3m)
Antenna Type:	PCB Antenna
Antenna Gain	0dBi

## 1.2 Test Standards

The tests were performed according to following standards:

**FCC Rules Part 15.225**: Operation within the band 13.110-14.010MHz.

**ANSI C63.10-2013**: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission/immunity, should be checked to ensure compliance has been maintained.

## 1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

## 1.4 Test Facility

### **Address of the test laboratory**

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

### **FCC – Registration No.: 125990**

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### **Industry Canada (IC) Registration No.: 11464A**

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A and the CAB identifier is CN0057.

## 1.5 EUT Setup and Test Mode

The EUT was operated in the continuous transmitting mode that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Transmitting	13.56MHz

Test Conditions	
Temperature:	22~25 °C
Relative Humidity:	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
DC Cable	0.23	Unshielded	Without Ferrite

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
RJ45	1.50	Shielded	Without Ferrite
Adapter DC Cable	1.56	Unshielded	Without Ferrite
Adapter AC Cable	1.26	Unshielded	Without Ferrite

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Notebook	Lenovo	E445	EB12648265
Adapter	SWITCHING	XH1200-2000	/

### 1.6 Measurement Uncertainty

<b>Measurement uncertainty</b>		
Parameter	Conditions	Uncertainty
Frequency Deviation	2.3%	±5%
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

## 1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due. Date
SEMT-1075	Communication Tester	Rohde & Schwarz	CMW500	148650	2022-03-22	2023-03-21
SEMT-1063	GSM Tester	Rohde & Schwarz	CMU200	114403	2022-03-22	2023-03-21
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2022-03-25	2023-03-24
SEMT-1079	Spectrum Analyzer	Agilent	N9020A	US47140102	2022-03-22	2023-03-21
SMET-1313	Spectrum Analyzer	Agilent	N9020A	MY54320548	2022-03-22	2023-03-21
SEMT-1080	Signal Generator	Agilent	83752A	3610A01453	2022-03-22	2023-03-21
SEMT-1081	Vector Signal Generator	Agilent	N5182A	MY47070202	2022-03-22	2023-03-21
SEMT-1028	Power Divider	Weinschel	1506A	PM204	2022-03-22	2023-03-21
SEMT-1082	Power Divider	RF-Lambda	RFLT4W5M18G	14110400027	2022-03-22	2023-03-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	/	/
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	/	/
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	/	/
SEMT-C004	Cable	Zheng DI	2M0RFC	/	/	/
SEMT-C005	Cable	Zheng DI	1M0RFC	/	/	/
SEMT-C006	Cable	Zheng DI	1M0RFC	/	/	/
<input type="checkbox"/> Chamber A: Below 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1008	Amplifier	HP	8447F	2805A03475	2022-01-07	2023-01-06
					2022-12-30	2023-12-29
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1068	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2021-03-20	2023-03-19
<input type="checkbox"/> Chamber A: Above 1GHz						
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2022-03-22	2023-03-21



SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2022-03-22	2023-03-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2022-03-22	2023-03-21
SEMT-1042	Horn Antenna	ETS	3117	00086197	2021-03-19	2023-03-18
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2021-04-27	2023-04-26
SEMT-1216	Pre-amplifier	Schwarzbeck	BBV 9721	9721-031	2022-03-25	2023-03-24
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2022-03-22	2023-03-21
<input type="checkbox"/> Chamber B:Below 1GHz						
SEMT-1068	Trilog Broadband Antenna	Schwarz beck	VULB9163(B)	9163-635	2021-04-09	2023-04-08
SEMT-1067	Amplifier	Agilent	8447D	2944A10179	2022-03-22	2023-03-21
SEMT-1066	EMI Test Receiver	Rohde & Schwarz	ESPI	101391	2022-03-22	2023-03-21
<input checked="" type="checkbox"/> Chamber C:Below 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
					2022-12-30	2023-12-29
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2021-03-20	2023-03-19
SEMT-1343	Trilog Broadband Antenna	Schwarz beck	VULB 9168	1194	2021-05-28	2023-05-27
SEMT-1333	Amplifier	HP	8447F	2944A03869	2022-03-22	2023-03-21
<input checked="" type="checkbox"/> Chamber C: Above 1GHz						
SEMT-1319	EMI Test Receiver	Rohde & Schwarz	ESIB 26	100401	2022-01-07	2023-01-06
					2022-12-30	2023-12-29
SEMT-1395	Horn Antenna	POAM	RTF-11A	LP228060221	2022-06-16	2024-06-15
SEMT-1396	Amplifier	Tonscend	TAP01018050	AP22E806235	2022-06-17	2023-06-16
<input checked="" type="checkbox"/> Conducted Room 1#						
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2022-03-21	2023-03-20
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2022-03-25	2023-03-24
SEMT-1003	AC LISN	Schwarz beck	NSLK8126	8126-224	2022-03-22	2023-03-21
<input type="checkbox"/> Conducted Room 2#						
SEMT-1334	EMI Test Receiver	Rohde & Schwarz	ESPI	101259	2022-03-22	2023-03-21

Reference No.: WTX22X12249978W001

SEMT-1336	LISN	Rohde & Schwarz	ENV 216	100097	2022-03-22	2023-03-21
-----------	------	-----------------	---------	--------	------------	------------

Software List			
Description	Manufacturer	Model	Version
EMI Test Software (Radiated Emission)*	Farad	EZ-EMC	RA-03A1
EMI Test Software (Conducted Emission)*	Farad	EZ-EMC	RA-03A1

\*Remark: indicates software version used in the compliance certification testing.

## 2. SUMMARY OF TEST RESULTS

---

FCC Rules	Description of Test Item	Result
§15.203	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§15.209	Radiated Emission	Compliant
§15.225(a)	Field Strength	Compliant
§15.225(b)(c)	Out of Band Emission	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.207(a)	Conducted Emission	Compliant
§15.215(c)	Emission Bandwidth	Compliant

N/A: not applicable.

### **3. Antenna Requirement**

---

#### **3.1 Standard Applicable**

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

#### **3.2 Test Result**

This product has a PCB Antenna, fulfill the requirement of this section.

## 4. Radiated Emissions

---

### 4.1 Standard Applicable

According to §15.225(a), the field strength of any emissions within the band 13.553–13.567MHz shall not exceed 15,848 microvolts/meter at 30 meters.


According to §15.225(d), the field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in §15.209.

Note: Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


### 4.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.225(d) and FCC Part 15.209 Limit.


The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm. The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30MHz to 1GHz.



The test setup for emission measurement above 1GHz.



Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

### 4.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} - \text{Corr. Factor}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dB $\mu$ V means the emission is 6dB $\mu$ V below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Part 15 Limit}$$

#### 4.4 Summary of Test Results/Plots

**Note:** this EUT was tested in 3 orthogonal positions and the worst case position data was reported.

➤ Below 30MHz

Model No.: 9531

Frequency	Reading	Correction Factor	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	X/Y/Z	
13.56	42.54	-2.06	40.48	124.00	-83.52	X	Peak
27.12	41.58	-2.27	39.31	69.50	-30.19	X	Peak
13.56	42.10	-2.06	40.04	124.00	-83.96	Y	Peak
27.12	41.34	-2.27	39.07	69.50	-30.43	Y	Peak
13.56	42.01	-2.06	39.95	124.00	-84.05	Z	Peak
27.12	41.18	-2.27	38.91	69.50	-30.59	Z	Peak


Model No.: 9532

Frequency	Reading	Correction Factor	Result	Limit	Margin	Polar	Detector
MHz	dBuV/m	dB/m	dBuV/m	dBuV/m	dB	X/Y/Z	
13.56	41.35	-2.04	39.31	124.00	-84.69	X	Peak
27.12	40.45	-2.28	38.17	69.50	-31.33	X	Peak
13.56	41.18	-2.04	39.14	124.00	-84.86	Y	Peak
27.12	40.35	-2.28	38.07	69.50	-31.43	Y	Peak
13.56	41.03	-2.04	38.99	124.00	-85.01	Z	Peak
27.12	40.10	-2.28	37.82	69.50	-31.68	Z	Peak




➤ Above 30MHz  
Model No.: 9531

Test Mode	TM1	Polarity:	Horizontal
-----------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (-)	Height (cm)	Remark
1	64.5319	43.83	-9.81	34.02	40.00	-5.98	-	-	peak
2	171.3890	44.44	-9.41	35.03	43.50	-8.47	-	-	peak
3	280.2936	48.37	-9.15	39.22	46.00	-6.78	-	-	peak
4	353.4472	49.10	-7.54	41.56	46.00	-4.44	-	-	peak
5	554.1708	44.92	-3.78	41.14	46.00	-4.86	-	-	peak
6	723.7930	41.68	-0.56	41.12	46.00	-4.88	-	-	peak


Test Mode	TM1	Polarity:	Vertical
-----------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (-)	Height (cm)	Remark
1	51.8999	44.14	-8.21	35.93	40.00	-4.07	-	-	peak
2	79.6764	47.59	-13.08	34.51	40.00	-5.49	-	-	peak
3	164.3129	43.75	-9.06	34.69	43.50	-8.81	-	-	peak
4	280.2936	41.56	-9.15	32.41	46.00	-13.59	-	-	peak
5	516.5651	44.87	-4.94	39.93	46.00	-6.07	-	-	peak
6	723.7930	38.91	-0.56	38.35	46.00	-7.65	-	-	peak


➤ Above 30MHz  
Model No.: 9532

Test Mode	TM1	Polarity:	Horizontal
-----------	-----	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (-)	Height (cm)	Remark
1	79.6764	44.22	-13.09	31.13	40.00	-8.87	-	-	peak
2	171.3889	41.44	-9.41	32.03	43.50	-11.47	-	-	peak
3	280.2934	44.87	-9.15	35.72	46.00	-10.28	-	-	peak
4	353.4470	45.10	-7.54	37.56	46.00	-8.44	-	-	peak
5	554.1707	41.92	-3.78	38.14	46.00	-7.86	-	-	peak
6	723.7930	38.68	-0.56	38.12	46.00	-7.88	-	-	peak

Test Mode	TM1	Polarity:	Vertical
-----------	-----	-----------	----------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (-)	Height (cm)	Remark
1	51.8997	42.64	-8.21	34.43	40.00	-5.57	-	-	peak
2	79.6764	46.60	-13.09	33.51	40.00	-6.49	-	-	peak
3	164.3129	42.75	-9.06	33.69	43.50	-9.81	-	-	peak
4	516.5650	42.37	-4.94	37.43	46.00	-8.57	-	-	peak
5	723.7930	36.41	-0.56	35.85	46.00	-10.15	-	-	peak
6	972.2826	33.77	3.21	36.98	54.00	-17.02	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics.

## 5. OUT OF BAND EMISSIONS

---

### 5.1 Standard Applicable

According to FCC 15.225 (b), within the bands 13.410–13.553MHz and 13.567–13.710MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters. (c) Within the bands 13.110–13.410MHz and 13.710–14.010MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.


### 5.2 Test Procedure

As the radiation test, set the RBW=10kHz VBW=30kHz, observed the outside band of 13.11MHz to 14.01MHz, than mark the higher-level emission for comparing with the FCC rules.

### 5.3 Summary of Test Results/Plots

**Note:** *this EUT was tested in 3 orthogonal positions and the worst case position data was reported.*

Test Mode	TM1	Polarity:	/
-----------	-----	-----------	---



No.	Frequency (MHz)	Reading (dBuV/m)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree (°)	Height (cm)	Remark
1	13.3773	38.89	-5.00	33.89	80.50	-46.61	-	-	peak
2	13.4960	38.87	-4.98	33.89	90.50	-56.61	-	-	peak
3	13.5534	49.05	-4.95	44.10	124.00	-79.90	-	-	peak
4	13.6256	38.64	-4.94	33.70	90.50	-56.80	-	-	peak
5	13.8188	38.96	-4.91	34.05	80.50	-46.45	-	-	peak

Remark: '-' Means the test Degree and Height are not recorded by the test software and only show the worst case in the test report.

## 6. Frequency Stability

---

### 6.1 Standard Applicable

According to 15.225(e), the frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### 6.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure.

### 6.3 Summary of Test Results/Plots

Reference Frequency: 13.56MHz, Limit: 100ppm				
Voltage(%)	Power(VDC)	TEMP(°C)	Freq.Dev(Hz)	Deviation(ppm)
100%	12	-30	110	8
100%		-20	124	13
100%		-10	136	16
100%		0	109	8
100%		+10	106	7
100%		+20	102	5
100%		+30	108	7
100%		+40	112	9
100%		+50	122	12
Low		10.2	+20	117
High	13.8	+20	108	8

## 7. EMISSION BANDWIDTH

---

### 7.1 Applicable Standard

According to 15.215(c), intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### 7.2 Test Procedure

According to the ANSI 63.10-2013, the emission bandwidth test method as follows.

Set span =  $1\sim 5 * EBW$ , centered on a transmitting channel

RBW =  $1\%\sim 5\% * EBW$ , VBW =  $3 * RBW$

Sweep = auto

Detector function = peak

Trace = max hold

All the trace to stabilize, use the marker-to-peak function to set the marker to the peak of the emission, use the marker-delta function to measure and record the 20dB down of the emission.


### 7.3 Summary of Test Results/Plots

Tx Frequency	20dB Emission bandwidth(KHz)
13.56MHz	0.082



Reference No.: WTX22X12249978W001

Please refer to the test plots as below:



Date: 14.DEC.2022 09:33:56

Note: The RBW of the analyzer measuring Bandwidth cannot be adjusted to 1%-5% 20dB Bandwidth, the RBW of the test setting is the closest value.

## 8. Conducted Emissions


---

### 8.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40cm long in the middle. The spacing between the peripherals was 10cm.

### 8.2 Basic Test Setup Block Diagram



### 8.3 Test Receiver Setup


During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency .....	150kHz
Stop Frequency .....	30MHz
Sweep Speed .....	Auto
IF Bandwidth.....	10kHz
Quasi-Peak Adapter Bandwidth .....	9kHz
Quasi-Peak Adapter Mode .....	Normal

### 8.4 Summary of Test Results/Plots


Model No.: 9531

Test Mode	TM1(AC120V 60Hz)	Polarity:	Neutral
-----------	------------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2580	12.12	10.26	22.38	51.49	-29.11	AVG
2	0.2620	22.86	10.26	33.12	61.36	-28.24	QP
3*	0.5580	25.03	10.21	35.24	56.00	-20.76	QP
4	0.5580	13.25	10.21	23.46	46.00	-22.54	AVG
5	0.7780	13.11	10.17	23.28	46.00	-22.72	AVG
6	0.8940	20.45	10.15	30.60	56.00	-25.40	QP
7	1.5220	8.57	10.20	18.77	46.00	-27.23	AVG
8	1.9420	17.41	10.24	27.65	56.00	-28.35	QP
9	9.4780	-1.69	10.35	8.66	50.00	-41.34	AVG
10	11.1500	13.08	10.33	23.41	60.00	-36.59	QP
11	16.3140	15.24	10.28	25.52	60.00	-34.48	QP
12	17.4420	-1.78	10.30	8.52	50.00	-41.48	AVG


Test Mode	TM1(AC120V 60Hz)	Polarity:	Line
-----------	------------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2819	22.44	10.25	32.69	60.76	-28.07	QP
2	0.3220	12.43	10.24	22.67	49.65	-26.98	AVG
3*	0.5580	25.73	10.21	35.94	56.00	-20.06	QP
4	0.5580	15.30	10.21	25.51	46.00	-20.49	AVG
5	1.4220	19.83	10.18	30.01	56.00	-25.99	QP
6	1.4740	8.57	10.19	18.76	46.00	-27.24	AVG
7	3.8500	11.25	10.30	21.55	56.00	-34.45	QP
8	3.8940	-0.88	10.30	9.42	46.00	-36.58	AVG
9	11.2020	12.65	10.33	22.98	60.00	-37.02	QP
10	11.8460	-1.68	10.31	8.63	50.00	-41.37	AVG
11	19.3660	-1.97	10.36	8.39	50.00	-41.61	AVG
12	21.1860	12.85	10.37	23.22	60.00	-36.78	QP


Model No.: 9532

Test Mode	TM1(AC120V 60Hz)	Polarity:	Neutral
-----------	------------------	-----------	---------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.3500	25.95	10.28	36.23	58.96	-22.73	QP
2	0.3660	14.27	10.28	24.55	48.59	-24.04	AVG
3*	0.7780	13.48	10.18	23.66	46.00	-22.34	AVG
4	0.9460	23.13	10.15	33.28	56.00	-22.72	QP
5	1.5020	21.70	10.24	31.94	56.00	-24.06	QP
6	1.6220	9.06	10.26	19.32	46.00	-26.68	AVG
7	2.6060	3.65	10.34	13.99	46.00	-32.01	AVG
8	2.8460	15.34	10.34	25.68	56.00	-30.32	QP
9	6.6700	12.27	10.38	22.65	60.00	-37.35	QP
10	7.7020	0.85	10.38	11.23	50.00	-38.77	AVG
11	12.2460	1.10	10.30	11.40	50.00	-38.60	AVG
12	12.7820	12.16	10.29	22.45	60.00	-37.55	QP

Test Mode	TM1(AC120V 60Hz)	Polarity:	Line
-----------	------------------	-----------	------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.2740	25.14	10.33	35.47	60.99	-25.52	QP
2	0.2779	12.35	10.31	22.66	50.88	-28.22	AVG
3*	0.4219	26.12	10.26	36.38	57.41	-21.03	QP
4	0.4219	14.74	10.26	25.00	47.41	-22.41	AVG
5	0.6660	22.19	10.20	32.39	56.00	-23.61	QP
6	0.7780	13.17	10.18	23.35	46.00	-22.65	AVG
7	1.0500	20.62	10.14	30.76	56.00	-25.24	QP
8	1.2579	9.54	10.19	19.73	46.00	-26.27	AVG
9	3.5939	1.79	10.36	12.15	46.00	-33.85	AVG
10	3.6539	15.59	10.36	25.95	56.00	-30.05	QP
11	11.5939	13.08	10.33	23.41	60.00	-36.59	QP
12	12.1180	0.66	10.31	10.97	50.00	-39.03	AVG

## APPENDIX PHOTOGRAPHS

---

Please refer to "ANNEX"

\*\*\*\* END OF REPORT \*\*\*\*