



# Appendix for 2.4G WiFi (RSE)



# 1. Appendix H: Radiated Spurious Emission & Spurious in Restricted Band

Note:

- 1. We tested all modes & antennas, the data presented below is the worst case.
- 2. The simultaneous transmission has been considered

3. The whole testing range is from "9 KHz to 26.5 GHz (10th harmonics)" is divided into 5 parts according to the test site settings, which are:

- (Part 1): Test range of "9 KHz to 30 MHz", RBW =9 kHz, VBW = 30 kHz
- (Part 2): Test range of "30 GHz to 1 GHz", RBW = 100 kHz, VBW = 300 kHz.
- (Part 3): Test range of "1 GHz to 3 GHz". RBW = 1 MHz, VBW = 3 MHz.
- (Part 4): Test range of "3 GHz to 18 GHz", RBW = 1 MHz, VBW = 3 MHz.
- (Part 5): Test range of "18 GHz to 26.5 GHz". RBW = 1 MHz, VBW = 3 MHz.

#### 1.1. Test Results

#### 1.1.1. 11b20SISO

Test Mode	Antenna Port	Test Channel	Spurious Emissions Result	Spurious Emissions Limit	Verdict
11b20SISO	Ant1	2412	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2462	(see Test Graphs)	(see Test Graphs)	PASS



# 1.1.2. 11g20SISO

Test Mode	Antenna Port	Test Channel	Spurious Emissions Result	Spurious Emissions Limit	Verdict
	Ant1	2412	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2417	(see Test Graphs)	(see Test Graphs)	PASS
11g20SISO	Ant1	2457	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2462	(see Test Graphs)	(see Test Graphs)	PASS

#### 1.1.3. 11n20SISO

Test Mode	Antenna Port	Test Channel	Spurious Emissions Result	Spurious Emissions Limit	Verdict
	Ant1	2412	(see Test Graphs)	(see Test Graphs)	PASS
11n20SISO	Ant1	2417	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2457	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2462	(see Test Graphs)	(see Test Graphs)	PASS



# 1.1.4. 11n40SISO

Test Mode	Antenna Port	Test Channel	Spurious Emissions Result	Spurious Emissions Limit	Verdict
	Ant1	2422	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2427	(see Test Graphs)	(see Test Graphs)	PASS
11n40SISO	Ant1	2432	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2442	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2447	(see Test Graphs)	(see Test Graphs)	PASS
	Ant1	2452	(see Test Graphs)	(see Test Graphs)	PASS



## 1.2. Test Graphs

#### 1.2.1. Part 1: Testing Range of "9 kHz to 30MHz"

Note 1: The test results and plot for testing range of "9 kHz to 30MHz" showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.



# 1.2.2. Part 2: Testing Range of "30 MHz to 1 GHz"

Note 1: The test results and plot for testing range of "30 MHz to 1 GHz" showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.





#### MEASUREMENT RESULT: QP Detector

Frequency	Level	Transd	Limit	Margin	Height	Azimuth	
MHz	dBµV/m	dB	dBµV/m	dB	cm	deg	Polarisation
51.825000	27.21	329.0	40.00	12.79	100.0	329.0	V
92.177000	27.01	196.0	43.50	16.49	100.0	196.0	V
154.499500	28.31	164.0	43.50	15.19	100.0	164.0	V
296.313500	25.99	49.0	46.00	20.01	100.0	49.0	Н
596.480000	31.15	9.0	46.00	14.85	100.0	9.0	Н
914.931000	35.96	112.0	46.00	10.04	100.0	112.0	Н

# 1.2.3. Part 3: Testing Range of "1 GHz to 3 GHz"

Note 1: The testing range of "1 GHz to 3 GHz" is for checking radiated emissions located in restricted bands near the EUT operating bands. The test results and plot for testing range of "1 GHz to 3 GHz" showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).

Note 3: The peak spike exceeds the limit line is EUT's operating frequency.



## 1.2.3.1. 11b20SISO







# 1.2.3.2. 11g20SISO









## 1.2.3.3. 11n20SISO









## 1.2.3.4. 11n40SISO











## 1.2.4. Part 4: Testing Range of "3 GHz to 18 GHz"

Note 1: The test results and plot for testing range of "3 GHz to 18 GHz" showed as below is the worst case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The testing range of "3 GHz to 18 GHz" is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.

Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).



## 1.2.5. Part 5: Testing Range of "18 GHz to 26.5 GHz"

Note 1: The test results and plot for testing range of "18 GHz to 26.5 GHz" showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2: The testing range of "18 GHz to 26.5 GHz" is for checking radiated emissions located in restricted bands faraway from the EUT operating bands.

Note 3: Two limits are required in the testing range above 1 GHz, that is Peak limit (74 dB $\mu$ V/m) and Average Limit (54 dB $\mu$ V/m).



# 2. Appendix I: Conducted Emission at Power Port

Note 1: The test results and plot for testing range of "150 kHz to 30 MHz" showed as below is the WORST case for all Test Modes and Channels. This range will not be presented for each Test Mode and each Channel.

Note 2 : RBW =9 kHz; VBW = 30 kHz

#### 2.1. Test Results

Test Mode	Antenna Port	Test Channel	Maximum Emissions	Limit	Verdict
11n20SISO	Ant1	2417	(see Test Graphs)	(see Test Graphs)	PASS



# 2.2. Test Graphs



## Note: Not found obvious spikes or see marked spikes on plots and listed emissions records.

# **MEASUREMENT RESULT: QP Detector**

Frequency	Level	Limit	Transd.	Margin	Line	PE
(MHz)	(dBµV)	(dBµV)	(dB)	(dB)		
0.153731	54.27	65.80	9.6	11.53	Ν	FLO
0.172388	50.57	64.85	9.6	14.28	L1	FLO
0.187313	48.49	64.16	9.6	15.67	L1	FLO
0.2694	44.43	61.14	9.7	16.71	N	FLO
0.437306	37.55	57.11	9.7	19.56	N	FLO
0.705956	39.28	56.00	9.6	16.72	L1	FLO

#### **MEASUREMENT RESULT: AV Detector**

Frequency	Level	Limit	Transd.	Margin	Line	PE
(MHz)	(dBµV)	(dBµV)	(dB)	(dB)		
0.172388	37.45	54.85	9.6	17.40	Ν	FLO
0.2694	39.58	51.14	9.7	11.57	N	FLO
0.437306	29.17	47.11	9.7	17.94	N	FLO
0.705956	33.09	46.00	9.7	12.91	N	FLO
0.89625	30.25	46.00	9.7	15.75	Ν	FLO

Report No.: SYBH(Z-RF)20221017002001-2004-B



1.855181	31.64	46.00	9.8	14.36	Ν	FLO		
Note:								
1, Level =Reading lev	1, Level =Reading level by receiver + Transd (Antenna factor + cable loss – preamplifier gain)							
The reading level is calculated by software which is not shown in the sheet.								
2, Margin=Limit - Level								

END