



EMC TEST REPORT

Applicant Huawei Device Co., Ltd.
FCC ID 2ATEYJPT-B29
Product Smart Watch
Model JPT-B29
Report No. R2111A0986-E1
Issue Date November 29, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC Code CFR47 Part15B (2020)/ ANSI C63.4 (2014)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Wei Liu

Prepared by: Wei Liu

Guangchang Fan

Approved by: Guangchang Fan

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

1	Test Laboratory.....	4
1.1	Notes of the Test Report.....	4
1.2	Test facility.....	4
1.3	Testing Location.....	4
2	General Description of Equipment under Test.....	5
2.1	Applicant and Manufacturer Information.....	5
2.2	General information.....	5
2.3	Applied Standards.....	6
2.4	Test Mode.....	7
3	Test Case Results.....	8
3.1	Radiated Emission.....	8
3.2	Conducted Emission.....	14
4	Main Test Instruments.....	17
	ANNEX A: The EUT Appearance.....	18
	ANNEX B: Test Setup Photos.....	19



Summary of measurement results

Number	Test Case	Clause in FCC Rules	Conclusion
1	Radiated Emission	FCC Part15.109, ANSI C63.4-2014	PASS
2	Conducted Emission	FCC Part15.107, ANSI C63.4-2014	PASS
Date of Testing: November 11, 2021 ~ November 15, 2021			
Date of Sample Received: November 8, 2021			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Fan Guangchang
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: fanguangchang@ta-shanghai.com

2 General Description of Equipment under Test

2.1 Applicant and Manufacturer Information

Applicant	Huawei Device Co., Ltd.
Applicant address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China
Manufacturer	Huawei Device Co., Ltd.
Manufacturer address	No.2 of Xincheng Road, Songshan Lake Zone, Dongguan, Guangdong 523808, People's Republic of China

2.2 General information

EUT Description			
Device Type	Portable Device		
Model	JPT-B29		
SN	EEDTQ21915000002		
HW Version	R0		
SW Version	2.1.0.197SP1		
Power Rating	DC 3.82V from battery		
Connecting I/O Port(s)	Please refer to the User's Manual.		
Antenna Type	Internal Antenna		
Frequency	Band	Tx (MHz)	Rx (MHz)
	Bluetooth	2400 ~ 2483.5	2400 ~ 2483.5
	WIFI 2.4G	2400 ~ 2483.5	2400 ~ 2483.5
	NFC	13.56	13.56
	WPT	110.5~148kHz	
EUT Accessory			
Accessory	Model	Manufacture	No.
Battery	HB532729ECW	Trademark:Huawei Technologies Co., Ltd. Factory:Tianjin lishen battery joint-stock Co.,LTD.	1
	HB532729ECW	Trademark:Huawei Technologies Co., Ltd. Factory:Dongguan NVT Technology Co.,LTD.	2
Charging dock	CP81-1	Huawei Device Co., Ltd.	1
<p>Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.</p> <p>2. There are more than one Battery , each one should be applied throughout the compliance test respectively, however, only the worst case (Battery 2)will be recorded in this report.</p>			



2.3 Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards

FCC Code CFR47 Part15B (2020)

ANSI C63.4 (2014)

2.4 Test Mode

Test Mode	
Mode 1	Charging dock + EUT power ON + Receiver
Mode 2	Charging dock + EUT power ON + Mp3
Mode 3	EUT power ON + Receiver
Mode 4	EUT power ON + Mp3

During the test, the preliminary test was performed in all modes with all batteries, mode 1 with Battery 2 is selected as the worst condition. The test data of the worst-case condition was recorded in this report.

3 Test Case Results

3.1 Radiated Emission

Ambient condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table 0.8m above the horizontal metal reference ground plane. The distance between EUT and receive antenna should be 3 meters. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier. During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turn table shall be rotated from 0 to 360 degrees for detecting the maximum of radiated signal level.

The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing. During the test, the EUT is worked at maximum output power.

Set the spectrum analyzer in the following:

Below 1GHz:

RBW=100 kHz / VBW=300 kHz / Sweep=AUTO

Above 1GHz:


(a) PEAK Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO

(b) AVERAGE Detector: RBW=1MHz / VBW=3MHz / Sweep=AUTO


The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (X axis) and the worst case was recorded.

Test Setup

Below 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m

Antenna Tower meets ANSI C63.4 requirements for measurements above 1 GHz by keeping the antenna aimed at the EUT during the antenna's ascent/ descent along the antenna mast.

Limits

Class B

Frequency (MHz)	Field Strength (dB μ V/m)	Detector
30 -88	40.0	Quasi-peak
88-216	43.5	Quasi-peak
216 – 960	46.0	Quasi-peak
960-1000	54.0	Quasi-peak
1000-5 th harmonic of the highest frequency or 40GHz, which is lower	54 74	Average Peak

Measurement Uncertainty


The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
30MHz~200MHz	4.17 dB
200MHz~1000MHz	4.84 dB
1GHz~18GHz	4.35 dB
18GHz~26.5GHz	5.90 dB
26.5GHz~40GHz	5.92 dB

Test Results

Sweep the whole frequency band through the range from 30MHz to the 5th harmonic of the carrier, the Emissions in the frequency band 18GHz –40GHz is more than 20dB below the limit are not reported.


The following graphs display the maximum values of horizontal and vertical by software.
 For above 1GHz, Blue trace uses the peak detection, Green trace uses the average detection.
 A font (Level in dB \square V/) in the test plot =(level in dB μ V/m)



Radiated Emission from 30MHz to 1GHz


Frequency (MHz)	Quasi-Peak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
36.552000	15.15	40.00	24.85	1000.0	100.0	V	182.0	18
52.117667	19.46	40.00	20.54	1000.0	100.0	V	339.0	20
101.712667	13.34	43.50	30.16	1000.0	109.0	V	245.0	19
202.690667	12.47	43.50	31.03	1000.0	109.0	H	194.0	18
327.052333	15.96	46.00	30.04	1000.0	110.0	V	305.0	21
482.210667	23.65	46.00	22.35	1000.0	100.0	V	102.0	24

- Remark: 1. Correction Factor = Antenna factor + Insertion loss(cable loss+amplifier gain)
- 2. Margin = Limit – Quasi-Peak




Radiated Emission from 1GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Average (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)
1458.433333	34.32	---	74.00	39.68	500.0	100.0	H	277.0	-16
1612.566667	---	23.93	54.00	30.07	500.0	200.0	V	145.0	-15
2604.800000	37.28	---	74.00	36.72	500.0	100.0	H	167.0	-10
2620.100000	---	27.62	54.00	26.38	500.0	200.0	V	343.0	-10
4114.966667	---	32.35	54.00	21.65	500.0	100.0	H	7.0	-3
4167.100000	42.31	---	74.00	31.69	500.0	200.0	H	43.0	-3
5401.866667	43.67	---	74.00	30.33	500.0	200.0	V	293.0	-1
5716.933333	---	33.95	54.00	20.05	500.0	200.0	V	123.0	0
8052.733333	---	34.52	54.00	19.48	500.0	200.0	H	6.0	2
8529.866667	46.07	---	74.00	27.93	500.0	200.0	V	198.0	4
10222.500000	47.36	---	74.00	26.64	500.0	100.0	V	143.0	5
10228.166667	---	37.52	54.00	16.48	500.0	200.0	V	242.0	5



Radiated Emission from 18GHz to 26.5GHz



Radiated Emission from 26.5GHz to 40GHz

3.2 Conducted Emission


Ambient condition

Temperature	Relative humidity	Pressure
15°C~35°C	30%~60%	101.5kPa

Methods of Measurement

The EUT is placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.4-2014. Connect the AC power line of the EUT to the L.I.S.N. Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9 kHz, VBW is set to 30kHz. The measurement result should include both L line and N line.

Test Setup



Note: Power Supply is AC Power source and it is used to change the voltage 120V/60Hz.

Limits

Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50


*: Decreases with the logarithm of the frequency.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$. $U = 2.57$ dB.

Test Results

Following plots, Blue trace uses the peak detection; Green trace uses the average detection.




Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.31	37.94	---	59.98	22.04	70.0	9.000	L1	ON	21
0.31	---	30.76	49.92	19.16	70.0	9.000	L1	ON	21
0.47	---	31.03	46.52	15.49	70.0	9.000	L1	ON	20
0.47	40.13	---	56.52	16.39	70.0	9.000	L1	ON	20
0.93	31.50	---	56.00	24.50	70.0	9.000	L1	ON	20
0.93	---	22.34	46.00	23.66	70.0	9.000	L1	ON	20
2.33	28.15	---	56.00	27.85	70.0	9.000	L1	ON	19
2.52	---	20.15	46.00	25.85	70.0	9.000	L1	ON	19
5.44	---	16.79	50.00	33.21	70.0	9.000	L1	ON	19
6.41	20.93	---	60.00	39.07	70.0	9.000	L1	ON	19
29.08	---	15.65	50.00	34.35	70.0	9.000	L1	ON	20
29.61	19.43	---	60.00	40.57	70.0	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line

Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.31	40.96	---	59.92	18.96	70.0	9.000	N	ON	21
0.31	---	32.53	49.86	17.33	70.0	9.000	N	ON	21
0.47	---	33.42	46.52	13.10	70.0	9.000	N	ON	20
0.47	42.83	---	56.52	13.69	70.0	9.000	N	ON	20
0.92	33.10	---	56.00	22.90	70.0	9.000	N	ON	20
1.74	---	26.13	46.00	19.87	70.0	9.000	N	ON	20
2.34	31.58	---	56.00	24.42	70.0	9.000	N	ON	20
3.08	---	24.25	46.00	21.75	70.0	9.000	N	ON	19
5.23	26.96	---	60.00	33.04	70.0	9.000	N	ON	19
5.23	---	21.20	50.00	28.80	70.0	9.000	N	ON	19
14.95	19.56	---	60.00	40.44	70.0	9.000	N	ON	20
29.61	---	23.39	50.00	26.61	70.0	9.000	N	ON	20

Remark: Correct factor=cable loss + LISN factor

N line

Conducted Emission from 150 KHz to 30 MHz

4 Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Time
Spectrum Analyzer	R&S	FSV40	100815	2020-12-13	2021-12-12
EMI Test Receiver	R&S	ESR	102389	2020-12-13	2021-12-12
Trilog Antenna	Schwarzbeck	BBHA 9120D	430	2018-07-07	2023-07-06
Horn Antenna	STEATITE	QSH-SL-26-40-K-15	16779	2019-12-24	2022-12-23
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2023-06-19
EMI Test Receiver	R&S	ESR	101667	2021-05-16	2022-05-15
LISN	R&S	ENV216	102191	2020-12-13	2022-12-12
Test software	EMC32	R&S	9.26.01	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.