

# FCC and ISED Test Report


## Disruptive Technologies Research AS

### Model: SDS Module (US)

In accordance with FCC 47 CFR Part 15C, ISED RSS-247 and ISED RSS-GEN (Short Range Device)

Prepared for: Disruptive Technologies Research AS  
Strandveien 17  
1366 Lysaker  
Norway

FCC ID: 2ATFX-102545 IC: 25087-102545



## COMMERCIAL-IN-CONFIDENCE

Document 75954295-04 Issue 01

### SIGNATURE

NAME	JOB TITLE	RESPONSIBLE FOR	ISSUE DATE
Steve Marshall	Senior Engineer	Authorised Signatory	10 August 2022

Signatures in this approval box have checked this document in line with the requirements of TÜV SÜD document control rules.

### ENGINEERING STATEMENT

The measurements shown in this report were made in accordance with the procedures described on test pages. All reported testing was carried out on a sample equipment to demonstrate limited compliance with FCC 47 CFR Part 15C, ISED RSS-247 and ISED RSS-GEN. The sample tested was found to comply with the requirements defined in the applied rules.

RESPONSIBLE FOR	NAME	DATE	SIGNATURE
Testing	Daniel Cameron	10 August 2022	
Testing	Graeme Lawler	10 August 2022	

FCC Accreditation  
90987 Octagon House, Fareham Test Laboratory

ISED Accreditation  
12669A Octagon House, Fareham Test Laboratory

### EXECUTIVE SUMMARY

A sample of this product was tested and found to be compliant with FCC 47 CFR Part 15C: 2020, ISED RSS-247: Issue 2 (02-2017) and ISED RSS-GEN: Issue 5 (04-2018) + A2 (02-2021) for the tests detailed in section 1.3.



### DISCLAIMER AND COPYRIGHT

This non-binding report has been prepared by TÜV SÜD with all reasonable skill and care. The document is confidential to the potential Client and TÜV SÜD. No part of this document may be reproduced without the prior written approval of TÜV SÜD. © 2022 TÜV SÜD. This report relates only to the actual item/items tested.

### ACCREDITATION

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation. Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

TÜV SÜD  
is a trading name of TÜV SÜD Ltd  
Registered in Scotland at East Kilbride,  
Glasgow G75 0QF, United Kingdom  
Registered number: SC215164

TÜV SÜD Ltd is a  
TÜV SÜD Group Company

Phone: +44 (0) 1489 558100  
Fax: +44 (0) 1489 558101  
[www.tuvsud.com/en](http://www.tuvsud.com/en)

TÜV SÜD  
Octagon House  
Concorde Way  
Fareham  
Hampshire PO15 5RL  
United Kingdom



## Contents

<b>1</b>	<b>Report Summary .....</b>	<b>2</b>
1.1	Report Modification Record.....	2
1.2	Introduction.....	2
1.3	Brief Summary of Results .....	3
1.4	Application Form .....	4
1.5	Product Information .....	7
1.6	Deviations from the Standard.....	7
1.7	EUT Modification Record .....	7
1.8	Test Location.....	8
<b>2</b>	<b>Test Details .....</b>	<b>9</b>
2.1	Emission Bandwidth .....	9
2.2	Maximum Conducted Output Power .....	19
2.3	Spurious Radiated Emissions .....	27
2.4	Authorised Band Edges .....	152
2.5	Power Spectral Density .....	160
2.6	Frequency Hopping Systems - 20 dB Bandwidth .....	163
2.7	Frequency Hopping Systems - Channel Separation.....	167
2.8	Frequency Hopping Systems - Average Time of Occupancy .....	170
2.9	Frequency Hopping Systems - Number of Hopping Channels .....	173
<b>3</b>	<b>Photographs .....</b>	<b>176</b>
3.1	Test Setup Photographs .....	176
<b>4</b>	<b>Measurement Uncertainty .....</b>	<b>182</b>



# 1 Report Summary

## 1.1 Report Modification Record

Alterations and additions to this report will be issued to the holders of each copy in the form of a complete document.

Issue	Description of Change	Date of Issue
1	First Issue	10-August-2022

Table 1

## 1.2 Introduction

Applicant	Disruptive Technologies Research AS
Manufacturer	Disruptive Technologies Research AS
Model Number(s)	SDS Module (US)
Serial Number(s)	US 2 and US 1
Hardware Version(s)	0
Software Version(s)	0.1.0
Number of Samples Tested	2
Test Specification/Issue/Date	FCC 47 CFR Part 15C: 2020 ISED RSS-247: Issue 2 (02-2017) ISED RSS-GEN: Issue 5 (04-2018) + A2 (02-2021)
Order Number	PO-DK-15
Date	12-January-2022
Date of Receipt of EUT	31-March-2022
Start of Test	02-May-2022
Finish of Test	24-June-2022
Name of Engineer(s)	Daniel Cameron and Graeme Lawler
Related Document(s)	ANSI C63.10 (2020)



### 1.3 Brief Summary of Results

A brief summary of the tests carried out in accordance with FCC 47 CFR Part 15C, ISED RSS-247 and ISED RSS-GEN is shown below.

Section	Specification Clause			Test Description	Result	Comments/Base Standard
	FCC Part 15C	RSS-247	RSS-GEN			
Configuration and Mode: Radio chip/PCB combination - Standard						
-	15.203	-	-	Antenna Requirements	Pass	The device complies with the provisions of this section, as it uses permanently attached integral antennas.
2.1	15.247 (a)(2)	5.2	6.7	Emission Bandwidth	Pass	
2.2	15.247 (b)	5.4	6.12	Maximum Conducted Output Power	Pass	
2.3	15.247 (d) and 15.209	3.3 and 5.5	6.13 and 8.9	Spurious Radiated Emissions	Pass	
2.4	15.247 (d)	5.5	-	Authorised Band Edges	Pass	
2.5	15.247 (e)	5.2	6.12	Power Spectral Density	Pass	
Configuration and Mode: Radio chip/PCB combination - Boost						
2.6	15.247 (a)(1)	5.1	6.7	Frequency Hopping Systems - 20 dB Bandwidth	Pass	
2.7	15.247 (a)(1)	5.1	-	Frequency Hopping Systems - Channel Separation	Pass	
2.8	15.247 (a)(1)	5.1	-	Frequency Hopping Systems - Average Time of Occupancy	Pass	
2.9	15.247 (a)(1)	5.1	-	Frequency Hopping Systems - Number of Hopping Channels	Pass	
2.2	15.247 (b)	5.4	6.12	Maximum Conducted Output Power	Pass	
2.3	15.247 (d) and 15.209	3.3 and 5.5	6.13 and 8.9	Spurious Radiated Emissions	Pass	
2.4	15.247 (d)	5.5	-	Authorised Band Edges	Pass	

**Table 2**



## 1.4 Application Form

### Equipment Description

Technical Description: <i>(Please provide a brief description of the intended use of the equipment including the technologies the product supports)</i>	The SDS Module (US) is designed to support the proprietary Disruptive Technologies RF protocol, Secure Data Shot (SDS). The module shall be used in products for establishing an RF link with SDS enabled devices. The SDS Module has two antennas and two radio modes.	
Manufacturer:	Zollner Elektronik AG, Manfred-Zollner-Str. 1, 93499 Zandt, Germany	
Model:	SDS Module (US)	
Part Number:	102545	
Hardware Version:	0	
Software Version:	0.1.0	
FCC ID of the product under test – <a href="#">see guidance here</a>	2ATFX-102545	
IC ID of the product under test – <a href="#">see guidance here</a>	25087-102545	

**Table 3**

### Intentional Radiators

Technology	SDS
Frequency Range (MHz to MHz)	903.250 to 926.750 (Standard) 902.775 to 927.225 (Boost)
Conducted Declared Output Power (dBm)	18 (Standard) 17 (Boost)
Antenna Gain (dBi)	-1.0 (Ant 1) -1.6 (Ant 2)
Supported Bandwidth(s) (MHz) (e.g. 1 MHz, 20 MHz, 40 MHz)	0.536 (Standard) 0.155 (Boost)
Modulation Scheme(s) (e.g. GFSK, QPSK etc)	GFSK
ITU Emission Designator <a href="#">(see guidance here)</a> (not mandatory for Part 15 devices)	
Bottom Frequency (MHz)	902.775
Middle Frequency (MHz)	915.000
Top Frequency (MHz)	927.225

**Table 4**



Un-intentional Radiators

Highest frequency generated or used in the device or on which the device operates or tunes	927.225 MHz
Lowest frequency generated or used in the device or on which the device operates or tunes	902.775 MHz
Class A Digital Device (Use in commercial, industrial or business environment) <b>X</b>	
Class B Digital Device (Use in residential environment only) <input type="checkbox"/>	

**Table 5**

AC Power Source

AC supply frequency:		Hz
Voltage		V
Max current:		A
Single Phase <input type="checkbox"/> Three Phase <input type="checkbox"/>		

**Table 6**

DC Power Source

Nominal voltage:	5	V
Extreme upper voltage:	5.25	V
Extreme lower voltage:	4.5	V
Max current:	1	A

**Table 7**

Battery Power Source

Voltage:		V
End-point voltage:		V (Point at which the battery will terminate)
Alkaline <b>X</b> Leclanche <input type="checkbox"/> Lithium <input type="checkbox"/> Nickel Cadmium <input type="checkbox"/> Lead Acid* <input type="checkbox"/> *(Vehicle regulated)		
Other <input type="checkbox"/>	Please detail:	

**Table 8**

Charging

Can the EUT transmit whilst being charged	Yes <input type="checkbox"/> No <b>X</b>
---	--

**Table 9**



Temperature

Minimum temperature:	-20	°C
Maximum temperature:	70	°C

**Table 10**

Cable Loss

Adapter Cable Loss (Conducted sample)	0	dB
--	---	----

**Table 11**

Antenna Characteristics

Antenna connector <input type="checkbox"/>			State impedance		Ohm
Temporary antenna connector <b>X</b>			State impedance	50	Ohm
Integral antenna <b>X</b>	Type:	PIFA Plate PCB antenna	Gain	-1.0 (Ant 1) -1.6 (Ant 2)	dBi
External antenna <input type="checkbox"/>	Type:		Gain		dBi
For external antenna only: Standard Antenna Jack <input type="checkbox"/> If yes, describe how user is prohibited from changing antenna (if not professional installed): Equipment is only ever professionally installed <input type="checkbox"/> Non-standard Antenna Jack <input type="checkbox"/>					

**Table 12**

Ancillaries (if applicable)

Manufacturer:		Part Number:	
Model:		Country of Origin:	

**Table 13**

I hereby declare that the information supplied is correct and complete.

Name: Øystein Moldsvor  
 Position held: VP Engineering  
 Date: 25 May 2022



## 1.5 Product Information

### 1.5.1 Technical Description

The SDS Module (US) is designed to support the proprietary Disruptive Technologies RF protocol, Secure Data Shot (SDS). The module shall be used in products for establishing an RF link with SDS enabled devices. The SDS Module has two antennas and two radio modes.

### 1.6 Deviations from the Standard

No deviations from the applicable test standard were made during testing.

### 1.7 EUT Modification Record

The table below details modifications made to the EUT during the test programme.

The modifications incorporated during each test are recorded on the appropriate test pages.

Modification State	Description of Modification still fitted to EUT	Modification Fitted By	Date Modification Fitted
Model: SDS Module (US), Serial Number: US 2			
0	As supplied by the customer	Not Applicable	Not Applicable
Model: SDS Module (US), Serial Number: US 1			
0	As supplied by the customer	Not Applicable	Not Applicable

**Table 14**



**1.8 Test Location**

TÜV SÜD conducted the following tests at our Fareham Test Laboratory.

Test Name	Name of Engineer(s)	Accreditation
Configuration and Mode: Radio chip/PCB combination - Standard		
Emission Bandwidth	Daniel Cameron	UKAS
Maximum Conducted Output Power	Daniel Cameron	UKAS
Spurious Radiated Emissions	Graeme Lawler	UKAS
Authorised Band Edges	Graeme Lawler	UKAS
Power Spectral Density	Daniel Cameron	UKAS
Configuration and Mode: Radio chip/PCB combination - Boost		
Frequency Hopping Systems - 20 dB Bandwidth	Daniel Cameron	UKAS
Frequency Hopping Systems - Channel Separation	Daniel Cameron	UKAS
Frequency Hopping Systems - Average Time of Occupancy	Daniel Cameron	UKAS
Frequency Hopping Systems - Number of Hopping Channels	Daniel Cameron	UKAS
Maximum Conducted Output Power	Daniel Cameron	UKAS
Spurious Radiated Emissions	Graeme Lawler	UKAS
Authorised Band Edges	Graeme Lawler	UKAS

**Table 15**

Office Address:

TÜV SÜD  
 Octagon House  
 Concorde Way  
 Fareham  
 Hampshire  
 PO15 5RL  
 United Kingdom



## 2 Test Details

### 2.1 Emission Bandwidth

#### 2.1.1 Specification Reference

FCC 47 CFR Part 15C, Clause 15.247 (a)(2)  
ISED RSS-247, Clause 5.2  
ISED RSS-GEN, Clause 6.7

#### 2.1.2 Equipment Under Test and Modification State

SDS Module (US), S/N: US 1 - Modification State 0

#### 2.1.3 Date of Test

11-May-2022

#### 2.1.4 Test Method

This test was performed in accordance with ANSI C63.10, clause 11.8.1 for 6 dB BW and 6.9.3 for 99% occupied bandwidth measurements.

#### 2.1.5 Environmental Conditions

Ambient Temperature	23.6 °C
Relative Humidity	47.9 %



**2.1.6 Test Results**

Radio chip/PCB combination - Standard

Test Configuration			
Frequency Range:	902-928 MHz	Band:	900 MHz
Limit Clause(s):	15.247 (a)(2) RSS-247 5.2 a)	Test Method(s):	C63.10 6.9.3 C63.10 11.8.1
Additional Reference(s):	-		

DUT Configuration			
Mode:	Standard	Duty Cycle (%):	-
Data Rate:	-	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	A (Ant 1)	Active Chain(s):	0

Test Frequency (MHz)	6 dB Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
902.775	0.536	-	-	-	≥500.0
915.000	0.544	-	-	-	≥500.0
927.225	0.556	-	-	-	≥500.0

**Table 16 - 6 dB Bandwidth Results**

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
902.775	0.680	-	-	-	-
915.000	0.712	-	-	-	-
927.225	0.772	-	-	-	-

**Table 17 - 99% Bandwidth Results**



Figure 1 - Ant 1 (A) 902.775 MHz 99% Bandwidth




Figure 2 - Ant 1 (A) 902.775 MHz 6 dB Bandwidth



Figure 3 - Ant 1 (A) 915.000 MHz 99% Bandwidth




Figure 4 - Ant 1 (A) 915.000 MHz 6 dB Bandwidth




Figure 5 - Ant 1 (A) 927.225 MHz 99% Bandwidth




Figure 6 - Ant 1 (A) 927.225 MHz 6 dB Bandwidth



Test Configuration			
Frequency Range:	902-928 MHz	Band:	900 MHz
Limit Clause(s):	15.247 (a)(2) RSS-247 5.2 a)	Test Method(s):	C63.10 6.9.3 C63.10 11.8.1
Additional Reference(s):	-		

DUT Configuration			
Mode:	Standard	Duty Cycle (%):	-
Data Rate:	-	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-
Active Port(s):	B (Ant2)	Active Chain(s):	0

Test Frequency (MHz)	6 dB Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
902.775	-	0.544	-	-	≥500.0
915.000	-	0.540	-	-	≥500.0
927.225	-	0.552	-	-	≥500.0

Table 18 - 6 dB Bandwidth Results

Test Frequency (MHz)	99% Bandwidth (MHz)				Limit (kHz)
	A	B	C	D	
902.775	-	0.748	-	-	-
915.000	-	0.684	-	-	-
927.225	-	0.732	-	-	-

Table 19 - 99% Bandwidth Results



Figure 7 - Ant2 (B) 902.775 MHz 99% Bandwidth




Figure 8 - Ant2 (B) 902.775 MHz 6 dB Bandwidth



Figure 9 - Ant2 (B) 915.000 MHz 99% Bandwidth



Figure 10 - Ant2 (B) 915.000 MHz 6 dB Bandwidth



Figure 11 - Ant2 (B) 927.225 MHz 99% Bandwidth



Figure 12 - Ant2 (B) 927.225 MHz 6 dB Bandwidth



FCC 47 CFR Part 15, Limit Clause 15.247(a)(2) and ISED RSS-247, Clause 5.2(a)

The minimum 6 dB Bandwidth shall be at least 500 kHz.

**2.1.7 Test Location and Test Equipment Used**

This test was carried out in RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Hygrometer	Rotronic	I-1000	3220	12	05-Nov-2022
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	30-Jun-2022
MXA Signal Analyser	Keysight Technologies	N9020B	5528	24	21-Mar-2024
Signal Conditioning Unit	TUV SUD	SCU001	5546	12	06-Apr-2023

**Table 20**



## **2.2 Maximum Conducted Output Power**

### **2.2.1 Specification Reference**

FCC 47 CFR Part 15C, Clause 15.247 (b)  
ISED RSS-247, Clause 5.4  
ISED RSS-GEN, Clause 6.12

### **2.2.2 Equipment Under Test and Modification State**

SDS Module (US), S/N: US 1 - Modification State 0

### **2.2.3 Date of Test**

11-May-2022 to 24-June-2022

### **2.2.4 Test Method**

Radio chip/PCB combination – Boost

The test was performed in accordance with ANSI C63.10 clause 7.8.5.

Radio chip/PCB combination – Standard

The test was performed in accordance with ANSI C63.10 clause 11.9.2.3.2 (AVGPM-G).

### **2.2.5 Environmental Conditions**

Ambient Temperature	23.6 – 23.8 °C
Relative Humidity	45.0 - 47.9 %



**2.2.6 Test Results**

Radio chip/PCB combination - Standard

Test Configuration			
Frequency Range:	902-928 MHz	Band:	900 MHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	Standard	Duty Cycle (%):	100.0
Data Rate:	-	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-1.00
Active Port(s):	A (Ant 1)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
902.775	18.39	-	-	-	-	30.00	-11.61
915.000	18.63	-	-	-	-	30.00	-11.37
927.225	19.06	-	-	-	-	30.00	-10.94

**Table 21 - FCC Maximum Conducted (average) Output Power Results**

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
902.775	18.39	-	-	-	-	30.00	-11.61	17.39	36.00	-18.61
915.000	18.63	-	-	-	-	30.00	-11.37	17.63	36.00	-18.37
927.225	19.06	-	-	-	-	30.00	-10.94	18.06	36.00	-17.94

**Table 22 - ISED Maximum Conducted (average) Output Power Results**



Test Configuration			
Frequency Range:	902-928 MHz	Band:	900 MHz
Limit Clause(s):	15.247 (b)(3) RSS-247 5.4 d)	Test Method(s):	C63.10 11.9.2.3.2
Additional Reference(s):	-		

DUT Configuration			
Mode:	Standard	Duty Cycle (%):	100.0
Data Rate:	-	DCCF (dB):	-
Antenna Configuration:	SISO	Peak Antenna Gain (dBi):	-1.60
Active Port(s):	B (Ant2)	Active Chain(s):	0

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)
	A	B	C	D	Σ		
902.775	-	18.78	-	-	-	30.00	-11.22
915.000	-	19.38	-	-	-	30.00	-10.62
927.225	-	18.82	-	-	-	30.00	-11.18

**Table 23 - FCC Maximum Conducted (average) Output Power Results**

Test Frequency (MHz)	Maximum Conducted Output Power (dBm)					Limit (dBm)	Margin (dB)	EIRP (dBm)	EIRP Limit (dBm)	EIRP Margin (dB)
	A	B	C	D	Σ					
902.775	-	18.78	-	-	-	30.00	-11.22	17.18	36.00	-18.82
915.000	-	19.38	-	-	-	30.00	-10.62	17.78	36.00	-18.22
927.225	-	18.82	-	-	-	30.00	-11.18	17.22	36.00	-18.78

**Table 24 - ISED Maximum Conducted (average) Output Power Results**

FCC 47 CFR Part 15, Limit Clause 15.247 (b)(3)

For systems using digital modulation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands: 1 Watt.

ISED RSS-247, Limit Clause 5.4 (d)

For DTSs employing digital modulation techniques operating in the bands 902-928 MHz and 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e) of the specification.




Radio chip/PCB combination – Boost

Port A (Ant 1)

Frequency (MHz)	Maximum Output Power	
	dBm	mW
902.775	19.01	79.62
915.000	19.50	89.13
927.225	19.01	76.62

**Table 25**



**Figure 13 - 927.225 MHz**




Figure 14 - 915.000 MHz




Figure 15 - 902.775 MHz



Port B (Ant 2)

Frequency (MHz)	Maximum Output Power	
	dBm	mW
902.775	20.42	110.15
915.000	20.85	121.62
927.225	20.18	104.23

Table 26




Figure 16 - 927.225 MHz



Figure 17 - 915.000 MHz



Figure 18 - 902.775 MHz

FCC 47 CFR Part 15, Limit Clause 15.247 (b)(2)

For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels.

ISED RSS-247, Limit Clause 5.4 (a)

For FHSs operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1.0 W, and the e.i.r.p. shall not exceed 4 W if the hopset uses 50 or more hopping channels; the maximum peak conducted output power shall not exceed 0.25 W and the e.i.r.p. shall not exceed 1 W if the hopset uses less than 50 hopping channels.



### 2.2.7 Test Location and Test Equipment Used

This test was carried out in RF Laboratory 1 and RF Laboratory 2.

Instrument	Manufacturer	Type No	TE No	Calibration Period (months)	Calibration Expires
Hygrometer	Rotronic	I-1000	3220	12	05-Nov-2022
Network Analyser	Rohde & Schwarz	ZVA 40	3548	12	24-Feb-2023
Calibration Unit	Rohde & Schwarz	ZV-Z54	4368	12	24-Feb-2023
Frequency Standard	Spectracom	SecureSync 1200-0408-0601	4393	6	30-Jun-2022
EXA	Keysight Technologies	N9010B	4968	24	19-Jan-2024
Signal Analyser	Keysight Technologies	MXA	4994	24	10-Feb-2024
Network Analyser	Keysight Technologies	E5063A	5018	12	30-Jul-2022
Electronic Calibration Module	Keysight Technologies	85093C	5188	12	22-Jul-2022
Attenuator 5W 20dB DC-18GHz	Aaren	AT40A-4041-D18-20	5500	12	04-May-2023
Attenuator 5W 30dB DC-18GHz	Aaren	AT40A-4041-D18-30	5503	12	18-May-2023
Signal Conditioning Unit	TUV SUD	SCU001	5546	12	06-Apr-2023
USB Power Sensor	Boonton	RTP5008	5820	12	06-Apr-2023
USB Power Sensor	Boonton	RTP5008	5831	12	06-Apr-2023
3.5mm Cable (1m)	Junkosha	MWX221/B	5837	12	23-Jul-2022

**Table 27**



## **2.3 Spurious Radiated Emissions**

### **2.3.1 Specification Reference**

FCC 47 CFR Part 15C, Clause 15.247 (d) and 15.209  
ISED RSS-247, Clause 3.3 and 5.5  
ISED RSS-GEN, Clause 13 and 8.9

### **2.3.2 Equipment Under Test and Modification State**

SDS Module (US), S/N: US 2 - Modification State 0

### **2.3.3 Date of Test**

02-May-2022 to 08-May-2022

### **2.3.4 Test Method**

Radio chip/PCB combination – Boost

This test was performed in accordance with ANSI C63.10, clause 6.3, 6.5 and 6.6.

For frequencies > 1 GHz, plots for average measurements were taken in accordance with ANSI C63.10, clause 4.1.4.2.5 to characterize the EUT. Where emissions were detected, final average measurements were taken in accordance with ANSI C63.10, clause 4.1.4.2.2.

The EUT was placed on the non-conducting platform in a manner typical of a normal installation. As the EUT was considered mobile/portable and therefore reasonable to be used in multiple planes, pre-scans were performed with the EUT orientated in X, Y and Z planes with reference to the ground plane.

The plots shown are the characterisation of the EUT. With the exception of 614 MHz to 960 MHz where the 15.247 limit has been applied, the limits on the plots represent the most stringent case for restricted bands, (74/54 dBuV/m) when compared to 20 dBc outside restricted bands. The limits shown have been used as a threshold to determine where further measurements are necessary. Where results are within 10 dB of the limits shown on the plots, further investigation was carried out and reported in results tables.

The following conversion can be applied to convert from dB $\mu$ V/m to  $\mu$ V/m:

$10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$ .

Where formal measurements have been necessary, the results have been presented in the emissions table.



#### Radio chip/PCB combination – Standard

This test was performed in accordance with ANSI C63.10, clause 6.3, 6.5 and 6.6.

For frequencies > 1 GHz, plots for average measurements were taken in accordance with ANSI C63.10, clause 11.12.2.5.2.

The EUT was placed on the non-conducting platform in a manner typical of a normal installation. As the EUT was considered mobile/portable and therefore reasonable to be used in multiple planes, pre-scans were performed with the EUT orientated in X, Y and Z planes with reference to the ground plane.

The plots shown are the characterisation of the EUT. With the exception of 614 MHz to 960 MHz where the 15.247 limit has been applied, the limits on the plots represent the most stringent case for restricted bands, (74/54 dBuV/m) when compared to 20 dBc outside restricted bands. The limits shown have been used as a threshold to determine where further measurements are necessary. Where results are within 10 dB of the limits shown on the plots, further investigation was carried out and reported in results tables.

The following conversion can be applied to convert from dB $\mu$ V/m to  $\mu$ V/m:

$10^{(\text{Field Strength in dB}\mu\text{V/m}/20)}$ .

Where formal measurements have been necessary, the results have been presented in the emissions table.

### 2.3.5 Example Test Setup Diagram




Figure 19

### 2.3.6 Environmental Conditions

Ambient Temperature 21.3 - 22.9 °C  
Relative Humidity 41.7 - 43.5 %




**2.3.7 Test Results**

Radio chip/PCB combination - Standard

Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation	Orientation
*								

**Table 28 - 902.775 MHz, 30 MHz to 1 GHz**

\*No emissions were detected within 10 dB of the limit.



**Figure 20 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, Z Orientation**




Figure 21 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, Z Orientation




Figure 22 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, Y Orientation




Figure 23 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, Y Orientation




Figure 24 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, X Orientation




Figure 25 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, X Orientation




Figure 26 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, Z Orientation




Figure 27 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, Z Orientation




Figure 28 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, Y Orientation




Figure 29 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, Y Orientation




Figure 30 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, X Orientation





Figure 31 - 902.775 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, X Orientation



Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation	Orientation
*								

**Table 29 - 902.775 MHz, 1 GHz to 10 GHz**

\*No emissions were detected within 10 dB of the limit.



**Figure 32 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, Z Orientation - Average**




Figure 33 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, Z Orientation - Peak




Figure 34 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, Z Orientation - Average




Figure 35 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, Z Orientation - Peak




Figure 36 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, Y Orientation - Average




Figure 37 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, Y Orientation - Peak




Figure 38 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, Y Orientation - Average




Figure 39 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, Y Orientation - Peak




Figure 40 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, X Orientation - Average




Figure 41 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Horizontal, X Orientation - Peak




Figure 42 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, X Orientation - Average




Figure 43 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 2, Vertical, X Orientation - Peak




Figure 44 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, Z Orientation - Average




Figure 45 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, Z Orientation - Peak




Figure 46 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, Z Orientation - Average




Figure 47 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, Z Orientation - Peak




Figure 48 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, Y Orientation - Average




Figure 49 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, Y Orientation - Peak




Figure 50 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, Y Orientation - Average




Figure 51 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, Y Orientation - Peak




Figure 52 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, X Orientation - Average




Figure 53 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Horizontal, X Orientation - Peak




Figure 54 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, X Orientation - Average





Figure 55 - 902.775 MHz, 1 GHz to 10 GHz - Antenna 1, Vertical, X Orientation - Peak



Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation	Orientation
*								

**Table 30 - 915.000 MHz, 30 MHz to 1 GHz**

\*No emissions were detected within 10 dB of the limit.



**Figure 56 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, Z Orientation**




Figure 57 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, Z Orientation






Figure 58 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, Y Orientation



**Figure 59 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, Y Orientation**



**Figure 60 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Horizontal, X Orientation**




Figure 61 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 2, Vertical, X Orientation




Figure 62 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, Z Orientation




Figure 63 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, Z Orientation




Figure 64 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, Y Orientation




Figure 65 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, Y Orientation




Figure 66 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Horizontal, X Orientation





Figure 67 - 915.000 MHz, 30 MHz to 1 GHz - Antenna 1, Vertical, X Orientation



Frequency (MHz)	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Detector	Angle (°)	Height (cm)	Polarisation	Orientation
*								

**Table 31 - 915.000 MHz - 1 GHz to 10 GHz**

\*No emissions were detected within 10 dB of the limit.



**Figure 68 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, Z Orientation - Average**




Figure 69 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, Z Orientation - Peak




Figure 70 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, Z Orientation - Average




Figure 71 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, Z Orientation - Peak




Figure 72 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, Y Orientation - Average




Figure 73 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, Y Orientation - Peak






Figure 74 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, Y Orientation - Average



**Figure 75 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, Y Orientation - Peak**



**Figure 76 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, X Orientation - Average**




Figure 77 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Horizontal, X Orientation - Peak




Figure 78 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, X Orientation - Average




Figure 79 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 2, Vertical, X Orientation - Peak




Figure 80 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, Z Orientation - Average




Figure 81 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, Z Orientation - Peak




Figure 82 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, Z Orientation - Average




Figure 83 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, Z Orientation - Peak




Figure 84 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, Y Orientation - Average




Figure 85 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, Y Orientation - Peak






Figure 86 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, Y Orientation - Average



**Figure 87 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, Y Orientation - Peak**



**Figure 88 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, X Orientation - Average**




Figure 89 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Horizontal, X Orientation - Peak





Figure 90 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, X Orientation - Average



**Figure 91 - 915.000 MHz - 1 GHz to 10 GHz - Antenna 1, Vertical, X Orientation - Peak**