







2. Unlock the screen by pressing each front button from left to right to unlock the remote screen.



Once unlocked, screen will stay active for 2 minutes before going into sleep mode.



- 3. Place the pump and remote within 2 in (50 mm) of each other during the pairing process.
- 4. If your pump's serial number does not show up on screen after a minute, press and hold the pump's blue button for 10 seconds to activate pairing mode. Then, check the screen again for your pump serial number.













5. On the remote, use to highlight the pump's serial number and press.



6. After selecting your pump serial number you will be prompted to confirm the selected pump. Press to confirm.













A Pairing To... message displays.

If pairing fails, see "Pairing Failed Attention Alarm" on page 166



7. Upon successful pairing the *Paired Pump* message displays. Press .





126









Walkaway Attention Alarm

To help you avoid forgetting your remote, setting this feature will let you know that you may have left your remote behind. The *Walkaway Attention Alarm* feature can be set to go off between 1 and 120 minutes.

Turn ON Walkaway Attention Alarm:

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow to Walkaway Alarm: OFF.
- 6. Press .



- 7. If needed, press the to edit the Walkaway Attention Alarm minutes.
- 8. Press the up and down arrows to select between 1 and 120 minutes.
- 9. Press to accept your selection.













- 10. Press the front button under **ON** to turn *ON* the Walkaway Attention Alarm feature.
- 11. Press to accept your selection.

A Sending request to the pump message displays.

Turn OFF Walkaway Attention Alarm:

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow to Walkaway Alarm:ON.
- 6. Press















- 7. Press the front button under **OFF** to turn *OFF* the Walkaway Attention Alarm feature.
- 8. Press to accept your selection.

A Sending request to the pump message displays.

Screen Timeout

The Screen Timeout feature allows you to set the time before the remote's screen will sleep.

- **Press** the **side button** to wake up the remote.
- Unlock (in >>> the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press
- 5. Press the down arrow to Screen Timeout.
- 6. Press













- 7. Press the up and down arrows to select one of four times:
 - One minute
 - Two minutes
 - Five minutes
 - Ten minutes
- 8. Press to accept your selection.

Any time the remote has not been used and the programmed screen timeout minutes have passed, you will need to press the side button to wake up the remote.



Remote Audio

The Remote Audio feature controls the feedback and volume options for the remote.

Feedback Options

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow Y to scroll to **Setup**.
- 4. Press
- 5. Press the down arrow to Remote Audio.
- 6. Press



DKPI-09153-001-Rev. 1.4









- 7. The **Feedback** option is already highlighted.
- 8. Press .
- 9. Press the up and down arrows to select one of three feedback options:
 - Audio and Vibration
 - Audio Only

DKPI-09153-001-Rev. 1.4

- Vibration Only
- 10. Press to accept your selection.

Volume Options

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow to Remote Audio.
- 6. Press .















- 7. Press the down arrow to the **Volume** option.
- 8. Press .



- 9. Press the up and down arrows to select one of five volume levels.
- 10. Press to accept your selection.













Change Rate Passcode

The Change Rate Passcode is Off by default. When turned On a passcode will be required to change the rate.

Turn ON Change Rate Passcode

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .



- 5. Press the down arrow to Passcode: OFF.
- 6. Press .











Press the front button under ON.



8. Use the up and down arrows to scroll through the first digit selection.





134











- 9. When you have the desired number press the right arrow \Rightarrow .
- 10. Repeat Step 8 and Step 9 for the remaining three digits.
- 11. Confirm the passcode by repeating *Step 8* and *Step 9* to enter your new four digit passcode.



A message displays that the *Passcode is Enabled*.

12. Press to return to the Setup Menu.











Turn OFF Change Rate Passcode

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow Y to Passcode: ON.
- 6. Press
- 7. Press the front button under OFF.





- 8. Use the up and down arrows to enter the first digit of your current passcode.
- 9. When finished entering the number press the right arrow .
- 10. Repeat Step 8 and Step 9 for the remaining three digits.















A message displays that the *Passcode is Disabled*.

11. Press to return to the Setup Menu.

Forgot My Change Rate Passcode

If you have forgotten your change rate passcode, you will need to follow the steps to factory reset your remote and pair to spare remote. See "Factory Reset" on page 140.

Airplane Mode

If you are asked to turn off all electronic devices during a commercial flight, follow the steps to put the device into airplane mode.

- 1. **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow to Airplane Mode.
- 6. Press



















7. Press to enable airplane mode.

A Sending request to the pump message displays.



A Press and hold pump button to exit message displays.



The pump will continue to deliver medication even when the remote is in airplane mode.















When the use of electronics is cleared during a commercial flight you can exit airplane mode.

8. You will need to press and hold the blue pump button until after you hear the four-tone delivering sound to exit airplane mode.



9. Verify the remote displays Delivering on the Home screen.











Factory Reset

A Factory Reset should not be performed unless directed by your specialty pharmacist.

- **Press** the **side button** to wake up the remote.
- 2. Unlock the screen by pressing each front button from left to right.
- 3. Use the down arrow to scroll to **Setup**.
- 4. Press .
- 5. Press the down arrow to scroll to **Factory** Reset.
- 6. Press

You will need to select whether you want to reset the remote or the pump.

See "Remote Factory Reset" below.

See "Pump Factory Reset" on the facing page.

Remote Factory Reset



1. Press to factory reset the remote.













A Reset the Remote to defaults? Pump will be disconnected! message displays.

2. Press to confirm or to cancel.

A Remote will restart when complete message displays.

The remote will display *Searching* until the pump is paired to the remote. See "Pair to a Spare Remote" on page 123.

Pump Factory Reset



- 1. Press the down arrow to highlight **Pump.**
- 2. Press to factory reset the pump.





