



RADIO TEST REPORT

FCC ID:2ATGH-100

Product Designation : HELM Sportsband HD Triple Driver

Trademark : HELM Audio

Model Name : HSB-100, HSB-100G, HSB-100B, HSB-100W

Applicant : Helm Audio LTD

Date of Issue : July. 10, 2020

Standard(s) : FCC Part 15.247

Report No : S20070300801001-01

Prepared for

Helm Audio LTD

35 Floor, Central Plaza, 18 Harbour Road, Wan Chai, Hong Kong

Prepared by

Shenzhen NTEK Testing Technology Co., Ltd.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street
Bao'an District, Shenzhen 518126 P.R. China

Tel.: +86-755-6115 9388 Fax.: +86-755-6115 6599

Website: <http://www.ntek.org.cn>

REPORT REVISE RECORD

Report No	Revise Time	Issued Date	Valid Version	Notes
S20070300801001-01	/	July 10, 2020	Invalid	Initial release

TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION.....	4
1.2. TABLE OF CARRIER FREQUENCIES.....	4
1.3 RELATED SUBMITTAL(S)/GRANT(S).....	5
1.4 TEST METHODOLOGY.....	5
1.5 SPECIAL ACCESSORIES.....	5
1.6 EQUIPMENT MODIFICATIONS.....	5
2. MEASUREMENT UNCERTAINTY.....	6
3. DESCRIPTION OF TEST MODES.....	7
4. SYSTEM TEST CONFIGURATION.....	7
4.1 CONFIGURATION OF TESTED SYSTEM.....	7
4.2 EQUIPMENT USED IN TESTED SYSTEM.....	7
4.3. SUMMARY OF TEST RESULTS.....	7
5. TEST FACILITY.....	8
6. PEAK OUTPUT POWER.....	9
6.1. MEASUREMENT PROCEDURE.....	9
6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	9
6.3. LIMITS AND MEASUREMENT RESULT.....	10
7. 6 DB BANDWIDTH.....	12
7.1. MEASUREMENT PROCEDURE.....	12
7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	12
7.3. LIMITS AND MEASUREMENT RESULTS.....	12
8. CONDUCTED SPURIOUS EMISSION.....	14
8.1. MEASUREMENT PROCEDURE.....	14
8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	14
8.3. MEASUREMENT EQUIPMENT USED.....	14
8.4. LIMITS AND MEASUREMENT RESULT.....	14
9. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY.....	19
9.1 MEASUREMENT PROCEDURE.....	19
9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION).....	19
9.3 MEASUREMENT EQUIPMENT USED.....	19
10.4 LIMITS AND MEASUREMENT RESULT.....	19
10. RADIATED EMISSION.....	21
10.1. MEASUREMENT PROCEDURE.....	21
10.2. TEST SETUP.....	22
10.3. LIMITS AND MEASUREMENT RESULT.....	23
10.4. TEST RESULT.....	23
13. FCC LINE CONDUCTED EMISSION TEST.....	33
13.1. LIMITS OF LINE CONDUCTED EMISSION TEST.....	33
13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST.....	33
13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	34
13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST.....	34
13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST.....	35
APPENDIX A: PHOTOGRAPHS OF TEST SETUP.....	37

TEST RESULT CERTIFICATION

Applicant's name.....: Helm Audio LTD
Address.....: 35 Floor, Central Plaza, 18 Harbour Road, Wan Chai, Hong Kong
Manufacturer's Name.....: Helm Audio LTD
Address.....: 35 Floor, Central Plaza, 18 Harbour Road, Wan Chai, Hong Kong
Product description
Product name.....: HELM Sportsband HD Triple Driver
Trademark: HELM Audio
Model Name: HSB-100
Series Model.....: HSB-100G, HSB-100B, HSB-100W
Difference Description.....: The circuit principle and internal structure are the same, appearance color and the model name are different.
Rating(s).....: Input: DC 5V 1.0A by Micro USB; 3.7V by Battery
Standards.....: FCC PART 15.247

We hereby certify that:

The above equipment was tested by Shenzhen NTEK Testing Technology Co., Ltd. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC PART 15.247.

Date of Test.....

Date (s) of performance of tests..... June. 13, 2020 to July.10, 2020

Date of Issue..... July.10, 2020

Test Result..... **Pass**

Testing Engineer : Allen Liu
(Allen Liu)

Technical Manager : Jason Chen
(Jason Chen)

Authorized Signatory : Sam. Chen
(Sam Chen)

1.GENERAL INFORMATION

1.1PRODUCT DESCRIPTION

The EUT is designed as a “Bluetooth True Headset”. It is designed by way of utilizing the GFSK technology to achieve the system operation.

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-0.351dBm(Max)
Bluetooth Version	V 5.0
Modulation	BR <input type="checkbox"/> GFSK, EDR <input type="checkbox"/> $\pi/4$ -DQPSK, <input type="checkbox"/> 8DPSK BLE <input checked="" type="checkbox"/> GFSK 1Mbps <input type="checkbox"/> GFSK 2Mbps
Number of channels	40 Channel
Antenna Designation	Ceramic Antenna(Comply with requirements of the FCC part 15.203)
Antenna Gain	1.0dBi
Hardware Version	V1.0
Software Version	V4
Power Supply	DC 3.7V by battery

Note:

The EUT comprises left and right channel headsets, both are the same and have been tested. Only the test data of left headset recorded in this report.

1.2. TABLE OF CARRIER FREQUENCIES

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2404MHZ
	:	:
	38	2478 MHZ
	39	2480 MHZ

1.3 RELATED SUBMITTAL(S)/GRANT(S)

This submittal(s) (test report) is intended for **FCC ID: 2ATGH-100** filing to comply with the FCC Part 15.247 requirements.

1.4 TEST METHODOLOGY

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10 (2013). Radiated testing was performed at an antenna to EUT distance 3 meters.

1.5 SPECIAL ACCESSORIES

Refer to section 2.2.

1.6 EQUIPMENT MODIFICATIONS

Not available for this EUT intended for grant.

2. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

- Uncertainty of Conducted Emission, $U_c = \pm 3.2$ dB
- Uncertainty of Radiated Emission below 1GHz, $U_c = \pm 3.9$ dB
- Uncertainty of Radiated Emission above 1GHz, $U_c = \pm 4.8$ dB
- Uncertainty of total RF power, conducted, $U_c = \pm 0.8$ dB
- Uncertainty of RF power density, conducted, $U_c = \pm 2.6$ dB
- Uncertainty of spurious emissions, conducted, $U_c = \pm 2.7$ dB
- Uncertainty of Occupied Channel Bandwidth: $U_c = \pm 2$ %

3. DESCRIPTION OF TEST MODES


NO.	TEST MODE DESCRIPTION
1	Low channel TX
2	Middle channel TX
3	High channel TX

Note:

1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
3. For Conducted Test method, a temporary antenna connector is provided by the manufacture.
4. The test software is the Blue Test3 which can set the EUT into the individual test modes.

4. SYSTEM TEST CONFIGURATION

4.1 CONFIGURATION OF TESTED SYSTEM



4.2 EQUIPMENT USED IN TESTED SYSTEM

Ite	Equipment	Model No.	ID or Specification	Remark
1	HELM Sportsband HD Triple Driver	HSB-100,HSB-100G,HSB-100B,HS B-100W	2ATGH-100	EUT

4.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
15.247 (b)(3)	Peak Output Power	Compliant
15.247 (a)(2)	6 dB Bandwidth	Compliant
15.247 (d)	Conducted Spurious Emission	Compliant
15.247 (e)	Maximum Conducted Output Power Density	Compliant
15.209	Radiated Emission	Compliant
15.207	Conducted Emission	Compliant

5.TEST FACILITY

Site Description	
CNAS-Lab.	The Laboratory has been assessed and proved to be in compliance with CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516.
IC-Registration	The Certificate Registration Number is 9270A-1.
FCC- Accredited	Test Firm Registration Number: 463705. Designation Number: CN1184
A2LA-Lab.	The Certificate Registration Number is 4298.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 8 January 2009).
Name of Firm	Shenzhen NTEK Testing Technology Co., Ltd.
Site Location	1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen 518126 P.R. China.

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESPI	101206	Jun. 10, 2020	Jun. 09, 2021
LISN	R&S	ESH2-Z5	101313	Apr. 18, 2020	Apr. 17, 2021

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun. 10, 2020	Jun. 09, 2021
EXA Signal Analyzer	Aglient	N9020A	MY49100060	May. 11, 2020	May. 10, 2021
2.4GHz Fliter	EM Electronics	2400-2500MHz	N/A	Feb. 27, 2020	Feb. 26, 2021
Attenuator	ZHINAN	E-002	N/A	Aug. 26, 2019	Aug. 25, 2020
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep. 21, 2017	Sep. 20, 2020
Active loop antenna (9K-30MHz)	ZHINAN	ZN30900C	18051	Jun. 14, 2020	Jun. 13, 2022
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May. 26, 2020	May. 25, 2022
Broadband Preamplifier	ETS LINDGREN	3117PA	00225134	Oct. 25, 2019	Oct. 24, 2020
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep. 28, 2020	Sep. 27, 2022
Spectrum analyzer	R&S	FSU	HKE-048	Dec. 20, 2019	Dec. 19, 2020

6. PEAK OUTPUT POWER

6.1. MEASUREMENT PROCEDURE


For peak power test:

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. $RBW \geq DTS \text{ bandwidth}$
3. $VBW \geq 3 * RBW$.
4. $SPAN \geq VBW$.
5. Sweep: Auto.
6. Detector function: Peak.
7. Trace: Max hold.

Allow trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power, after any corrections for external attenuators and cables.

6.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)


PEAK POWER TEST SETUP




6.3. LIMITS AND MEASUREMENT RESULT

PEAK OUTPUT POWER MEASUREMENT RESULT FOR GFSK MOUDULATION			
Frequency (GHz)	Peak Power (dBm)	Applicable Limits (dBm)	Pass or Fail
2.402	-0.663	30	Pass
2.440	-0.391	30	Pass
2.480	-0.351	30	Pass


CH0



CH19



CH39



7. 6 DB BANDWIDTH

7.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Centre Frequency = Operation Frequency, RBW= 100 KHz, VBW $\geq 3 \times$ RBW.
4. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.


7.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

7.3. LIMITS AND MEASUREMENT RESULTS

LIMITS AND MEASUREMENT RESULT			
Applicable Limits	Applicable Limits		
	Test Data (kHz)		Criteria
>500KHZ	Low Channel	719.9	PASS
	Middle Channel	707.6	PASS
	High Channel	708.2	PASS


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



8. CONDUCTED SPURIOUS EMISSION

8.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set SPA Trace 1 Max hold, then View.

Note: The EUT was tested according to ANSI C63.10 for compliance to FCC PART 15.247 requirements.

8.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

The same as described in section 7.2.

8.3. MEASUREMENT EQUIPMENT USED

The same as described in section 6.

8.4. LIMITS AND MEASUREMENT RESULT

LIMITS AND MEASUREMENT RESULT		
Applicable Limits	Measurement Result	
	Test Data	Criteria
In any 100 KHz Bandwidth Outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produce by the intentional radiator shall be at least 20 dB below that in 100KHz bandwidth within the band that contains the highest level of the desired power.	At least -20dBc than the reference level	PASS PASS

Agilent Spectrum Analyzer - Swept SA

Marker 1 2.402023250775 GHz

Ref 20.00 dBm

Trig: Free Run

Avg Type: Log-Pwr

Span 5.000 MHz

Center 2.402000 GHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 2.000 ms (30000 pts)

Mkr1 2.402 023 25 GHz -0.778 dBm

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr→CF

Mkr→Ref Lvl

More

1 of 2

Agilent Spectrum Analyzer - Swept SA

Marker 3 1.941933397780 GHz

Ref 20.00 dBm

Trig: Free Run

Avg Type: Log-Pwr

Span 25.00 GHz

Start 30 MHz

#Res BW 100 kHz

#VBW 300 kHz

Sweep 2.388 s (30000 pts)

Mkr3 1.941 9 GHz -50.570 dBm

Peak Search

Next Peak

Next Pk Right

Next Pk Left

Marker Delta

Mkr→CF

Mkr→Ref Lvl

More

1 of 2

MKR	MODE	TRC	SCL	X	Y	FUNCTION	FUNCTION WIDTH	FUNCTION VALUE
1	N	1	f	20.873 2 GHz	-49.102 dBm			
2	N	1	f	119.9 MHz	-50.324 dBm			
3	N	1	f	1.941 9 GHz	-50.570 dBm			
4								
5								
6								
7								
8								
9								
10								
11								

File <Screen_0013.png> saved

Agilent Spectrum Analyzer - Swept SA

Marker 1 2.440008583619 GHz

PNO: Wide IFGain: Low Trig: Free Run Atten: 30 dB

Avg Type: Log-Pwr Avg/Hold: >100/100

TRACE 1 2 3 4 5 TYPE M P DET P N N N N N


10 dB/div Ref 20.00 dBm

Mkr1 2.440 008 58 GHz -0.685 dBm

Center 2.440000 GHz Span 5.000 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.000 ms (30000 pts)

MSG STATUS




GFSK MODULATION IN HIGH CHANNEL




Note: The peak emissions without marker on the above plots are fundamental wave and need not to compare with the limit.

TEST RESULT FOR BAND EDGE
GFSK MODULATION IN LOW CHANNEL



GFSK MODULATION IN HIGH CHANNEL



9. MAXIMUM CONDUCTED OUTPUT POWER SPECTRAL DENSITY

9.1 MEASUREMENT PROCEDURE

- (1). Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
- (2). Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- (3). Set SPA Trace 1 Max hold, then View.

Note: The method of PKPSD in the KDB 558074 item 10.2 was used in this testing.

9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)

Refer To Section 7.2.

9.3 MEASUREMENT EQUIPMENT USED

Refer To Section 6.

10.4 LIMITS AND MEASUREMENT RESULT

Channel No.	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Result
Low Channel	-15.525	8	Pass
Middle Channel	-15.101	8	Pass
High Channel	-15.413	8	Pass


TEST PLOT OF SPECTRAL DENSITY FOR LOW CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR MIDDLE CHANNEL



TEST PLOT OF SPECTRAL DENSITY FOR HIGH CHANNEL




10. RADIATED EMISSION

10.1. MEASUREMENT PROCEDURE


1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz RBW and 3MHz VBW for peak reading. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

10.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



10.3. LIMITS AND MEASUREMENT RESULT

15.209 Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,
the test records reported below are the worst result compared to other modes.

10.4. TEST RESULT


RADIATED EMISSION BELOW 30MHZ

Emission from 9kHz to 30MHz are more than 20dB below the limit.

RADIATED EMISSION BELOW 1GHZ

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal


66.9 dBuV/m



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		41.3167	0.23	20.04	20.27	40.00	-19.73	peak			
2		148.0167	2.33	19.21	21.54	43.50	-21.96	peak			
3		299.9833	5.88	19.47	25.35	46.00	-20.65	peak			
4		545.7167	1.04	25.89	26.93	46.00	-19.07	peak			
5		768.8167	2.20	29.71	31.91	46.00	-14.09	peak			
6	*	930.4833	1.76	31.96	33.72	46.00	-12.28	peak			

RESULT: PASS

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	30.0000	17.67	18.17	35.84	40.00	-4.16	peak			
2		127.0000	6.18	18.41	24.59	43.50	-18.91	peak			
3		299.9833	6.45	19.47	25.92	46.00	-20.08	peak			
4		579.6667	2.26	26.55	28.81	46.00	-17.19	peak			
5		733.2500	1.50	28.90	30.40	46.00	-15.60	peak			
6		839.9500	2.76	30.93	33.69	46.00	-12.31	peak			

RESULT: PASS

Note:

1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.
2. All test modes had been tested. The mode 1 is the worst case and recorded in the report.

RADIATED EMISSION ABOVE 1GHZ

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	44.19	0.08	44.27	74	-29.73	peak
4804.000	37.53	0.08	37.61	54	-16.39	AVG
7206.000	39.08	2.21	41.29	74	-32.71	peak
7206.000	33.5	2.21	35.71	54	-18.29	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4804.000	42.95	0.08	43.03	74	-30.97	peak
4804.000	36.86	0.08	36.94	54	-17.06	AVG
7206.000	36.8	2.21	39.01	74	-34.99	peak
7206.000	30.64	2.21	32.85	54	-21.15	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4880.000	43.15	0.14	43.29	74	-30.71	peak
4880.000	38.33	0.14	38.47	54	-15.53	AVG
7320.000	38.34	2.36	40.7	74	-33.3	peak
7320.000	31.51	2.36	33.87	54	-20.13	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 2	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4880.000	42.02	0.14	42.16	74	-31.84	peak
4880.000	35.52	0.14	35.66	54	-18.34	AVG
7320.000	37.25	2.36	39.61	74	-34.39	peak
7320.000	30.78	2.36	33.14	54	-20.86	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	42.46	0.22	42.68	74	-31.32	peak
4960.000	36.61	0.22	36.83	54	-17.17	AVG
7440.000	37.72	2.64	40.36	74	-33.64	peak
7440.000	31.56	2.64	34.2	54	-19.8	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

Frequency (MHz)	Meter Reading (dBμV)	Factor (dB)	Emission Level (dBμV/m)	Limits (dBμV/m)	Margin (dB)	Value Type
4960.000	41.1	0.22	41.32	74	-32.68	peak
4960.000	35	0.22	35.22	54	-18.78	AVG
7440.000	35.78	2.64	38.42	74	-35.58	peak
7440.000	29.19	2.64	31.83	54	-22.17	AVG

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

RESULT: PASS

Note:

Other emissions from 1G to 25 GHz are considered as ambient noise. No recording in the test report.


Factor = Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.


TEST RESULT FOR RESTRICTED BANDS REQUIREMENTS

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Horizontal

PK




AV




RESULT: PASS

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 1	Antenna	Vertical

PK




AV




RESULT: PASS

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Horizontal

PK




AV



RESULT: PASS

EUT	HELM Sportsband HD Triple Driver	Model Name	HSB-100
Temperature	25° C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	Mode 3	Antenna	Vertical

PK



AV



RESULT: PASS

Note: The factor had been edited in the “Input Correction” of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μV) to represent the Amplitude. Use the F dB(μV/m) to represent the Field Strength. So A=F.

13. FCC LINE CONDUCTED EMISSION TEST


13.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received AC120V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.


Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



No. Mk.	Freq.	Reading	Correct	Measure-	Limit	Over		
	MHz	dBuV	Factor	ment	dBuV	dB	Detector	Comment
1	0.1556	10.18	9.94	20.12	55.70	-35.58	AVG	
2 *	0.1580	37.48	9.94	47.42	65.57	-18.15	QP	
3	0.1940	31.30	9.90	41.20	63.86	-22.66	QP	
4	0.1940	9.66	9.90	19.56	53.86	-34.30	AVG	
5	0.2300	28.55	9.90	38.45	62.45	-24.00	QP	
6	0.2300	5.32	9.90	15.22	52.45	-37.23	AVG	
7	0.5740	17.63	9.93	27.56	56.00	-28.44	QP	
8	0.5820	6.39	9.93	16.32	46.00	-29.68	AVG	
9	1.2820	13.13	9.99	23.12	56.00	-32.88	QP	
10	1.3099	3.23	9.99	13.22	46.00	-32.78	AVG	
11	15.5700	14.39	12.06	26.45	60.00	-33.55	QP	
12	15.6420	3.37	12.08	15.45	50.00	-34.55	AVG	



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1700	34.30	9.93	44.23	64.96	-20.73	QP	
2		0.1700	8.39	9.93	18.32	54.96	-36.64	AVG	
3		0.1997	6.32	9.90	16.22	53.62	-37.40	AVG	
4		0.2020	26.22	9.90	36.12	63.53	-27.41	QP	
5		0.2500	18.21	9.90	28.11	61.76	-33.65	QP	
6		0.2540	4.87	9.91	14.78	51.63	-36.85	AVG	
7		0.4900	5.04	9.94	14.98	46.17	-31.19	AVG	
8		0.4940	16.38	9.94	26.32	56.10	-29.78	QP	
9		0.5660	4.41	9.94	14.35	46.00	-31.65	AVG	
10		0.5780	16.51	9.94	26.45	56.00	-29.55	QP	
11		1.3140	14.13	9.99	24.12	56.00	-31.88	QP	
12		1.3140	3.24	9.99	13.23	46.00	-32.77	AVG	

RESULT: PASS


Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.

APPENDIX A: PHOTOGRAPHS OF TEST SETUP


CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP BELOW 1GHZ



RADIATED EMISSION TEST SETUP ABOVE 1GHZ



----END OF REPORT----