

FCC REPORT

Applicant: UBIO LABS, INC.

Address of Applicant: 2821 Northup Way, Suite 250 Bellevue, WA 98004 USA

Equipment Under Test (EUT)

Product Name: Wireless Charging Stand

Model No.: AWC1073SG, AWC1073XX (where XX can be any arabian numbers or English letters or blank)

Trade mark: ubiolabs

FCC ID: 2ATGY-AWC1073

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.209

Date of sample receipt: 06 Jan., 2020

Date of Test: 07 Jan., to 12 Jan., 2020

Date of report issue: 17 Mar., 2020

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	12 Jan., 2020	Original
01	17 Mar., 2020	Update Page 5, 9, 12, 16, 19

Prepared By: Yayo Wu Date: 17 Mar., 2020
Report Clerk

Check By: Winner Zhang Date: 17 Mar., 2020
Project Engineer

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF E.U.T.....	5
5.3 TEST MODE	5
5.4 DESCRIPTION OF SUPPORT UNITS.....	5
5.5 MEASUREMENT UNCERTAINTY.....	6
5.6 DESCRIPTION OF CABLE USED	6
5.7 LABORATORY FACILITY.....	6
5.8 LABORATORY LOCATION	6
5.9 TEST INSTRUMENTSLIST.....	7
6 TEST RESULTS ANDMEASUREMENT DATA	8
6.1 ANTENNA REQUIREMENT	8
6.2 RADIATED EMISSION	9
6.3 CONDUCTED EMISSION	16
6.4 BANDWIDTH	19
7 TEST SETUP PHOTOS.....	21
8 EUT CONSTRUCTIONAL DETAILS	23

4 Test Summary

Test Item	Section in CFR 47	Result
Spurious emissions	15.209	Pass
20dB Bandwidth	15.215(c)	Pass
Conducted Emission	15.207	Pass
<p>Remark:</p> <ol style="list-style-type: none"> 1. Pass: The EUT complies with the essential requirements in the standard. 2. The cable insertion loss used by "RF Output Power" and other conduction measurement items is 0.5dB (provided by the customer). 		
Test Method:	ANSI C63.10-2013	

5 General Information

5.1 Client Information

Applicant:	UBIO LABS, INC.
Address of Applicant:	2821 Northup Way, Suite 250 Bellevue, WA 98004 USA
Manufacturer:	UBIO LABS, INC.
Address:	2821 Northup Way, Suite 250 Bellevue, WA 98004 USA
Factory:	SHENZHEN LANNENGSHITONG ELECTRONICS CO., LTD
Address:	Floor3 No.40, Xinhe Road, Shangmugu Village, Pinghu Neighborhood, Longgang District, Shenzhen City, Guangdong Province, China.

5.2 General Description of E.U.T.

Product Name:	Wireless Charging Stand
Model No.:	AWC1073SG, AWC1073XX (where XX can be any arabian numbers or English letters or blank)
Operation Frequency:	127.70 kHz
Modulation type:	Load modulation
Antenna Type:	Coil Antenna
Power supply (Wireless Charger):	Model: AWC1073SG Input: DC 15V, 3.5A Input (USB-A): DC 5V,2.4A, 12W per port, total: 24W Max Output Wireless: 5W-10W
AC Adapter:	Model: CHG1088 Input: AC 110-240V, 50-60 Hz, 1.1A Output: 15V / 3.5A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.
Remark:	Model No.: AWC1073SG, AWC1073XX were identical inside, the electrical circuit design, layout, components used and internal wiring. with only difference being model name and color.

5.3 Test mode

Transmitting mode:	Keep the EUT in transmitting mode with modulation
--------------------	---

5.4 Description of Support Units

Manufacturer	Description	Model	S/N	FCC ID/DoC
Skytek	Wireless charging match load	N/A	N/A	N/A
Apple	Mobile phone	iPhone 11 Pro	MWDE2CH/A	Doc

5.5 Measurement Uncertainty

Parameter	Expanded Uncertainty (Confidence of 95%)
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 26.5GHz)	±3.36 dB (k=2)

5.6 Description of Cable Used

N/A

5.7 Laboratory Facility

<p>The test facility is recognized, certified, or accredited by the following organizations:</p> <ul style="list-style-type: none"> ● FCC - Designation No.: CN1211 Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551. ● ISED – CAB identifier.: CN0021 The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1. ● CNAS - Registration No.: CNAS L6048 Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048. ● A2LA - Registration No.: 4346.01 This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: https://portal.a2la.org/scopepdf/4346-01.pdf
--

5.8 Laboratory Location

<p>Shenzhen Zhongjian Nanfang Testing Co., Ltd. Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road, Bao'an District, Shenzhen, Guangdong, China Tel: +86-755-23118282, Fax: +86-755-23116366 Email: info@ccis-cb.com, Website: http://www.ccis-cb.com</p>


5.9 Test Instrumentslist

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-16-2019	03-15-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-16-2019	03-15-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2019	11-20-2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	00044	04-28-2019	04-27-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-07-2019	03-06-2020
Pre-amplifier	CD	PAP-1G18	11804	03-07-2019	03-06-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-07-2019	03-06-2020
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2019	11-20-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-07-2019	03-06-2020
Simulated Station	Anritsu	MT8820C	6201026545	03-07-2019	03-06-2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-07-2019	03-06-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-07-2019	03-06-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-07-2019	03-06-2020

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-07-2019	03-06-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-07-2019	03-06-2020
LISN	CHASE	MN2050D	1447	03-19-2019	03-18-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2021
Cable	HP	10503A	N/A	03-07-2019	03-06-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		

6 Test results and Measurement Data

6.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203
<p>15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>	
E.U.T Antenna:	
	

6.2 Radiated Emission

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10				
Test Frequency Range:	9kHz to 1000MHz				
Test site:	Measurement Distance: 3m(Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	9kHz-150kHz	Quasi-peak	200Hz	600Hz	Quasi-peak Value
	150kHz-30MHz	Quasi-peak	9kHz	30kHz	Quasi-peak Value
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
Limit:	Frequency (MHz)	Limit (uV/m)		Distance (m)	
	0.009-0.490	2400/F(kHz)		300	
	0.490-1.705	24000/F(kHz)		30	
	1.705-30	30		30	
	30-88	100		3	
	88-216	150		3	
	216-960	200		3	
	Above 1GHz	500		3	
Test Procedure:	<p>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</p> <p>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</p> <p>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</p> <p>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum reading.</p> <p>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</p> <p>f. If the emission level of the EUT in peak mode was 10dB lower than the limits specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</p>				
Test setup:	<p>9kHz-30MHz</p> <p>30MHz-1GHz</p>				

	<p>The diagram illustrates the test setup. An EUT (Equipment Under Test) is placed on a Turn Table at a height of 0.8m from the Ground Plane. The Turn Table is positioned 3m horizontally from the center of the Antenna Tower. The Search Antenna is mounted on the Antenna Tower at a height of 4m from the top of the Turn Table. The RF Test Receiver is connected to the Search Antenna. The Ground Plane is indicated by a hatched area at the bottom.</p>
<p>Test Instruments:</p>	<p>Refer to section 5.9 for details</p>
<p>Test mode:</p>	<p>Refer to section 5.3 for details</p>
<p>Test results:</p>	<p>Pass</p>
<p>Remark:</p>	<p>The emission levels of above 1 GHz are very lower than the limit and not show in test report.</p>


Measurement Data:

a) Fundamental field strength

Peak value				
Test Polarization	Frequency (kHz)	H-field@3m (dBμV)	Limit@3m (dBμV)	Result
Horizontal	127.70	54.81	125.48	Pass
Vertical	127.70	50.68	125.48	Pass
Average value				
Test Polarization	Frequency (kHz)	H-field@3m (dBμV)	Limit@3m (dBμV)	Result
Horizontal	127.70	41.58	105.48	Pass
Vertical	127.70	39.24	105.48	Pass

b) Radiated spurious (By 9 kHz ~ 30 MHz):

Product name:	Wireless Charging Stand	Product Model:	AWC1073SG
Test by:	Yaro	Test mode:	TX mode
Test frequency:	9 kHz ~ 30 MHz	Phase:	Horizontal
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	39.34	-25.86	0.05	17.50	47.53	123.71	-76.18	Peak
2	34.97	-25.95	0.12	17.50	43.14	117.65	-74.51	Peak
3	29.37	-25.99	0.17	17.50	37.55	114.13	-76.58	Peak
4	25.33	-26.27	0.37	17.50	33.43	95.90	-62.47	Peak
5	16.73	-26.30	0.53	17.50	24.96	71.54	-46.58	Peak
6	14.60	-26.30	0.60	17.50	22.90	68.58	-45.68	Peak

Notes:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamp Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product name:	Wireless Charging Stand	Product model:	AWC1073SG
Test by:	Yaro	Test mode:	TX mode
Test frequency:	9 kHz ~ 30 MHz	Phase:	Vertical
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Remark	
-----	-----	-----	-----	-----	-----	-----	-----	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	0.016	37.38	-25.86	0.05	17.50	45.57	123.71	-78.14 Peak
2	0.031	32.07	-25.95	0.12	17.50	40.24	117.65	-77.41 Peak
3	0.047	26.51	-25.99	0.17	17.50	34.69	114.13	-79.44 Peak
4	0.159	22.47	-26.17	0.28	17.50	30.58	103.60	-73.02 Peak
5	0.385	20.53	-26.27	0.37	17.50	28.63	95.90	-67.27 Peak
6	4.836	8.57	-26.60	0.59	17.50	16.56	69.50	-52.94 Peak

Notes:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Radiated spurious (By 30 MHz ~ 1 GHz):

Product Name:	Wireless Charging Stand	Product Model:	AWC1073SG
Test By:	Yaro	Test mode:	TX mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%




	Read	Antenna	Cable	Preamp	Level	Limit	Over	Remark
-----	Freq	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	52.760	48.21	11.83	1.29	29.81	31.52	40.00	-8.48 QP
2	60.280	46.94	11.31	1.38	29.77	29.86	40.00	-10.14 QP
3	92.139	51.30	10.54	2.03	29.56	34.31	43.50	-9.19 QP
4	173.814	49.61	9.76	2.68	29.02	33.03	43.50	-10.47 QP
5	269.428	45.86	13.08	2.86	28.50	33.30	46.00	-12.70 QP
6	327.887	42.81	14.17	3.03	28.51	31.50	46.00	-14.50 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	Wireless Charging Stand	Product Model:	AWC1073SG
Test By:	Yaro	Test mode:	TX mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Humi: 57%



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	93.768	54.00	10.98	2.02	29.56	37.44	43.50	-6.06	QP
2	100.581	50.58	12.46	1.94	29.52	35.46	43.50	-8.04	QP
3	106.759	49.47	11.94	2.02	29.48	33.95	43.50	-9.55	QP
4	173.814	54.21	9.76	2.68	29.02	37.63	43.50	-5.87	QP
5	267.546	55.45	13.03	2.86	28.51	42.83	46.00	-3.17	QP
6	352.943	46.55	14.64	3.10	28.57	35.72	46.00	-10.28	QP

Remark:


1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Pre-amplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

6.3 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.207		
Test Method:	ANSI C63.10		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)	Limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	<p><i>Remark</i> E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). The provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement. 		
Test environment:	Temp.:	23 °C	Humid.: 56% Press.: 101kPa
Test Instruments:	Refer to section 5.9 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement Data:

Product name:	Wireless Charging Stand	Product Model:	AWC1073SG
Test by:	Yaro	Test mode:	TX mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




Trace: 17

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	51.87	-0.45	-0.05	10.78	62.15	66.00	-3.85	QP
2	0.150	40.42	-0.45	-0.05	10.78	50.70	56.00	-5.30	Average
3	0.162	35.00	-0.44	-0.08	10.77	45.25	55.34	-10.09	Average
4	0.170	48.07	-0.43	-0.10	10.77	58.31	64.94	-6.63	QP
5	0.182	31.96	-0.42	-0.12	10.77	42.19	54.42	-12.23	Average
6	0.182	44.86	-0.42	-0.13	10.77	55.08	64.37	-9.29	QP
7	0.194	42.71	-0.41	-0.15	10.76	52.91	63.84	-10.93	QP
8	0.219	40.60	-0.40	-0.18	10.76	50.78	62.88	-12.10	QP
9	0.365	26.93	-0.38	0.21	10.73	37.49	48.61	-11.12	Average
10	0.377	35.93	-0.37	0.27	10.72	46.55	58.34	-11.79	QP
11	0.437	28.69	-0.38	0.11	10.74	39.16	47.11	-7.95	Average
12	1.276	18.68	-0.39	0.18	10.90	29.37	46.00	-16.63	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

Product name:	Wireless Charging Stand	Product Model:	AWC1073SG
Test by:	Yaro	Test mode:	TX mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Humi: 55%




Trace: 19

	Freq	Read Level	LISN Factor	Aux Factor	Cable Loss	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dB	
1	0.150	51.36	-0.68	0.01	10.78	61.47	66.00	-4.53	QP
2	0.151	34.39	-0.68	0.01	10.78	44.50	55.96	-11.46	Average
3	0.166	46.64	-0.68	0.01	10.77	56.74	65.16	-8.42	QP
4	0.170	31.73	-0.68	0.01	10.77	41.83	54.94	-13.11	Average
5	0.178	45.63	-0.69	0.00	10.77	55.71	64.59	-8.88	QP
6	0.219	40.52	-0.68	0.00	10.76	50.60	62.88	-12.28	QP
7	0.286	24.39	-0.64	0.01	10.74	34.50	50.63	-16.13	Average
8	0.426	33.09	-0.64	-0.03	10.73	43.15	57.33	-14.18	QP
9	0.431	23.07	-0.64	-0.03	10.73	33.13	47.24	-14.11	Average
10	0.521	30.88	-0.65	0.03	10.76	41.02	56.00	-14.98	QP
11	1.276	18.18	-0.64	0.11	10.90	28.55	46.00	-17.45	Average
12	3.364	17.47	-0.68	0.39	10.91	28.09	46.00	-17.91	Average

Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss.

6.4 Bandwidth


Test Requirement:	FCC Part15 C Section 15.215 (c)
Test Method:	ANSI C63.10
Receiver setup:	RBW=1 kHz, VBW=3 kHz, detector: Peak
Limit:	The fundamentelemission be kept within atleast the central 80% of the permittedband
Test Procedure:	<ol style="list-style-type: none"> 1. According to the follow Test-setup, keep the relative position between the artificial antenna and the EUT. 2. Set the EUT to proper test channel. 3. Max hold the radiated emissions, mark the peak power frequency point and the -20dB upper and lower frequency points. 4. Read 20dB bandwidth.
Test setup:	 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instruments:	Refer to section 5.9 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed

Measurement Data

20dB bandwidth (kHz)	Limits
2.70	N/A
<i>Remark: For report purpose only.</i>	

99% bandwidth (kHz)	Limits
2.26	N/A
<i>Remark: For report purpose only.</i>	

Test plot as follows:



Test Frequency= 127.70 kHz