

TEST REPORT

Reference No..... : WTX21X07066563W-2
FCC ID : 2ATGY-AWC1115
Applicant : UBIO LABS, INC.
Address : 2821 Northup Way, Suite 250, Bellevue, WA 98004 USA
Product Name : Aspect 15W Wireless Pad with 25W USB-C
Test Model : AWC1115
Standards : KDB 680106 D01 V03
Date of Receipt sample : Jul. 06, 2021
Date of Test..... : Jul. 06, 2021 to Aug. 03, 2021
Date of Issue : Aug. 03, 2021
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China



Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

Reviewed By:

Approved & Authorized By:



Jason Su / Project Engineer

Lion Cai / RF Manager

Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION.....4
 1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....4
 1.2 TEST EQUIPMENT LIST AND DETAILS5
2. RF EXPOSURE TEST REPORT6
 2.1 STANDARD APPLICABLE.....6
 2.2 TEST CONDITIONS6
 2.3 TEST PROCEDURE.....7
 2.4 TEST RESULT.....7
 2.5 TEST PHOTOS9
APPENDIX PHOTOGRAPHS.....10

Report version

Version No.	Date of issue	Description
Rev.00	Aug. 03, 2021	Original
/	/	/

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: UBIO LABS, INC.
 Address of applicant: 2821 Northup Way, Suite 250, Bellevue, WA 98004
 USA

Manufacturer: UBIO LABS, INC.
 Address of manufacturer: 2821 Northup Way, Suite 250, Bellevue, WA 98004
 USA

General Description of EUT	
Product Name:	Aspect 15W Wireless Pad with 25W USB-C
Trade Name:	ubiolabs
Model No.:	AWC1115
Adding Model(s):	/
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

Technical Characteristics of EUT	
Frequency Range:	120~130KHz
Power adapter	CHG1088 Input: AC110-240V, 50-60Hz, 1.1A Output: DC15V, 3.5A
Antenna Type:	Coil Antenna
Modulation Type:	FSK
Rated Voltage:	Input: DC15V
Rated Current:	Input: 3.5A
Rated Power:	Output: 5W, 10W, 7.5W, 15W

1.2 Test Equipment List and Details

Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
ELECTRIC AND MAGNETIC FIELD ANALYZER	Narda	EHP-200AC	180ZX10226	2021-05-20	2024-05-19

2. RF Exposure Test Report

2.1 Standard Applicable

According to § 1.1310 system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f ²	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30


f = frequency in MHz * = Plane-wave equivalent power density

2.2 Test Conditions

Test Mode	Description	Remark
TM1	Wireless Charging	Worst case maximum output power 15W
Measurement Distance: 15 cm		

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
Wireless charging load	/	YBZ	

2.3 Test Procedure



- The measurement probe was placed at test distance (15 cm for A, B, C, D, F and 20 cm for E) which is between the edge of the charger and the geometric center of probe.
- The highest emission level was recorded at the measurement points (A, B, C, D, E, F).
- The EUT was measured according to the distance of KDB 680106 D01 V03.

2.4 Test Result

The EUT dose comply with item 5.2 of KDB 680106 D01V03

- Power transfer frequency is less than 1 MHz
- Yes, the device operate in the frequency range from 120kHz to 130kHz.
- Output power from each primary coil is less than or equal to 15 watts
Yes, the maximum output power of the primary coil is less than 15W.
- The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils
Yes, the client device includes only single primary coils.
- Client device is inserted in or placed directly in contact with the transmitter
Yes, Client device is placed directly in contact with the transmitter.
- Mobile exposure conditions only (portable exposure conditions are not covered by this exclusion).

Yes, It is mobile exposure conditions only.

7. The aggregate H-field strengths at 15 cm surrounding the device and 20 cm above the top surface from all simultaneous transmitting coils are demonstrated to be less than 50% of the MPE limit.

Yes, The EUT field strength levels are less than 50% of the MPE limit, refer to test TM1 list, and the coils can't transmitted simultaneous.

Test Mode: TM1

Electric Field Emissions			
Test Position	Measure Value (V/m)	Limit(V/m)	50% Limit (V/m)
Top	1.9610	614	307
Bottom	1.9548	614	307
Side 1	1.9574	614	307
Side 2	1.9601	614	307
Side 3	1.9574	614	307
Side 4	1.9541	614	307
Magnetic Field Emissions			
Test Position	Measure Value (A/m)	Limit(A/m)	50% Limit (A/m)
Top	0.9329	1.63	0.815
Bottom	0.9310	1.63	0.815
Side 1	0.9321	1.63	0.815
Side 2	0.9322	1.63	0.815
Side 3	0.9314	1.63	0.815
Side 4	0.9309	1.63	0.815

Note: 1. The EUT was tested at 3 (X, Y, Z) orthogonal positions, and the worst-case position data was reported. Worst data for Electric Field Emissions (X), worst data for Magnetic Field Emissions (Z).

2.5 Test Photos



APPENDIX PHOTOGRAPHS

Please refer to “ANNEX”

******* END OF REPORT *******