

## RF Exposure Requirements

---

Product Description: Handheld stabilizer

Model No.: Smart,S1

FCC ID: 2ATH2-YGE

According to the KDB 447498 D01 v06 section 4.3.1, for 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$\left[ \frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

-  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

- The result is rounded to one decimal place for comparison

### Calculation Result:

Tx frequency range: 2402 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: -4.18 dBm (0.382 mW)

Tune-Up output power: 1 dBm (1.26 mW)

RF channel transmit frequency: 2402 MHz

Result: 0.813

Limit: 3.0

Tx frequency range: 2442 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: -1.68 dBm (0.679 mW)

Tune-Up output power: 1 dBm (1.26 mW)

RF channel transmit frequency: 2442 MHz

Result: 0.8063

Limit: 3.0

Tx frequency range: 2480 MHz

Min. test separation distance: 5 mm

Maximum Conducted Output Power: -1.29 dBm (0.743 mW)

Tune-Up output power: 1 dBm (1.26 mW)

RF channel transmit frequency: 2480 MHz

Result: 0.8

Limit: 3.0

The exclusion thresholds is  $0.813 < 3$ , so the transmitter complies with the RF exposure requirements and the SAR is not required.