


Smart Stack Coaster STO/ Pro/EVO Paging system

Mode : AT201



- 10 mWatt UHF Paging transmitter
- Frequency : 430 ~ 470 MHz, default :433.92MHz
- Send out both Numeric and Alpha messages via USB keyboard with attached PC software
- Send out Numeric message via on board buttons directly.
- Backlit LCD display and numeric keypad
- Power DC12V, 2A
- Size : 14 x 12 x 4 cm (5.5 x 4.7 x 1.6 inch)

Operation :

1. Plug 12V2A Adapter to AT201
2. Press membrane number 1-9 buttons for coaster's number
3. Press SEND button to call the coaster
4. This product belongs to fixed equipment

Federal Communications Commission (FCC) Statement

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Warning: Changes or modifications made to this device not expressly approved by **Pagertec Corp.** may void the FCC authorization to operate this device.

Note: The manufacturer is not responsible for any radio or TV interference caused by unauthorized modifications to this equipment. Such modifications could void the user's authority to operate the equipment.

RF exposure statement:

The transmitter must not be colocated or operated in conjunction with any other antenna or transmitter. This equipment complies with the FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a Minimum distance of 20cm between the radiator and any part of your body.