

# TEST REPORT

## CERTIFICATE OF CONFORMITY

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Report No.:** RFBDKX-WTW-P22120419

**FCC ID:** 2ATIO4

**Product:** Home IOT Gateway

**Brand:** Level

**Model No.:** H4

**Received Date:** 2022/12/13

**Test Date:** 2023/2/8 ~ 2023/2/21

**Issued Date:** 2023/3/30

**Applicant:** Level Home Inc.

**Address:** 935 Main Street, Redwood City, California 94063, United States of America

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Lin Kou Laboratories

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**Test Location:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

**FCC Registration /** 198487 / TW2021

**Designation Number:**

**Approved by:**



, **Date:**

2023/3/30

Jeremy Lin / Project Engineer

This test report consists of 50 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Annie Chang / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

<b>Release Control Record .....</b>	<b>4</b>
<b>1      Certificate.....</b>	<b>5</b>
<b>2      Summary of Test Results .....</b>	<b>6</b>
2.1    Measurement Uncertainty .....	6
2.2    Supplementary Information .....	6
<b>3      General Information .....</b>	<b>7</b>
3.1    General Description.....	7
3.2    Antenna Description of EUT .....	7
3.3    Channel List.....	8
3.4    Test Mode Applicability and Tested Channel Detail.....	9
3.5    Duty Cycle of Test Signal.....	10
3.6    Test Program Used and Operation Descriptions.....	11
3.7    Connection Diagram of EUT and Peripheral Devices .....	11
3.8    Configuration of Peripheral Devices and Cable Connections .....	11
<b>4      Test Instruments .....</b>	<b>12</b>
4.1    RF Output Power.....	12
4.2    Power Spectral Density .....	12
4.3    6 dB Bandwidth .....	12
4.4    Conducted Out of Band Emissions .....	12
4.5    AC Power Conducted Emissions .....	13
4.6    Unwanted Emissions below 1 GHz .....	14
4.7    Unwanted Emissions above 1 GHz.....	15
<b>5      Limits of Test Items.....</b>	<b>16</b>
5.1    RF Output Power.....	16
5.2    Power Spectral Density .....	16
5.3    6 dB Bandwidth .....	16
5.4    Conducted Out of Band Emissions .....	16
5.5    AC Power Conducted Emissions .....	16
5.6    Unwanted Emissions below 1 GHz .....	16
5.7    Unwanted Emissions above 1 GHz.....	17
<b>6      Test Arrangements.....</b>	<b>18</b>
6.1    RF Output Power.....	18
6.1.1    Test Setup .....	18
6.1.2    Test Procedure.....	18
6.2    Power Spectral Density .....	18
6.2.1    Test Setup .....	18
6.2.2    Test Procedure.....	18
6.3    6 dB Bandwidth .....	19
6.3.1    Test Setup .....	19
6.3.2    Test Procedure.....	19
6.4    Conducted Out of Band Emissions .....	19
6.4.1    Test Setup .....	19
6.4.2    Test Procedure.....	19
6.5    AC Power Conducted Emissions .....	20
6.5.1    Test Setup .....	20
6.5.2    Test Procedure.....	20
6.6    Unwanted Emissions below 1 GHz .....	21
6.6.1    Test Setup .....	21
6.6.2    Test Procedure.....	22
6.7    Unwanted Emissions above 1 GHz.....	23
6.7.1    Test Setup .....	23
6.7.2    Test Procedure.....	23
<b>7      Test Results of Test Item .....</b>	<b>24</b>



BUREAU  
VERITAS

7.1	RF Output Power.....	24
7.2	Power Spectral Density .....	26
7.3	6 dB Bandwidth .....	28
7.4	Conducted Out of Band Emissions .....	30
7.5	AC Power Conducted Emissions .....	33
7.6	Unwanted Emissions below 1 GHz .....	35
7.7	Unwanted Emissions above 1 GHz.....	37
<b>8</b>	<b>Pictures of Test Arrangements .....</b>	<b>49</b>
<b>9</b>	<b>Information of the Testing Laboratories .....</b>	<b>50</b>



## Release Control Record

Issue No.	Description	Date Issued
RFBDKX-WTW-P22120419	Original release.	2023/3/30



## 1 Certificate

**Product:** Home IOT Gateway

**Brand:** Level

**Test Model:** H4

**Sample Status:** Engineering sample

**Applicant:** Level Home Inc.

**Test Date:** 2023/2/8 ~ 2023/2/21

**Standard:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

**Measurement**  
**procedure:** ANSI C63.10-2013

KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -14.56 dB at 0.43925 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -14.8 dB at 689.60 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -1.7 dB at 2390.00 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Specification	Expanded Uncertainty (k=2) ( $\pm$ )
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.63 dB
AC Power Conducted Emissions	150 kHz ~ 30 MHz	3.00 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	2.38 dB
	30 MHz ~ 1 GHz	5.7 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 6 GHz	4.83 dB
	6 GHz ~ 18 GHz	5.37 dB
	18 GHz ~ 40 GHz	5.24 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

### 2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

### 3 General Information

#### 3.1 General Description

Product	Home IOT Gateway
Brand	Level
Test Model	H4
Status of EUT	Engineering sample
Power Supply Rating	3.6Vdc from battery or 5Vdc from Adapter
Modulation Type	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
Modulation Technology	DSSS, OFDM
Transfer Rate	Up to 72.2Mbps
Operating Frequency	2.412 GHz ~ 2.462 GHz
Number of Channel	802.11b, 802.11g, 802.11n (HT20):11
Output Power	219.786 mW (23.42 dBm)

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
Battery	Grand-Pro	INR18650	Power Rating : 3.6V 3350mah/ 12.06Wh
AC Adapter	TENPO	S024AMP0500350	AC Input : 100-240Vac, 50/60Hz, 0.6A DC Output : 5.0Vdc 3.5A, 17.5W DC Cable : Nonshielded without cord, 1.0m AC Cable : Nonshielded without cord, 1.0m
LAN Cable	-	-	Nonshielded without cord, 1.0m

2. There are Z-wave, WLAN and WWAN technology used for the EUT.
3. WLAN and WWAN technology can transmit at same time.
4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

#### 3.2 Antenna Description of EUT

1. The antenna information is listed as below.

Gain (dBi)			Antenna Type	Connector Type
2400 MHz	2450 MHz	2500 MHz		
3.33	3.66	3.08	PIFA	ipex

\* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

2. The EUT incorporates a SISO function:

Modulation Mode	TX & RX Configuration	
802.11b	1TX	1RX
802.11g	1TX	1RX
802.11n (HT20)	1TX	1RX

### 3.3 Channel List

11 channels are provided for 802.11b, 802.11g, 802.11n (HT20):

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

### 3.4 Test Mode Applicability and Tested Channel Detail

Pre-Scan:	1. EUT can be used in the following ways: Wall Mount/ X-axis/ Y-axis/ Z-axis. Pre-scan these ways and find the worst case as a representative test condition. 2. For Unwanted Emission below/ above 1 GHz has Battery / EUT with Adapter mode of power supply. Pre-scan these modes and find the worst case as a representative test condition.
Worst Case:	1. Wall Mount/ X-axis/ Y-axis/ Z-axis Worst Condition: X-axis. 2. For Unwanted Emission below/ above 1 GHz EUT with Adapter mode is the worst case of power supply.

Following channel(s) was (were) selected for the final test as listed below:


Test Item	Mode	Signal Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power / Power Spectral Density	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0
6 dB Bandwidth / Conducted Out of Band Emissions	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0
AC Power Conducted Emissions	802.11g	CDD	1	BPSK	6Mb/s
Unwanted Emissions below 1 GHz	802.11g	CDD	1	BPSK	6Mb/s
Unwanted Emissions above 1 GHz	802.11b	CDD	1, 6, 11	DBPSK	1Mb/s
	802.11g	CDD	1, 6, 11	BPSK	6Mb/s
	802.11n (HT20)	CDD	1, 6, 11	BPSK	MCS0

### 3.5 Duty Cycle of Test Signal

**802.11b:** Duty cycle =  $8.614 \text{ ms} / 8.703 \text{ ms} \times 100\% = 99.0\%$

**802.11g:** Duty cycle =  $1.429 \text{ ms} / 1.529 \text{ ms} \times 100\% = 93.5\%$ , duty factor =  $10 * \log(1/\text{Duty cycle}) = 0.29 \text{ dB}$


**802.11n (HT20):** Duty cycle =  $1.337 \text{ ms} / 1.436 \text{ ms} \times 100\% = 93.1\%$ , duty factor =  $10 * \log(1/\text{Duty cycle}) = 0.31 \text{ dB}$



### 3.6 Test Program Used and Operation Descriptions

Controlling software (Tera Term v4.8) has been activated to set the EUT under transmission condition continuously at specific channel frequency.

### 3.7 Connection Diagram of EUT and Peripheral Devices



### 3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	TENPO	S024AMP0500350	N/A	N/A	Supplied by applicant
B	Laptop	Lenovo	81A4	YD02TWDP	N/A	Provided by Lab
C	Adapter	Lenovo	PA-1450-55LL	N/A	N/A	Provided by Lab

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	DC Cable	1	1	N	0	Supplied by applicant
2	AC Cable	1	1	N	0	Supplied by applicant
3	USB to LAN cable	1	0.2	N	0	Provided by Lab
4	DC cable	1	1.9	N	0	Provided by Lab
5	LAN cable	1	1	N	0	Supplied by applicant

## 4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

### 4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
MIMO Powermeasurement Test set (4X4) KEYSIGHT	U2021XA	U2021XA_001	2022/6/13	2023/6/12
MXG Vector Signal Generator KEYSIGHT	N5182B	MY53052658	2022/5/9	2023/5/8
Peak Power meter Anritsu	ML2495A	0842014	2022/4/27	2023/4/26
Pulse Power Sensor Anritsu	MA2411B	0738404	2022/4/27	2023/4/26
Spectrum Analyzer KEYSIGHT	N9030A	MY54490260	2022/7/14	2023/7/13
Spectrum Analyzer R&S	FSV40	101042	2022/9/5	2023/9/4
		101544	2022/5/9	2023/5/8
Temperature & Humidity Chamber TERCHY	MHU-225AU	920409	2022/6/27	2023/6/26
Voltage Meter FLUKE	179	89610322	2022/10/3	2023/10/2

Notes:

1. The test was performed in LK - Oven
2. Tested Date: 2023/2/13

### 4.2 Power Spectral Density

Refer to section 4.1 to get information of the instruments.

### 4.3 6 dB Bandwidth

Refer to section 4.1 to get information of the instruments.

### 4.4 Conducted Out of Band Emissions

Refer to section 4.1 to get information of the instruments.

#### 4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal LYNICS	0900510	E1-011285	2022/9/19	2023/9/18
		E1-011286	2022/9/19	2023/9/18
50 Ohms Terminator LYNICS	0900510	E1-01-305	2023/2/13	2024/2/12
Attenuator STI	STI02-2200-10	NO.4	2022/9/2	2023/9/1
DC LISN R&S	ESH3-Z6	100219	2022/8/2	2023/8/1
		844950/018	2022/8/2	2023/8/1
DC LISN Schwarzbeck	NNLK 8121	8121-808	2022/4/29	2023/4/28
High Voltage Probe Schwarzbeck	TK9420	00982	2022/12/14	2023/12/13
Isolation Transformer Erika Fiedler	D-65396	017	2022/9/8	2023/9/7
LISN R&S	ENV216	101196	2022/5/24	2023/5/23
LISN Schwarzbeck	NNLK 8121	8121-731	2022/5/26	2023/5/25
		8121-00759	2022/8/18	2023/8/17
	NNLK8129	8129229	2022/6/8	2023/6/7
	NSLK 8128	8128-244	2022/11/8	2023/11/7
RF Coaxial Cable Commate	5D-FB	Cable-CO5-01	2023/1/19	2024/1/18
Software BVADT	Cond_V7.3.7.4	N/A	N/A	N/A
Test Receiver R&S	ESR3	102412	2022/12/21	2023/12/20

Notes:

1. The test was performed in Linkou Conduction 5.
2. Tested Date: 2023/2/21

#### 4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
* LOOP ANTENNA EMCI	LPA600	270	2021/9/2	2023/9/1
Bi_Log Antenna Schwarzbeck	VULB 9168	137	2022/10/21	2023/10/20
Coupling/Dcoupling Network Schwarzbeck	CDNE-M2	00097	2022/6/1	2023/5/31
	CDNE-M3	00091	2022/6/1	2023/5/31
Pre_Amplifier EMCI	EMC001340	980269	2022/6/28	2023/6/27
Pre_Amplifier HP	8447D	2432A03504	2023/2/16	2024/2/15
RF Coaxial Cable Pacific	8D-FB	Cable-CH6-02	2022/6/30	2023/6/29
Software BVADT	Radiated_V7.7.1.1.1	N/A	N/A	N/A
	Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	101544	2022/5/9	2023/5/8
Test Receiver Agilent	N9038A	MY51210129	2022/4/8	2023/4/7
		MY51210137	2022/6/9	2023/6/8
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. \* The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA
2. The test was performed in Linkou 966 Chamber 6 (CH 6).
3. Tested Date: 2023/2/20

#### 4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Band Pass Filter MICRO-TRONICS	BRM17690	005	2022/5/26	2023/5/25
Boresight antenna tower fixture BV	BAF-02	6	N/A	N/A
High Pass Filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	2022/5/26	2023/5/25
Horn Antenna EMCO	3115	00028257	2022/11/13	2023/11/12
Horn Antenna ETS-Lindgren	3117-PA	00215857	2023/2/3	2024/2/2
Horn Antenna Schwarzbeck	BBHA 9170	212	2022/10/20	2023/10/19
Notch Filter MICRO-TRONICS	BRC50703-01	010	2022/5/26	2023/5/25
Pre-amplifier HP	8449B	3008A01201	2022/2/17	2023/2/16
Pre-amplifier (18GHz-40GHz) EMCI	EMC184045B	980175	2022/9/3	2023/9/2
Pre_Amplifier EMCI	EMC0126545	980076	2022/2/17	2023/2/16
	EMC184045B	980235	2022/2/17	2023/2/16
RF Coaxial Cable EM	EM102-KMKG-3.5+1M	EM102-KMKG-3.5+1M-01	2022/7/7	2023/7/6
RF Coaxial Cable EMCI	EMC104	190801	2022/7/7	2023/7/6
		190804	2022/7/7	2023/7/6
RF Coaxial Cable HUBER SUHNER	SF-104	Cable-CH6-01	2022/9/20	2023/9/19
Software BVADT	Radiated_V7.7.1.1.1	N/A	N/A	N/A
	Radiated_V8.7.08	N/A	N/A	N/A
Spectrum Analyzer R&S	FSV40	101042	2022/9/5	2023/9/4
		101544	2022/5/9	2023/5/8
Test Receiver Agilent	N9038A	MY51210129	2022/4/8	2023/4/7
Tower ADT	AT100	0306	N/A	N/A
Turn Table ADT	TT100	0306	N/A	N/A

Notes:

1. The test was performed in Linkou 966 Chamber 6 (CH 6).
2. Tested Date: 2023/2/8 ~ 2023/2/9

## 5 Limits of Test Items

### 5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

### 5.2 Power Spectral Density

The Maximum of Power Spectral Density Measurement is 8 dBm in any 3 kHz.

### 5.3 6 dB Bandwidth

The minimum of 6 dB Bandwidth Measurement is 0.5 MHz.

### 5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

### 5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

## 5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>uV</sub>/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

## 6 Test Arrangements

### 6.1 RF Output Power

#### 6.1.1 Test Setup



#### 6.1.2 Test Procedure

**Peak Power:**

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

**Average Power:**

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

### 6.2 Power Spectral Density

#### 6.2.1 Test Setup




#### 6.2.2 Test Procedure

- a. Set analyzer center frequency to DTS channel center frequency.
- b. Set the span to 1.5 times the DTS bandwidth.
- c. Set the RBW to: 3 kHz.
- d. Set the VBW  $\geq 3 \times$  RBW.
- e. Detector = peak.
- f. Sweep time = auto couple.
- g. Trace mode = max hold.
- h. Allow trace to fully stabilize.
- i. Use the peak marker function to determine the maximum amplitude level within the RBW.

### 6.3 6 dB Bandwidth

#### 6.3.1 Test Setup




#### 6.3.2 Test Procedure

- Set resolution bandwidth (RBW) = 100 kHz.
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### 6.4 Conducted Out of Band Emissions

#### 6.4.1 Test Setup



#### 6.4.2 Test Procedure

#### MEASUREMENT PROCEDURE REF


- Set the RBW = 100 kHz.
- Set the VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

- Set RBW = 100 kHz.
- Set VBW  $\geq 300$  kHz.
- Detector = peak.
- Sweep = auto couple.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

## 6.5 AC Power Conducted Emissions

### 6.5.1 Test Setup



**Note: 1. Support units were connected to second LISN.**

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.5.2 Test Procedure


- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


## 6.6 Unwanted Emissions below 1 GHz

### 6.6.1 Test Setup

**For Radiated emission below 30 MHz**



**For Radiated emission above 30 MHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

## 6.6.2 Test Procedure

### For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode, except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

### For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. All modes of operation were investigated and the worst-case emissions are reported.

## 6.7 Unwanted Emissions above 1 GHz

### 6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 6.7.2 Test Procedure

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

1. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
2. For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is  $\geq 1/T$  (Duty cycle  $< 98\%$ ) or 10 Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1 GHz.
3. All modes of operation were investigated and the worst-case emissions are reported.

## 7 Test Results of Test Item

### 7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Waydi Tuan
--------------	----------------	---------------------------	--------------	------------	------------

#### For Peak Power

##### 802.11b

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	90.365	19.56	30	Pass
6	2437	89.950	19.54	30	Pass
11	2462	61.944	17.92	30	Pass

Note: The antenna gain is 3.66 dBi < 6 dBi, so the output power limit shall not be reduced.

##### 802.11g

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	219.786	23.42	30	Pass
6	2437	209.894	23.22	30	Pass
11	2462	160.694	22.06	30	Pass

Note: The antenna gain is 3.66 dBi < 6 dBi, so the output power limit shall not be reduced.

##### 802.11n (HT20)

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
1	2412	134.276	21.28	30	Pass
6	2437	138.995	21.43	30	Pass
11	2462	83.176	19.20	30	Pass

Note: The antenna gain is 3.66 dBi < 6 dBi, so the output power limit shall not be reduced.

#### For Average Power

##### 802.11b

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	52.481	17.20
6	2437	52.360	17.19
11	2462	36.475	15.62

**802.11g**

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	30.061	14.78
6	2437	29.717	14.73
11	2462	18.836	12.75

**802.11n (HT20)**

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
1	2412	18.967	12.78
6	2437	19.498	12.90
11	2462	11.940	10.77

## 7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Waydi Tuan
--------------	----------------	---------------------------	--------------	------------	------------

### 802.11b

Channel	Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-5.64	8	Pass
6	2437	-5.96	8	Pass
11	2462	-8.23	8	Pass

Note: The antenna gain is 3.66 dBi < 6 dBi, so the power density limit shall not be reduced.

### 802.11g

Channel	Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-11.46	8	Pass
6	2437	-10.92	8	Pass
11	2462	-12.02	8	Pass


Note: The antenna gain is 3.66 dBi < 6 dBi, so the power density limit shall not be reduced.

### 802.11n (HT20)

Channel	Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Pass / Fail
1	2412	-13.59	8	Pass
6	2437	-12.90	8	Pass
11	2462	-15.46	8	Pass

Note: The antenna gain is 3.66 dBi < 6 dBi, so the power density limit shall not be reduced.

### Spectrum Plot of Maximum Value



### 7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Waydi Tuan
--------------	----------------	---------------------------	--------------	------------	------------

#### 802.11b

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	8.57	0.5	Pass
6	2437	9.02	0.5	Pass
11	2462	8.62	0.5	Pass


#### 802.11g

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.18	0.5	Pass
6	2437	15.19	0.5	Pass
11	2462	15.18	0.5	Pass

#### 802.11n (HT20)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
1	2412	15.19	0.5	Pass
6	2437	15.18	0.5	Pass
11	2462	15.19	0.5	Pass


## Spectrum Plot of Minimum Value




## 7.4 Conducted Out of Band Emissions


Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 76% RH	Tested By:	Waydi Tuan
--------------	----------------	---------------------------	--------------	------------	------------

### 802.11b



**802.11g**


## 802.11n (HT20)




## 7.5 AC Power Conducted Emissions

<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	25°C, 75% RH
<b>Tested By</b>	Jed Wu		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15719	10.00	40.17	19.58	50.17	29.58	65.61	55.61	-15.44	-26.03
2	<b>0.43925</b>	<b>10.06</b>	<b>32.46</b>	<b>21.55</b>	<b>42.52</b>	<b>31.61</b>	<b>57.08</b>	<b>47.08</b>	<b>-14.56</b>	<b>-15.47</b>
3	0.76190	10.08	22.95	15.13	33.03	25.21	56.00	46.00	-22.97	-20.79
4	3.95059	10.18	16.75	9.18	26.93	19.36	56.00	46.00	-29.07	-26.64
5	5.53944	10.22	14.65	7.23	24.87	17.45	60.00	50.00	-35.13	-32.55
6	11.06677	10.36	16.02	6.40	26.38	16.76	60.00	50.00	-33.62	-33.24

### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	150kHz ~ 30MHz	<b>Detector Function &amp; Resolution Bandwidth</b>	Quasi-Peak (QP) / Average (AV), 9 kHz
<b>Input Power</b>	120 Vac, 60 Hz	<b>Environmental Conditions</b>	25°C, 75% RH
<b>Tested By</b>	Jed Wu		

**Phase Of Power : Neutral (N)**

<b>No</b>	<b>Frequency (MHz)</b>	<b>Correction Factor (dB)</b>	<b>Reading Value (dBuV)</b>		<b>Emission Level (dBuV)</b>		<b>Limit (dBuV)</b>		<b>Margin (dB)</b>	
			<b>Q.P.</b>	<b>AV.</b>	<b>Q.P.</b>	<b>AV.</b>	<b>Q.P.</b>	<b>AV.</b>	<b>Q.P.</b>	<b>AV.</b>
1	0.16564	10.03	39.88	16.61	49.91	26.64	65.18	55.18	-15.27	-28.54
2	0.34936	10.06	32.94	19.42	43.00	29.48	58.98	48.98	-15.98	-19.50
3	0.72276	10.09	23.22	16.38	33.31	26.47	56.00	46.00	-22.69	-19.53
4	4.58776	10.21	12.66	7.41	22.87	17.62	56.00	46.00	-33.13	-28.38
5	7.47049	10.28	10.77	5.79	21.05	16.07	60.00	50.00	-38.95	-33.93
6	10.31624	10.36	12.05	6.38	22.41	16.74	60.00	50.00	-37.59	-33.26

**Remarks:**

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




## 7.6 Unwanted Emissions below 1 GHz

<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	30 MHz ~ 1 GHz	<b>Detector Function &amp; Bandwidth</b>	(QP) RB = 120kHz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	25°C, 68% RH
<b>Tested By</b>	Ian Chang		

Antenna Polarity & Test Distance : Horizontal at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	40.67	21.3 QP	40.0	-18.7	1.48 H	54	30.8	-9.5
2	119.24	22.6 QP	43.5	-20.9	2.00 H	106	33.7	-11.1
3	280.26	24.0 QP	46.0	-22.0	2.34 H	139	30.7	-6.7
4	350.10	25.9 QP	46.0	-20.1	3.94 H	297	31.2	-5.3
5	450.01	28.9 QP	46.0	-17.1	2.59 H	163	31.4	-2.5
6	<b>689.60</b>	<b>31.2 QP</b>	<b>46.0</b>	<b>-14.8</b>	<b>3.11 H</b>	<b>215</b>	<b>28.8</b>	<b>2.4</b>

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be reported.




<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	30 MHz ~ 1 GHz	<b>Detector Function &amp; Bandwidth</b>	(QP) RB = 120kHz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	25°C, 68% RH
<b>Tested By</b>	Ian Chang		

**Antenna Polarity & Test Distance : Vertical at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	71.71	22.6 QP	40.0	-17.4	2.21 V	196	34.0	-11.4
2	99.84	21.2 QP	43.5	-22.3	2.36 V	211	34.2	-13.0
3	280.26	23.0 QP	46.0	-23.0	2.65 V	240	29.7	-6.7
4	368.53	24.3 QP	46.0	-21.7	2.86 V	261	28.9	-4.6
5	477.17	26.5 QP	46.0	-19.5	3.21 V	295	28.7	-2.2
6	630.43	28.9 QP	46.0	-17.1	3.56 V	330	27.4	1.5

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The emission levels were very low against the limit of frequency range 9 kHz ~ 30 MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



## 7.7 Unwanted Emissions above 1 GHz

<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 1 : 2412 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	17°C, 62.2% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	55.4 PK	74.0	-18.6	1.18 H	67	53.3	2.1
2	2390.00	50.9 AV	54.0	-3.1	1.18 H	67	48.8	2.1
3	*2412.00	107.9 PK			1.18 H	67	105.5	2.4
4	*2412.00	106.1 AV			1.18 H	67	103.7	2.4
5	4824.00	53.0 PK	74.0	-21.0	1.00 H	3	40.8	12.2
6	4824.00	46.5 AV	54.0	-7.5	1.00 H	3	34.3	12.2
Antenna Polarity & Test Distance : Vertical at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	52.8 PK	74.0	-21.2	3.45 V	332	50.7	2.1
2	2390.00	46.3 AV	54.0	-7.7	3.45 V	332	44.2	2.1
3	*2412.00	104.9 PK			3.45 V	332	102.5	2.4
4	*2412.00	103.1 AV			3.45 V	332	100.7	2.4
5	4824.00	54.2 PK	74.0	-19.8	1.39 V	157	42.0	12.2
6	4824.00	48.8 AV	54.0	-5.2	1.39 V	157	36.6	12.2

### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

BUREAU  
VERITAS

RF Mode	802.11b	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
Input Power	120Vac,60Hz	Environmental Conditions	17°C, 62.2% RH
Tested By	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.0 PK			1.86 H	57	105.6	2.4
2	*2437.00	105.9 AV			1.86 H	57	103.5	2.4
3	4874.00	52.7 PK	74.0	-21.3	1.68 H	13	40.1	12.6
4	4874.00	46.0 AV	54.0	-8.0	1.68 H	13	33.4	12.6

**Antenna Polarity & Test Distance : Vertical at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	105.1 PK			2.77 V	322	102.7	2.4
2	*2437.00	102.9 AV			2.77 V	322	100.5	2.4
3	4874.00	53.9 PK	74.0	-20.1	1.46 V	157	41.3	12.6
4	4874.00	48.3 AV	54.0	-5.7	1.46 V	157	35.7	12.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



BUREAU  
VERITAS

<b>RF Mode</b>	802.11b	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 10 Hz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	17°C, 62.2% RH
<b>Tested By</b>	Jed Wu		

Antenna Polarity & Test Distance : Horizontal at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.1 PK			1.01 H	52	104.6	2.5
2	*2462.00	105.2 AV			1.01 H	52	102.7	2.5
3	2483.50	54.8 PK	74.0	-19.2	1.01 H	52	52.3	2.5
4	2483.50	45.8 AV	54.0	-8.2	1.01 H	52	43.3	2.5
5	4924.00	52.7 PK	74.0	-21.3	1.17 H	18	40.0	12.7
6	4924.00	46.1 AV	54.0	-7.9	1.17 H	18	33.4	12.7
Antenna Polarity & Test Distance : Vertical at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	104.2 PK			3.28 V	317	101.7	2.5
2	*2462.00	101.9 AV			3.28 V	317	99.4	2.5
3	2483.50	53.6 PK	74.0	-20.4	3.28 V	317	51.1	2.5
4	2483.50	44.7 AV	54.0	-9.3	3.28 V	317	42.2	2.5
5	4924.00	53.8 PK	74.0	-20.2	1.22 V	142	41.1	12.7
6	4924.00	48.4 AV	54.0	-5.6	1.22 V	142	35.7	12.7

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

BUREAU  
VERITAS

RF Mode	802.11g	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120Vac,60Hz	Environmental Conditions	17°C, 62.2% RH
Tested By	Jed Wu		

## Antenna Polarity &amp; Test Distance : Horizontal at

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	65.4 PK	74.0	-8.6	1.19 H	58	63.3	2.1
2	<b>2390.00</b>	<b>52.3 AV</b>	<b>54.0</b>	<b>-1.7</b>	<b>1.19 H</b>	<b>58</b>	<b>50.2</b>	<b>2.1</b>
3	*2412.00	110.0 PK			1.19 H	58	107.6	2.4
4	*2412.00	100.9 AV			1.19 H	58	98.5	2.4
5	4824.00	53.1 PK	74.0	-20.9	1.01 H	12	40.9	12.2
6	4824.00	46.6 AV	54.0	-7.4	1.01 H	12	34.4	12.2

## Antenna Polarity &amp; Test Distance : Vertical at

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	63.1 PK	74.0	-10.9	3.44 V	333	61.0	2.1
2	2390.00	49.7 AV	54.0	-4.3	3.44 V	333	47.6	2.1
3	*2412.00	107.8 PK			3.44 V	333	105.4	2.4
4	*2412.00	98.8 AV			3.44 V	333	96.4	2.4
5	4824.00	54.0 PK	74.0	-20.0	1.38 V	156	41.8	12.2
6	4824.00	48.6 AV	54.0	-5.4	1.38 V	156	36.4	12.2

## Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

BUREAU  
VERITAS

RF Mode	802.11g	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120Vac,60Hz	Environmental Conditions	17°C, 62.2% RH
Tested By	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	109.7 PK			1.34 H	63	107.3	2.4
2	*2437.00	101.1 AV			1.34 H	63	98.7	2.4
3	4874.00	53.2 PK	74.0	-20.8	1.16 H	17	40.6	12.6
4	4874.00	46.7 AV	54.0	-7.3	1.16 H	17	34.1	12.6

**Antenna Polarity & Test Distance : Vertical at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	107.5 PK			3.29 V	336	105.1	2.4
2	*2437.00	98.9 AV			3.29 V	336	96.5	2.4
3	4874.00	54.2 PK	74.0	-19.8	1.55 V	161	41.6	12.6
4	4874.00	49.0 AV	54.0	-5.0	1.55 V	161	36.4	12.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.



BUREAU  
VERITAS

<b>RF Mode</b>	802.11g	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	17°C, 62.2% RH
<b>Tested By</b>	Jed Wu		

#### Antenna Polarity & Test Distance : Horizontal at

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.1 PK			1.01 H	57	106.6	2.5
2	*2462.00	100.2 AV			1.01 H	57	97.7	2.5
3	2483.50	64.4 PK	74.0	-9.6	1.01 H	57	61.9	2.5
4	2483.50	48.1 AV	54.0	-5.9	1.01 H	57	45.6	2.5
5	4924.00	52.6 PK	74.0	-21.4	1.49 H	11	39.9	12.7
6	4924.00	46.1 AV	54.0	-7.9	1.49 H	11	33.4	12.7

#### Antenna Polarity & Test Distance : Vertical at

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	106.2 PK			3.28 V	332	103.7	2.5
2	*2462.00	97.5 AV			3.28 V	332	95.0	2.5
3	2483.50	62.1 PK	74.0	-11.9	3.28 V	332	59.6	2.5
4	2483.50	45.7 AV	54.0	-8.3	3.28 V	332	43.2	2.5
5	4924.00	53.7 PK	74.0	-20.3	1.22 V	158	41.0	12.7
6	4924.00	48.2 AV	54.0	-5.8	1.22 V	158	35.5	12.7

#### Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

BUREAU  
VERITAS

RF Mode	802.11n (HT20)	Channel	CH 1 : 2412 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120Vac,60Hz	Environmental Conditions	17°C, 62.2% RH
Tested By	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.6 PK	74.0	-13.4	1.18 H	57	58.5	2.1
2	2390.00	48.9 AV	54.0	-5.1	1.18 H	57	46.8	2.1
3	*2412.00	108.1 PK			1.18 H	57	105.7	2.4
4	*2412.00	99.2 AV			1.18 H	57	96.8	2.4
5	4824.00	53.2 PK	74.0	-20.8	1.02 H	11	41.0	12.2
6	4824.00	46.7 AV	54.0	-7.3	1.02 H	11	34.5	12.2

**Antenna Polarity & Test Distance : Vertical at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	58.7 PK	74.0	-15.3	3.46 V	331	56.6	2.1
2	2390.00	46.8 AV	54.0	-7.2	3.46 V	331	44.7	2.1
3	*2412.00	105.6 PK			3.46 V	331	103.2	2.4
4	*2412.00	96.5 AV			3.46 V	331	94.1	2.4
5	4824.00	54.4 PK	74.0	-19.6	1.40 V	158	42.2	12.2
6	4824.00	49.0 AV	54.0	-5.0	1.40 V	158	36.8	12.2

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

BUREAU  
VERITAS

RF Mode	802.11n (HT20)	Channel	CH 6 : 2437 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
Input Power	120Vac,60Hz	Environmental Conditions	17°C, 62.2% RH
Tested By	Jed Wu		

**Antenna Polarity & Test Distance : Horizontal at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	108.7 PK			2.25 H	62	106.3	2.4
2	*2437.00	99.4 AV			2.25 H	62	97.0	2.4
3	4874.00	53.0 PK	74.0	-21.0	2.09 H	16	40.4	12.6
4	4874.00	46.5 AV	54.0	-7.5	2.09 H	16	33.9	12.6

**Antenna Polarity & Test Distance : Vertical at**

No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	106.1 PK			2.38 V	327	103.7	2.4
2	*2437.00	96.9 AV			2.38 V	327	94.5	2.4
3	4874.00	54.2 PK	74.0	-19.8	2.46 V	152	41.6	12.6
4	4874.00	48.8 AV	54.0	-5.2	2.46 V	152	36.2	12.6

**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.


<b>RF Mode</b>	802.11n (HT20)	<b>Channel</b>	CH 11 : 2462 MHz
<b>Frequency Range</b>	1 GHz ~ 25 GHz	<b>Detector Function &amp; Bandwidth</b>	(PK) RB = 1 MHz, VB = 3 MHz (AV) RB = 1 MHz, VB = 1 kHz
<b>Input Power</b>	120Vac,60Hz	<b>Environmental Conditions</b>	17°C, 62.2% RH
<b>Tested By</b>	Jed Wu		









Antenna Polarity & Test Distance : Horizontal at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	107.8 PK			1.84 H	61	105.3	2.5
2	*2462.00	98.8 AV			1.84 H	61	96.3	2.5
3	2483.50	60.1 PK	74.0	-13.9	1.84 H	61	57.6	2.5
4	2483.50	46.2 AV	54.0	-7.8	1.84 H	61	43.7	2.5
5	4924.00	52.1 PK	74.0	-21.9	1.66 H	9	39.4	12.7
6	4924.00	45.6 AV	54.0	-8.4	1.66 H	9	32.9	12.7
Antenna Polarity & Test Distance : Vertical at								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	104.9 PK			2.79 V	326	102.4	2.5
2	*2462.00	95.7 AV			2.79 V	326	93.2	2.5
3	2483.50	57.9 PK	74.0	-16.1	2.79 V	326	55.4	2.5
4	2483.50	44.0 AV	54.0	-10.0	2.79 V	326	41.5	2.5
5	4924.00	53.3 PK	74.0	-20.7	2.05 V	163	40.6	12.7
6	4924.00	47.9 AV	54.0	-6.1	2.05 V	163	35.2	12.7









**Remarks:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " \* ": Fundamental frequency, the limit was restricted at the RF Output Power.

## Plot of Band Edge



**802.11g Channel 1**
**Horizontal (Peak)**

**Horizontal (Average)**

**Vertical (Peak)**

**Vertical (Average)**

**802.11g Channel 11**
**Horizontal (Peak)**

**Horizontal (Average)**

**Vertical (Peak)**

**Vertical (Average)**


**802.11n (HT20) Channel 1**
**Horizontal (Peak)**

**Horizontal (Average)**

**Vertical (Peak)**

**Vertical (Average)**

**802.11n (HT20) Channel 11**
**Horizontal (Peak)**

**Horizontal (Average)**

**Vertical (Peak)**

**Vertical (Average)**


## 8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

## 9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Lin Kou EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565

Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@bureauveritas.com](mailto:service.adt@bureauveritas.com)

**Web Site:** <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---