## **RF Exposure Evaluation**

#### Limits

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm²)	Averaging time (minutes)	
	(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6	
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6	
30–300	61.4	0.163	1.0	6	
300–1500			f/300	6	
1500–100,000			5	6	
	(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30	
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30	
30–300	27.5	0.073	0.2	30	
300–1500			f/1500	30	
1500-100,000			1.0	30	

f = frequency in MHz

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

### Where

**Pd** = power density in mW/cm<sup>2</sup>, **Pout** = output power to antenna in mW;

**G** = gain of antenna in linear scale, **Pi** = 3.1416;

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

### **Test Procedure**

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

# **Test Result of RF Exposure Evaluation**

### WiFi 2.4G

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm <sup>2</sup> )	Result
Lowest (2412MHz)	31.189	0.00620	1.0	PASS
Middle (2437MHz)	30.549	0.00608	1.0	PASS
Highest (2462MHz)	31.405	0.00625	1.0	PASS

## WiFi 5G

Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm²)	Limit (mW/cm <sup>2</sup> )	Result
5580MHz	38.459	0.00765	1.0	PASS

### WiFi 5.8G

	Channel	Output power to antenna (mW)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Result
Ī	5745MHz	15.704	0.00312	1.0	PASS

### Remark:

- 1. Antenna gain=0dBi
- 2. The max power density is less than SAR exempt limit, so SAR evaluation is not required.