

TEST REPORT

Report No.: BCTC2101803096E

Applicant: Shenzhen Dayunlinks Co., Ltd

Product Name: Wireless Home Security Battery Camera System

Model/Type Ref.: BC-HC12

Tested Date: 2021-01-18 to 2021-03-08

Issued Date: 2021-03-08


Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2ATJW-BCHC12

Product Name: Wireless Home Security Battery Camera System
Trademark: N/A
Model/Type Ref.: BC-HC12
BC-HC14, BC-H1, BC-C1
Prepared For: Shenzhen Dayunlinks Co., Ltd
Address: 30th Park West Zhangbei Yuanhu Road Longcheng Street
Longgang District Shenzhen City. 518000. Guangdong
Province. China
Manufacturer: Shenzhen Dayunlinks Co., Ltd
Address: 30th Park West Zhangbei Yuanhu Road Longcheng Street
Longgang District Shenzhen City. 518000. Guangdong
Province. China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan
1st Road, Tangwei, Fuhai Subdistrict, Bao'an District,
Shenzhen, Guangdong, China
Sample Received Date: 2021-01-18
Sample tested Date: 2021-01-18 to 2021-03-08
Issue Date: 2021-03-08
Report No.: BCTC2101803096E
FCC Part15.247
Test Standards ANSI C63.10:2013
KDB 662911 D01 v02r01
558074 D01 15.247 Meas Guidance v05r02
Test Results PASS

Tested by:



Kelsey Tan/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table of Contents		Page
1 .VERSION		6
2 . SUMMARY OF TEST RESULTS		7
2.1 MEASUREMENT UNCERTAINTY		8
3 . GENERAL INFORMATION		9
3.1 GENERAL DESCRIPTION OF EUT		9
3.2 DESCRIPTION OF TEST MODES		11
3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED		11
3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)		12
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS		13
3.5.1TEST FACILITY		13
4 . EMC EMISSION TEST		15
4.1 CONDUCTED EMISSION MEASUREMENT		15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS		15
4.1.2 TEST PROCEDURE		15
4.1.3 DEVIATION FROM TEST STANDARD		15
4.1.4 TEST SETUP		16
4.1.5 EUT OPERATING CONDITIONS		16
4.1.6 TEST RESULTS		17
4.2 RADIATED EMISSION MEASUREMENT		19
4.2.1 RADIATED EMISSION LIMITS		19
4.2.2 TEST PROCEDURE		20
4.2.3 DEVIATION FROM TEST STANDARD		20
4.2.4 TEST SETUP		21
4.2.5 EUT OPERATING CONDITIONS		22
4.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)		23
4.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)		24
4.2.8 TEST RESULTS		26
4.3 RADIATED BAND EMISSION MEASUREMENT		30
4.3.1 TEST REQUIREMENT		30
4.3.2 TEST PROCEDURE		30
4.3.3 DEVIATION FROM TEST STANDARD		31
4.3.4 TEST SETUP		31
4.3.5 EUT OPERATING CONDITIONS		31
5 . POWER SPECTRAL DENSITY TEST		34

Table of Contents		Page
5.1 APPLIED PROCEDURES / LIMIT		34
5.1.1 TEST PROCEDURE		34
5.1.2 DEVIATION FROM STANDARD		34
5.1.3 TEST SETUP		34
5.1.4 EUT OPERATION CONDITIONS		34
5.1.5 TEST RESULTS		35
6 . BANDWIDTH TEST		43
6.1 APPLIED PROCEDURES / LIMIT		43
6.1.1 TEST PROCEDURE		43
6.1.2 DEVIATION FROM STANDARD		43
6.1.3 TEST SETUP		43
6.1.4 EUT OPERATION CONDITIONS		43
6.1.5 TEST RESULTS		44
7 . PEAK OUTPUT POWER TEST		52
7.1 APPLIED PROCEDURES/LIMIT		52
7.1.1 TEST PROCEDURE		52
7.1.2 DEVIATION FROM STANDARD		52
7.1.3 TEST SETUP		52
7.1.4 EUT OPERATION CONDITIONS		52
7.1.5 TEST RESULTS		53
8 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE		54
8.1 APPLICABLE STANDARD		54
8.2 TEST PROCEDURE		54
8.3 DEVIATION FROM STANDARD		54
8.4 TEST SETUP		54
8.5 EUT OPERATION CONDITIONS		54
9 . DUTY CYCLE OF TEST SIGNAL		64
9.1 STANDARD REQUIREMENT		64
9.2 FORMULA:		64
10 . ANTENNA REQUIREMENT		67
10.1 STANDARD REQUIREMENT		67
10.2 EUT ANTENNA		67
11 . EUT TEST PHOTO		68


Table of Contents

	Page
12 . EUT PHOTO APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS	70



1.VERSION

Report No.	Issue Date	Description	Approved
BCTC2101803096E	2021-03-08	Original	Valid




2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (d)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Restricted Band of Operation	PASS	
15.247 (d)	Band Edge (Out of Band Emissions)	PASS	
15.203	Antenna Requirement	PASS	

NOTE:


(1) "N/A" denotes test is not applicable in this Test Report



2.1 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement $y \pm U$, where expanded uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately **95 %**.


No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	3m chamber Radiated spurious emission(1GHz-18GHz)	U=4.5dB
3	3m chamber Radiated spurious emission(18GHz-40GHz)	U=3.34dB
4	Conducted Adjacent channel power	U=1.38dB
5	Conducted output power uncertainty Above 1G	U=1.576dB
6	Conducted output power uncertainty below 1G	U=1.28dB
7	humidity uncertainty	U=5.3%
8	Temperature uncertainty	U=0.59°C



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Model/Type Ref.:	BC-HC12 BC-HC14, BC-H1, BC-C1
Model differences:	All the model are the same circuit and RF module, except model names.
Hardware Version:	N/A
Software Version:	N/A
Operation Frequency:	802.11b/g/n20MHz:2412~2462 MHz 802.11n40MHz:2422~2452 MHz
Bit Rate of Transmitter	802.11b:11/5.5/2/1 Mbps 802.11g:54/48/36/24/18/12/9/6Mbps 802.11n Up to 75Mbps
Type of Modulation:	WIFI: OFDM/DSSS
Number Of Channel	802.11b/g/n20MHz:11 CH 802.11n40MHz: 7 CH
Antenna installation:	Internal Antenna
Antenna Gain:	Antenna A: 3dBi Antenna B: 3dBi
Ratings:	DC12V 1A
Adapter Information:	Model No.:SAN-12010 Input: AC100-240V 50/60Hz 0.35A Output:DC12V 1A



1.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

Channel List for 802.11n(40)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
03	2422	05	2432	07	2442	09	2452
04	2427	06	2437	08	2447		

2

Table for Internal Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
A	N/A	N/A	Internal Antenna	3	
B	N/A	N/A	Internal Antenna	3	


EUT has two External antennas with Max gain GANT 3dBi on every antenna, CDD device with two spatial streams, also can operate with one spatial streams according to KDB662911 D01 v02r01, Directional gain= GANT + Array Gain, where Array Gain is as follows.

1) For power spectral density (PSD) measurements,
 Array Gain = $10 \log(\text{NANT}/\text{NSS}) \text{ dB} = 10 \log(2/1) = 3.01 \text{ dB}$,
 So the directional gain for PSD is 6.01 dBi

2) For power measurements,

The Array gain = 0 dB for $\text{NANT} \leq 4$,

So the directional gain for Power measurements is 1 dBi



3.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9
Mode 5	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 5	Link Mode


For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	802.11n40 CH3/ CH6/ CH9

Note:


(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

3.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Conducted Emission Test:



Radiated Spurious Emission:



3.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Device Type	Brand	Model	Series No.	Note
E-1	Wireless Home Security Battery Camera System	N/A	BC-HC12	N/A	EUT
E-2	Adapter	N/A	SAN-12010	N/A	Auxiliary

Item	Shielded Type	Ferrite Core	Length	Note
C-1	NO	NO	0.4M	DC cable unshielded

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS


3.5.1 TEST FACILITY

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

IC Registered No.: 23583

Conducted emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	Jun. 08, 2020	Jun. 07, 2021
LISN	R&S	ENV216	101375	Jun. 04, 2020	Jun. 03, 2021
ISN	HPX	ISN T800	S1509001	Jun. 04, 2020	Jun. 03, 2021
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\



Radiated emissions Test (966 chamber)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	Jun. 06. 2020	Jun. 05, 2023
Receiver	R&S	ESR3	102075	Jun. 08, 2020	Jun. 07, 2021
Receiver	R&S	ESRP	101154	Jun. 08, 2020	Jun. 07, 2021
Amplifier	Schwarzbeck	BBV9718	9718-309	Jun. 04, 2020	Jun. 03, 2021
Amplifier	Schwarzbeck	BBV9744	9744-0037	Jun. 04, 2020	Jun. 03, 2021
TRILOG Broadband Antenna	schwarzbeck	VULB 9163	VULB9163-942	Jun. 08, 2020	Jun. 07, 2021
Horn Antenna	SCHWARZBEC K	BBHA9120 D	1201	Jun. 10, 2020	Jun. 09, 2021
Horn Antenna (18GHz-40GHz)	SCHWARZBEC K	BBHA9170	822	Jun. 10, 2020	Jun. 09, 2021
Amplifier (18GHz-40GHz)	MITEQ	TTA1840-3 5-HG	2034381	Jun. 08, 2020	Jun. 07, 2021
Loop Antenna (9kHz-30MHz)	SCHWARZBEC K	FMZB1519 B	014	Jun. 08, 2020	Jun. 07, 2021
RF cables1 (9kHz-30MHz)	Huber+Suhnar	9kHz-30MH z	B1702988-0 008	Jun. 08, 2020	Jun. 07, 2021
RF cables2 (30MHz-1GHz)	Huber+Suhnar	30MHz-1G Hz	1486150	Jun. 08, 2020	Jun. 07, 2021
RF cables3 (1GHz-40GHz)	Huber+Suhnar	1GHz-40G Hz	1607106	Jun. 08, 2020	Jun. 07, 2021
Power Metter	Keysight	E4419B	\	Jun. 08, 2020	Jun. 07, 2021
Power Sensor (AV)	Keysight	E9 300A	\	Jun. 08, 2020	Jun. 07, 2021
Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY4910006 0	Jun. 04, 2020	Jun. 03, 2021
Spectrum Analyzer 9kHz-40GHz	Agilent	FSP40	100363	Jun. 13, 2020	Jun. 12, 2021
Software	Frad	EZ-EMC	FA-03A2 RE	\	\

RF conducted test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power Metter	Keysight	E4419B	\	Jun. 08, 2020	Jun. 07, 2021
Power Sensor (AV)	Keysight	E9 300A	\	Jun. 08, 2020	Jun. 07, 2021
Signal Analyzer 20kHz-26.5GHz	KEYSIGHT	N9020A	MY49100060	Jun. 04, 2020	Jun. 03, 2021
Spectrum Analyzer 9kHz-40GHz	Agilent	FSP40	100363	Jun. 13, 2020	Jun. 12, 2021

4. EMC EMISSION TEST

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	L
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 5




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2292	40.41	9.50	49.91	62.48	-12.57	QP
2		0.2292	25.92	9.50	35.42	52.48	-17.06	AVG
3	*	0.4889	44.68	9.58	54.26	56.19	-1.93	QP
4		0.4889	29.36	9.58	38.94	46.19	-7.25	AVG
5		0.7935	37.27	9.63	46.90	56.00	-9.10	QP
6		0.7935	19.82	9.63	29.45	46.00	-16.55	AVG
7		2.1614	32.29	9.60	41.89	56.00	-14.11	QP
8		2.1614	14.14	9.60	23.74	46.00	-22.26	AVG
9		5.5725	33.78	9.78	43.56	60.00	-16.44	QP
10		5.5725	16.36	9.78	26.14	50.00	-23.86	AVG
11		11.8860	32.10	9.69	41.79	60.00	-18.21	QP
12		11.8860	13.77	9.69	23.46	50.00	-26.54	AVG

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Phase :	N
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 5


Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq. MHz	Reading Level	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2442	36.30	9.51	45.81	61.95	-16.14	QP
2		0.2442	26.53	9.51	36.04	51.95	-15.91	AVG
3		0.4863	44.68	9.58	54.26	56.23	-1.97	QP
4	*	0.4863	36.52	9.58	46.10	46.23	-0.13	AVG
5		0.9633	40.05	9.58	49.63	56.00	-6.37	QP
6		0.9633	26.19	9.58	35.77	46.00	-10.23	AVG
7		2.0441	34.40	9.59	43.99	56.00	-12.01	QP
8		2.0441	21.76	9.59	31.35	46.00	-14.65	AVG
9		7.6464	32.50	9.71	42.21	60.00	-17.79	QP
10		7.6464	18.98	9.71	28.69	50.00	-21.31	AVG
11		27.5616	26.04	9.72	35.76	60.00	-24.24	QP
12		27.5616	9.53	9.72	19.25	50.00	-30.75	AVG

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:


- g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



4.2.3 DEVIATION FROM TEST STANDARD

No deviation




4.2.4 TEST SETUP


(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



(C) Radiated Emission Test-Up Frequency Above 1GHz


4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	26 °C	Relative Humidity :	54%
Pressure:	101kPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 5	Polarization :	--


Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance}/\text{test distance})$ (dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



4.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101 kPa	Polarization :	Horizontal
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 5




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		73.8756	50.07	-18.12	31.95	40.00	-8.05	QP
2		98.4866	47.18	-15.78	31.40	43.50	-12.10	QP
3		199.9856	49.98	-15.26	34.72	43.50	-8.78	QP
4		258.3264	53.92	-13.93	39.99	46.00	-6.01	QP
5	!	289.0021	53.21	-12.80	40.41	46.00	-5.59	QP
6	*	385.2805	51.91	-10.09	41.82	46.00	-4.18	QP

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Polarization :	Vertical
Test Voltage :	AC 120V/60Hz	Test Mode :	Mode 5



Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1	!	30.5305	50.20	-16.05	34.15	40.00	-5.85	QP
2	*	66.2862	55.84	-16.28	39.56	40.00	-0.44	QP
3	!	104.5361	58.35	-15.76	42.59	43.50	-0.91	QP
4		250.3011	48.36	-14.22	34.14	46.00	-11.86	QP
5		389.3548	47.55	-9.98	37.57	46.00	-8.43	QP
6		483.9094	44.71	-7.91	36.80	46.00	-9.20	QP

4.2.8 TEST RESULTS

Between 1GHz – 25GHz

802.11b

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low channel:2412MHz							
V	4824.00	53.09	-0.43	52.66	74.00	-21.34	PK
V	4824.00	43.46	-0.43	43.03	54.00	-10.97	AV
V	7236.00	44.20	8.31	52.51	74.00	-21.49	PK
V	7236.00	34.72	8.31	43.03	54.00	-10.97	AV
H	4804.00	48.56	-0.43	48.13	74.00	-25.87	PK
H	4804.00	39.13	-0.43	38.70	54.00	-15.30	AV
H	7236.00	41.43	8.31	49.74	74.00	-24.26	PK
H	7236.00	32.83	8.31	41.14	54.00	-12.86	AV
Middle channel:2437MHz							
V	4874.00	49.27	-0.38	48.89	74.00	-25.11	PK
V	4874.00	42.21	-0.38	41.83	54.00	-12.17	AV
V	7311.00	41.05	8.83	49.88	74.00	-24.12	PK
V	7311.00	32.36	8.83	41.19	54.00	-12.81	AV
H	4874.00	45.65	-0.38	45.27	74.00	-28.73	PK
H	4874.00	34.90	-0.38	34.52	54.00	-19.48	AV
H	7311.00	38.25	8.83	47.08	74.00	-26.92	PK
H	7311.00	30.69	8.83	39.52	54.00	-14.48	AV
High channel:2462MHz							
V	4924.00	51.64	-0.32	51.32	74.00	-22.68	PK
V	4924.00	41.24	-0.32	40.92	54.00	-13.08	AV
V	7386.00	43.10	9.35	52.45	74.00	-21.55	PK
V	7386.00	32.22	9.35	41.57	54.00	-12.43	AV
H	4924.00	49.69	-0.32	49.37	74.00	-24.63	PK
H	4924.00	39.27	-0.32	38.95	54.00	-15.05	AV
H	7386.00	41.08	9.35	50.43	74.00	-23.57	PK
H	7386.00	32.55	9.35	41.90	54.00	-12.10	AV

Remark:

1. Emission Level = Meter Reading + Factor,

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over = Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. The Worst mode is Antenna A.

802.11g

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low channel:2412MHz							
V	4824.00	52.84	-0.43	52.41	74.00	-21.59	PK
V	4824.00	43.46	-0.43	43.03	54.00	-10.97	AV
V	7236.00	45.34	8.31	53.65	74.00	-20.35	PK
V	7236.00	35.44	8.31	43.75	54.00	-10.25	AV
H	4804.00	51.36	-0.43	50.93	74.00	-23.07	PK
H	4804.00	40.77	-0.43	40.34	54.00	-13.66	AV
H	7236.00	44.04	8.31	52.35	74.00	-21.65	PK
H	7236.00	35.61	8.31	43.92	54.00	-10.08	AV
Middle channel:2437MHz							
V	4874.00	49.81	-0.38	49.43	74.00	-24.57	PK
V	4874.00	42.74	-0.38	42.36	54.00	-11.64	AV
V	7311.00	42.48	8.83	51.31	74.00	-22.69	PK
V	7311.00	32.74	8.83	41.57	54.00	-12.43	AV
H	4874.00	44.90	-0.38	44.52	74.00	-29.48	PK
H	4874.00	35.60	-0.38	35.22	54.00	-18.78	AV
H	7311.00	41.24	8.83	50.07	74.00	-23.93	PK
H	7311.00	32.38	8.83	41.21	54.00	-12.79	AV
High channel:2462MHz							
V	4924.00	51.13	-0.32	50.81	74.00	-23.19	PK
V	4924.00	42.71	-0.32	42.39	54.00	-11.61	AV
V	7386.00	42.25	9.35	51.60	74.00	-22.40	PK
V	7386.00	32.71	9.35	42.06	54.00	-11.94	AV
H	4924.00	48.26	-0.32	47.94	74.00	-26.06	PK
H	4924.00	38.89	-0.32	38.57	54.00	-15.43	AV
H	7386.00	40.18	9.35	49.53	74.00	-24.47	PK
H	7386.00	31.43	9.35	40.78	54.00	-13.22	AV

Remark:

1. Emission Level = Meter Reading + Factor,

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over = Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. The Worst mode is Antenna A.

802.11n20

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low channel:2412MHz							
V	4824.00	54.40	-0.43	53.97	74.00	-20.03	PK
V	4824.00	43.77	-0.43	43.34	54.00	-10.66	AV
V	7236.00	46.02	8.31	54.33	74.00	-19.67	PK
V	7236.00	35.80	8.31	44.11	54.00	-9.89	AV
H	4804.00	51.27	-0.43	50.84	74.00	-23.16	PK
H	4804.00	41.03	-0.43	40.60	54.00	-13.40	AV
H	7236.00	44.75	8.31	53.06	74.00	-20.94	PK
H	7236.00	36.08	8.31	44.39	54.00	-9.61	AV
Middle channel:2437MHz							
V	4874.00	52.77	-0.38	52.39	74.00	-21.61	PK
V	4874.00	43.98	-0.38	43.60	54.00	-10.40	AV
V	7311.00	43.51	8.83	52.34	74.00	-21.66	PK
V	7311.00	34.90	8.83	43.73	54.00	-10.27	AV
H	4874.00	50.08	-0.38	49.70	74.00	-24.30	PK
H	4874.00	40.07	-0.38	39.69	54.00	-14.31	AV
H	7311.00	42.03	8.83	50.86	74.00	-23.14	PK
H	7311.00	33.59	8.83	42.42	54.00	-11.58	AV
High channel:2462MHz							
V	4924.00	54.14	-0.32	53.82	74.00	-20.18	PK
V	4924.00	45.34	-0.32	45.02	54.00	-8.98	AV
V	7386.00	46.55	9.35	55.90	74.00	-18.10	PK
V	7386.00	37.35	9.35	46.70	54.00	-7.30	AV
H	4924.00	52.91	-0.32	52.59	74.00	-21.41	PK
H	4924.00	42.88	-0.32	42.56	54.00	-11.44	AV
H	7386.00	43.88	9.35	53.23	74.00	-20.77	PK
H	7386.00	36.79	9.35	46.14	54.00	-7.86	AV

Remark:

1. Emission Level = Meter Reading + Factor,

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over = Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. Test Mode is MIMO Mode.

802.11n40

Polar (H/V)	Frequency	Reading Level	Correct Factor	Measure- ment	Limits	Over	Detector Type
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dBuV/ m)	(dB)	
Low channel:2422MHz							
V	4844.00	53.46	-0.43	53.03	74.00	-20.97	PK
V	4844.00	43.67	-0.43	43.24	54.00	-10.76	AV
V	7266.00	44.43	8.31	52.74	74.00	-21.26	PK
V	7266.00	34.67	8.31	42.98	54.00	-11.02	AV
H	4844.00	49.98	-0.43	49.55	74.00	-24.45	PK
H	4844.00	39.17	-0.43	38.74	54.00	-15.26	AV
H	7266.00	43.02	8.31	51.33	74.00	-22.67	PK
H	7266.00	34.14	8.31	42.45	54.00	-11.55	AV
Middle channel:2437MHz							
V	4874.00	49.98	-0.38	49.60	74.00	-24.40	PK
V	4874.00	42.63	-0.38	42.25	54.00	-11.75	AV
V	7311.00	41.14	8.83	49.97	74.00	-24.03	PK
V	7311.00	32.47	8.83	41.30	54.00	-12.70	AV
H	4874.00	46.48	-0.38	46.10	74.00	-27.90	PK
H	4874.00	35.54	-0.38	35.16	54.00	-18.84	AV
H	7311.00	39.59	8.83	48.42	74.00	-25.58	PK
H	7311.00	30.91	8.83	39.74	54.00	-14.26	AV
High channel:2452MHz							
V	4904.00	51.38	-0.32	51.06	74.00	-22.94	PK
V	4904.00	42.46	-0.32	42.14	54.00	-11.86	AV
V	7356.00	43.83	9.35	53.18	74.00	-20.82	PK
V	7356.00	32.89	9.35	42.24	54.00	-11.76	AV
H	4904.00	50.00	-0.32	49.68	74.00	-24.32	PK
H	4904.00	40.25	-0.32	39.93	54.00	-14.07	AV
H	7356.00	42.56	9.35	51.91	74.00	-22.09	PK
H	7356.00	34.61	9.35	43.96	54.00	-10.04	AV

Remark:

1. Emission Level = Meter Reading + Factor,

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

Over = Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. In restricted bands of operation, The spurious emissions below the permissible value more than 20dB

4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. Test Mode is MIMO Mode.

4.3 RADIATED BAND EMISSION MEASUREMENT

4.3.1 TEST REQUIREMENT

FCC Part15 C Section 15.209 and 15.205

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(2)
13.36-13.41			

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

4.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

- a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the Highest channel

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

4.3.3 DEVIATION FROM TEST STANDARD

No deviation

4.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



4.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

4.3.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measurement (dBuV/m)	Limits (dBuV/m)		Result
					PK	PK	AV	
802.11b	Low Channel 2412MHz							
	H	2390.00	56.38	-6.70	49.68	74.00	54.00	PASS
	H	2400.00	47.82	-6.71	41.11	74.00	54.00	PASS
	V	2390.00	55.90	-6.70	49.20	74.00	54.00	PASS
	V	2400.00	47.12	-6.71	40.41	74.00	54.00	PASS
	High Channel 2462MHz							
	H	2483.50	55.85	-6.79	49.06	74.00	54.00	PASS
	H	2485.00	48.03	-6.81	41.22	74.00	54.00	PASS
	V	2483.50	54.88	-6.79	48.09	74.00	54.00	PASS
	V	2485.00	47.73	-6.81	40.92	74.00	54.00	PASS
802.11g	Low Channel 2412MHz							
	H	2390.00	57.14	-6.70	50.44	74.00	54.00	PASS
	H	2400.00	49.74	-6.71	43.03	74.00	54.00	PASS
	V	2390.00	58.09	-6.70	51.39	74.00	54.00	PASS
	V	2400.00	51.02	-6.71	44.31	74.00	54.00	PASS
	High Channel 2462MHz							
	H	2483.50	57.13	-6.79	50.34	74.00	54.00	PASS
	H	2485.00	49.58	-6.81	42.77	74.00	54.00	PASS
	V	2483.50	58.02	-6.79	51.23	74.00	54.00	PASS
	V	2485.00	49.41	-6.81	42.60	74.00	54.00	PASS
Remark:								
1. Emission Level = Meter Reading + Factor, Factor = Antenna Factor + Cable Loss – Pre-amplifier. Over= Emission Level - Limit 2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit. 3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB 4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.								

	Polar (H/V)	Frequency (MHz)	Reading Level (dBuV/m)	Correct Factor (dB)	Measurement (dBuV/m)	Limits (dBuV/m)		Result
					PK	PK	AV	
802.11 n20	Low Channel 2412MHz							
	H	2390.00	56.73	-6.70	50.03	74.00	54.00	PASS
	H	2400.00	49.10	-6.71	42.39	74.00	54.00	PASS
	V	2390.00	56.88	-6.70	50.18	74.00	54.00	PASS
	V	2400.00	48.84	-6.71	42.13	74.00	54.00	PASS
	High Channel 2462MHz							
	H	2483.50	54.99	-6.79	48.20	74.00	54.00	PASS
	H	2500.00	48.62	-6.81	41.81	74.00	54.00	PASS
	V	2483.50	55.72	-6.79	48.93	74.00	54.00	PASS
	V	2500.00	47.17	-6.81	40.36	74.00	54.00	PASS
802.11 n40	Low Channel 2422MHz							
	H	2390.00	56.78	-6.70	50.08	74.00	54.00	PASS
	H	2400.00	48.38	-6.71	41.67	74.00	54.00	PASS
	V	2390.00	57.26	-6.70	50.56	74.00	54.00	PASS
	V	2400.00	49.97	-6.71	43.26	74.00	54.00	PASS
	High Channel 2452MHz							
	H	2483.50	56.00	-6.79	49.21	74.00	54.00	PASS
	H	2500.00	48.69	-6.81	41.88	74.00	54.00	PASS
	V	2483.50	57.43	-6.79	50.64	74.00	54.00	PASS
	V	2500.00	49.15	-6.81	42.34	74.00	54.00	PASS

Remark:

1. Emission Level = Meter Reading + Factor,
Factor = Antenna Factor + Cable Loss – Pre-amplifier.
Over= Emission Level - Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.
- 3 In restricted bands of operation, The spurious emissions below the permissible value more than 20dB
4. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. POWER SPECTRAL DENSITY TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS


5.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{RBW}$.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.

Note: Power Spectral Density(dBm)=Reading+Cable Loss

5.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX b Mode		

Frequency	Power Spectral Density (dBm/3KHz) ANTA	Power Spectral Density (dBm/3KHz) ANTB	Total power density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2412 MHz	-16.167	-15.414	/	8	PASS
2437 MHz	-15.795	-16.265	/	8	PASS
2462 MHz	-15.430	-16.232	/	8	PASS

Note: A(B) Represent the value of antenna A and A, The worst data is Antenna B, only shown Antenna B Plot.

TX CH01


TX CH06


TX CH11




Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX g Mode		

Frequency	Power Spectral Density (dBm/3KHz) ANTA	Power Spectral Density (dBm/3KHz) ANTB	Total power density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2412 MHz	-22.868	-23.719	/	8	PASS
2437 MHz	-23.619	-23.180	/	8	PASS
2462 MHz	-21.908	-23.022	/	8	PASS

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

TX CH01



TX CH06

TX CH11



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX n Mode(20M)		



Frequency	Power Spectral Density (dBm/3KHz) ANTA	Power Spectral Density (dBm/3KHz) ANTB	Total power density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2412 MHz	-23.186	-22.960	-20.06	8	PASS
2437 MHz	-21.188	-23.008	-18.99	8	PASS
2462 MHz	-19.727	-24.074	-18.37	8	PASS

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

Note: Antenna A gain: 3dBi, Antenna B gain: 3dBi,
 Array Gain = $10 \log(NANT/NSS) \text{dB} = 10 \log(2/1) = 3.01 \text{dB}$,
 So the directional gain for PSD is 6.01dBi

TX CH01



TX CH06

TX CH11



Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX n Mode(40M)		



Frequency	Power Spectral Density (dBm/3KHz) ANTA	Power Spectral Density (dBm/3KHz) ANTB	Total power density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2422 MHz	-23.749	-23.660	-20.69	8	PASS
2437 MHz	-25.749	-24.365	-21.99	8	PASS
2452 MHz	-24.969	-24.665	-21.80	8	PASS

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna B, only shown Antenna B Plot.

Note: Antenna A gain: 3dBi, Antenna B gain: 3dBi,
 Array Gain = $10 \log(NANT/NSS) \text{ dB} = 10 \log(2/1) = 3.01 \text{ dB}$,
 So the directional gain for PSD is 6.01dBi

TX CH03



TX CH06

TX CH09


6. BANDWIDTH TEST

6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	$\geq 500\text{KHz}$ (6dB bandwidth)	2400-2483.5	PASS


6.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



6.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX b Mode		

Frequency (MHz)	6dB bandwidth (MHz) ANTA	6dB bandwidth (MHz) ANTB	Limit (kHz)	Result
2412	9.57	9.57	500	Pass
2437	9.57	9.14	500	Pass
2462	9.14	9.57	500	Pass

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.




TX CH 06

TX CH 11




Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX g Mode		

Frequency (MHz)	6dB bandwidth (MHz) ANTA	6dB bandwidth (MHz) ANTB	Limit (kHz)	Result
2412	15.13	15.14	500	Pass
2437	15.11	15.07	500	Pass
2462	15.11	15.04	500	Pass

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

TX CH 01




TX CH 06

TX CH 11




Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX n Mode(20M)		

Frequency (MHz)	6dB bandwidth (MHz) ANTA	6dB bandwidth (MHz) ANTB	Limit (kHz)	Result
2412	15.13	15.13	500	Pass
2437	15.10	15.13	500	Pass
2462	15.12	15.13	500	Pass

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna B, only shown Antenna B Plot.

TX CH 01




TX CH 06

TX CH 11




Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX n Mode(40M)		

Frequency (MHz)	6dB bandwidth (MHz) ANTA	6dB bandwidth (MHz) ANTB	Limit (kHz)	Result
2422	35.14	35.13	500	Pass
2437	35.13	35.13	500	Pass
2452	35.14	35.13	500	Pass

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A, only shown Antenna A Plot.

TX CH 03



TX CH 06

TX CH 09


7. PEAK OUTPUT POWER TEST

7.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

7.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the Power meter

7.1.2 DEVIATION FROM STANDARD

No deviation.

7.1.3 TEST SETUP



7.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1.5 TEST RESULTS

Temperature :	26 °C	Relative Humidity :	54%
Pressure :	101kPa	Test Voltage :	AC120V/60Hz

Note:Antenna A gain:3Bi, Antenna B gain: 3dBi, The Array gain=0 dB for NANT \leq 4,
So the directional gain for Power measurements is 3dBi

	Frequency	Maximum Conducted Output Power(PK) ANTA	Maximum Conducted Output Power(PK) ANTB	Total Power Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	(dBm)	(dBm)	dBm
802.11b	2412	9.552	9.253	/	30
	2437	9.478	9.151	/	30
	2462	9.199	9.444	/	30
802.11g	2412	8.778	8.578	/	30
	2437	8.997	8.113	/	30
	2462	7.932	8.785	/	30
802.11n 20	2412	7.230	7.454	10.35	30
	2437	7.738	7.647	10.70	30
	2462	7.266	6.629	9.97	30
802.11n 40	2422	6.457	6.348	9.41	30
	2437	6.220	5.984	9.11	30
	2452	6.137	6.205	9.18	30

8. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

8.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

8.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

- a) Set the RBW = 100KHz.
- b) Set the VBW = 300KHz.
- c) Sweep time = auto couple.
- d) Detector function = peak.
- e) Trace mode = max hold.
- f) Allow trace to fully stabilize.

8.3 DEVIATION FROM STANDARD

No deviation.

8.4 TEST SETUP




8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


8.6 TEST RESULTS

Note: A(B) Represent the value of antenna A and B, The worst data is Antenna A ,only shown Antenna A Plot.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side



802.11n-HT20: Band Edge, Right Side

