

A20935 Ra FCC ID: 2ATK4LPSMHT013451 IC MODEL: LP.SMHT01.345.1 IC: 27198-LPSMHT01345.

This device complies with Part 15 of the FCC Rules and RSS-247 of Industry Canada. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Cet appareil est conforme à la partie règles de la FCC & de RSS-247 des Industries Canada. Son fonctionnement est soumis aux conditions es : (1) Cet appareil ne doit pas causer d'interférences nuisibles. (2) Cet appareil doit accepter toute ence reçue, y compris les interférences causant une reception indésirable.

10012054-001 Rev X1

Model: LP.SMHT01.345.1 IC: 27198-LPSMHT01345.1
This device complies with Part 15 of the FCC Rules and RSS-247 of Industry Canada. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Cet appareil est conforme à la partie règles de la FCC & de RSS-247 des Industries Canada. Son fonctionnement est soumis aux conditions es : (1) Cet appareil ne doit pas causer d'interférences nuisibles. (2) Cet appareil doit accepter toute ence reçue, y compris les interférences causant une reception indésirable.

FCC IC LABEL

Model: **ESAGGOV**
Single Station Multicriteria Smoke Alarm



WARNING

Please see user manual for important information on maintenance and battery life (B19380 Rev1). Constant use at high or low temperature or high humidity may reduce battery life. Use only batteries specified, the use of other batteries may have a detrimental effect on alarm operation. Maintenance: Clean Alarm monthly by gently vacuuming the openings in the exterior of the Alarm.

Standby: No Beep or flash
Low Battery: 1 beep + 1 yellow flash every 48 sec
Alarm: 3 long beeps, repeating with flashing red LED
End Of Life: 3 beeps with 3 yellow flashes
Alarm Silence: 1 red flash every 8 secs
Sensitivity: = 1.82% - 2.92% OBS/Ft
Conforms to: ANSI/UL 217 8th ed
Certified to: ULC-S531 3rd ed.
For Servicing, return to:

EN FRANÇAIS

