

According to Appendix B of 447498 D04 Interim General RF Exposure Guidance v01, the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold  $P_{th}$  (mW) described in the following formula.

$P_{th}$  is given by:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz .

$P_{th}$  is given by:

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}}(d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and  $f$  is in GHz,  $d$  is the separation distances (cm).

Tx Interface	Frequency (GHz)	Output Power		Antenna Gain (dBi)	ERP (dBm)	ERP Threshold (mW)	Separation Distances (cm)	$P_{th}$ (mW)	Exemption result
		dBm	mW						
<b>1.5GHz ≤ f ≤ 6GHz</b>									
BLE	2.48	1.00	1.26	0.1	-1.05	0.79	0.5	3	-EXEMPT-

**Note:**

1. The tune up power referred the AVG power of the test report **TMWK2307002626KR** for SAR test exclusion purpose.