

# FCC 47 CFR MPE REPORT

Soundlab Technology Company Limited

Soundbar

Model Number: Cinema 201

Additional Model: ASB2.1.0, SBA2.1.0, A4TV2.1.0, ASB201,  
SBA2.1, A4TV2.1, klipsch A300

FCC ID: 2ATKO-BAR201

Applicant:	Soundlab Technology Company Limited
Address:	No.101,202,Building 1, Microlab Industrial Park, No.2 Baozi South Road, Kengzi, Pingshan District, ShenZhen, China
Prepared By:	EST Technology Co., Ltd. Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2308216
Date of Test:	May. 15~Aug. 15, 2023
Date of Report:	Aug. 16, 2023

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: Pd (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	5.18	3.296
	2441	4.36	2.729
	2480	4.13	2.588
$\pi/4$ -DQPSK	2402	5.58	3.614
	2441	4.96	3.133
	2480	4.59	2.877
8-DPSK	2402	6.23	4.198
	2441	5.46	3.516
	2480	5.25	3.350
BLE 1M	2402	4.96	3.133
	2440	4.34	2.716
	2480	4.04	2.535
BLE 2M	2402	5.15	3.273
	2440	4.49	2.812
	2480	4.20	2.630

### 3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	5.18	5±1	6	3.61	2.296	0.00182	1	Complies
$\pi/4$ -DQPSK	5.58	5±1	6	3.61	2.296	0.00182	1	Complies
8-DPSK	6.23	6±1	7	3.61	2.296	0.00229	1	Complies
BLE 1M	4.96	4±1	5	3.61	2.296	0.00144	1	Complies
BLE 2M	5.15	5±1	6	3.61	2.296	0.00182	1	Complies

**End of Test Report**