

## 5 FCC §2.1091, §15.247(i) - RF Exposure

### 5.1 Applicable Standards

According to FCC §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

#### Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minutes)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	* (100)	30
1.34-30	824/f	2.19/f	* (180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### 5.2 MPE Prediction

Predication of MPE limit at a given distance, Equation from OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

### 5.3 MPE Results

Maximum output power at antenna input terminal (dBm):	19.84
Maximum output power at antenna input terminal tune-up (dBm):	20.84
Maximum output power at antenna input terminal tune-up (mW):	121.34
Prediction distance (cm):	20
Prediction frequency (MHz):	2402
Maximum Antenna Gain, typical (dBi):	0.5
Maximum Antenna Gain (numeric):	1.12
Power density of prediction frequency at 20.0 cm (mW/cm <sup>2</sup> ):	0.027
FCC MPE limit for uncontrolled exposure at prediction frequency (mW/cm <sup>2</sup> ):	1.0

The device is compliant with the requirement MPE limit for uncontrolled exposure. The maximum power density at the distance of 20 cm is 0.027mW/cm<sup>2</sup>. Limit is 1.0 mW/cm<sup>2</sup>.