

TEST REPORT

Reference No. : WTU19S11077436W002
FCC ID..... : 2ATL8VC4SMN512
Applicant : Vesta Lighting Inc.
Address : 815 Brazos Street, Austin,Texas, 78701 USA
Manufacturer : Shanghai Shangquan IoT Co., Ltd.
Address : Room 501, Building 1, No. 615, Ningqiao Road, Pudong New District, Shanghai, China
Product : Wireless Module
Model(s)..... : VC4SMN512
Standards : FCC CFR47 Part 1 Section 1.1037:2019
: FCC CFR47 Part 2 Section 2.1091:2019
Date of Receipt sample : 2019-11-12
Date of Test : 2019-11-14 to 2019-11-26
Date of Issue : 2019-11-26
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Test site/Test Location:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen, Guangdong, China

Tel :+86-755-83551033

Fax:+86-755-83552400

Compiled by:

Frank Yin

Frank Yin / Test Engineer

Approved by:



Philo Zhong

Philo Zhong / Manager

1 Contents

	Page
COVER PAGE.....	1
1 CONTENTS	2
2 REVISION HISTORY	3
3 GENERAL INFORMATION.....	4
3.1 GENERAL DESCRIPTION OF E.U.T	4
3.2 DETAILS OF E.U.T.....	4
4 RF EXPOSURE.....	5
4.1 REQUIREMENTS.....	5
4.2 EVALUATION RESULT	6

2 Revision History

Test report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTU19S11077436W002	2019-11-12	2019-11-14 to 2019-11-26	2019-11-26	original	-	Valid

3 General Information

3.1 General Description of E.U.T

Product	: Wireless Module
Model(s)	: VC4SMN512
Operation Frequency	: 2405-2480MHz
Antenna installation	: Integrated Antenna
Antenna Gain	: 0dBi
Type of Modulation	: O-QPSK

3.2 Details of E.U.T

Ratings	: DC 3.3V
----------------	-----------

4 RF Exposure

Test Requirement: FCC Part 1.1307

Test Method: FCC Part 2.1091

4.1 Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

4.2 Evaluation Result

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Output Power (dBm)	Output Power (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
0	1.0	19.96	99.08	0.0197	1

Result: Compliance

No SAR measurement is required.

=====End of Report=====