

# Human Exposure Report

**Application No.:** SZEM2101000945CR  
**Applicant:** ShenZhen ShuoYu Technology Co., Ltd.  
**Address of Applicant:** 30F East Block, Wenhua Bldg, 1027 Shennan East Road, Luohu District, Shenzhen, Guangdong, China  
**Manufacturer:** ShenZhen ShuoYu Technology Co., Ltd.  
**Address of Manufacturer:** 30F East Block, Wenhua Bldg, 1027 Shennan East Road, Luohu District, Shenzhen, Guangdong, China  
**Factory:** ShenZhen ShuoYu Technology Co., Ltd.  
**Address of Factory:** 30F East Block, Wenhua Bldg, 1027 Shennan East Road, Luohu District, Shenzhen, Guangdong, China

**Equipment Under Test (EUT):**  
**EUT Name:** Alarm Clock Wireless Charger  
**Model No.:** SY-W0281  
**Trade Mark:** Pointuch  
**FCC ID:** 2ATLB-SY-W0281  
**Standards:** 47 CFR PART 1, Subpart I, Section 1.1310  
47 CFR PART 2, Subpart J, Section 2.1091

**Date of Receipt:** 2021-01-22  
**Date of Test:** 2021-01-25 to 2021-02-09  
**Date of Issue:** 2021-02-19

<b>Test Result :</b>	<b>Pass*</b>
----------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above



Keny Xu  
EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.  
**Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com**



<i>Revision Record</i>				
<i>Version</i>	<i>Chapter</i>	<i>Date</i>	<i>Modifier</i>	<i>Remark</i>
01		2021-02-19		Original

<b>Authorized for issue by:</b>			
			
		<hr/> <b>Leo Li/Project Engineer</b>	
			
		<hr/> <b>Eric Fu/Reviewer</b>	





# 1 Contents

	Page
<b>1 COVER PAGE</b> .....	<b>1</b>
<b>1 CONTENTS</b> .....	<b>3</b>
<b>2 GENERAL INFORMATION</b> .....	<b>4</b>
2.1 DETAILS OF E.U.T. ....	4
2.2 DESCRIPTION OF SUPPORT UNITS .....	4
2.3 TEST LOCATION .....	5
2.4 TEST FACILITY .....	5
2.5 DEVIATION FROM STANDARDS.....	5
2.6 ABNORMALITIES FROM STANDARD CONDITIONS .....	5
<b>3 EQUIPMENTS USED DURING TEST</b> .....	<b>6</b>
<b>4 TEST RESULTS</b> .....	<b>7</b>
4.1 RF EXPOSURE TEST .....	7
4.1.1 E.U.T. Operation .....	7
Operating Environment:.....	7
EUT Operation: .....	7-8



## 2 General Information

### 2.1 Details of E.U.T.

Power supply:	Input: 5V/2.1A, 9V/2.5A, 12V/2A
	Wireless Output: 5W/7.5W/10W/15W(MAX)
	USB-A Output: 5V/1A
Operation frequency:	120.19kHz to 149.84kHz
Modulation type:	Load modulation
Antenna type:	Loop Antenna
Remark:	Tests were conducted in all load modes and the worst case 15W is reported only.

### 2.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Type-C Cable	SGS	N/A	REF. No.SEA07B00
Adapter	DJI	QC24-US	REF. No.SEA05F01C
Dummy Load	Client Supply	NuVolta	DN3000002
Frame Radio Alarm Clock	ShuoYu	SY-W0280	N/A
Mobile Phone	SAMSUNG	SM-G9810	REF. No.SEA16K00



## 2.3 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Shenzhen, Guangdong, China 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 2.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

## 2.5 Deviation from Standards

None.

## 2.6 Abnormalities from Standard Conditions

None.





### 3 Equipments Used during Test

Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal. Due date (yyyy-mm-dd)
1	Electric and Magnetic Field Analyzer	Narda	EHP-50F	EMC092	2021-11-26



## 4 Test Results

### 4.1 RF Exposure test

Test Requirement: 47 CFR PART 1, Subpart I, Section 1.1310

Measurement Distance: 15cm

Limit:

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposures</b>				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	f/300	6
1500-100,000	/	/	5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

F=frequency in MHz  
 \*=Plane-wave equivalent power density  
 RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

#### 4.1.1 E.U.T. Operation

##### Operating Environment:

Temperature: 23.4 °C Humidity: 52 % RH Atmospheric Pressure: 1015 mbar

##### EUT Operation:

This device has been tested the worst status of full loads and the device has been tested with mobile phone at zero charge, intermediate charge, and full charge.



**4.1.2 Measurement Data**

**Output Voltage=DC 12V; The max output power =15W;Calculation of resistor value=9.6Ω**

**Magnetic Field Emissions**

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result (A/m)	50% Limit (A/m)
135 kHz	15	Side 1	0.0406	0.815
		Side 2	0.0224	0.815
		Side 3	0.0386	0.815
		Side 4	0.0458	0.815
		Top	0.0185	0.815

**Mobile phone has been charge at zero charge, intermediate charge, and full charge.**

**Magnetic Field Emissions**

Operation frequency	Test Distance (cm)	Test Position	Probe Measure Result(A/m)			50%Limit (A/m)
			zero charge	intermediate charge	full charge	
135 kHz	15	Side 1	0.0438	0.0378	0.0319	0.815
		Side 2	0.0249	0.0203	0.0182	0.815
		Side 3	0.0409	0.0346	0.0318	0.815
		Side 4	0.0495	0.0417	0.0352	0.815
		Top	0.0143	0.0163	0.0147	0.815

- End of the Report -

