RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ATLHOM841

EUT Specification

EUT	GDO31x		
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz		
	☐ WLAN: 5.18GHz ~ 5.24GHz		
	☐ WLAN: 5.745GHz ~ 5.825GHz		
Device category	☐ Portable (<20cm separation)		
	⊠ Mobile (>20cm separation)		
	☐ Others		
Exposure classification	☐ Occupational/Controlled exposure		
	☐ General Population/Uncontrolled exposure		
Antenna diversity	⊠ Single antenna		
	☐ Multiple antennas		
	☐ Tx diversity		
	☐ Rx diversity		
	☐ Tx/Rx diversity		
Antenna gain (Max)	2.18 dBi		
Evaluation applied	⊠ MPE Evaluation		
	☐ SAR Evaluation		

Limits for Maximum Permissible Exposure(MPE)

Frequency	Electric Field	Magnetic Field Power		Average				
Range(MHz)	Strength(V/m)	Strength(A/m) Density(mW/cm ²)		Time				
(A) Limits for Occupational/Control Exposures								
300-1500			F/300	6				
1500-100000			5	6				
(B) Limits for General Population/Uncontrol Exposures								
300-1500			F/1500	30				
1500-100000			1	30				

Friis transmission formula: $Pd=(Pout*G)\setminus(4*pi*R2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Max Measurement Result

Operating Mode	Measured	Max. Tune	Antenna	Power	Power density
	Power	up Power	Gain	density at 20cm	Limits
	(dBm)	(dBm)	(dBi)	(mW/cm2)	(mW/cm2)
Lora	21.435	22.00	2.18	0.0521	0.610