

# FCC ID: 2ATNP-COEUS-X65

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \qquad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

## Measurement Result

Operation Frequency: 2.4GWIFI 802.11b/g/n HT20: 2412-2462MHz, HT40:2422-2452MHz

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: Cable Antenna

Antenna gain: 0dBi,

R=20cm

### 2.4G WIFI:

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2412	802.11b	13.1	13±1	14	25.119	0.00	1.00	0.0050	1
2437		13.9	13±1	14	25.119	0.00	1.00	0.0050	1
2462		13.9	13±1	14	25.119	0.00	1.00	0.0050	1
2412	802.11g	11.5	11±1	12	15.849	0.00	1.00	0.0032	1
2437		11.1	11±1	12	15.849	0.00	1.00	0.0032	1
2462		11.3	11±1	12	15.849	0.00	1.00	0.0032	1
2412	802.11n H20	10.9	11±1	12	15.849	0.00	1.00	0.0032	1
2437		11.1	11±1	12	15.849	0.00	1.00	0.0032	1
2462		11.2	11±1	12	15.849	0.00	1.00	0.0032	1
2422	802.11n H40	10.8	10±1	11	12.589	0.00	1.00	0.0025	1
2437		10.7	10±1	11	12.589	0.00	1.00	0.0025	1
2452		10.9	10±1	11	12.589	0.00	1.00	0.0025	1

### Conclusion:

For the max result : 0.0050 ≤ 1.0, compliance with FCC's RF Exposure.

Signature:

2019-07-23

*Yanting Xu*

Date:

**NAME AND TITLE** (Please print or type): yanting xu/Manager

**COMPANY** (Please print or type): Guangzhou Coeus Digital Technology Co., Ltd. / Room 204-206, Building B, No.7 Creative Park, No.10 East Yuangang Avenue, Panyu District, Guangzhou, China