

RF Exposure Evaluation Report

Product : Robosen Elite Optimus Prime
Roller
Trade mark : robosen
Model/Type reference : GZ30, GZ40
Serial Number : N/A
Report Number : EED32O80874102
FCC ID : 2ATN WGZ3040
Date of Issue : Jul. 26, 2022
: 47 CFR Part 1.1307
Test Standards : 47 CFR Part 2.1093
KDB447498D01 General
RF Exposure Guidance v06
Test result : PASS

Prepared for:

Robosen Robotics (ShenZhen) Co., Ltd
A3703, Bldg 11, Shenzhen Bay ECO-Tech Park,
No.16, Gaoxin South Science and Tech Rd.,
Nanshan Dist. Shenzhen, Guangdong, China

Prepared by:

Centre Testing International Group Co., Ltd.
Hongwei Industrial Zone, Bao'an 70 District,
Shenzhen, Guangdong, China

TEL: +86-755-3368 3668

FAX: +86-755-3368 3385

Compiled by:

Frazer Li

Frazer Li

Reviewed by:

Tom Chen

Tom Chen

Approved by:

Aaron Ma

Aaron Ma

Date:

Jul. 26, 2022



Check No.: 7718110422

2 Version

Version No.	Date	Description
00	Jul. 26, 2022	Original

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT.....	4
4.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD.....	4
4.4 TEST LOCATION.....	5
4.5 DEVIATION FROM STANDARDS.....	5
4.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	5
4.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	5
5 RF EXPOSURE EVALUATION.....	6
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	6
5.2 MAXIMUM PERMISSIBLE EXPOSURE.....	7

4 General Information

4.1 Client Information

Applicant:	Robosen Robotics (ShenZhen) Co., Ltd
Address of Applicant:	A3703, Bldg 11, Shenzhen Bay ECO-Tech Park, No.16,Gaoxin South Science and Tech Rd., Nanshan Dist. Shenzhen, Guangdong, China
Manufacturer:	Robosen Robotics (ShenZhen) Co., Ltd
Address of Manufacturer:	A3703, Bldg 11, Shenzhen Bay ECO-Tech Park, No.16,Gaoxin South Science and Tech Rd., Nanshan Dist. Shenzhen, Guangdong, China
Factory:	Dongguan Wirear Electronics Limited.
Address of Factory:	No. 7, Yihong Road, Changtang Industrial Zone, Yantian Village, Fenggang Town, Dongguan City, Guangdong Province, China

4.2 General Description of EUT

Product Name:	Robosen Elite Optimus Prime Roller
Model No.:	GZ30, GZ40
Test Model No.:	GZ30
Trade mark:	robosen
EUT Supports Radios application:	Bluetooth 5.0 dual mode: 2402-2480MHz

4.3 Product Specification subjective to this standard

Frequency Range:	2402-2480MHz	
Modulation Type:	GFSK	
Test Power Grade:	Default	
Antenna Type	Internal Antenna	
Antenna Gain	-0.8dBi	
Power Supply:	Adapter 1:	MODEL:ZL-030CL1262000US01 INPUT:100-240V~50/60Hz,1.2A Max OUTPUT:12.6V,2000mA
	Adapter 2:	MODEL:GFD24-1262000U INPUT:100-240V~50/60Hz,1.0A Max OUTPUT:12.6V,2A
	Battery:	DC 11.1V,850mAh,9.435Wh
Max Conducted Peak Output Power:	-0.16dBm The Max Conducted Peak Output Power data refer to the report EED32O80874101	
Sample Received Date:	Jun. 25, 2022	
Sample tested Date:	Jun. 25, 2022 to Jul. 08, 2022	
Remark:	<p>Company Name and Address shown on Report, the sample(s) and sample Information was/ were provided by the applicant who should be responsible for the authenticity which CTI hasn't verified.</p> <p>model No.:GZ30,GZ40 Only the model of GZ30 was tested.And only the model name is different among all models,representing different shell colors and customers. The circuit principle, safety structure and key components are the same, and the differences do not affect product safety and electromagnetic compatibility performance.</p>	

4.4 Test Location

All tests were performed at:

Centre Testing International Group Co., Ltd

Building C, Hongwei Industrial Park Block 70, Bao'an District, Shenzhen, China

Telephone: +86 (0) 755 33683668 Fax: +86 (0) 755 33683385

No tests were sub-contracted.

FCC Designation No.: CN1164

4.5 Deviation from Standards

None.

4.6 Abnormalities from Standard Conditions

None.

4.7 Other Information Requested by the Customer

None.

5 RF Exposure Evaluation

5.1 RF Exposure Compliance Requirement

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{377}$

Where E = Field strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{377 d^2}$$

Changing to units of mW and cm, using:

P (mW) = P (W) / 1000 and

d (cm) = d(m) / 100

Yields

$$S = \frac{30 \times (P/1000) \times G}{377 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2} \quad \text{Equation 1}$$

Where d = Distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

5.2 Maximum Permissible Exposure

Substituting the MPE safe distance using $d = 20$ cm into Equation 1:

$$S = 0.000199 \times P \times G$$

Where P = Power in mW

G = Numeric antenna gain

S = Power density in mW / cm²

BLE:

Test Mode	Antenna	Channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
					(dBm)	(mW)
BLE_1M	Ant1	2402	-0.16	-1.±1.00	0	1.00
		2440	-0.48	-1.±1.00	0	1.00
		2480	-0.98	-1.±1.00	0	1.00
BLE_2M	Ant1	2402	-0.17	-1.±1.00	0	1.00
		2440	-0.44	-1.±1.00	0	1.00
		2480	-1.09	-1.±1.00	0	1.00

Worst case:

Maximum tune-up Power(dBm)	P (mW)	Gain (num.)	D (cm)	Power density in mW / cm ²	Limit (mW/cm ²)
0	1	0.832	20	0.0002	1

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CTI, this report can't be reproduced except in full.

*** End of Report ***