


<b>ICECO</b>	
Item number	APL55
Compartment type	Refrigerator
Protective classification of electric shock resistance	I
Rated voltage AC	110-120V~
Rated frequency	60Hz
Rated voltage DC	12V/24V
Rated current AC	1.1A-0.9A
Rated current DC	7.0A/3.5A
Rafrigerant / charge	R513A(38g)
Insulation blowing gas	C-Pentane
SN	


**Intertek** Conforms to UL STD.60335-1 and 60335-2-24  
 5005493 Certified to CSA STD.C22.2 No.60335-1 and 60335-2-24  
 FCC ID:2ATOGAPL55  
 This device complies with part 15 of the FCC Rules.  
 Operation is subject to the following two conditions:  
 (1) This device may not cause harmful interference, and  
 (2) this device must accept any interference received, including interference that may cause undesired operation.

勾选符号√  
 属于客户化物料  
 是  
 否 ✓

技术要求:

- 1.标注\*号处尺寸为重要检测尺寸,未注公差按GB/T 1804-m级;
- 2.字体要求清晰,间距均匀;
- 3.制件材质为哑银龙/25um,表面过膜,底色为哑光银色,LOGO、字体及图形为黑色;
- 4.背涂UL耐高温胶,胶层粘性按GB/T 2792 胶粘带与不锈钢180 度剥离方法测试,剥离黏着力>10N/25mm。
- 5.高温、低温测试(贴于塑料件24H后再做测试);  
 60°C (6H) → -10°C (6H) → 60°C (6H) → -10°C (6H),无起翘、无烧焦现象。

D						物料编码	零件名称	电路图铭牌
C						1. 15. 055-0910		
B			全新改版,增加FCC认证要求	黄玉莲	2023. 1. 29	材料	比例	零件号 FCD55. 05-06
	标记	处数	序号	更改描述	签名	更改日期	1:1	产品号 FCD55
	设计	黄玉莲	2022. 12. 2	标准化	林文华	2022. 12. 2	重量	版本 B版
	审核	罗舟明	2022. 12. 2	发布	韩梦茹	2022. 12. 2		广东英得尔实业发展有限公司
	会签			批准	谢羽	2022. 12. 2	第1页 共1页	



Label location