





# DIRECTORY

- 1. Technical Information..... 3
- 1.1. Applicant and Manufacturer Information..... 3
- 1.2. Equipment Under Test (EUT) Description.....3
- 1.3. Applied Reference Documents..... 3
- 2. Device category and RF exposure limit.....4
- 3. RF Exposure Evaluation..... 5
- Annex A General Information.....6

Change History		
Version	Date	Reason for change
1.0	2021-02-20	First edition



# 1. Technical Information

**Note:** Provide by manufacturer.

## 1.1. Applicant and Manufacturer Information

<b>Applicant:</b>	LEXI Devices, Inc.
<b>Applicant Address:</b>	2342 Shattuck Ave, #260, Berkeley, CA 94704 US
<b>Manufacturer:</b>	LEEDARSON LIGHTING CO., LTD.
<b>Manufacturer Address:</b>	Xingtai Industrial Zone, Economic Development Zone, Changtai County, Zhangzhou city, Fujian Province, P.R.China

## 1.2. Equipment Under Test (EUT) Description

<b>EUT Type:</b>	BR30 Bulb-Smart Color & Tunable White
<b>Hardware Version:</b>	V2.1
<b>Software Version:</b>	V100
<b>Frequency Bands:</b>	BLE:2402MHz - 2480MHz; Zigbee:2405MHz - 2480MHz;
<b>Modulation Mode:</b>	GFSK;O-QPSK
<b>Antenna type:</b>	internal antenna
<b>Antenna Gain:</b>	0.15dBi

## 1.3. Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title
1	<b>47 CFR§2.1091</b>	Radiofrequency Radiation Exposure Evaluation: mobile devices
2	<b>KDB 447498 D01v06</b>	General RF Exposure Guidance

## 2. Device category and RF exposure limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

### Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

### GENERAL POPULATION / UNCONTROLLED EXPOSURE

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

**TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### 3. RF Exposure Evaluation

#### Standalone transmission MPE evaluation

Mode	Frequency	Antenna Gain	Conducted Peak Power		Power density(S)	Limit for MPE
	(MHz)		(dBi)	(dBm)		
<b>BLE</b>	2480	0.15	9.626	9.49730	0.001890	1
<b>Zigbee</b>	2480	0.15	8.733	7.73215	0.001539	1

**According to KDB447498 D01 General RF Exposure Guidance v06, simultaneous transmission is evaluated:**

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is  $\leq 1.0$ .

#### Calculation method:

$$S = P \cdot G / 4\pi R^2$$

Where:

S = power density(in appropriate units, e.g., mW/cm<sup>2</sup> )

P = power input to the antenna (in appropriate units, e.g., mW )

G = antenna gain

R = Separation distance (20cm)



## Annex A General Information

### 1. Identification of the Responsible Testing Laboratory

<b>Laboratory Name:</b>	Kehu-Morlab Test Laboratory
<b>Laboratory Address:</b>	Unit 101, No.1732 Gangzhong Road, Xiamen Area, Pilot Free Trade Zone (Fujian) P.R. China
<b>Telephone:</b>	+86 592 5612050
<b>Facsimile:</b>	+86 592 5612095

### 2. Identification of the Responsible Testing Location

<b>Name:</b>	Kehu-Morlab Test Laboratory
<b>Address:</b>	Unit 101, No.1732 Gangzhong Road, Xiamen Area, Pilot Free Trade Zone (Fujian) P.R. China

————— END OF REPORT —————