

RF EXPOSURE EVALUATION

EUT Specification

EUT	True Wireless Earbuds
Frequency band (Operating)	<input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input checked="" type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
Antenna diversity	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
Max. output power	-0.910dBm (0.81mW) for BDR EDR -2.851dBm(0.52mW) for BLE
Antenna gain	1.24dBi
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation

Standard Requirement

Portable Device

According to §15.247(i) and §1.1307b(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See KDB 447498 D01 General RF Exposure Guidance v06, section 4.3.1.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,¹⁶ where

·f(GHz) is the RF channel transmit frequency in GHz

·Power and distance are rounded to the nearest mW and mm before calculation¹⁷

·The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Max Output power (mW)	Calculation Value (Note 1)	Threshold Value
GFSK					
Low	2402	-2.431	0.5713	0.1771	3.0
Middle	2441	-2.270	0.5929	0.1853	3.0
High	2480	-1.755	0.6676	0.2103	3.0
$\pi/4$-DQPSK					
Low	2402	-1.681	0.6790	0.2105	3.0
Middle	2441	-1.413	0.7223	0.2257	3.0
High	2480	-0.910	0.8110	0.2554	3.0
BLE 1M					
Low	2402	-3.754	0.4213	0.1306	3.0
Middle	2440	-3.461	0.4507	0.1408	3.0
High	2480	-2.851	0.5187	0.1634	3.0
BLE 2M					
Low	2402	-3.726	0.4240	0.1314	3.0
Middle	2440	-3.492	0.4475	0.1398	3.0
High	2480	-2.923	0.5102	0.1607	3.0

Note 1: Calculation Value = [(max. power of channel, mW)/(min. test separation distance, mm)] · \sqrt{f} (GHz).
 For example: $0.8110/5 \cdot \sqrt{2.48} = 0.2554 \leq 3.0$

According to KDB447498 D01 V06, threshold at which no SAR required is ≤ 3.0 for 1-g SAR, separation distance is 5mm, and no simultaneous SAR measurement is required.