FCC ID: 2ATPO-A9G

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

|--|

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)					
(A) Limits for Occupational/Controlled Exposure									
0.3-3.0	614	1.63	*100	6					
3.0-30	1842/1	4.89/f	*900/f ²	6					
30-300	61.4	0.163	1.0	6					
300-1,500			f/300	6					
1,500-100,000			5	6					
(B) Limits for General Population/Uncontrolled Exposure									
0.3-1.34	614	1.63	*100	30					
1.34-30	824/1	2.19/f	*180/f ²	30					
30-300	27.5	0.073	0.2	30					
300-1,500			f/1500	30					
1,500-100,000			1.0	30					

f = frequency in MHz * = Plane-wave equivalent power density

MPE Calculation Method

$$\mathsf{E}(\mathsf{V/m}) = \frac{\sqrt{30*P*G}}{d}$$
 Power Density: $Pd(\mathsf{W/m^2}) = \frac{E^2}{377}$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30*P*G}{377*D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

Measurement Result

GSM850/GSM1900 Antenna Type: PIFA Antenna Antenna gain: 3 dBi,

Operating Mode	Maximum turn up power	Frame-Avg Power	Frame-Avg Power	Evaluation result	Power density Limits
	(dBm)	(dBm)	(mW)	(mW/cm2)	(mW/cm2)
GSM 850	33.00	23.97	249.46	0.0993	0.5576
GSM 1900	31.00	21.97	157.40	0.0627	1.0000

Note: The frame-averaged power is linearly scaled the maximum turn up power over 8 time slots. The calculated method are shown as below:

Frame-averaged power = Maximum turn up power (1 TS) - 9.03 dB

Conclusion:

For the max result : 0.0993≤0.5576 for Max Power Density, compliance the RF Exposure.

Jason chen

Signature:

Date: 2020/01/06

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.