

RF EXPOSURE REPORT

FOR

Applicant	:	Guangdong Sygole Intelligent Technology Co.,Ltd
Address	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province
Equipment under Test	:	UHF RFID READER
Model No.	:	SG-UR-I81
Trade Mark	:	N/A
FCC ID	:	2ATQ4SGURI81
Manufacturer	:	Guangdong Sygole Intelligent Technology Co.,Ltd
Address	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan
City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

TABLE OF CONTENTS

- Test report declares.....3
- 1. General information.....5
 - 1.1. Description of Equipment5
 - 1.2. Assess laboratory5
- 2. RF Exposure evaluation5
 - 2.1. Requirement.....5
 - 2.2. Calculation Method.....6
 - 2.3. Estimation Result.....6

TEST REPORT DECLARE

Applicant	:	Guangdong Sygole Intelligent Technology Co.,Ltd
Address	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province
Equipment under Test	:	UHF RFID READER
Model No.	:	SG-UR-I81
Trade mark	:	N/A
Manufacturer	:	Guangdong Sygole Intelligent Technology Co.,Ltd
Address	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R19072206-1E2		
Date of Receipt:	July. 22, 2019	Date of Test:	July. 22, 2019 ~ Aug. 17, 2019

Prepared By:

Ella Gong

Ella Gong/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Aug. 17, 2019	

1. General information

1.1. Description of Equipment

EUT* Name	: UHF RFID READER
Model Number	: SG-UR-I81
EUT function description	: Please reference user manual of this device
Power supply	: DC 24V from AC/DC ADAPTER
Operation frequency	: 902-928 MHz
Modulation	: ASK
Antenna Type	: Dedicated antenna , maximum PK gain: 3 dBi
Sample Type	: Series production

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com

2. RF Exposure evaluation

2.1. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2. Calculation Method

$$E(\text{V/m}) = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } S(\text{mW/cm}^2) = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Peak RF output power (mW)

G = EUT Antenna numeric gain (numeric)=

d = Separation distance between radiator and human body (m)

The formula can be changed to

We can change the formula to:

$$S = \frac{30 \times P \times G}{377 \times d^2} \quad \text{or, } d = \sqrt{\frac{30 \times P \times G}{377 \times S}}$$

From the peak EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the gain of the used antenna, the RF power density can be obtained.

2.3. Estimation Result

Mode	PK Output power (dBm)	Output power (mW)	Antenna Gain (dBi)	Antenna Gain (linear)	MPE Values (mW/cm ²)	MPE Limit (mW/cm ²)
Max power	24.33	271.02	3	2	0.108	1

Note: The estimation distance is 20cm

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold

END OF REPORT