

## FCC CERTIFICATION TEST REPORT

### FOR

<b>Applicant</b>	:	Guangdong Sygole Intelligent Technology Co.,Ltd
<b>Address</b>	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province
<b>Equipment under Test</b>	:	UHF RFID READER
<b>Model No.</b>	:	SG-UR-I84
<b>Trade Mark</b>	:	N/A
<b>FCC ID</b>	:	2ATQ4SGURI84
<b>Manufacturer</b>	:	Guangdong Sygole Intelligent Technology Co.,Ltd
<b>Address</b>	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province

**Issued By: Dongguan Dongdian Testing Service Co., Ltd.**

**Add:** No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan  
City, Guangdong Province, China, 523808

**Tel:** +86-0769-89201699, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

## TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results .....	6
2.	General test information.....	7
2.1.	Description of EUT .....	7
2.2.	Accessories of EUT .....	7
2.3.	Assistant equipment used for test.....	7
2.4.	Block diagram of EUT configuration for test.....	7
2.5.	Deviations of test standard .....	8
2.6.	Test environment conditions .....	8
2.7.	Test laboratory .....	8
2.8.	Measurement uncertainty .....	9
3.	Equipment used during test .....	10
4.	Maximum Peak Output Power .....	11
4.1.	Block diagram of test setup .....	11
4.2.	Limits .....	11
4.3.	Test Procedure.....	11
4.4.	Test Result .....	11
4.5.	Original test data .....	12
5.	20dB Bandwidth and 99% Bandwidth .....	14
5.1.	Block diagram of test setup .....	14
5.2.	Limits .....	14
5.3.	Test Procedure.....	14
5.4.	Test Result .....	14
5.5.	Original test data .....	15
6.	Carrier Frequency Separation .....	17
6.1.	Block diagram of test setup .....	17
6.2.	Limits .....	17
6.3.	Test Procedure.....	17
6.4.	Test Result .....	17
6.5.	Original test data .....	17
7.	Number Of Hopping Channel .....	18
7.1.	Block diagram of test setup .....	18
7.2.	Limits .....	18
7.3.	Test Procedure.....	18
7.4.	Test Result .....	18

7.5. Original test data ..... 18

8. Dwell Time ..... 19

8.1. Block diagram of test setup ..... 19

8.2. Limits ..... 19

8.3. Test Procedure..... 19

8.4. Test Result ..... 19

8.5. Original test data ..... 19

9. Band Edge Compliance (conducted method) ..... 20

9.1. Block diagram of test setup ..... 20

9.2. Limit..... 20

9.3. Test result..... 20

9.4. Original test data ..... 20

10. Radiated emission ..... 23

10.1. Block diagram of test setup ..... 23

10.2. Limit..... 24

10.3. Test Procedure..... 25

10.4. Test result..... 27

11. RF Conducted Spurious Emissions..... 35

11.1. Block diagram of test setup ..... 35

11.2. Limits ..... 35

11.3. Test Procedure..... 35

11.4. Test Result ..... 36

11.5. Original test data ..... 36

12. Band Edge Compliance (radiated method) ..... 41

12.1. Block diagram of test setup ..... 41

12.2. Limit..... 41

12.3. Test Procedure..... 41

12.4. Test result..... 41

13. Power Line Conducted Emission..... 46

13.1. Block diagram of test setup ..... 46

13.2. Power Line Conducted Emission Limits ..... 46

13.3. Test Procedure..... 46

13.4. Test Result ..... 47

14. Antenna Requirements ..... 50

14.1. Limit..... 50

14.2. Result ..... 50

## TEST REPORT DECLARE

<b>Applicant</b>	:	Guangdong Sygole Intelligent Technology Co.,Ltd
<b>Address</b>	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province
<b>Equipment under Test</b>	:	UHF RFID READER
<b>Model No.</b>	:	SG-UR-I84
<b>Trade mark</b>	:	N/A
<b>Manufacturer</b>	:	Guangdong Sygole Intelligent Technology Co.,Ltd
<b>Address</b>	:	Building 19, Songke Yuan, No.4 Libin Road, Dongguan Songshan Lake High-tech Industrial Development Zone, Guangdong Province

**Test Standard Used:**

FCC Rules and Regulations Part 15 Subpart C.

**Test procedure used:**

ANSI C63.10:2013.

**We Declare:**

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

**After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.**

<b>Report No.:</b>	DDT-R19072206-2E1		
<b>Date of Receipt:</b>	July. 22, 2019	<b>Date of Test:</b>	July. 22, 2019 ~ Sep. 16, 2019

**Prepared By:**

*Talent Zhang*

**Talent Zhang/Engineer**

**Approved By:**



**Damon Hu/EMC Manager**

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

### Revision history

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 16, 2019	

## 1. Summary of test results

Description of Test Item	Standard	Results
Maximum Peak Output Power	FCC Part 15: 15.247(b)(1) ANSI C63.10:2013	PASS
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10:2013	PASS
Carrier Frequency Separation	F FCC Part 15: 15.247(a)(1) ANSI C63.10:2013	PASS
Number Of Hopping Channel	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	PASS
Dwell Time	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10:2013	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.247(d) ANSI C63.10:2013	PASS
Band Edge Compliance	FCC Part 15: 15.247(d) ANSI C63.10:2013	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10:2013	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

## 2. General test information

### 2.1. Description of EUT

EUT* Name	: UHF RFID READER
Model Number	: SG-UR-I84
EUT function description	: Please reference user manual of this device
Power supply	: DC 24V from AC/DC ADAPTER
Operation frequency	: 902-928 MHz
Modulation	: ASK
Antenna Type	: Dedicated antenna , maximum PK gain: 3 dBi
Sample Type	: Series production

Note: EUT is the ab. of equipment under test.

### 2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number	Serial No.	Mark
N/A	N/A	N/A	N/A	N/A

### 2.3. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Serial No.	Other
Notebook	DELL	Latitude D610	00045-534-136-300	N/A
AC/DC ADAPTER	FO SHAN SHUNDE GUANYUDA POWER SUPPLY CO.,LTD	GM50-240100-F	N/A	N/A
USB-RS-485/422	N/A	UT-890A	UT036296362	N/A

### 2.4. Block diagram of EUT configuration for test



Test software: Sygole UHF Reader.exe

The test software was used to control EUT work in Continuous TX mode, and select test channel, wireless mode as blow table.

Tested mode, channel, information		
Mode	Channel	Frequency (MHz)
Hopping on TX mode	CH0 to CH49	902 to 928
Hopping off TX mode	CH0	902.75
	CH25	915.25
	CH49	927.25

## 2.5. Deviations of test standard

No Deviation.

## 2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	-20-55°C
Humidity range:	40-75%
Pressure range:	86-106kPa

## 2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-89201699, <http://www.dgddt.com>, Email: [ddt@dgddt.com](mailto:ddt@dgddt.com)

CNAS Accreditation No. L6451; A2LA Accreditation No. 3870.01

Designation Number: CN1182; Test Firm Registration Number: 540522

Industry Canada site registration number: 10288A-1



## 2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB (10 MHz ≤ f < 3.6 GHz);
	1.38 dB (3.6 GHz ≤ f < 8 GHz)
Frequencies Stability	6.7 x 10 <sup>-8</sup> (Antenna couple method)
	5.5 x 10 <sup>-8</sup> (Conducted method)
Conducted spurious emissions	0.86 dB (10 MHz ≤ f < 3.6 GHz);
	1.40 dB (3.6 GHz ≤ f < 8 GHz)
	1.66 dB (8 GHz ≤ f < 22 GHz)
Uncertainty for radio frequency (RBW<20 kHz)	3x10 <sup>-8</sup>
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (30 MHz-1 GHz)	4.70 dB (Antenna Polarize: V)
	4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz-40 GHz)	4.10 dB (1-6 GHz)
	4.40 dB (6 GHz-18 GHz)
	3.54 dB (18 GHz-26 GHz)
	4.30 dB (26 GHz-40 GHz)
Uncertainty for Power line conduction emission test	3.32 dB (150 kHz-30 MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

### 3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
<b>RF Connected Test (Tonscend RF Measurement System)</b>					
Spectrum analyzer	R&S	FSU26	200071	Oct. 12, 2018	1 Year
Wideband Radio Communication tester	R&S	CMW500	117491	Jun. 25, 2019	1 Year
Vector Signal Generator	Agilent	E8267D	US49060192	Oct. 12, 2018	1 Year
Vector Signal Generator	Agilent	N5182A	MY48180737	Jun. 25, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150010	Jun. 28, 2019	1 Year
Power Sensor	Agilent	U2021XA	MY55150011	Jun. 28, 2019	1 Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	Aug. 18, 2019	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	Aug. 18, 2019	1 Year
RF Cable	Micable	C10-01-01-1	100309	Oct. 21, 2018	1 Year
Temp&Humi Programmable	ZHIXIANG	ZXGDJS-150L	ZX170110-A	Oct. 21, 2018	1 Year
Test Software	JS Tonscend	JS1120-3	Ver.2.7	N/A	N/A
<b>Radiation 1#chamber</b>					
EMI Test Receiver	R&S	ESU8	100316	Oct. 12, 2018	1 Year
Spectrum analyzer	Agilent	E4447A	MY50180031	Jun. 25, 2019	1 Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	Nov. 09, 2018	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	Oct. 20, 2018	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	Nov. 16, 2018	1 Year
Broad Band Horn Antenna	Schwarzbeck	BBHA 9170	790	Oct. 25, 2018	1 Year
Pre-amplifier	A.H.	PAM-0118	360	Oct. 12, 2018	1 Year
Pre-amplifier	TERA-MW	TRLA-0040 G35	101303	Oct. 12, 2018	1 Year
RF Cable	HUBSER	CP-X2+ CP-X1	W11.03+ W12.02	Oct. 21, 2018	1 Year
RF Cable	N/A	SMAJ-SMA J-1M+ 11M	17070133+17070131	Nov. 08, 2018	1 Year
MI Cable	HUBSER	C10-01-01-1 M	1091629	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A
<b>Power Line Conducted Emissions Test</b>					
EMI Test Receiver	R&S	ESU8	100316	Oct. 21, 2018	1 Year
LISN 1	R&S	ENV216	101109	Oct. 21, 2018	1 Year
LISN 2	R&S	ESH2-Z5	100309	Oct. 21, 2018	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	Oct. 21, 2018	1 Year
CE Cable 1	HUBSER	N/A	W10.01	Oct. 21, 2018	1 Year
Test software	Audix	E3	V 6.11111b	N/A	N/A

## 4. Maximum Peak Output Power

### 4.1. Block diagram of test setup



### 4.2. Limits

For frequency hopping systems operating in the 902-928 MHz band: 1 watt for systems employing at least 50 hopping channels; and 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

### 4.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Measure the maximum output power of EUT by spectrum analyzer with PK detector and RBW=3MHz(above 20dB bandwidth of measured signal), VBW=10MHz


Note: The attenuator loss was inputted into spectrum analyzer as amplitude offset.

### 4.4. Test Result

Mode	Freq (MHz)	Result (dBm)	Limit (dBm)	Conclusion
ASK	902.75	27.66	30	PASS
	915.25	27.62	30	PASS
	927.25	27.52	30	PASS

### 4.5. Original test data





## 5. 20dB Bandwidth and 99% Bandwidth

### 5.1. Block diagram of test setup

Same as section 4.1

### 5.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


### 5.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 3 kHz RBW and 10 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

### 5.4. Test Result


Mode	Freq. (MHz)	20dB bandwidth Result (kHz)	99% bandwidth Result (kHz)	Conclusion
ASK	902.75	45.513	55.128	PASS
	915.25	44.872	55.449	PASS
	927.25	44.872	56.089	PASS

### 5.5. Original test data



#### 915.25 MHz

#### 927.25 MHz





## 6. Carrier Frequency Separation

### 6.1. Block diagram of test setup

Same as section 4.1

### 6.2. Limits

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.


### 6.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The carrier frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW.

### 6.4. Test Result

Mode	Channel separation (kHz)	Limit (kHz)	Conclusion
Hopping	501.603	≥25	PASS

### 6.5. Original test data



## 7. Number Of Hopping Channel

### 7.1. Block diagram of test setup

Same as section 4.1

### 7.2. Limits

For frequency hopping systems operating in the 902-928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies


### 7.3. Test Procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The number of hopping channel was measured by spectrum analyzer with 100 kHz RBW and 300kHz VBW.

### 7.4. Test Result

Mode	Number of hopping channel	Limit	Conclusion
Hopping	50	≥50	PASS

### 7.5. Original test data



## 8. Dwell Time

### 8.1. Block diagram of test setup

Same as section 4.1

### 8.2. Limits

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 8.3. Test Procedure


- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) The test period:  $T = 0.4 \text{ Second/Channel} \times 50 \text{ Channel} = 20 \text{ s}$

Measure the hopping number and on time of each pulse with spectrum analyzer in zero span set, and calculate dwell time with formula  $\text{Dwell time} = \text{total hops} \times \text{pulse's on time}$ .

### 8.4. Test Result

Mode	Dwell time (ms)	Pulse time (ms)	Total hops	Limit	Conclusion
ASK	128.204	32.051	4	<400ms	PASS

### 8.5. Original test data



## 9. Band Edge Compliance (conducted method)

### 9.1. Block diagram of test setup

Same as section 4.1


### 9.2. Limit


All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

### 9.3. Test result


Mode	Freq (MHz)	Conclusion
ASK	Hopping off 902.75	PASS
	Hopping off 927.25	PASS
	Hopping on	PASS

### 9.4. Original test data






Low




High




## 10. Radiated emission

### 10.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9kHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test an appropriate high pass filter was inserted in the input port of AMP.

## 10.2. Limit

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.G
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(?)
13.36-13.41			



## (2) FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		$\mu\text{V}/\text{m}$	$\text{dB}(\mu\text{V})/\text{m}$
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB( $\mu\text{V}$ )/m (Peak) 54.0 dB( $\mu\text{V}$ )/m (Average)	

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3\text{m}}(\text{dB}\mu\text{V}/\text{m}) = \text{Limit}_{30\text{m}}(\text{dB}\mu\text{V}/\text{m}) + 40\text{Log}(30\text{m}/3\text{m})$$

## (3) Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

**10.3. Test Procedure**

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a semi-anechoic chamber for above 1G.

(2) Test antenna was located 3m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9kHz-30MHz	Active Loop antenna	3m
30MHz-1GHz	Trilog Broadband Antenna	3m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1m

According ANSI C63.10:2013 clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also

be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of

Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9kHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9kHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 10GHz to 25GHz, so below final test was performed with frequency range from 9kHz to 10GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9kHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90kHz, 110-490kHz, for emissions from 9kHz-90kHz,110kHz-490kHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9kHz to 1GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9kHz-150kHz	200Hz
150kHz-30MHz	9kHz
30MHz-1GHz	120kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure), and for the radiated emissions which outside of there stricted bands, according FCC Part 15: 15.247(d), the RBW is set at 100 kHz, VBW is set at

300kHz for Peak measure, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

(8) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

#### **10.4. Test result**

**PASS. (See below detailed test result)**

Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 10GHz to 25GHz.


Note2: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

## Radiated Emission test (below 1GHz)

## TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/HORIZONTAL  
**Memo** : 902.75MHz

Data: 48



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	222.06	19.82	12.07	0.00	4.89	36.78	46.00	-9.22	QP	HORIZONTAL
2	296.75	18.79	13.93	0.00	5.17	37.89	46.00	-8.11	QP	HORIZONTAL
3	369.50	17.94	15.16	0.00	5.41	38.51	46.00	-7.49	QP	HORIZONTAL
4	742.95	12.21	20.37	0.00	6.49	39.07	46.00	-6.93	QP	HORIZONTAL
5	813.76	12.31	20.84	0.00	6.64	39.79	46.00	-6.21	QP	HORIZONTAL
6	902.75	84.77	21.73	0.00	6.93	113.43	/	/	Peak	HORIZONTAL
7	912.70	13.60	21.85	0.00	6.98	42.43	46.00	-3.57	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2019-08-07  
**EUT** : UHF RFID READER  
**Power Supply** : AC 220V/60Hz  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa  
**Memo** : 902.75MHz

**D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6**  
**Tested By** : JACKY  
**Model Number** : SG-UR-I84  
**Test Mode** : TX mode  
**Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL

Data: 49



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	296.75	17.79	13.93	0.00	5.17	36.89	46.00	-9.11	QP	VERTICAL
2	369.50	14.63	15.16	0.00	5.41	35.20	46.00	-10.80	QP	VERTICAL
3	518.88	10.94	17.38	0.00	5.88	34.20	46.00	-11.80	QP	VERTICAL
4	666.32	10.34	19.59	0.00	6.28	36.21	46.00	-9.79	QP	VERTICAL
5	742.95	10.76	20.37	0.00	6.49	37.62	46.00	-8.38	QP	VERTICAL
6	813.76	9.34	20.84	0.00	6.64	36.82	46.00	-9.18	QP	VERTICAL
7	902.75	83.22	21.73	0.00	6.93	111.88	/	/	Peak	VERTICAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2019-08-07  
**EUT** : UHF RFID READER  
**Power Supply** : AC 220V/60Hz  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa  
**Memo** : 915.75MHz

**D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6**  
**Tested By** : JACKY  
**Model Number** : SG-UR-I84  
**Test Mode** : TX mode  
**Antenna/Distance** : 2018 VULB 9163 1#/3m/HORIZONTAL

Data: 50



Item (Mark)	Freq. (MHz)	Read Level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB $\mu$ V/m)	Limit Line (dB $\mu$ V/m)	Over Limit (dB)	Detector	Polarization
1	219.15	20.97	11.99	0.00	4.88	37.84	46.00	-8.16	QP	HORIZONTAL
2	384.05	17.38	15.37	0.00	5.45	38.20	46.00	-7.80	QP	HORIZONTAL
3	517.91	13.26	17.37	0.00	5.88	36.51	46.00	-9.49	QP	HORIZONTAL
4	594.54	11.98	18.43	0.00	6.07	36.48	46.00	-9.52	QP	HORIZONTAL
5	741.98	10.94	20.36	0.00	6.48	37.78	46.00	-8.22	QP	HORIZONTAL
6	814.73	9.68	20.85	0.00	6.64	37.17	46.00	-8.83	QP	HORIZONTAL
7	915.75	87.15	21.88	0.00	6.99	116.02	/	/	Peak	HORIZONTAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2019-08-07  
**EUT** : UHF RFID READER  
**Power Supply** : AC 220V/60Hz  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa  
**Memo** : 915.75MHz

**D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6**  
**Tested By** : JACKY  
**Model Number** : SG-UR-I84  
**Test Mode** : TX mode  
**Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL

Data: 51



Item (Mark)	Freq. (MHz)	Read Level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dB $\mu$ V/m)	Limit Line (dB $\mu$ V/m)	Over Limit (dB)	Detector	Polarization
1	83.35	19.49	9.28	0.00	4.10	32.87	40.00	-7.13	QP	VERTICAL
2	295.78	18.33	13.91	0.00	5.17	37.41	46.00	-8.59	QP	VERTICAL
3	371.44	14.09	15.19	0.00	5.42	34.70	46.00	-11.30	QP	VERTICAL
4	517.91	13.06	17.37	0.00	5.88	36.31	46.00	-9.69	QP	VERTICAL
5	666.32	10.72	19.59	0.00	6.28	36.59	46.00	-9.41	QP	VERTICAL
6	740.04	10.65	20.35	0.00	6.48	37.48	46.00	-8.52	QP	VERTICAL
7	915.75	84.29	21.88	0.00	6.99	113.16	/	/	Peak	VERTICAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1#  
**Test Date** : 2019-08-07  
**EUT** : UHF RFID READER  
**Power Supply** : AC 220V/60Hz  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa  
**Memo** : 927.25MHz

**D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6**  
**Tested By** : JACKY  
**Model Number** : SG-UR-I84  
**Test Mode** : TX mode  
**Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL

Data: 52



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	43.58	15.65	13.86	0.00	3.81	33.32	40.00	-6.68	QP	VERTICAL
2	196.84	18.85	10.97	0.00	4.80	34.62	43.50	-8.88	QP	VERTICAL
3	295.78	18.39	13.91	0.00	5.17	37.47	46.00	-8.53	QP	VERTICAL
4	517.91	14.05	17.37	0.00	5.88	37.30	46.00	-8.70	QP	VERTICAL
5	666.32	11.36	19.59	0.00	6.28	37.23	46.00	-8.77	QP	VERTICAL
6	912.70	12.96	21.85	0.00	6.98	41.79	46.00	-4.21	QP	VERTICAL
7	927.25	83.61	22.01	0.00	7.05	112.67	/	/	Peak	VERTICAL


- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.



# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5°C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/HORIZONTAL  
**Memo** : 927.25MHz

Data: 53



Item (Mark)	Freq. (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Detector	Polarization
1	191.99	21.95	10.28	0.00	4.78	37.01	43.50	-6.49	QP	HORIZONTAL
2	295.78	14.63	13.91	0.00	5.17	33.71	46.00	-12.29	QP	HORIZONTAL
3	540.22	12.03	17.69	0.00	5.94	35.66	46.00	-10.34	QP	HORIZONTAL
4	666.32	12.07	19.59	0.00	6.28	37.94	46.00	-8.06	QP	HORIZONTAL
5	740.04	9.68	20.35	0.00	6.48	36.51	46.00	-9.49	QP	HORIZONTAL
6	912.70	13.23	21.85	0.00	6.98	42.06	46.00	-3.94	QP	HORIZONTAL
7	927.25	86.49	22.01	0.00	7.05	115.55	/	/	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

**Radiated Emission test (above 1GHz)**

Freq. (MHz)	Read level (dB $\mu$ V)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dB $\mu$ V/m)	Limit (dB $\mu$ V /m)	Margin (dB)	Detector type	Polarization
Tx mode 902.75MHz									
4060.00	50.60	32.99	44.39	5.67	44.87	74.00	-29.13	Peak	HORIZONTAL
5428.00	49.53	34.24	44.11	5.93	45.59	74.00	-28.41	Peak	HORIZONTAL
6373.00	48.62	35.15	43.81	6.10	46.06	74.00	-27.94	Peak	HORIZONTAL
7903.00	47.70	36.22	43.14	6.57	47.35	74.00	-26.65	Peak	HORIZONTAL
8830.00	48.02	36.80	43.54	7.17	48.45	74.00	-25.55	Peak	HORIZONTAL
9757.00	47.81	37.26	43.99	7.71	48.79	74.00	-25.21	Peak	HORIZONTAL
3970.00	50.53	32.85	44.40	5.62	44.60	74.00	-29.40	Peak	VERTICAL
5230.00	49.36	34.09	44.15	5.91	45.21	74.00	-28.79	Peak	VERTICAL
5995.00	52.50	34.70	44.00	6.00	49.20	74.00	-24.80	Peak	VERTICAL
7183.00	47.77	35.71	43.44	6.34	46.38	74.00	-27.62	Peak	VERTICAL
8002.00	47.60	36.30	43.10	6.60	47.40	74.00	-26.60	Peak	VERTICAL
9352.00	47.86	37.02	43.80	7.49	48.57	74.00	-25.43	Peak	VERTICAL
Tx mode 915.25MHz									
3277.00	50.24	31.72	44.40	4.80	42.36	74.00	-31.64	Peak	HORIZONTAL
4087.00	50.90	33.03	44.38	5.68	45.23	74.00	-28.77	Peak	HORIZONTAL
5995.00	49.32	34.70	44.00	6.00	46.02	74.00	-27.98	Peak	HORIZONTAL
7822.00	47.78	36.16	43.17	6.54	47.31	74.00	-26.69	Peak	HORIZONTAL
8830.00	47.27	36.80	43.54	7.17	47.70	74.00	-26.30	Peak	HORIZONTAL
9568.00	47.94	37.15	43.90	7.61	48.80	74.00	-25.20	Peak	HORIZONTAL
3943.00	50.05	32.81	44.40	5.59	44.05	74.00	-29.95	Peak	VERTICAL
5365.00	49.74	34.20	44.12	5.92	45.74	74.00	-28.26	Peak	VERTICAL
5995.00	55.85	34.70	44.00	6.00	52.55	74.00	-21.45	Peak	VERTICAL
7093.00	47.84	35.66	43.48	6.31	46.33	74.00	-27.67	Peak	VERTICAL
8848.00	47.07	36.80	43.55	7.19	47.51	74.00	-26.49	Peak	VERTICAL
9685.00	47.32	37.22	43.96	7.67	48.25	74.00	-25.75	Peak	VERTICAL
Tx mode 927.25MHz									
3340.00	49.50	31.83	44.40	4.87	41.80	74.00	-32.20	Peak	HORIZONTAL
5005.00	49.23	33.90	44.20	5.88	44.81	74.00	-29.19	Peak	HORIZONTAL
5995.00	50.43	34.70	44.00	6.00	47.13	74.00	-26.87	Peak	HORIZONTAL
7255.00	48.08	35.76	43.41	6.36	46.79	74.00	-27.21	Peak	HORIZONTAL
8002.00	49.00	36.30	43.10	6.60	48.80	74.00	-25.20	Peak	HORIZONTAL
9865.00	48.11	37.32	44.04	7.77	49.16	74.00	-24.84	Peak	HORIZONTAL
3763.00	49.61	32.53	44.40	5.38	43.12	74.00	-30.88	Peak	VERTICAL
4600.00	49.98	33.66	44.27	5.79	45.16	74.00	-28.84	Peak	VERTICAL
5995.00	51.95	34.70	44.00	6.00	48.65	74.00	-25.35	Peak	VERTICAL
7075.00	48.69	35.65	43.48	6.30	47.16	74.00	-26.84	Peak	VERTICAL
8245.00	48.16	36.55	43.24	6.77	48.24	74.00	-25.76	Peak	VERTICAL
9748.00	47.66	37.25	43.99	7.71	48.63	74.00	-25.37	Peak	VERTICAL
Result: Pass									

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

## 11. RF Conducted Spurious Emissions

### 11.1. Block diagram of test setup

Same as section 4.1

### 11.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 11.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100kHz
VBW:	300kHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:


RBW:	100kHz
VBW:	300kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{span/RBW}$
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold


(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band .

### 11.4. Test Result


Mode	Freq. (MHz)	Conclusion
ASK	Hopping off 902.75	PASS
	Hopping off 915.25	PASS
	Hopping off 927.25	PASS

### 11.5. Original test data







915.25 MHz \_Ref




915.25 MHz \_30~1000




915.25 MHz \_1000~12750




927.25 MHz \_Ref



927.25 MHz \_30~1000




927.25 MHz \_1000~12750





## 12. Band Edge Compliance (radiated method)

### 12.1. Block diagram of test setup



### 12.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

### 12.3. Test Procedure

Same with clause 10.3 except change investigated frequency range.

Remark: All restriction band have been tested, and only the worse case is shown in report.

### 12.4. Test result


PASS. (See below detailed test result)

Remark: hopping on and hopping off mode all have been test, hopping off mode is worst and reported only.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL  
**Memo** : 902.75 MHz

Data: 54




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	608.06	9.61	18.64	0.00	6.12	34.37	46.00	-11.63	Peak	VERTICAL
2	614.00	8.56	18.74	0.00	6.13	33.43	46.00	-12.57	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/HORIZONTAL  
**Memo** : 902.75 MHz

Data: 55




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	608.68	10.35	18.65	0.00	6.12	35.12	46.00	-10.88	Peak	HORIZONTAL
2	614.00	9.10	18.74	0.00	6.13	33.97	46.00	-12.03	Peak	HORIZONTAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/HORIZONTAL  
**Memo** : 927.25 MHz

Data: 56




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	960.00	8.63	22.37	0.00	7.06	38.06	46.00	-7.94	Peak	HORIZONTAL
2	964.24	9.98	22.42	0.00	7.06	39.46	54.00	-14.54	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

# TR-4-E-009 Radiated Emission Test Result

**Test Site** : DDT 3m Chamber 1# D:\2019 RE1# Report Data\Q19072206-1E SG-UR-181\FCC BELOW 1G.EM6  
**Test Date** : 2019-08-07 **Tested By** : JACKY  
**EUT** : UHF RFID READER **Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz **Test Mode** : TX mode  
**Condition** : Temp:24.5'C,Humi:55%,Press:100.1kPa **Antenna/Distance** : 2018 VULB 9163 1#/3m/VERTICAL  
**Memo** : 927.25 MHz

Data: 57




Item (Mark)	Freq. (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	960.08	8.70	22.37	0.00	7.06	38.13	54.00	-15.87	Peak	VERTICAL
2	961.44	11.03	22.39	0.00	7.06	40.48	54.00	-13.52	Peak	VERTICAL

- Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.  
 2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

## 13. Power Line Conducted Emission

### 13.1. Block diagram of test setup



### 13.2. Power Line Conducted Emission Limits

Frequency	Quasi-Peak Level dB( $\mu$ V)	Average Level dB( $\mu$ V)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: \* Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

### 13.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 kHz.

#### **13.4. Test Result**

##### **PASS. (See below detailed test result)**


Note1: All emissions not reported below are too low against the prescribed limits.

Note2: "----" means Peak detection; "-----" means Average detection.

Note3: Pre-test AC conducted emission at both voltage AC 220V/60Hz and AC 240V/60Hz, recorded worse case.

## TR-4-E-010 Conducted Emission Test Result

: DDT 5# Shield Room  
 D:\2019 report data\Q19072206-1E\CE.EM6  
**Test Date** : 2019-08-14  
**Tested By** : Carl  
**EUT** : UHF RFID READER  
**Model Number** : SG-UR-I84  
**Power Supply** : AC 220V/60Hz  
**Test Mode** : TX mode  
**Condition** : Temp:24.5°C,Humi:55.5%,Press:100.1kPa  
**LISN** : 2018 ENV216 2#/NEUTRAL  
**Memo** :



Item (Mark)	Freq. (MHz)	Read Level (dB $\mu$ V)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limite r Factor (dB)	Result Level (dB $\mu$ V)	Limit Line (dB $\mu$ V)	Over Limit (dB)	Detector	Phase
1	0.64	22.44	9.64	0.21	9.78	42.07	56.00	-13.93	QP	NEUTRAL
2	0.64	20.21	9.64	0.21	9.78	39.84	46.00	-6.16	Average	NEUTRAL
3	0.78	18.21	9.64	0.21	9.78	37.84	56.00	-18.16	QP	NEUTRAL
4	0.78	13.46	9.64	0.21	9.78	33.09	46.00	-12.91	Average	NEUTRAL
5	1.05	15.33	9.64	0.23	9.78	34.98	56.00	-21.02	QP	NEUTRAL
6	1.05	10.12	9.64	0.23	9.78	29.77	46.00	-16.23	Average	NEUTRAL
7	1.38	15.49	9.64	0.27	9.78	35.18	56.00	-20.82	QP	NEUTRAL
8	1.38	10.53	9.64	0.27	9.78	30.22	46.00	-15.78	Average	NEUTRAL
9	2.06	11.28	9.64	0.32	9.77	31.01	56.00	-24.99	QP	NEUTRAL
10	2.06	6.02	9.64	0.32	9.77	25.75	46.00	-20.25	Average	NEUTRAL
11	3.78	9.55	9.63	0.36	9.48	29.02	56.00	-26.98	QP	NEUTRAL
12	3.78	4.96	9.63	0.36	9.48	24.43	46.00	-21.57	Average	NEUTRAL

Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.

2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).

4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.



# TR-4-E-010 Conducted Emission Test Result

	: DDT 5# Shield Room	D:\2019 report data\Q19072206-1E\CE.EM6
<b>Test Date</b>	: 2019-08-14	<b>Tested By</b> : Carl
<b>EUT</b>	: UHF RFID READER	<b>Model Number</b> : SG-UR-I84
<b>Power Supply</b>	: AC 220V/60Hz	<b>Test Mode</b> : TX mode
<b>Condition</b>	: Temp:24.5°C,Humi:55.5%,Press:100.1kPa	<b>LISN</b> : 2018 ENV216 2#/LINE
<b>Memo</b>	:	



Item (Mark)	Freq. (MHz)	Read Level (dBμV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBμV)	Limit Line (dBμV)	Over Limit (dB)	Detector	Phase
1	0.63	22.36	9.64	0.21	9.78	41.99	56.00	-14.01	QP	LINE
2	0.63	19.68	9.64	0.21	9.78	39.31	46.00	-6.69	Average	LINE
3	0.78	18.37	9.64	0.21	9.78	38.00	56.00	-18.00	QP	LINE
4	0.78	13.67	9.64	0.21	9.78	33.30	46.00	-12.70	Average	LINE
5	0.93	15.87	9.64	0.22	9.78	35.51	56.00	-20.49	QP	LINE
6	0.93	11.06	9.64	0.22	9.78	30.70	46.00	-15.30	Average	LINE
7	1.44	15.69	9.64	0.27	9.78	35.38	56.00	-20.62	QP	LINE
8	1.44	10.83	9.64	0.27	9.78	30.52	46.00	-15.48	Average	LINE
9	1.94	12.74	9.64	0.32	9.78	32.48	56.00	-23.52	QP	LINE
10	1.94	8.29	9.64	0.32	9.78	28.03	46.00	-17.97	Average	LINE
11	2.68	10.32	9.64	0.34	9.64	29.94	56.00	-26.06	QP	LINE
12	2.68	5.48	9.64	0.34	9.64	25.10	46.00	-20.90	Average	LINE

- Note: 1. Result Level = Read Level + LISN Factor + Pulse Limiter Factor + Cable loss.  
 2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).  
 4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

## **14. Antenna Requirements**

### **14.1. Limit**

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### **14.2. Result**

The antenna used for this product is dedicated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 5.5 dBi.

**END OF REPORT**