

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

*FCC PART 15.247, SUBPART C
IC RSS-247
TEST REPORT*

*for**the*

Drone

Model: SDRC2V1

Prepared for

Skydio, Inc.
114 Hazel Avenue
Redwood City, California, 94605

Prepared by: _____

Andreas Davidsson

Approved by: _____

Kevin Bothmann

Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, California 94043
(650) 965-4000

Date: January 14, 2020

	REPORT BODY	APPENDICES				TOTAL
		A	B	C	D	
PAGES	26	52	3	2	3	86

This report shall not be reproduced except in full, without the written approval of Electro Magnetic Test, Inc.



Electro Magnetic Test, Inc. (EMT) is accredited by NVLAP, Lab Code 200147-0 to perform the tests listed in this report, except where noted otherwise. This report and the information contained herein represent the test results related only to the sample tested. This report should not be relied upon as an endorsement or certification by EMT or NVLAP for the sample tested, nor does it represent any statement whatsoever as to its marketing status or fitness of the equipment for a particular purpose.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

REVISION HISTORY

VERSION	DATE	COMMENTS	MODIFIED BY
1.0	January 14, 2020	Original Document	AD
2.0	January 22, 2020	Updated following comments from reviewer.	AD
2.1	January 30, 2020	Updated PSD Plot.	AD


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TABLE OF CONTENTS

SECTION	TITLE	PAGE
REVISION HISTORY		2
GENERAL REPORT SUMMARY		5
SUMMARY OF TEST RESULTS		6
TECHNICAL DESCRIPTION OF THE EUT		7
1. PURPOSE		8
2. ADMINISTRATIVE DATA		9
2.1 Location of Testing		9
2.2 Traceability Statement		9
2.3 Cognizant Personnel		9
2.4 Date Test Sample was Received		9
2.5 Disposition of the Test Sample		9
2.6 Abbreviations and Acronyms		9
3. APPLICABLE DOCUMENTS		10
4. DESCRIPTION OF TEST CONFIGURATION		11
4.1 Description of Test Configuration - EMI		11
4.1.1 Cable Construction and Termination		12
5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT		13
5.1 EUT and Accessory List		13
5.2 EMI Test Equipment		14
6. TEST SITE DESCRIPTION		16
6.1 Test Facility Description		16
6.2 EUT Mounting, Bonding and Grounding		16
6.3 Facility Environmental Characteristics		16
7. TEST PROCEDURES		17
7.1 Emissions in Restricted and Non-Restricted Bands		17
7.2 Conducted Emissions Test – Mains Ports		21
7.3 Occupied Bandwidth		22
7.3.3 Test Result		22
7.4 Maximum Peak Output Power		23
7.4.3 Test Result		23
7.5 Maximum Peak Power Spectral Density		24
7.5.3 Test Result		24
7.6 Antenna Requirement		25
7.6.2 Test Result		25
8. CONCLUSIONS / COMPLIANCE STATEMENT		26

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

LIST OF APPENDICES

APPENDIX	TITLE
A	Radiated and Conducted Data Sheets • Radiated Emissions Test Data (General Requirements, and Restricted Bands) • Conducted Emissions Test Data • Emissions in Non-Restricted Frequency Bands Test Data • Occupied Bandwidth Test Data • Maximum Peak Output Power Test Data • Maximum Peak Power Spectral Density Test Data
B	Test Setup Diagrams
C	Modifications To The EUT
D	Additional Models Covered Under This Report

LIST OF FIGURES

FIGURE	TITLE
1	Conducted Emissions Test Setup
2	Plot Map And Layout of Test Site
3	Layout of 5 Meter Semi-Anechoic Chamber


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY

This electromagnetic emission test report is generated by Electro Magnetic Test, Inc., which is an independent testing and consulting firm. The test report is based on testing performed Electro Magnetic Test, Inc. personnel according to the measurement procedure described in the test specification given below and in the "Test Procedures" section of this report.

The measurement data and conclusions appearing herein relate only to the sample tested and this report may not be reproduced in any form unless done so in full.

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Federal Government.

The measurement data and conclusions contained in this test report are deemed satisfactory evidence of compliance with Industry Canada Interference-Causing Equipment Standard ICES-003, Issue 6, January 2016.

Electro Magnetic Test, Inc. is recognized by the following agencies for performing EMI/EMC testing:

COUNTRY	AGENCY	IDENTIFYING #
USA	Federal Communications Commission (FCC) (EMT's test site is recognized by the FCC)	Registration Number: 90576
USA, Canada, Taiwan, Australia/New Zealand, European Community	National Voluntary Lab Accreditation Program (NVLAP) (EMT is accredited by NVLAP. A copy of the NVLAP Scope Of Accreditation is available upon request.)	Lab Code: 200147-0
Canada	Industry Canada	File No.: IC 2804
Japan	Voluntary Control Council For Interference (VCCI)	A-0118
	Open Field Test Site "A"	-
	Mains Conducted Emissions Test Site "D"	-
	Telecom Conducted Emissions Test Site "D"	-
	3 Meter Semi-Anechoic Chamber Site "E"	-
	3 Meter Semi-Anechoic Chamber Site "E" (1GHz – 6GHz)	-
	Mains Conducted Emissions Test Site "E"	-
	Telecom Conducted Emissions Test Site "E"	-
Korea	Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (A copy of the Scope Of Accreditation is available upon request)	US0036
Taiwan	Bureau Of Standards, Metrology and Inspection (BSMI)	Reference Number: SL2-IN-E-1024
Australia / New Zealand	Australian Communications Authority (AUSTEL)	*

*These agencies do not issue an identifying number to test labs.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

GENERAL REPORT SUMMARY (CONTINUED)

Device Tested: Drone
 Model: SDRC2V1
 S/N: N/A

Product Description: The EUT is a quadcopter intended to capture video by moving autonomously through the world. The EUT communicates to either a user's cell phone or a Skydio sold beacon or controller over the 2.4 GHz & 5 GHz Wi-Fi bands. The EUT is stores video on a removable SD card and is capable of video processing when not in flight. The EUT can also charge the Skydio LiPo battery via a USB-C port using the provided 65W AC adapter.

Modifications: The EUT was not modified during the testing.

Manufacturer: Skydio, Inc.
 114 Hazel Avenue
 Redwood City, California, 94605

Test Date(s): December 2, 18, 19, 20, 23, 24, 26, January 8, and 9, 2020

Test Specifications: EMI requirements
 Limits: CISPR 22: 1997 plus A1:2000 & A2:2002 Class B
 FCC Title 47, Part 15 Subpart B, Class B
 FCC Title 47, Part 15 Subpart C
 Test Procedure: ANSI C63.8: 2013

Test Deviations: The test procedure was not deviated from during the testing.

SUMMARY OF TEST RESULTS

TEST	DESCRIPTION	FCC STANDARD	IC STANDARD	RESULTS
7.1	Emissions in Restricted and Non-Restricted Bands	15.209, 15.247, 15.247(d)	RSS-GEN Issue 5, [8.9] RSS 247 Issue 2, [5.5]:	PASS
7.2	Conducted Emissions	15.207(a)	RSS-GEN Issue 5 [8.8]	PASS
7.3	Occupied Bandwidth	15.247(a)(2)	RSS 247 Issue 2, [5.2.1, 6.2.4.1]	PASS
7.4	Maximum Peak Output Power	15.247 (b)	RSS 247 Issue 2, [5.4.4]	PASS
7.5	Maximum Peak Power Spectral Density	15.247(e)	RSS 247 Issue 2, [5.2.2]	PASS
7.6	Antenna Requirement	15.203,15.247(b)(4),	N/A	PASS


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

TECHNICAL DESCRIPTION OF THE EUT

Manufacturer:		Skydio, Inc.			
Manufacturer Address:		114 Hazel Avenue			
EUT Name:		Drone			
Model No:		Model: SDRC2V1			
Operation frequency:		2412 MHz to 2462 MHz, 5180MHz to 5240MHz, and 5745MHz to 5825MHz			
Channel Number:		11			
Modulation Technology:		DSSS			
Antenna Type:		PCB Antenna			
Antenna Gain:		3 dBi			
Maximum Output Power:		26.36 dBm			
Description of Channel:					
802.11 b/g/n (5+10MHz)					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	5	2432	9	2452
2	2417	6	2437	10	2457
3	2422	7	2442	11	2462
4	2427	8	2447		

***ELECTRO MAGNETIC TEST, INC.***1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

1. PURPOSE

This document is a qualification test report based on the Electromagnetic Interference (EMI) tests performed on the Drone Model: SDRC2V1. The EMI measurements were performed according to the measurement procedure described in ANSI C63.8 2013. The tests were performed in order to determine whether the electromagnetic emissions from the equipment under test, referred to as EUT hereafter, are within the specification limits defined in FCC Title 47, Part 15, Subpart C.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

2. ADMINISTRATIVE DATA

2.1 Location of Testing

The EMI tests described herein were performed at the test facility of Electro Magnetic Test, Inc., 1547 Plymouth Street, Mountain View, California, 94043.

2.2 Traceability Statement

The calibration certificates of all test equipment used during the test are on file at the location of the test. The measurement results in this report and the calibration of the test equipment are traceable to the National Institute of Standards and Technology (NIST).

2.3 Cognizant Personnel

Skydio, Inc.

Joe Marcinkowski Engineering Program Manager

Electro Magnetic Test, Inc.

Andreas Davidsson	Test Technician
David Vivanco	Test Technician
Simeet Gandhi	Test Technician
Manan Modi	Test Technician
Kevin Bothmann	Lab Manager

2.4 Date Test Sample was Received

The test sample was received on June 25, 2019

2.5 Disposition of the Test Sample

The test sample has not yet been returned to Skydio, Inc.

2.6 Abbreviations and Acronyms

The following abbreviations and acronyms may be used in this document.

RF	Radio Frequency
EMI	Electromagnetic Interference
EUT	Equipment Under Test
P/N	Part Number
S/N	Serial Number
HP	Hewlett Packard
ITE	Information Technology Equipment
CML	Corrected Meter Limit
LISN	Line Impedance Stabilization Network
CISPR	International Special Committee On Radio Interference
FCC	Federal Communications Commission

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

3. APPLICABLE DOCUMENTS

The following documents are referenced or used in the preparation of this EMI Test Report.

SPEC	TITLE
FCC Title 47, Part 15, Subpart C	FCC Rules - Radio frequency devices (including digital devices).
FCC Publication KDB558074	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the fcc rules, August 24, 2018
ANSI C63.10-2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.
RSS-Gen Issue 5, April 2018	General Requirements for Compliance of Radio Apparatus
RSS 247, Issue 2, February 2017	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4. DESCRIPTION OF TEST CONFIGURATION

4.1 Description of Test Configuration - EMI

The EUT had 3 modes of operation, Flight Mode, USB Transfer Mode, and Charging Mode, the configuration for each mode is listed below:

Flight Mode: The vehicle is simulating flight conditions, with all motors spinning and the user camera recording. The onboard computer is calculating flight dynamics and processing images from the navigation cameras. The wireless link is operating a maximum power output.

USB Transfer Mode: The vehicle is in a mode where it has landed from a flight and is processing the captured video. This video is also transferred to a computer over a USBC cable. The motors are not operational and the cameras are not recording, but the computer is running and the wireless link is operational.

Charging Mode: The vehicle is charging the Skydio battery via the USB-C port and provided 65W AC adapter. A small amount of compute is required and the wireless system is operational, but the motors are not spinning and the cameras are not recording.

The EUT was tested in three physical configurations across all modes, flat, vertical with antenna facing upwards, and vertical with antenna facing downwards. The flat orientation in flight mode was found to have the highest intentional and unintentional emissions.

It was determined that the emissions were at their highest level when the EUT was operating in the above configuration. The final conducted as well as radiated data was taken in this mode of operation. All initial investigations were performed with the EMI receiver in manual mode scanning the frequency range continuously.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

4.1.1 Cable Construction and Termination

Flight Mode:

The EUT did not have any cables connected to it in this mode of operation.

USB Transfer Mode:

Cable #1

This is a 1ft 8 in foil and braid shielded USB Type C cable connecting the EUT to the Storage Drive. It has a USB Type C connection on both ends of the cable.

Charging Mode:

Cable #1

This is a 4 ft. foil and braid shielded USB Type C cable connecting the EUT to its AC power supply. It has a USB Type C connection on both ends of the cable.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5. LISTS OF EUT, ACCESSORIES AND TEST EQUIPMENT

5.1 EUT and Accessory List

EQUIPMENT TYPE	MANUFACTURER	MODEL	SERIAL NUMBER	FCC ID
Drone (EUT)	Skydio, Inc.	SDRC2V1	N/A	2ATQRSDRC2V1
AC Adapter (For Charging Mode Only)	Acbel Polytech Inc.	WAH232	W232A8AU02BB 2	DOC
Storage Drive (For USB Transfer Mode Only)	Seagate	LRD0TU6	NL352G2P	DOC
THE FOLLOWING WERE LOCATED OUTSIDE THE TEST SITE:				
Laptop	Dell	Precision 5510	7W0GNH2	DOC
Laptop AC Adapter	Dell	HA130PM130	CN-0RN7NW- 75661-343-20SJ- A00	DOC
Charging Dock	Skydio, Inc.	N/A	N/A	N/A
Charging AC Adapter	Delta Electronics, Inc.	ADP-100PB B	0432- 03AE0RV6210004 67	DOC


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5.2 EMI Test Equipment

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100295	February 15, 2019	1 Year
Radiated EMI Software	Sector Design	N/A	Ver.1.4.6	N/A	N/A
EMI Receiver (Conducted EMI)	Rohde & Schwarz	ESU40	100295	February 15, 2019	1 Year
Conducted EMI Software	ETS-Lindgren	Tile!	Rev. 7.0.12.697	N/A	N/A
Preamplifier	Hewlett Packard	8447D	1937A02579	March 5, 2019	1 Year
RF Attenuator	Com-Power	LIT-153A	531175	December 15, 2018 / December 15, 2019	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150701	January 2, 2019	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150702	January 2, 2019	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150703	January 2, 2019	1 Year
LISN	Solar Electronics	Type 21107-50-TS-50-N	21107150704	January 2, 2019	1 Year
Biconical Antenna	Com Power	AB-100	01557	July 20, 2019	1 Year
Log Periodic Antenna	Com Power	AL-100	16001	August 9, 2019	1 Year
Antenna Mast	Com Power	AM-400	N/A	N/A	N/A
Turntable	Com Power	TT-100	N/A	N/A	N/A
Computer	Dell, Inc.	DHS	DNSV641	N/A	N/A
Printer	Hewlett Packard	C8124A	CN39A220ZD	N/A	N/A


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

5.2 EMI Test Equipment (Continued)

EQUIPMENT TYPE	MANUFACTURER	MODEL NUMBER	SERIAL NUMBER	CAL. DATE	CAL. CYCLE
EMI Receiver	Rohde & Schwarz	ESU40	100127	February 16, 2019	1 Year
EMI Test Software	Rohde & Schwarz	EMC32	V8.54.0	N/A	N/A
BiConiLog Antenna	ETS-Lindgren	3143B	00206757	August 28, 2019	1 Year
Horn Antenna	ETS-Lindgren	3117	00109294	September 18, 2019	1 Year
Preamplifier	Rohde & Schwarz	TS-PR18	100056	December 12, 2018/ December 12, 2019	1 Year
Antenna Mast	ETS-Lindgren	2171B	00150364	N/A	N/A
Turntable	ETS-Lindgren	2187-3.0	00118231	N/A	N/A
Computer	Dell, Inc.	Precision Tower 3620	GPQCDH2	N/A	N/A
Multi-Function Controller	ETS-Lindgren	2090	00102270	N/A	N/A

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

6. TEST SITE DESCRIPTION

6.1 Test Facility Description

Please refer to the table below and section 7.1 of this report for the details of which sites were used for testing. All sites are located at 1547 Plymouth Street, Mountain View, California 94043.

Site Used For Test	Site Description
	Open Field Test Site "A"
X	Mains Conducted Emissions Test Site "D"
	Telecom Conducted Emissions Test Site "D"
X	3 Meter Semi-Anechoic Chamber Site "E"
	Mains Conducted Emissions Test Site "E"
	Telecom Conducted Emissions Test Site "E"

6.2 EUT Mounting, Bonding and Grounding

The EUT was mounted on a 1.0 by 1.5 meter non-conductive table 0.8 meters above the ground plane for all tests not including radiated measurements above 1GHz.

For radiated measurements above 1GHz the EUT was mounted on a 0.7 meter non-conductive hollow cube that was placed on a 1.0 by 1.5 meter table 0.8 meters above the ground plane with a total height of 1.5 meters.

The EUT was not grounded in Flight or USB Transfer Mode, in Charging mode it was grounded only through the safety ground in its power cable.

6.3 Facility Environmental Characteristics

All tests were performed in a climate controlled building. The temperature was 22° C, humidity 43%, and barometric pressure 101.8 kPa.


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7. TEST PROCEDURES

The following sections describe the test methods and the specifications for the tests.

7.1 Emissions in Restricted and Non-Restricted Bands

7.1.1 General Requirements Limit (FCC PART 15 Section 15.209(a)(1), IC-RSS-GEN Issue 5, [8.9])

Frequency of Emission (MHz)	Field Strength		Measurement Distance (Meters)
	$\mu\text{V/m}$	$\text{dB}\mu\text{V/m}$	
0.009-0.49	2400/F(kHz)		300
0.49-1.705	24000/F(kHz)		30
1.705-30	30		30
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

7.1.2 Emissions in Restricted and Non-Restricted Bands Limit (FCC PART 15 Section 15.247(d), IC RSS-GEN Issue 5, [8.10], IC-RSS 247 Issue 1, [5.5])

Emissions in Restricted and Non-Restricted Bands FCC PART 15 Section 15.247(d):

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.2**Emissions in Restricted and Non-Restricted Bands Limit (FCC PART 15 Section 15.247(d), IC-RSS-GEN Issue 5, [8.10], IC-RSS 247 Issue 1, [5.5]) (Continued)****Emissions in Restricted Bands IC-RSS-GEN Issue 5, [8.10]:**

Restricted bands, identified in Table 6, are designated primarily for safety-of-life services (distress calling and certain aeronautical bands), certain satellite downlinks, radio astronomy and some government uses. Except where otherwise indicated, the following restrictions apply:

- (a) Fundamental components of modulation of licence-exempt radio apparatus shall not fall within the restricted bands of Table 6 except for apparatus complying under RSS-287
- (b) Unwanted emissions that fall into restricted bands of Table 6 shall comply with the limits specified in RSS-Gen; and
- (c) Unwanted emissions that do not fall within the restricted frequency bands of Table 6 shall comply either with the limits specified in the applicable RSS or with those specified in this RSS-Gen.

Limit (For Restricted Bands)
See General Limits Requirement In Above Chart (Section 7.1.1)

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.3 Test Procedure (Radiated)

The Rohde & Schwarz ESU40 EMI receiver was used as a measuring meter while under software control by the Rohde & Schwarz EMC32 software. To increase the sensitivity of the instrument, the built in preamplifier was used from 9 KHz to 1 GHz and an external preamplifier was used from 1 GHz to 26.5 GHz. The EMI receiver was used in the peak detect mode with the "Max Hold" feature activated. In this mode, the EMI receiver records the highest measured reading over all the sweeps. The built in quasi-peak or average detector was used only for those readings which are marked accordingly on the data sheets. The effective measurement bandwidth used for the radiated emissions test was 100 kHz from 9 kHz to 26.5 GHz.

The Loop Antenna, Broadband BiConiLog and horn antennas were used as transducers during the measurement. The Loop antenna was used from 9 KHz to 30 MHz, the BiConiLog antenna was used from 30 MHz to 1000 MHz and horn antennas were used from 1GHz – 26.5 GHz. The frequency spans were wide (9 kHz to 150 kHz, 150 kHz to 30 MHz, 30 MHz to 88 MHz, 88 MHz to 216 MHz, 216 to 300 MHz, 300 MHz to 1 GHz, 1 GHz to 18 GHz and 18 GHz to 26.5 GHz) during preliminary investigations. The final data was taken with a frequency span of 1 MHz. Furthermore, the frequency span was reduced during the preliminary investigations as deemed necessary.

The 5 meter semi-anechoic chamber of Electro Magnetic Test, Inc. was used for radiated emission testing. This test site is set up according to ANSI C63.8: 2013. Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The turntable supporting the EUT is remote controlled using a motor. The turntable permits EUT rotation of 360 degrees in order to maximize emissions. Also, the antenna mast allows height variation of the antenna from 1 meter to 4 meters. Data was collected in the worst case (highest emission) configuration of the EUT. The EUT was rotated 360 degrees and the antenna height was varied from 1 to 4 meters (for E field radiated field strength).

The presence of non EUT signals was verified by turning the EUT off. In case a non EUT signal was detected, the measurement bandwidth was reduced temporarily and verification was made that an additional adjacent peak did not exist. This ensures that the other signal does not hide any emissions from the EUT. The EUT was tested at a 3 meter test distance from 9 kHz to 26.5 GHz. to obtain final test data.

The test was run through fully three times with the EUT having its output set to low, middle, and high channels on each test respectively. The data was then combined to provide the worst case of all three tests. This was tested against all applicable modes and bandwidths with the worst case being plotted in each measurement range.

Calculation Of Radiated Emission Test Data:

Amplitude - Gain + Antenna Factor + Cable Loss = Corrected Amplitude

Corrected Amplitude - Limit = Margin

Associated with the radiated emission test data in this report is a ± 5.1 dB measurement uncertainty.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.1.4 Test Procedure (Conducted)

The Rohde & Schwarz ESU40 EMI receiver was used as a measuring meter. The data was collected with the EMI receiver in the peak detect mode with the "Max Hold" feature activated. The quasi-peak and average detectors were used only where indicated in the data sheets. A 10 dB attenuation pad was used for the protection of the EMI receiver input stage, and the EMI receiver offset was adjusted accordingly to read the actual data measured. The LISN output was read by the Rohde & Schwarz ESU40 EMI receiver. The output of the second LISN was terminated by a 50 ohm termination. The effective measurement bandwidth used for the conducted emissions test was 9 kHz.

Please see section 6.2 of this report for mounting, bonding and grounding of the EUT. The EUT was powered through the LISN, which was bonded to the ground plane. The LISN power was filtered and the filter was bonded to the ground plane. The EUT was set up with the minimum distances from any conductive surfaces as specified in ANSI C63.8: 2013. The excess power cord was wrapped in a figure eight pattern to form a bundle not exceeding 0.4 meters in length.

The initial test data was taken in manual mode while scanning the frequency ranges of 0.15 MHz to 1.6 MHz, 1.6 MHz to 5 MHz and 5 MHz to 30 MHz. The conducted emissions from the EUT were maximized for operating mode as well as cable and peripheral placement. Once a predominant frequency (within 12 dB of the limit) was found, it was more closely examined with the spectrum analyzer span adjusted to 1 MHz.

The final data was collected under program control by the ETS-Lindgren Tile! software in several overlapping sweeps by running the spectrum analyzer at a minimum scan rate of 10 seconds per octave.

Calculation Of Conducted Emission Test Data:

Amplitudes shown on the test data are already corrected and include the following equation:

Raw Amplitude + LISN Insertion Loss + Attenuator + Cable Loss = Corrected Amplitude

Corrected Amplitude - Limit = Margin

Associated with the conducted emission test data in this report is a ± 3.4 dB measurement uncertainty.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.2 Conducted Emissions Test – Mains Ports**7.2.1 Limit (FCC PART 15 Section 15.207(a), IC RSS-GEN Issue 5 [8.8])**

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56 *	56 to 46 *
0.5-5	56	46
5-30	60	50

*Note: Decreases with the logarithm of the frequency

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.3 Occupied Bandwidth

7.3.1 Limits FCC PART 15 Section 15.247(a)(2), IC-RSS 247 Issue 1, [5.2.1])

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz

Limit
6 dB Bandwidth $\geq$ 500 kHz

7.3.2 Test Procedure

Follow the radiated test procedure but set the Spectrum Analyzer as below:

RBW: 100 kHz

VBW: $\geq 3 \times$ RBW

Detector: Peak

Trace Mode: Max Hold

- (1) Set analyzer center frequency to center of signal
- (2) Turn on occupied bandwidth measurement mode
- (3) Set measurement to 6db bandwidth

Associated with the Occupied Bandwidth test data in this report is a $\pm 2.5\%$ measurement uncertainty.

7.3.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.4 Maximum Peak Output Power

7.4.1 Limits FCC PART 15 Section 15.247(b)(3), IC-RSS 247 Issue 1, [5.4.4]

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt.

Limit
Maximum Peak Output Power (Digital Modulation) $\leq$ 1Watt or 30 dBm

7.4.2 Test Procedure

RBW = 1 MHz

VBW $\geq$ 3 x RBW

Span $\geq$ 1.5 DTS Bandwidth

Detector: Peak

Trace Mode: Max Hold

Amplitude Offset: Cable Loss

When the trace is completed use the Channel Power function with the Bandwidth set to the DTS Bandwidth edges.

Calculate the Peak Output Power by using the following equation:

a. Peak Power = Conducted Output Power

Cable Loss = 3.1 dBm

Associated with the Maximum Peak Output Power test data in this report is a ± 5.1 dB measurement uncertainty.

7.4.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.5 Maximum Peak Power Spectral Density**7.5.1 Limits FCC PART 15 Section 15.247(e), IC-RSS 247 Issue 1, [5.2.2]**

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density

Limit
2412-2462MHz: 8 dBm / 3 kHz

7.5.2 Test Procedure

Follow the conducted test procedure but set the Spectrum Analyzer as below:

$3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$

$\text{VBW} \geq 3 \times \text{RBW}$

$\text{Span} \geq 1.5 \times \text{DTS Bandwidth}$

Amplitude Offset: Cable Loss

Detector: Peak

1.) Connect EUT to Spectrum Analyzer

2.) Record data values and calculate Power Spectral Density by using the following equation:

b. Power Spectral Density = Conducted Output Power

Cable Loss = 3.1 dBm

Associated with the Maximum Peak Power Spectral Density test data in this report is a ± 5.1 dB measurement uncertainty.

7.5.3 Test Result

The EUT meets the requirements. Please see the datasheets in Appendix A for the measurement results.

**ELECTRO MAGNETIC TEST, INC.**1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

7.6 Antenna Requirement

7.6.1 Requirement (FCC PART 15 SECTION 15.203,15.247(b)(4))

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section.

(4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

.

7.6.2 Test Result

The antennas are integrated on the main PCB with no consideration for replacement on the Drone.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

8. CONCLUSIONS / COMPLIANCE STATEMENT

Based upon the results contained in this report, Electro Magnetic Test, Inc. has determined that the Drone, Model: SDRC2V1 meets all of the specification limits defined in FCC Title 47, Part 15, Subpart C.



APPENDIX A

RADIATED AND CONDUCTED EMISSIONS DATA SHEETS

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Andreas Davidsson

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 5MHz, 25dB, 2412

FCC Class B Radiated Scan 3m PK QP



----- FCC Class B 3m
◆ Final Result 1-PK+

----- Preview Result 1V-PK+
◆ Final Result 2-QP

----- Preview Result 1H-PK+

Final Result 1 2412MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.380000	23.4	114.0	H	204.0	20.0	16.60	40.00	
105.630000	20.5	187.0	V	359.0	13.8	23.00	43.50	
357.030000	40.0	100.0	H	260.0	21.9	6.00	46.00	
434.130000	37.2	182.0	H	93.0	23.9	8.80	46.00	
571.200000	32.0	136.0	H	63.0	27.0	14.00	46.00	
936.690000	36.9	100.0	V	266.0	32.0	9.10	46.00	

Final Result 2 2412MHz 5MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.380000	17.8	114.0	H	204.0	20.0	22.20	40.00	
105.630000	16.3	187.0	V	359.0	13.8	27.20	43.50	
357.030000	36.2	100.0	H	260.0	21.9	9.80	46.00	
434.130000	32.7	182.0	H	93.0	23.9	13.30	46.00	
571.200000	25.9	136.0	H	63.0	27.0	20.10	46.00	
936.690000	31.5	100.0	V	266.0	32.0	14.50	46.00	

Final Result 1 2437MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.620000	24.4	400.0	H	35.0	19.9	15.60	40.00	
88.500000	15.7	349.0	H	135.0	12.3	27.80	43.50	
105.630000	21.0	165.0	V	23.0	13.8	22.50	43.50	
366.060000	39.8	100.0	H	274.0	22.2	6.20	46.00	
434.820000	36.8	181.0	H	282.0	24.0	9.20	46.00	
815.970000	37.5	137.0	V	280.0	31.5	8.50	46.00	

Final Result 2 2437MHz 5MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.620000	17.6	400.0	H	35.0	19.9	22.40	40.00	
88.500000	10.3	349.0	H	135.0	12.3	33.20	43.50	
105.630000	16.2	165.0	V	23.0	13.8	27.30	43.50	
366.060000	35.8	100.0	H	274.0	22.2	10.20	46.00	
434.820000	32.4	181.0	H	282.0	24.0	13.60	46.00	
815.970000	31.7	137.0	V	280.0	31.5	14.30	46.00	

Final Result 1 2462MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.890000	23.4	264.0	V	38.0	19.7	16.60	40.00	
105.720000	20.9	216.0	V	37.0	13.8	22.60	43.50	
367.620000	35.8	100.0	H	276.0	22.2	10.20	46.00	
408.360000	35.9	205.0	H	92.0	23.5	10.10	46.00	
798.600000	37.4	365.0	V	92.0	31.6	8.60	46.00	
949.590000	38.4	114.0	H	80.0	32.1	7.60	46.00	

Final Result 2 2462MHz 5MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
31.890000	17.5	264.0	V	38.0	19.7	22.50	40.00	
105.720000	16.9	216.0	V	37.0	13.8	26.60	43.50	
367.620000	31.7	100.0	H	276.0	22.2	14.30	46.00	
408.360000	31.2	205.0	H	92.0	23.5	14.80	46.00	
798.600000	31.3	365.0	V	92.0	31.6	14.70	46.00	
949.590000	31.7	114.0	H	80.0	32.1	14.30	46.00	

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Chinmay Shendurnikar

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 10MHz, 25dB, 2412

FCC Class B Radiated Scan 3m PK QP



--- FCC Class B 3m
◆ Final Result 1-PK+

--- Preview Result 1V-PK+
◆ Final Result 2-QPK

--- Preview Result 1H-PK+

Final Result 1 2412MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
358.320000	39.2	100.0	H	280.0	21.9	6.80	46.00	
805.530000	37.2	222.0	V	304.0	31.6	8.80	46.00	

Final Result 2 2412MHz 10MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
358.320000	35.3	100.0	H	280.0	21.9	10.70	46.00	
805.530000	31.1	222.0	V	304.0	31.6	14.90	46.00	

Final Result 1 2437MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
435.570000	36.4	183.0	H	86.0	24.0	9.60	46.00	
792.960000	36.9	310.0	H	238.0	31.4	9.10	46.00	

Final Result 2 2437MHz 10MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
435.570000	31.5	183.0	H	86.0	24.0	14.50	46.00	
792.960000	31.1	310.0	H	238.0	31.4	14.90	46.00	

Final Result 1 2462MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
949.320000	38.0	100.0	H	267.0	32.1	8.00	46.00	


Final Result 2 2462MHz 10MHz BW

Frequency (MHz)	QuasiPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
949.320000	31.7	100.0	H	267.0	32.1	14.30	46.00	



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



FRONT VIEW

Skydio, Inc.

Drone

Model: SDRC2V1


CISPR 22/FCC Class B – Radiated Emissions

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



REAR VIEW

Skydio, Inc.

Drone

Model: SDRC2V1

CISPR 22/FCC Class B – Radiated Emissions


**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650)965-4000 Fax: (650)965-3000

AC Line Conducted Emissions Test Data



Line 1 - (Line) Test Results


Frequency (MHz)	Peak (dBuV)	Quasi-Peak (dBuV)	Average (dBuV)	Corr. Factor (dB)	Quasi-Peak Limit	QP Margin	Average Limit	Average Margin
0.155	58.733	52.653	28.834	10.493	65.851	-13.198	55.851	-27.018
0.212	48.043	44.208	28.196	10.274	64.227	-20.019	54.227	-26.031
0.551	38.983	30.274	16.070	9.908	56.000	-25.726	46.000	-29.930
1.632	36.120	31.493	19.240	9.990	56.000	-24.507	46.000	-26.760
4.985	39.582	33.408	23.020	10.374	56.000	-22.592	46.000	-22.980
15.433	38.816	34.675	28.276	11.057	60.000	-25.325	50.000	-21.724



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

AC Line Conducted Emissions Test Data



Line 2 - (Neutral) Test Results

Frequency (MHz)	Peak (dBuV)	Quasi-Peak (dBuV)	Average (dBuV)	Corr. Factor (dB)	Quasi-Peak Limit	QP Margin	Average Limit	Average Margin
0.153	59.674	54.072	31.409	10.519	65.918	-11.847	55.918	-24.510
0.161	54.289	45.781	22.432	10.447	65.681	-19.900	55.681	-33.249
0.208	48.895	44.586	25.334	10.291	64.346	-19.761	54.346	-29.013
0.407	37.897	33.002	17.524	10.019	58.661	-25.659	48.661	-31.138
0.787	38.343	36.536	28.327	10.079	56.000	-19.464	46.000	-17.673
1.874	36.917	34.511	25.201	10.162	56.000	-21.489	46.000	-20.799
4.960	42.139	35.708	25.395	10.524	56.000	-20.292	46.000	-20.605
16.091	39.240	33.305	26.729	11.021	60.000	-26.695	50.000	-23.271

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Chinmay Shendurnikar

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 5MHz, 19dB, 2412

FCC Class B Radiated Sweep 1GHz-18GHz 3m PK AVG



— FCC Class B 3m_20 - - - - - FCC Class B 3m — Preview Result 1V-PK+
— Preview Result 1H-PK+ ◆ Final Result 1-PK+ ◆ Final Result 2-AVG

Final Result 1 2412MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2235.900000	46.4	100.0	V	132.0	-0.1	27.60	74.00	
3216.233333	47.5	240.0	V	57.0	3.2	26.50	74.00	
4824.433333	52.3	204.0	H	168.0	5.6	21.70	74.00	
7237.300000	58.9	220.0	V	56.0	9.7	15.10	74.00	
9650.166667	55.7	200.0	V	256.0	13.5	18.30	74.00	
16887.633333	58.8	153.0	H	339.0	23.0	15.20	74.00	

Final Result 2 2412MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2235.900000	33.5	100.0	V	132.0	-0.1	20.50	54.00	
3216.233333	42.0	240.0	V	57.0	3.2	12.00	54.00	
4824.433333	42.6	204.0	H	168.0	5.6	11.40	54.00	
7237.300000	46.3	220.0	V	56.0	9.7	7.70	54.00	
9650.166667	48.3	200.0	V	256.0	13.5	5.70	54.00	
16887.633333	46.0	153.0	H	339.0	23.0	8.00	54.00	

Final Result 1 2437MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2219.466667	44.4	114.0	V	156.0	-0.2	29.60	74.00	
3249.666667	45.6	100.0	V	53.0	3.2	28.40	74.00	
4874.866667	53.0	359.0	V	292.0	5.7	21.00	74.00	
7312.100000	57.5	335.0	V	161.0	9.9	16.50	74.00	
9749.900000	54.4	316.0	V	206.0	13.8	19.60	74.00	
14624.933333	60.7	238.0	V	57.0	20.3	13.30	74.00	

Final Result 2 2437MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2219.466667	30.0	114.0	V	156.0	-0.2	24.00	54.00	
3249.666667	39.0	100.0	V	53.0	3.2	15.00	54.00	
4874.866667	46.2	359.0	V	292.0	5.7	7.80	54.00	
7312.100000	46.7	335.0	V	161.0	9.9	7.30	54.00	
9749.900000	46.0	316.0	V	206.0	13.8	8.00	54.00	
14624.933333	51.3	238.0	V	57.0	20.3	2.70	54.00	

Final Result 1 2462MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1019.833333	41.6	181.0	H	89.0	-4.1	32.40	74.00	
3283.100000	44.2	122.0	V	244.0	3.1	29.80	74.00	
4924.733333	45.9	311.0	H	211.0	5.8	28.10	74.00	
7387.466667	63.6	251.0	V	113.0	10.2	10.40	74.00	
11213.600000	49.4	129.0	H	276.0	15.9	24.60	74.00	
16620.733333	55.7	244.0	V	145.0	22.8	18.30	74.00	

Final Result 2 2462MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
1019.833333	37.2	181.0	H	89.0	-4.1	16.80	54.00	
3283.100000	36.2	122.0	V	244.0	3.1	17.80	54.00	
4924.733333	35.2	311.0	H	211.0	5.8	18.80	54.00	
7387.466667	51.7	251.0	V	113.0	10.2	2.30	54.00	
11213.600000	35.9	129.0	H	276.0	15.9	18.10	54.00	
16620.733333	42.2	244.0	V	145.0	22.8	11.80	54.00	

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Chinmay Shendurnikar

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 5MHz, 22dB, 2412

FCC Class B Radiated Sweep 18GHz-26.5GHz 3m PK AVG



— FCC Class B 3m_20 - - - FCC Class B 3m — Preview Result 1V-PK+
— Preview Result 1H-PK+ ◆ Final Result 1-PK+ ◆ Final Result 2-AVG

Final Result 1 2412MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18713.150000	46.8	160.0	H	237.0	10.4	27.20	74.00	
19749.725000	47.5	149.0	H	289.0	10.8	26.50	74.00	
20915.925000	47.8	176.0	V	176.0	11.1	26.20	74.00	
22033.675000	47.7	100.0	V	192.0	11.3	26.30	74.00	
24303.600000	47.7	118.0	V	239.0	11.5	26.30	74.00	
25682.725000	48.0	100.0	H	15.0	11.7	26.00	74.00	

Final Result 2 2412MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18713.150000	33.6	160.0	H	237.0	10.4	20.40	54.00	
19749.725000	34.1	149.0	H	289.0	10.8	19.90	54.00	
20915.925000	34.3	176.0	V	176.0	11.1	19.70	54.00	
22033.675000	34.3	100.0	V	192.0	11.3	19.70	54.00	
24303.600000	34.5	118.0	V	239.0	11.5	19.50	54.00	
25682.725000	34.9	100.0	H	15.0	11.7	19.10	54.00	

Final Result 1 2437MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19520.225000	47.2	300.0	V	58.0	10.7	26.80	74.00	
20714.050000	47.7	249.0	V	124.0	11.1	26.30	74.00	
21999.250000	47.8	256.0	V	67.0	11.3	26.20	74.00	
23575.575000	47.5	156.0	V	71.0	11.4	26.50	74.00	
25106.000000	48.0	133.0	H	222.0	11.8	26.00	74.00	
26201.225000	49.2	237.0	V	76.0	12.5	24.80	74.00	

Final Result 2 2437MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19520.225000	33.9	300.0	V	58.0	10.7	20.10	54.00	
20714.050000	34.0	249.0	V	124.0	11.1	20.00	54.00	
21999.250000	34.3	256.0	V	67.0	11.3	19.70	54.00	
23575.575000	34.2	156.0	V	71.0	11.4	19.80	54.00	
25106.000000	35.1	133.0	H	222.0	11.8	18.90	54.00	
26201.225000	35.8	237.0	V	76.0	12.5	18.20	54.00	

Final Result 1 2462MHz 5MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19699.575000	50.5	205.0	V	94.0	10.8	23.50	74.00	
20693.225000	47.4	291.0	V	118.0	11.1	26.60	74.00	
21831.375000	47.4	285.0	V	138.0	11.2	26.60	74.00	
22977.175000	47.8	114.0	V	245.0	11.6	26.20	74.00	
24019.275000	48.2	256.0	H	248.0	11.4	25.80	74.00	
24994.650000	48.1	240.0	V	151.0	11.8	25.90	74.00	

Final Result 2 2462MHz 5MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19699.575000	39.5	205.0	V	94.0	10.8	14.50	54.00	
20693.225000	34.2	291.0	V	118.0	11.1	19.80	54.00	
21831.375000	34.3	285.0	V	138.0	11.2	19.70	54.00	
22977.175000	34.7	114.0	V	245.0	11.6	19.30	54.00	
24019.275000	34.6	256.0	H	248.0	11.4	19.40	54.00	
24994.650000	34.8	240.0	V	151.0	11.8	19.20	54.00	

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	Chinmay Shendurnikar

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 10MHz, 22dB, 2412

FCC Class B Radiated Sweep 1GHz-18GHz 3m PK AVG



— FCC Class B 3m_20 - - - - - FCC Class B 3m — Preview Result 1V-PK+
— Preview Result 1H-PK+ ◆ Final Result 1-PK+ ◆ Final Result 2-AVG

Final Result 1 2412MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2235.333333	48.8	100.0	V	149.0	0.0	25.20	74.00	
3215.666667	47.4	100.0	V	39.0	3.0	26.60	74.00	
4823.866667	51.1	355.0	V	290.0	5.5	22.90	74.00	
7235.033333	51.8	296.0	V	197.0	9.8	22.20	74.00	
14471.933333	56.6	239.0	V	71.0	19.8	17.40	74.00	
17456.566667	55.5	144.0	V	137.0	22.7	18.50	74.00	

Final Result 2 2412MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2235.333333	37.2	100.0	V	149.0	0.0	16.80	54.00	
3215.666667	42.2	100.0	V	39.0	3.0	11.80	54.00	
4823.866667	45.4	355.0	V	290.0	5.5	8.60	54.00	
7235.033333	41.3	296.0	V	197.0	9.8	12.70	54.00	
14471.933333	47.7	239.0	V	71.0	19.8	6.30	54.00	
17456.566667	42.1	144.0	V	137.0	22.7	11.90	54.00	

Final Result 1 2437MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2243.266667	45.0	100.0	V	131.0	0.1	29.00	74.00	
3249.100000	46.5	122.0	V	20.0	3.1	27.50	74.00	
4873.733333	51.3	100.0	V	298.0	5.6	22.70	74.00	
7310.400000	53.4	299.0	V	159.0	9.7	20.60	74.00	
9748.200000	54.7	247.0	V	253.0	13.8	19.30	74.00	
17058.766667	58.4	212.0	V	279.0	22.0	15.60	74.00	

Final Result 2 2437MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2243.266667	31.2	100.0	V	131.0	0.1	22.80	54.00	
3249.100000	40.8	122.0	V	20.0	3.1	13.20	54.00	
4873.733333	44.1	100.0	V	298.0	5.6	9.90	54.00	
7310.400000	42.6	299.0	V	159.0	9.7	11.40	54.00	
9748.200000	47.5	247.0	V	253.0	13.8	6.50	54.00	
17058.766667	46.6	212.0	V	279.0	22.0	7.40	54.00	

Final Result 1 2462MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2229.100000	46.7	100.0	V	154.0	0.0	27.30	74.00	
4923.600000	50.3	100.0	V	231.0	5.7	23.70	74.00	
7385.200000	55.5	302.0	H	110.0	9.9	18.50	74.00	
7385.766667	57.5	322.0	V	194.0	9.9	16.50	74.00	
9847.933333	57.8	283.0	V	254.0	14.0	16.20	74.00	
17234.433333	61.1	217.0	V	259.0	22.8	12.90	74.00	
17618.633333	56.0	202.0	V	324.0	23.2	18.00	74.00	

Final Result 2 2462MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
2229.100000	33.0	100.0	V	154.0	0.0	21.00	54.00	
4923.600000	42.8	100.0	V	231.0	5.7	11.20	54.00	
7385.200000	43.0	302.0	H	110.0	9.9	11.00	54.00	
7385.766667	46.1	322.0	V	194.0	9.9	7.90	54.00	
9847.933333	52.6	283.0	V	254.0	14.0	1.40	54.00	
17234.433333	51.5	217.0	V	259.0	22.8	2.50	54.00	
17618.633333	42.5	202.0	V	324.0	23.2	11.50	54.00	

Radiated Emission Test Report

Tested At:
Electro Magnetic Test, Inc.
1547 Plymouth Street
Mountain View, CA 94043
Tel. 650-965-4000
Fax. 650-965-3000


Common Information

Test Description:	FCC Class B Radiated Emissions
Operating Conditions:	Normal
Test Engineer:	David Vivanco

EUT Information

Company Name:	Skydio
EUT Name	Drone
Model Number:	SBEC1V1
Serial Number:	N/A
Comment:	Flat, Battery Facing Down, 10MHz, 22dB, 2412

FCC Class B Radiated Sweep 18GHz-26.5GHz 3m PK AVG



— FCC Class B 3m_20 - - - FCC Class B 3m — Preview Result 1V-PK+
— Preview Result 1H-PK+ ◆ Final Result 1-PK+ ◆ Final Result 2-AVG

Final Result 1 2412MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18763.725000	47.7	200.0	V	245.0	10.4	26.30	74.00	
19707.225000	47.7	193.0	V	211.0	10.8	26.30	74.00	
20867.050000	47.4	114.0	H	30.0	11.1	26.60	74.00	
22112.725000	47.7	271.0	H	241.0	11.2	26.30	74.00	
23214.325000	48.0	145.0	H	160.0	11.7	26.00	74.00	
25097.925000	48.9	249.0	H	212.0	11.8	25.10	74.00	

Final Result 2 2462MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18763.725000	33.8	200.0	V	245.0	10.4	20.20	54.00	
19707.225000	34.1	193.0	V	211.0	10.8	19.90	54.00	
20867.050000	34.3	114.0	H	30.0	11.1	19.70	54.00	
22112.725000	34.4	271.0	H	241.0	11.2	19.60	54.00	
23214.325000	34.8	145.0	H	160.0	11.7	19.20	54.00	
25097.925000	35.5	249.0	H	212.0	11.8	18.50	54.00	

Final Result 1 2437MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18638.350000	47.7	169.0	H	129.0	10.4	26.30	74.00	
19765.450000	47.6	300.0	V	214.0	10.8	26.40	74.00	
20671.975000	47.4	243.0	V	39.0	11.1	26.60	74.00	
22638.025000	48.8	206.0	V	6.0	11.7	25.20	74.00	
24526.725000	47.3	292.0	H	231.0	11.5	26.70	74.00	
25117.050000	48.2	300.0	H	142.0	11.8	25.80	74.00	

Final Result 2 2437MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
18638.350000	33.9	169.0	H	129.0	10.4	20.10	54.00	
19765.450000	34.1	300.0	V	214.0	10.8	19.90	54.00	
20671.975000	34.2	243.0	V	39.0	11.1	19.80	54.00	
22638.025000	34.3	206.0	V	6.0	11.7	19.70	54.00	
24526.725000	33.9	292.0	H	231.0	11.5	20.10	54.00	
25117.050000	35.1	300.0	H	142.0	11.8	18.90	54.00	

Final Result 1 2462MHz 10MHz BW

Frequency (MHz)	MaxPeak (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19180.225000	46.9	100.0	V	20.0	10.5	27.10	74.00	
20933.350000	47.6	144.0	V	99.0	11.1	26.40	74.00	
21645.225000	47.9	260.0	V	119.0	11.1	26.10	74.00	
22197.300000	47.7	134.0	V	29.0	11.3	26.30	74.00	
23174.800000	47.4	233.0	H	244.0	11.7	26.60	74.00	
25082.625000	48.8	198.0	H	2.0	11.8	25.20	74.00	


Final Result 2 2462MHz 10MHz BW

Frequency (MHz)	Average (dBμV/m)	Height (cm)	Polarization	Azimuth (deg)	Corr. (dB)	Margin (dB)	Limit (dBμV/m)	Comment
19180.225000	33.7	100.0	V	20.0	10.5	20.30	54.00	
20933.350000	34.3	144.0	V	99.0	11.1	19.70	54.00	
21645.225000	34.3	260.0	V	119.0	11.1	19.70	54.00	
22197.300000	34.6	134.0	V	29.0	11.3	19.40	54.00	
23174.800000	34.5	233.0	H	244.0	11.7	19.50	54.00	
25082.625000	35.3	198.0	H	2.0	11.8	18.70	54.00	



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



FRONT VIEW

Skydio, Inc.

Drone

Model: SDRC2V1


CISPR 22/FCC Class B – Radiated Emissions (>1GHz)

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000



REAR VIEW

Skydio, Inc.

Drone

Model: SDRC2V1

CISPR 22/FCC Class B – Radiated Emissions (>1GHz)

**PHOTOGRAPH SHOWING THE EUT CONFIGURATION
FOR MAXIMUM EMISSIONS**


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

6/26 dB Bandwidth and Occupied Bandwidth Test

Company:	Skydio, Inc.			Test Date:		1/8/2020, 1/9/2020	
EUT Name:	Drone			Test Engineer:		Andreas Davidsson	
Model:	SDRC2V1			Test Result:		PASS	
Operating Mode:	TX Mode						
Mode	Antenna	Test CH	Frequency (MHz)	6 dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	6/26 dB Bandwidth Limit (MHz)	Conclusion
802.11 b (5MHz)	1	1	2412	2.049	3.2306	≥ 0.5	PASS
	2	1	2412	2.049	3.2300	≥ 0.5	PASS
	1	6	2437	2.048	3.2362	≥ 0.5	PASS
	2	6	2437	2.050	3.2336	≥ 0.5	PASS
	1	11	2462	2.049	3.2339	≥ 0.5	PASS
	2	11	2462	2.050	3.2272	≥ 0.5	PASS
802.11 b (10MHz)	1	1	2412	4.053	6.4686	≥ 0.5	PASS
	2	1	2412	4.053	6.4673	≥ 0.5	PASS
	1	6	2437	4.053	6.4837	≥ 0.5	PASS
	2	6	2437	4.053	6.4763	≥ 0.5	PASS
	1	11	2462	4.053	6.4754	≥ 0.5	PASS
	2	11	2462	4.054	6.4669	≥ 0.5	PASS
802.11 g (5MHz)	1	1	2412	2.047	3.1682	≥ 0.5	PASS
	2	1	2412	2.047	3.1778	≥ 0.5	PASS
	1	6	2437	2.047	3.1651	≥ 0.5	PASS
	2	6	2437	2.048	3.1503	≥ 0.5	PASS
	1	11	2462	2.047	3.1391	≥ 0.5	PASS
	2	11	2462	2.047	3.1448	≥ 0.5	PASS




802.11 g (10MHz)	1	1	2412	4.053	6.4052	≥ 0.5	PASS
	2	1	2412	4.052	6.3952	≥ 0.5	PASS
	1	6	2437	4.052	6.4331	≥ 0.5	PASS
	2	6	2437	4.052	6.4144	≥ 0.5	PASS
	1	11	2462	4.053	6.4393	≥ 0.5	PASS
	2	11	2462	4.053	6.4414	≥ 0.5	PASS
802.11 n (5MHz)	1	1	2412	2.048	3.2073	≥ 0.5	PASS
	2	1	2412	2.048	3.1506	≥ 0.5	PASS
	1	6	2437	2.048	3.1864	≥ 0.5	PASS
	2	6	2437	2.048	3.1550	≥ 0.5	PASS
	1	11	2462	2.048	3.1880	≥ 0.5	PASS
	2	11	2462	2.047	3.1539	≥ 0.5	PASS
802.11 n (10MHz)	1	1	2412	4.053	6.4645	≥ 0.5	PASS
	2	1	2412	4.052	6.4231	≥ 0.5	PASS
	1	6	2437	4.053	6.3959	≥ 0.5	PASS
	2	6	2437	4.053	6.4516	≥ 0.5	PASS
	1	11	2462	4.052	6.4406	≥ 0.5	PASS
	2	11	2462	4.052	6.4438	≥ 0.5	PASS
	Test Equipment: Please refer to section 5.2						


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Antenna 1 + 2
Channel 0 (2412 MHz)
(5MHz)





Antenna 1 + 2
Channel 6 (2437MHz)
(5MHz)





**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Antenna 1 + 2
Channel 11 (2462 MHz)
(5MHz)****Antenna 1 + 2
Channel 0 (2412 MHz)
(10MHz)**

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Antenna 1 + 2
Channel 6 (2437MHz)
(10MHz)****Antenna 1 + 2
Channel 11 (2462 MHz)
(10MHz)**


ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Peak Output Power Test Data

Company:	Skydio, Inc.			Test Date	1/8/2020,1/9/2020		
EUT Name	Drone			Test Engineer	Andreas Davidsson		
Model:	SDRC2V1			Test Result	PASS		
Operating Mode	TX Mode						
Mode	Antenna	Test CH	Frequency (MHz)	Raw Data (dBm)	Peak Output Power (dBm)	Limit (dBm)	Conclusion
802.11 b (5MHz)	1	1	2412	22.41	25.46	≤ 30	Pass
	2	1	2412	22.49			
	1	6	2437	22.80	25.65	≤ 30	Pass
	2	6	2437	22.48			
	1	11	2462	23.16	25.99	≤ 30	Pass
	2	11	2462	22.79			
802.11 b (10MHz)	1	1	2412	21.71	25.05	≤ 30	Pass
	2	1	2412	22.36			
	1	6	2437	22.06	24.97	≤ 30	Pass
	2	6	2437	21.86			
	1	11	2462	21.90	25.11	≤ 30	Pass
	2	11	2462	22.28			
802.11 g (5MHz)	1	1	2412	21.67	24.92	≤ 30	Pass
	2	1	2412	22.14			
	1	6	2437	21.64	24.88	≤ 30	Pass
	2	6	2437	22.09			
	1	11	2462	21.75	25.01	≤ 30	Pass
	1	11	2462	22.23			




802.11 g (10MHz)	1	1	2412	22.56	25.76	≤ 30	Pass
	2	1	2412	22.94			
	1	6	2437	23.08	26.00	≤ 30	Pass
	2	6	2437	22.89			
	1	11	2462	23.49	26.36	≤ 30	Pass
	1	11	2462	23.20			
802.11 n (5MHz)	1	1	2412	22.22	25.20	≤ 30	Pass
	2	1	2412	22.16			
	1	6	2437	22.15	25.14	≤ 30	Pass
	2	6	2437	22.12			
	1	11	2462	22.25	25.26	≤ 30	Pass
	1	1	2462	22.26			
802.11 n (10MHz)	1	1	2412	21.72	24.95	≤ 30	Pass
	2	1	2412	22.15			
	1	6	2437	22.21	24.91	≤ 30	Pass
	2	6	2437	21.56			
	1	11	2462	22.40	25.09	≤ 30	Pass
	1	1	2462	21.74			
	Test Equipment: Please refer to section 5.2						


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Antenna 1 + 2
Channel 0 (2412 MHz)
(5MHz)




Antenna 1 + 2
Channel 6 (2437MHz)
(5MHz)




**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Antenna 1 + 2
Channel 11 (2462 MHz)
(5MHz)




Antenna 1 + 2
Channel 0 (2412 MHz)
(10MHz)




**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Antenna 1 + 2
Channel 6 (2437MHz)
(10MHz)



Antenna 1 + 2
Channel 11 (2462 MHz)
(10MHz)




ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Maximum Power Spectral Density Test Data

Company:	Skydio, Inc.			Test Date	1/8/2020,1/9/2020		
EUT Name	Drone			Test Engineer	Andreas Davidsson		
Model:	SDRC2V1			Test Result	PASS		
Operating Mode	TX Mode						
Mode	Antenna	Test CH	Frequency (MHz)	Raw Peak (dBm)	Corrected PSD (dBm)	Limit (dBm)	Conclusion
802.11 b (5MHz)	1	1	2412	3.849	6.60	≤ 8	Pass
	2	1	2412	3.307			
	1	6	2437	4.823	7.73	≤ 8	Pass
	2	6	2437	4.609			
	1	11	2462	4.753	7.71	≤ 8	Pass
	2	11	2462	4.637			
802.11 b (10MHz)	1	1	2412	2.42	5.56	≤ 8	Pass
	2	1	2412	2.68			
	1	6	2437	2.72	5.62	≤ 8	Pass
	2	6	2437	2.51			
	1	11	2462	2.78	5.77	≤ 8	Pass
	2	11	2462	2.74			
802.11 g (5MHz)	1	1	2412	3.20	6.12	≤ 8	Pass
	2	1	2412	3.02			
	1	6	2437	3.08	5.95	≤ 8	Pass
	2	6	2437	2.80			
	1	11	2462	3.11	5.93	≤ 8	Pass
	2	11	2462	2.71			




802.11 g (10MHz)	1	1	2412	0.505	3.77	≤ 8	Pass
	2	1	2412	1.002			
	1	6	2437	1.037	4.25	≤ 8	Pass
	2	6	2437	1.429			
	1	11	2462	1.596	4.51	≤ 8	Pass
	2	11	2462	1.397			
802.11 n (5MHz)	1	1	2412	2.67	5.59	≤ 8	Pass
	2	1	2412	2.50			
	1	6	2437	3.03	5.93	≤ 8	Pass
	2	6	2437	2.81			
	1	11	2462	3.03	6.13	≤ 8	Pass
	2	11	2462	3.20			
802.11 n (10MHz)	1	1	2412	2.52	5.48	≤ 8	Pass
	2	1	2412	2.42			
	1	6	2437	2.71	5.59	≤ 8	Pass
	2	6	2437	2.44			
	1	11	2462	2.45	5.53	≤ 8	Pass
	2	11	2462	2.59			
	Test Equipment: Please refer to 5.2						


**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

Antenna 1 + 2
Channel 0 (2412 MHz)
(5MHz)





Antenna 1 + 2
Channel 6 (2437MHz)
(5MHz)





**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Antenna 1 + 2
Channel 11 (2462 MHz)
(5MHz)****Antenna 1 + 2
Channel 0 (2412 MHz)
(10MHz)**

**ELECTRO MAGNETIC TEST, INC.**

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

**Antenna 1 + 2
Channel 6 (2437MHz)
(10MHz)****Antenna 1 + 2
Channel 11 (2462 MHz)
(10MHz)**



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX B

TEST SETUP DIAGRAMS



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000




FIGURE 1 – TABLETOP CONDUCTED EMISSIONS TEST SETUP – SITE “D”




FIGURE 1a – FLOORSTANDING CONDUCTED EMISSIONS TEST SETUP – SITE “D”



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000




FIGURE 2 - PLOT MAP AND LAYOUT OF TEST SITE "A"




FIGURE 3 - LAYOUT OF 5 METER SEMI-ANECHOIC CHAMBER



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX C

MODIFICATIONS TO THE EUT



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

MODIFICATIONS TO THE EUT

No modifications were made to the EUT by Electro Magnetic Test, Inc. personnel during the testing.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

APPENDIX D

ADDITIONAL MODELS COVERED UNDER THIS REPORT



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

ADDITIONAL MODELS COVERED UNDER THIS REPORT

There are no additional models to be covered under this report.



ELECTRO MAGNETIC TEST, INC.

1547 Plymouth Street, Mountain View, CA 94043 Tel: (650) 965-4000 Fax: (650) 965-3000

End of Report

This page is intentionally left blank
and marks the last page of this report