


Test report No:
2150775R-RF-US-P06V02

FCC & ISED TEST REPORT

Product Name	VR All-In-One Headset
Trademark	
Model and /or type reference	HMD Model:A7H10
FCC ID	2ATRW-A7H10-1
IC	25707-A7H10-1
Applicant's name / address	Qingdao Pico Technology Co., Ltd. 4 Floor, 3 Building, No. 393 Songling Road, Laoshan District, Qingdao, China
Test method requested, standard	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10: 2013 KD558074 D01 15.247 Meas Guidance v05r02 RSS-Gen Issue 5 RSS-247 Issue 2
Verdict Summary	IN COMPLIANCE
Tested by (name / position & signature)	Tim Cao/Project Manager 
Approved by (name / position & signature)	Jack Zhang/ Manager 
Date of issue	2023-07-15
Report Version	V2.0
Report template No	Template_FCC 15.247-RF-V1.0

INDEX

	page
General conditions	4
Environmental conditions	4
Possible test case verdicts	5
Abbreviations.....	5
Document History.....	6
Remarks and Comments	6
Used Equipment.....	7
Uncertainty	9
1 General Information	10
1.1 General Description of the Item(s).....	10
1.2 Antenna Information	11
1.3 Channel List.....	12
2 Description of Test Setup.....	13
2.1 Operating mode(s) used for tests	13
2.2 Auxiliary equipment / Test software for the EUT	13
2.3 Test Configuration / Block diagram used for tests.....	14
2.4 Testing process	15
3 Verdict summary section.....	16
3.1 Standards	16
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	16
3.3 Overview of results	17
3.4 Test Facility.....	18
4 Test Results	19
4.1 AC Power Line Conducted Emission.....	19
4.1.1 Limit	19
4.1.2 Test Setup	19
4.1.3 Test Procedure	19
4.1.4 Test Data	20
4.2 Emissions in restricted frequency bands	22
4.2.1 Limit	22
4.2.2 Test Setup	24
4.2.3 Test Procedure	25
4.2.4 Test Data	26
4.3 Emissions in non-restricted frequency band	54

4.3.1	Limit	54
4.3.2	Test Setup	54
4.3.3	Test Procedure	54
4.3.4	Test Data	55
4.4	Duty cycle	59
4.4.1	Limit	59
4.4.2	Test Setup	59
4.4.3	Test Procedure	59
4.4.4	Test Data	60
4.5	Band Edge	61
4.5.1	Limit	61
4.5.2	Test Setup	61
4.5.3	Test Procedure	61
4.5.4	Test Procedure	62
4.5.5	Test Data	63
4.6	DTS Bandwidth	95
4.6.1	Limit	95
4.6.2	Test Setup	95
4.6.3	Test Procedure	95
4.6.4	Test Data	96
4.7	Fundamental emission output power	97
4.7.1	Limit	97
4.7.2	Test Setup	97
4.7.3	Test Procedure	98
4.7.4	Test Data	99
4.8	Power Density	100
4.8.1	Limit:	100
4.8.2	Test Setup	100
4.8.3	Test Procedure	100
4.8.4	Test Data	101
4.9	Antenna Requirement	102
4.9.1	Limit:	102
4.9.2	Antenna Connector Construction:	102
5	Test setup photo and EUT Photo	103

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	May. 24, 2021
Date (start test)	May. 24, 2021
Date (finish test)	July. 22, 2021

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2150775R-RF-US-P06V02	V1.0	Initial issue of report.	2021-07-09
2150775R-RF-US-P06V02	V1.1	Page 77-78,for Emissions in non-restricted frequency band, added test data.	2021-07-22
2150775R-RF-US-P06V02	V2.0	Page 1,10: Update FCC ID and IC number, also update hardware version, software version and firmware version.	2023-07-15

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with Part 15 Subpart C Paragraph 15.247, RSS-Gen Issue 5, RSS-247 Issue 2.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Antenna Information;
 - Chapter 1.3 Channel List.

USED EQUIPMENT

AC Power Line Conducted Emission / TR1

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMI Test Receiver	R&S	ESCI	100906	2021.04.28	2022.04.27
Two-Line V-Network	R&S	ENV216	101044	2021.03.20	2022.03.19
50ohm Termination	SHX	TF2	7081402	2020.09.23	2021.09.22
50ohm Termination	SHX	TF2	7081403	2020.09.23	2021.09.22
50ohm Coaxial Switch	Anritsu	MP59B	6200464462	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	TR1-TH	2020.08.23	2021.08.22
Dekra test software	Dekra	-	-	-	-

Emissions in non-restricted frequency bands/ Occupied Bandwidth/ Fundamental emission output power/ Power Spectral Density/Band Edge/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
Spectrum Analyzer	Agilent	N9010A	MY48030494	2020.08.15	2021.08.14
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2021.03.20	2022.03.19
MXA Signal Analyzer	Keysight	N9020A	MY56060147	2020.08.15	2021.08.14
4TX MIMO Power Sensor	Keysight	X8750A	MY59400102	2021.02.11	2022.02.10
Coaxial Cable	Woken	SFL402	F02-150410-044	2021.01.01	2021.12.31
Temperature/Humidity Meter	RTS	RTS-8S	RF08	2020.08.13	2021.08.12

Radiated Emission(30MHz-1GHz) / AC3

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EMI Test Receiver	R&S	ESCI	100176	2020.08.15	2021.08.14
Loop Antenna	R&S	HFH2-Z2	833799/003	2021.03.04	2022.03.03
Bilog Antenna	Teseq GmbH	CBL6112D	27613	2020.08.19	2021.08.18
Coaxial Cable	Huber+Suhner	RG 214	AC3-C	2021.03.31	2022.03.30
Temperature/Humidity Meter	RTS	RTS-8S	AC3-TH	2020.08.13	2021.08.12
Dekra test software	Dekra	-	-	-	-

Radiated Emission(1GHz-40GHz) / AC5

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date
EXA Spectrum Analyzer	Keysight	N9010A	MY55370495	2021.03.20	2022.03.19
Amplifier	Keleto	LNPA	SK20190225	2020.09.25	2021.09.24
Preamplifier	EMCI	EMC184045SE	980263	2021.05.24	2022.05.23
DRG Horn Antenna	ETS-Lindgren	3117	00167055	2020.08.06	2021.08.05
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	294	2021.04.14	2023.04.13
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC5-C2	2021.03.31	2022.03.30
Coaxial Cable	ROSENBERGER	LA1-C011- 2000/3000	AC5-40G	2021.03.20	2022.03.19
Temperature/Humidity Meter	RTS	RTS-8S	AC5-TH	2020.08.13	2021.08.12
Dekra test software	Dekra	-	-	-	-

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%. The Uncertainties is comply with standard required as below.

Test item	Uncertainty
AC Power Line Conducted Emission	9kHz~150kHz: 2.80dB 150kHz~30MHz: 2.40dB
Peak Power Output	± 1.27 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 3.50 dB 300MHz~1GHz: 3.60 dB Vertical: 30MHz~200MHz: 3.60 dB 300MHz~1GHz: 3.50 dB
Radiated Emission(1GHz~26.5GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB
RF antenna conducted test	± 1.27 dB
Radiated Emission Band Edge	± 3.9 dB
DTS Bandwidth	± 150 Hz
Occupied Bandwidth	± 1 kHz
Power Density	± 1.27 dB

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name	VR All-In-One Headset
Model No.	HMD Model:A7H10
Hardware Version.	R4
Software Version.	5.9.0.0
Firmware Version.	5.9.0.0
FCC ID	2ATRW-A7H10-1
IC	25707-A7H10-1
Manufacturer	Qingdao Pico Technology Co., Ltd.
Manufacturer Address	4 Floor, 3 Building, No. 393 Songling Road, Laoshan District, Qingdao, China
Test Sample SN	#1

Wireless specification..... :	Bluetooth 5.0					
Operating frequency range(s) :	2400~2483.5MHz					
Type of Modulation..... :	GFSK					
PHYs :	☒	LE 1M	☒	LE 2M	☐	LE Coded S=2/8
Data Rate :	☒	1Mbit/s	☒	2Mbit/s	☐	500/125 Kbit/s
Number of channel..... :	40					

Rated power supply	Voltage and Frequency				
	☐	AC: 220 – 240 V, 50/60 Hz			
	☐	AC: 100 – 240 V, 50/60 Hz			
	☐	DC: 3.85 Vdc			
	☒	Battery: ...3.85Vdc...			
	☒	Adapter: Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 3A/9V, 2A/12V, 1.5A			
Mounting position	☐	Table top equipment			
	☐	Wall/Ceiling mounted equipment			
	☐	Floor standing equipment			
	☒	Head-mounted equipment			
	☐	Other: Watch			

1.2 Antenna Information

Antenna Delivery	☒	1TX + 1RX		
	☐	2TX + 2RX		
Antenna technology	☒	SISO		
	☐	MIMO	☐	CDD
			☐	Beam-forming
Antenna Type	☐	External	☐	Dipole
			☐	Sectorized
	☒	Internal	☒	FPC
			☐	Chip
			☐	Metal Monopole Antenna
			☐	Others.....
Antenna Gain	5.12 dBi			

1.3 Channel List

Bluetooth Working Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

Note: The general description of the Item(s), antenna information and channel list in clause 1 are provided and confirmed by the client.

2 DESCRIPTION OF TEST SETUP

2.1 Operating mode(s) used for tests

During the tests the following operating mode(s) has(have) been used.


Test Mode For Bluetooth	Mode1: Transmit by LE_1Mbps
	Mode2: Transmit by LE_2Mbps
	Mode3: Transmit by LE_Code S=8
	Mode4: Transmit by LE_Code S=2

2.2 Auxiliary equipment / Test software for the EUT


Auxiliary equipment	Type / Version	Manufacturer	Supplied by
Notebook	2526	Think Pad	N/A
Software	Type / Version	Manufacturer	Supplied by
QDART	qdart_conn.win.1.0_installer_00065.1	Qualcomm	N/A

2.3 Test Configuration / Block diagram used for tests

Test setup Diagram- AC Line Conducted Emission Test



Test setup Diagram- Radiated Emission



2.4 Testing process

1	Setup the EUT as shown in Section 2.3
2	Execute the test program.
3	Configure the test mode and test channel.
4	Verify that the EUT works properly.

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
FCC CFR Title 47 Part 15 Subpart C Section 15.247	2021	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
KDB558074 D01 v05r02	2019	Guidance for performing compliance measurements on Digital Transmission System (DTS) operating under section 15.247
RSS-Gen Issue 5 Amendment 2	2021	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 2	2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

For FCC

Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	FCC 15.207	PASS	---
Emissions in restricted frequency bands	FCC 15.247(b)(3)	PASS	---
Duty cycle	ANSI C63.10:2013	PASS	---
Emissions in non-restricted frequency bands	FCC 15.247(d), FCC 15.209	PASS	---
Band Edge	FCC 15.247(d)	PASS	---
Fundamental emission output power	FCC 15.247(d), FCC 15.209	PASS	---
DTS Bandwidth	FCC 15.247(a)(2)	PASS	---
Power Spectral Density	FCC 15.247(e)	PASS	---
Antenna Requirement	FCC 15.203	PASS	---

For ISED

Requirement – Test case	Basic standard(s)	Verdict	Remark
AC Power Line Conducted Emission	RSS-Gen Issue 5 Section 8.8	PASS	---
Emissions in restricted frequency bands	RSS-Gen Issue 5 Section 8.9	PASS	---
Duty cycle	ANSI C63.10:2013	PASS	---
Emissions in non-restricted frequency bands	RSS-247 Issue 2 Section 5.5	PASS	---
Band Edge	RSS-Gen Issue 5 Section 8.10	PASS	---
Fundamental emission output power	RSS-247 Issue 2 Section 5.4(d)	PASS	---
DTS Bandwidth	RSS-Gen Issue 5 Section 6.7	PASS	---
Power Spectral Density	RSS-247 Issue 2 Section 5.2(b)	PASS	---
Antenna Requirement	RSS-Gen Issue 5 Section 6.8	PASS	---

3.4 Test Facility

USA	:	FCC Designation Number: CN1199
CA	:	ISED CAB identifier: CN0040

4 TEST RESULTS

4.1 AC Power Line Conducted Emission

VERDICT: PASS

4.1.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.207	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾]	Limit: AV [dB(μV) ¹⁾]
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50


¹⁾ At the transition frequency, the lower limit applies.

²⁾ The limit decreases linearly with the logarithm of the frequency.

NOTE 1: The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.

NOTE 2: Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.

4.1.2 Test Setup



4.1.3 Test Procedure

	References Rule	Chapter	Item
☒	ANSI C63.10-2013	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.1.4 Test Data

Engineer: Tongben

Site: TR1

Time: 2021/06/16

Limit: FCC_Part15.207_CE_AC Power_ClassB

Margin: 0


Probe: ENV216_101189(0.009-30MHz)

Polarity: Line

EUT: VR All-In-One Headset

Power: AC 120V/60Hz

Note: Simultaneous transmission with BT + 5G WIFI



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.298	24.074	14.394	-36.210	60.284	9.646	0.034	0.000	QP
2		0.298	19.709	10.029	-30.575	50.284	9.646	0.034	0.000	AV
3		0.510	30.756	21.074	-25.244	56.000	9.640	0.042	0.000	QP
4		0.510	17.863	8.181	-28.137	46.000	9.640	0.042	0.000	AV
5		0.899	22.005	12.309	-33.995	56.000	9.640	0.055	0.000	QP
6		0.899	17.112	7.417	-28.888	46.000	9.640	0.055	0.000	AV
7		9.902	23.651	13.683	-36.349	60.000	9.768	0.199	0.000	QP
8		9.902	14.334	4.367	-35.666	50.000	9.768	0.199	0.000	AV
9		19.201	33.723	23.478	-26.277	60.000	9.964	0.281	0.000	QP
10	*	19.201	26.065	15.820	-23.935	50.000	9.964	0.281	0.000	AV
11		24.900	23.650	13.182	-36.350	60.000	10.147	0.321	0.000	QP
12		24.900	13.810	3.342	-36.190	50.000	10.147	0.321	0.000	AV

Note:

1. " * ", means this data is the worst emission level.

2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

Engineer: Tongben

Site: TR1

Time: 2021/06/16

Limit: FCC_Part15.207_CE_AC Power_ClassB

Margin: 0


Probe: ENV216_101189(0.009-30MHz)

Polarity: Neutral

EUT: VR All-In-One Headset

Power: AC 120V/60Hz

Note: Simultaneous transmission with BT + 5G WIFI



No	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Probe (dB)	Cable (dB)	Amp (dB)	Type
1		0.301	18.814	9.160	-41.408	60.222	9.620	0.034	0.000	QP
2		0.301	15.540	5.885	-34.683	50.222	9.620	0.034	0.000	AV
3		0.510	23.964	14.303	-32.036	56.000	9.620	0.042	0.000	QP
4		0.510	11.206	1.545	-34.794	46.000	9.620	0.042	0.000	AV
5		2.101	16.256	6.536	-39.744	56.000	9.632	0.088	0.000	QP
6		2.101	12.469	2.749	-33.531	46.000	9.632	0.088	0.000	AV
7		10.198	22.266	12.280	-37.734	60.000	9.784	0.202	0.000	QP
8		10.198	15.235	5.249	-34.765	50.000	9.784	0.202	0.000	AV
9		18.899	30.015	19.828	-29.985	60.000	9.909	0.278	0.000	QP
10	*	18.899	21.892	11.705	-28.108	50.000	9.909	0.278	0.000	AV
11		24.601	23.766	13.297	-36.234	60.000	10.150	0.319	0.000	QP
12		24.601	15.089	4.621	-34.911	50.000	10.150	0.319	0.000	AV

Note:

1. " * ", means this data is the worst emission level.
2. Measurement Level = Reading Level + Factor(Probe+Cable-Amp).

4.2 Emissions in restricted frequency bands**VERDICT: PASS****4.2.1 Limit****Standard** FCC Part 15 Subpart C Paragraph 15.209

Restricted Bands of operationfor FCC

Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Bands of operationfor IC

0.090 - 0.110	13.36 - 13.41	960 - 1427	9.0 - 9.2
0.495 - 0.505	16.42 - 16.423	1435 - 1626.5	9.3 - 9.5
2.1735 - 2.1905	16.69475 - 16.69525	1645.5 - 1646.5	10.6 - 12.7
3.020 - 3.026	16.80425 - 16.80475	1660 - 1710	13.25 - 13.4
4.125 - 4.128	25.5 - 25.67	1718.8 - 1722.2	14.47 - 14.5
4.17725 - 4.17775	37.5 - 38.25	2200 - 2300	15.35 - 16.2
4.20725 - 4.20775	73 - 74.6	2310 - 2390	17.7 - 21.4
5.677 - 5.683	74.8 - 75.2	2483.5 - 2500	22.01 - 23.12
6.215 - 6.218	108 - 138	2655 - 2900	23.6 - 24.0
6.26775 - 6.26825	149.9 - 150.05	3260 - 3267	31.2 - 31.8
6.31175 - 6.31225	156.52475 - 156.52525	3332 - 3339	36.43 - 36.5
8.291 - 8.294	156.7 - 156.9	3345.8 - 3358	Above 38.6
8.362 - 8.366	162.0125 - 167.17	3500 - 4400	
8.37625 - 8.38675	167.72 - 173.2	4500 - 5150	
8.81425 - 8.81475	240 - 285	5350 - 5460	
12.29 - 12.293	322 - 335.4	7250 - 7750	
12.51975 - 12.52025	399.9 - 410	8025 - 8500	
12.57675 - 12.57725	608 - 614	--	

Restricted Band Emissions Limit

Frequency (MHz)	Field strength (μ V/m)	Field strength (dB μ V/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88-216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)


Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment.


Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.2.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:




4.2.3 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	11.12.2.7	Radiated spurious emission test
		☒ ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
		☒ ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
		☒ ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz


4.2.4 Test Data

Profile: 2150755R	Page No.: 67
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.399	42.442	-36.601	74.000	-5.044	PK
2		7206.000	39.846	40.892	-34.154	74.000	-1.046	PK
3	*	9608.000	40.448	37.618	-33.552	74.000	2.830	PK

Profile: 2150755R	Page No.: 68
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.892	42.935	-36.108	74.000	-5.044	PK
2		7206.000	39.819	40.865	-34.181	74.000	-1.046	PK
3	*	9608.000	41.393	38.563	-32.607	74.000	2.830	PK

Profile: 2150755R	Page No.: 69
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	37.845	42.672	-36.155	74.000	-4.827	PK
2		7320.000	40.759	41.652	-33.241	74.000	-0.893	PK
3	*	9760.000	41.056	38.058	-32.944	74.000	2.998	PK

Profile: 2150755R	Page No.: 70
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2440MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	36.901	41.728	-37.099	74.000	-4.827	PK
2		7320.000	39.619	40.512	-34.381	74.000	-0.893	PK
3	*	9760.000	41.189	38.191	-32.811	74.000	2.998	PK

Profile: 2150755R	Page No.: 71
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	37.562	42.224	-36.438	74.000	-4.662	PK
2		7440.000	39.006	40.049	-34.994	74.000	-1.043	PK
3	*	9920.000	41.470	38.423	-32.530	74.000	3.047	PK

Profile: 2150755R	Page No.: 72
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	37.708	42.370	-36.292	74.000	-4.662	PK
2		7440.000	39.461	40.504	-34.539	74.000	-1.043	PK
3	*	9920.000	41.328	38.281	-32.672	74.000	3.047	PK

Profile: 2150755R	Page No.: 73
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	39.051	44.094	-34.949	74.000	-5.044	PK
2		7206.000	40.801	41.847	-33.199	74.000	-1.046	PK
3	*	9608.000	41.718	38.888	-32.282	74.000	2.830	PK

Profile: 2150755R	Page No.: 74
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.486	42.529	-36.514	74.000	-5.044	PK
2		7206.000	40.173	41.219	-33.827	74.000	-1.046	PK
3	*	9608.000	40.625	37.795	-33.375	74.000	2.830	PK

Profile: 2150755R	Page No.: 75
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2440MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	38.245	43.072	-35.755	74.000	-4.827	PK
2	*	7320.000	40.045	40.938	-33.955	74.000	-0.893	PK
3		9760.000	39.766	36.768	-34.234	74.000	2.998	PK

Profile: 2150755R	Page No.: 76
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2440MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	37.616	42.443	-36.384	74.000	-4.827	PK
2		7320.000	40.226	41.119	-33.774	74.000	-0.893	PK
3	*	9760.000	41.197	38.199	-32.803	74.000	2.998	PK

Profile: 2150755R	Page No.: 77
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:27
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	37.884	42.546	-36.116	74.000	-4.662	PK
2		7440.000	40.624	41.667	-33.376	74.000	-1.043	PK
3	*	9920.000	41.856	38.809	-32.144	74.000	3.047	PK

Profile: 2150755R	Page No.: 78
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	38.972	43.634	-35.028	74.000	-4.662	PK
2		7440.000	41.432	42.475	-32.568	74.000	-1.043	PK
3	*	9920.000	42.066	39.019	-31.934	74.000	3.047	PK

Profile: 2150755R	Page No.: 79
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	36.978	42.021	-37.022	74.000	-5.044	PK
2		7206.000	40.980	42.026	-33.020	74.000	-1.046	PK
3	*	9608.000	41.744	38.914	-32.256	74.000	2.830	PK

Profile: 2150755R	Page No.: 80
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.699	42.742	-36.301	74.000	-5.044	PK
2		7206.000	40.990	42.036	-33.010	74.000	-1.046	PK
3	*	9608.000	41.913	39.083	-32.087	74.000	2.830	PK

Profile: 2150755R	Page No.: 81
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2440MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	38.610	43.437	-35.390	74.000	-4.827	PK
2		7320.000	39.299	40.192	-34.701	74.000	-0.893	PK
3	*	9760.000	41.205	38.207	-32.795	74.000	2.998	PK

Profile: 2150755R	Page No.: 82
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2440MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	39.263	44.090	-34.737	74.000	-4.827	PK
2		7320.000	40.903	41.796	-33.097	74.000	-0.893	PK
3	*	9760.000	41.722	38.724	-32.278	74.000	2.998	PK

Profile: 2150755R	Page No.: 83
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	36.195	40.857	-37.805	74.000	-4.662	PK
2		7440.000	39.980	41.023	-34.020	74.000	-1.043	PK
3	*	9920.000	42.617	39.570	-31.383	74.000	3.047	PK

Profile: 2150755R	Page No.: 84
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2480MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	37.987	42.649	-36.013	74.000	-4.662	PK
2		7440.000	40.485	41.528	-33.515	74.000	-1.043	PK
3	*	9920.000	41.099	38.052	-32.901	74.000	3.047	PK

Profile: 2150755R	Page No.: 85
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2402MHz by LE_Code S=2	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.017	42.060	-36.983	74.000	-5.044	PK
2		7206.000	40.181	41.227	-33.819	74.000	-1.046	PK
3	*	9608.000	40.862	38.032	-33.138	74.000	2.830	PK

Profile: 2150755R	Page No.: 86
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2402MHz by LE_Code S=2	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	37.431	42.474	-36.569	74.000	-5.044	PK
2	*	7206.000	41.682	42.728	-32.318	74.000	-1.046	PK
3		9608.000	41.106	38.276	-32.894	74.000	2.830	PK

Profile: 2150755R	Page No.: 87
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2440MHz by LE_Code S=2	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	37.829	42.656	-36.171	74.000	-4.827	PK
2		7320.000	39.513	40.406	-34.487	74.000	-0.893	PK
3	*	9760.000	40.309	37.311	-33.691	74.000	2.998	PK

Profile: 2150755R	Page No.: 88
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2440MHz by LE_Code S=2	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4880.000	38.545	43.372	-35.455	74.000	-4.827	PK
2	*	7320.000	40.385	41.278	-33.615	74.000	-0.893	PK
3		9760.000	40.346	37.348	-33.654	74.000	2.998	PK

Profile: 2150755R	Page No.: 89
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:28
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2480MHz by LE_Code S=2	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	36.476	41.138	-37.524	74.000	-4.662	PK
2		7440.000	40.269	41.312	-33.731	74.000	-1.043	PK
3	*	9920.000	41.874	38.827	-32.126	74.000	3.047	PK

Profile: 2150755R	Page No.: 90
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 19:29
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 4:Transmit at 2480MHz by LE_Code S=2	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4960.000	36.889	41.551	-37.111	74.000	-4.662	PK
2		7440.000	40.106	41.149	-33.894	74.000	-1.043	PK
3	*	9920.000	41.337	38.290	-32.663	74.000	3.047	PK

Note:

1. Measured Level = Reading Level + Factor.
2. The test frequency range, 9kHz~30MHz, 18GHz~26GHz, both of the worst case are at least 20dB below the limits, therefore no data appear in the report.
3. This limit applies for using average detector, if the test result on peak is lower than average limit, then average measurement needn't be performed.
4. As the radiated emission was performed, so conducted emission was not tested.


The worst case of Radiated Emission below 1GHz:

Profile: 2150775R	Page No.: 13
Engineer: wangyingfei	
Site: AC2	Time: 2021/06/15 - 22:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Simultaneous transmission with BT + 5G WIFI	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		37.033	18.169	-6.437	-21.831	40.000	24.606	200	217	QP
2		102.144	11.015	-5.529	-32.485	43.500	16.543	100	108	QP
3		136.821	12.949	-4.602	-30.551	43.500	17.551	200	197	QP
4		224.849	13.574	-5.017	-32.426	46.000	18.591	100	307	QP
5		365.135	18.641	-5.221	-27.359	46.000	23.862	100	55	QP
6	*	665.107	25.685	-3.572	-20.315	46.000	29.257	100	248	QP

Profile: 2150775R	Page No.: 14
Engineer: wangyingfei	
Site: AC2	Time: 2021/06/15 - 22:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: AC3_3m (30-1000MHz)	Polarity: Vertical
Note: Simultaneous transmission with BT + 5G WIFI	Power: AC 120V/60Hz
Note: Simultaneous transmission with BT + 5G WIFI	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Type
1		35.335	15.245	-6.948	-24.755	40.000	22.193	100	227	QP
2		104.569	14.442	-7.491	-29.058	43.500	21.934	100	169	QP
3		210.420	15.863	-7.358	-27.637	43.500	23.221	200	316	QP
4		280.503	18.429	-6.108	-27.571	46.000	24.537	200	127	QP
5		343.189	17.998	-5.623	-28.002	46.000	23.621	100	95	QP
6	*	698.088	24.167	-5.678	-21.833	46.000	29.846	200	268	QP

Note:

1. All Readings below 1GHz are Quasi-Peak, above are performed with peak and/or average measurements as necessary.
2. " * ", means this data is the worst emission level.
3. Measurement Level = Reading Level + Factor(Probe+Cable-Amp)


The worst case of Simultaneous Radiated Emission:

Profile: 2150775R	Page No.: 238
Engineer: Juliuszhou	
Site: AC5	Time: 2021/06/18 - 11:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Vertical
EUT: Touch All In One Computer	Power: AC 120V/60Hz
Note: Simultaneous transmission with BT + 5G WIFI	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	33.382	39.791	-40.618	74.000	-6.409	PK
2		4824.000	31.880	38.294	-42.120	74.000	-6.414	PK
3	*	7206.000	39.143	41.542	-34.857	74.000	-2.399	PK
4		7236.000	37.355	40.081	-36.645	74.000	-2.726	PK
5		9608.000	35.573	36.778	-38.427	74.000	-1.204	PK
6		9648.000	36.027	37.225	-37.973	74.000	-1.198	PK

Profile: 2150775R	Page No.: 239
Engineer: Juliuszhou	
Site: AC5	Time: 2021/06/18 - 11:54
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00167055(1-18GHz)	Polarity: Horizontal
EUT: Touch All In One Computer	Power: AC 120V/60Hz
Note: Simultaneous transmission with BT + 5G WIFI	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		4804.000	33.291	39.700	-40.709	74.000	-6.409	PK
2		4824.000	33.476	39.890	-40.524	74.000	-6.414	PK
3		7206.000	37.515	39.914	-36.485	74.000	-2.399	PK
4	*	7236.000	37.987	40.713	-36.013	74.000	-2.726	PK
5		9608.000	36.939	38.144	-37.061	74.000	-1.204	PK
6		9648.000	36.760	37.958	-37.240	74.000	-1.198	PK

4.3 Emissions in non-restricted frequency band

VERDICT: PASS


4.3.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d)
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).


4.3.2 Test Setup




4.3.3 Test Procedure

References Rule	Chapter	Description
☒ ANSI C63.10	11.11	Emissions in non-restricted frequency bands
☒ ANSI C63.10	11.11.1	General
☒ ANSI C63.10	11.11.2	Reference level measurement
☒ ANSI C63.10	11.11.3	Emission level measurement


Mode 3 CH00 (2402MHz)




Mode 3 CH39(2480MHz)




Mode 4 CH00 (2402MHz)




Mode 4 CH39(2480MHz)




Mode 1 CH00 (2402MHz)




Mode 1 CH39(2480MHz)




Mode 2 CH00 (2402MHz)




Mode 2 CH39(2480MHz)




Mode 3 CH00 (2402MHz)




Mode 3 CH39(2480MHz)



Mode 4 CH00 (2402MHz)



Mode 4 CH39(2480MHz)




4.4 Duty cycle

VERDICT: PASS

4.4.1 Limit

N/A

4.4.2 Test Setup



4.4.3 Test Procedure

References Rule		Chapter	Description
☒	ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level


4.4.4 Test Data

Test Mode	Tx On (us)	VBW (kHz)	Tx On + Tx Off (us)	Duty Cycle (%)
Mode 1	380	3	624	60.89
Mode 2	200	5	628	31.84
Mode 3	1060	1	1876	56.50
Mode 4	3080	1	3750	82.13


Note 1: T means the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

Note 2: According to KDB 558074, when test for Radiated Emission Band Edge and Radiated Emission, for average detector set: $VBW \geq 1/T$ will be used.


Mode 1 CH19 2440MHz




Mode 2 CH19 2440MHz



Mode 3 CH19 2440MHz




Mode 4 CH19 2440MHz



4.5 Band Edge**VERDICT: PASS****4.5.1 Limit**

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) ,15.209		
Frequency bands (MHz)	Detector	Limit (dB μ V/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.5.2 Test Setup**4.5.3 Test Procedure**


	References Rule	Chapter	Description
☒	ANSI C63.10	6.10	Band-edge testing
☒	☒ ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	☐ ANSI C63.10	6.10.6	Marker-delta method
☒	ANSI C63.10	11.12	Emissions in restricted frequency bands
☒	☒ ANSI C63.10	11.12.2	Antenna-port conducted measurements
	☐ ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
	☒ ANSI C63.10	11.12.2.4	Peak power measurement procedure
	☒ ANSI C63.10	11.12.2.5	Average power measurement procedures

4.5.4 Test Procedure

	References Rule		Chapter	Description
☒	ANSI C63.10		6.10	Band-edge testing
	☒	ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	☐	ANSI C63.10	6.10.6	Marker-delta method
☒	ANSI C63.10		11.12	Emissions in restricted frequency bands
	☒	ANSI C63.10	11.12.1	Radiated emission measurements
	☒	ANSI C63.10	6.3	Radiated spurious emission test
☐	ANSI C63.10		6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
☐	ANSI C63.10		6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
☒	ANSI C63.10		6.6	Radiated emissions from unlicensed wireless devices above 1 GHz
	☐	ANSI C63.10	11.12.2	Antenna-port conducted measurements
	☐	ANSI C63.10	11.12.2.3	Quasi-peak measurement procedure
		ANSI C63.10	11.12.2.4	Peak power measurement procedure
		ANSI C63.10	11.12.2.5	Average power measurement procedures
	☐	ANSI C63.10	11.12.2.5.1	Trace averaging with continuous EUT transmission at full power
		ANSI C63.10	11.12.2.5.2	Trace averaging across ON and OFF times of the EUT transmissions followed by duty cycle correction
		ANSI C63.10	11.12.2.5.3	Reduced VBW averaging across ON and OFF times of the EUT transmissions with max hold


4.5.5 Test Data

Profile: 2150707R	Page No.: 25
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:15
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2353.937	47.192	11.736	-6.808	54.000	35.456	AV
2		2390.000	38.724	3.265	-15.276	54.000	35.459	AV

Profile: 2150707R	Page No.: 26
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:19
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	50.741	15.282	-23.259	74.000	35.459	PK

Profile: 2150707R	Page No.: 27
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:21
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2353.937	44.678	9.222	-9.322	54.000	35.456	AV
2		2390.000	38.912	3.453	-15.088	54.000	35.459	AV

Profile: 2150707R	Page No.: 28
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:22
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2402MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	50.741	15.282	-23.259	74.000	35.459	PK

Profile: 2150707R	Page No.: 29
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:23
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		2483.500	39.145	3.470	-14.855	54.000	35.675	AV
2	*	2485.293	43.410	7.731	-10.590	54.000	35.679	AV

Profile: 2150707R	Page No.: 30
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:24
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	51.107	15.432	-22.893	74.000	35.675	PK

Profile: 2150707R	Page No.: 31
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:25
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	39.051	3.376	-14.949	54.000	35.675	AV

Profile: 2150707R	Page No.: 32
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:26
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 1:Transmit at 2480MHz by LE_1Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	51.556	15.881	-22.444	74.000	35.675	PK

Profile: 2150707R	Page No.: 33
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:33
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2354.032	47.178	11.723	-6.822	54.000	35.455	AV
2		2390.000	39.174	3.715	-14.826	54.000	35.459	AV

Profile: 2150707R	Page No.: 34
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:34
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	50.785	15.326	-23.215	74.000	35.459	PK

Profile: 2150707R	Page No.: 35
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:35
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2353.748	43.809	8.349	-10.191	54.000	35.459	AV
2		2390.000	39.348	3.889	-14.652	54.000	35.459	AV

Profile: 2150707R	Page No.: 36
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:36
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2402MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	51.550	16.091	-22.450	74.000	35.459	PK

Profile: 2150707R	Page No.: 37
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:38
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	39.825	4.150	-14.175	54.000	35.675	AV

Profile: 2150707R	Page No.: 38
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:39
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	52.588	16.913	-21.412	74.000	35.675	PK

Profile: 2150707R	Page No.: 39
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:41
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	39.766	4.091	-14.234	54.000	35.675	AV

Profile: 2150707R	Page No.: 40
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:42
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 2:Transmit at 2480MHz by LE_2Mbps	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2483.500	50.694	15.019	-23.306	74.000	35.675	PK

Profile: 2150707R	Page No.: 41
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:43
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2354.080	46.708	11.254	-7.292	54.000	35.454	AV
2		2390.000	38.014	2.555	-15.986	54.000	35.459	AV

Profile: 2150707R	Page No.: 42
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:46
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Horizontal
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	49.258	13.799	-24.742	74.000	35.459	PK

Profile: 2150707R	Page No.: 43
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:47
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2353.985	43.778	8.323	-10.222	54.000	35.456	AV
2		2390.000	37.864	2.405	-16.136	54.000	35.459	AV

Profile: 2150707R	Page No.: 44
Engineer: Juliuszhou	
Site: AC5	Time: 2021/05/23 - 18:48
Limit: FCC_Part15.209_RE(3m)	Margin: 0
Probe: Horn_3117_00123988_(1-18GHz)	Polarity: Vertical
EUT: VR All-In-One Headset	Power: AC 120V/60Hz
Note: Mode 3:Transmit at 2402MHz by LE_Code S=8	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1	*	2390.000	49.482	14.023	-24.518	74.000	35.459	PK