



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V04
Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No. : CQASZ20200200074E-02
Applicant: Trackerwave Private Limited
Address of Applicant: 4/363, Block C, 3rd Floor, OMR Road, Kanthanchavadi, Chennai, India – 600 096
Equipment Under Test (EUT):
EUT Name: BLE - Patient Wrist Band with Call Button
Mode No.: TWBL2
Brand Name: OVITAG
FCC ID: 2ATS5-TWBL2
Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-02-21
Date of Test: 2020-02-21 to 2020-02-25
Date of Issue: 2020-02-25
Test Result : **PASS***

* In the configuration tested, the EUT complied with the standards specified above.

Tested By: Tom Chen.
(Tom Chen)
Reviewed By: Aaron Ma
(Aaron Ma)
Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200200074E-02	Rev.01	Initial report	2020-02-25

2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i>	5
4.1.2 <i>Limits</i>	5
4.1.3 <i>EUT RF Exposure</i>	6

3 General Information

3.1 Client Information

Applicant:	Trackerwave Private Limited
Address of Applicant:	4/363, Block C, 3rd Floor, OMR Road, Kanthanchavadi, Chennai, India – 600 096
Manufacturer:	Shenzhen Minew Technologies Co., Ltd
Address of Manufacturer:	3 rd Floor, Bldg I, Gangzhilong Science Park, Qinglong Rd., Longhua Dist., Shenzhen 518109, China

3.2 General Description of EUT

Product Name:	BLE - Patient Wrist Band with Call Button
Model No.:	TWBL2
Trade Mark:	OVITAG
Hardware Version:	1.2
Software Version:	1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Type:	GFSK
Transfer Rate:	1Mbps/2Mbps
Number of Channel:	40
Product Type:	<input type="checkbox"/> Mobile <input checked="" type="checkbox"/> Portable <input type="checkbox"/> Fix Location
Test Software of EUT:	nRFgo Studio (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	-7.6dBi
EUT Power Supply:	button battery:DC3.0V

4 SAR Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

4.1.3 EUT RF Exposure

For BLE

Measurement Data

GFSK(1Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.32	-1.0±1	0	1.000
Middle(2440MHz)	-0.55	-1.0±1	0	1.000
Highest(2480MHz)	-0.42	-1.0±1	0	1.000
GFSK(2Mbps) mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-0.42	-1.0±1	0	1.000
Middle(2440MHz)	-0.65	-1.0±1	0	1.000
Highest(2480MHz)	-0.55	-1.0±1	0	1.000

Worst case: GFSK(1Mbps)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune- up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
Lowest (2402MHz)	-0.32	-1.0±1	0	1.000	0.310	3.0
Middle (2440MHz)	-0.55	-1.0±1	0	1.000	0.312	
Highest (2480MHz)	-0.42	-1.0±1	0	1.000	0.315	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

Remark: The Max Conducted Peak Output Power data refer to report Report No.: CQASZ20200200074E-01.