




Report No.:AGC03576190601FE04 Page 30 of 61

Test Graph
























11. RADIATED EMISSION

11.1. MEASUREMENT PROCEDURE


- 1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- 4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- 5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- 6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- 7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
- 8.If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
- 9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High Low scan is not required in this case.





11.2. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz





Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technial Industrial Park, Gushu,

11.3. LIMITS AND MEASUREMENT RESULT

15.209(a) Limit in the below table has to be followed

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note: All modes were tested For restricted band radiated emission,

the test records reported below are the worst result compared to other modes.





Report No.:AGC03576190601FE04 Page 35 of 61


11.4. TEST RESULT

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ) -HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		52.6333	-0.02	19.50	19.48	40.00	-20.52	peak			
2		156.1000	-0.35	19.20	18.85	43.50	-24.65	peak			
3		445.4833	1.28	23.89	25.17	46.00	-20.83	peak			
4		634.6332	0.93	27.37	28.30	46.00	-17.70	peak			
5		809.2333	1.11	30.53	31.64	46.00	-14.36	peak			
6	*	927.2500	2.16	31.93	34.09	46.00	-11.91	peak			

RESULT: PASS







RADIATED EMISSION TEST- (30MHZ-1GHZ) -VERTICAL

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		49.4000	-0.79	19.75	18.96	40.00	-21.04	peak			
2		154.4832	-0.40	19.20	18.80	43.50	-24.70	peak			
3		406.6833	0.01	23.11	23.12	46.00	-22.88	peak			
4		616.8500	0.58	27.15	27.73	46.00	-18.27	peak			
5	*	818.9333	0.85	30.65	31.50	46.00	-14.50	peak			
6		987.0667	1.88	32.45	34.33	54.00	-19.67	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin= Result -Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.

3. All test modes had been pre-tested. The 802.11b at low channel is the worst case and recorded in the report.





RADIATED EMISSION ABOVE 1GHZ

Frequency	Emission Level	Limits	Margin	Detector	Comment
(MHz)	(dBµV/m)	(dBµV/m)	(dB)	Туре	Comment
0		TX 11b 2412M	Ηz		
4824	49.17	74	-24.83	Pk	Horizontal
4824	35.55	54	-18.45	AV	Horizontal
7236	50.45	74	-23.55	pk	Horizontal
7236	34.51	54	-19.49	AV	Horizontal
4824	50.26	74	-23.74	Pk	Vertical
4824	34.77	54	-19.23	AV	Vertical
7236	50.50	74	-23.5	Pk	Vertical
7236	38.60	54	-15.40	AV	Vertical
		TX 11b 2437M	Ηz		SU.
4874	50.16	74	-23.84	Pk	Horizontal
4874	31.95	54	-22.05	AV	Horizontal
7311	46.63	74	-27.37	Pk	Horizontal
7311	34.88	54	-19.12	AV	Horizontal
4874	49.48	74	-24.52	Pk	Vertical
4874	40.45	54	-13.55	AV	Vertical
7311	47.72	74	-26.28	Pk	Vertical
7311	37.80	54	-16.20	AV	Vertical
	G ^C aC	TX 11b 2462MH	Hz	- 60	C
4924	50.32	74	-23.68	Pk	Horizontal
4924	33.72	54	-20.28	AV	Horizontal
7386	48.73	74	-25.27	Pk	Horizontal
7386	38.89	54	-15.11	AV	Horizontal
4924	50.15	74	-23.85	Pk	Vertical
4924	38.49	54	-15.51	AV	Vertical
7386	48.62	74	-25.38	Pk	Vertical
7386	36.50	54	-17.50	AV	Vertical

RESULT: PASS Note:

1. Margin = Emission Level - Limit

2.1GHz-25GHz(All test modes had been pre-tested. The 802.11b mode is the worst case and recorded in the report. No recording in the test report at least have 20dB margin).





12. BAND EDGE EMISSION

12.1. MEASUREMENT PROCEDURE

1)Radiated restricted band edge measurements

The radiated restricted band edge measurements are measured with an EMI test receiver connected to the receive antenna while the EUT is transmitting

2)Conducted Emissions at the bang edge

a)The transmitter output was connected to the spectrum analyzer

b)Set RBW=100kHz,VBW=300kHz

c)Suitable frequency span including 100kHz bandwidth from band edge

12.2. TEST SET-UP

Radiated same as 11.2

Note:


1. Factor=Antenna Factor + Cable loss - Amplifier gain. Field Strength=Factor + Reading level 2. The factor had been edited in the "Input Correction" of the Spectrum Analyzer. So the Amplitude of test plots is equal to Reading level plus the Factor in dB. Use the A dB(μ V) to represent the Amplitude. Use the F dB(μ V/m) to represent the Field Strength. So A=F.





12.3. TEST RESULT

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Horizontal



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 40 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2412MHZ	Antenna	Vertical

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 41 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Horizontal



AV



RESULT: PASS



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

ΡK



Report No.:AGC03576190601FE04 Page 42 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11b with data rate 1 2462MHZ	Antenna	Vertical

PK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 43 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Horizontal

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 44 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2412MHZ	Antenna	Vertical

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 45 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Horizontal

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 46 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11g with data rate 6 2462MHZ	Antenna	Vertical

PK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 47 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Horizontal



AV



RESULT: PASS



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

ΡK



Report No.:AGC03576190601FE04 Page 48 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2412MHZ	Antenna	Vertical

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 49 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Horizontal

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 50 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 20 with data rate 6.5 2462MHZ	Antenna	Vertical

PK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 51 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Horizontal

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 52 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2422MHZ	Antenna	Vertical

ΡK

ALIGN AUTO Avg Type: Log-Pwr Avg|Hold:>100/100 ker 1 2.417475000000 GHz Peak Search Trig: Free Run #Atten: 20 dB NextPe 1kr1 2.417 475 G 100.011 dBu\ Ref 106.00 dBµV/m Next Pk Righ Next Pk Let Marker Delt Start 2.37000 GHz #Res BW 1.0 MHz Stop 2.44500 GHz Sweep 1.000 ms (1001 pts) #VBW 3.0 MHz Mkr→C 2.417 475 GHz 100.011 dBµV 2.390 000 GHz 60.084 dBµV Mkr→RefL More 1 of 2





RESULT: PASS





Report No.:AGC03576190601FE04 Page 53 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40with data rate 13.5 2452MHZ	Antenna	Horizontal

ΡK



AV



RESULT: PASS





Report No.:AGC03576190601FE04 Page 54 of 61

EUT	Portable Translator	Model Name	HYP10
Temperature	25°C	Relative Humidity	55.4%
Pressure	960hPa	Test Voltage	Normal Voltage
Test Mode	802.11n 40 with data rate 13.5 2452MHZ	Antenna	Vertical

PK

Peak Sear 1 2.458000000000 GHz Avg Type: Log-Pwr Avg|Hold:>100/100 NextPe Mkr1 Ref 106.00 dBµV/m Next Pk Righ Next Pk Le Marker Delt Start 2.43000 GHz #Res BW 1.0 MHz 0 GHz #VBW 3.0 MHz Mkr→C Sweep 2.458 00 GHz 100.520 dBµV 2.483 50 GHz 66.419 dBµV Mkr→RefL Mor





RESULT: PASS



13. FCC LINE CONDUCTED EMISSION TEST

13.1. LIMITS OF LINE CONDUCTED EMISSION TEST


Francisco	Maximum RF Line Voltage					
Frequency	Q.P.(dBuV)	Average(dBuV)				
150kHz~500kHz	66-56	56-46				
500kHz~5MHz	56	46				
5MHz~30MHz	60	50				

Note:

1. The lower limit shall apply at the transition frequency.

2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

13.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST







13.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received charging voltage by adapter which received 120V/60Hzpower by a LISN..
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.





13.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.





13.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

LINE CONDUCTED EMISSION TEST LINE 1-L



MEASUREMENT RESULT: "TEST_fin"

7/1/2019 11:5		_					
Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.410000 0.514000 0.822000	38.90 39.20 31.30	10.4 11.1 10.8	58 56 56	18.7 16.8 24.7	QP QP OP	L1 L1 L1	FLO FLO FLO
1.078000 1.130000 1.390000	27.60 28.00 28.30	11.4 11.5 11.5	56 56 56	28.4 28.0 27.7	QP QP QP QP	L1 L1 L1	FLO FLO FLO FLO

MEASUREMENT RESULT: "TEST fin2"


7/1/2019 11:5 Frequency MHz		Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.410000 0.514000 0.822000 1.078000 1.130000 1.386000	27.30 27.40 17.70 15.90 17.30 16.20	10.4 11.1 10.8 11.4 11.5 11.5	48 46 46 46 46	20.3 18.6 28.3 30.1 28.7 29.8	AV AV AV AV AV AV	L1 L1 L1 L1 L1 L1	FLO FLO FLO FLO FLO FLO



Attestation of Global Compliance(Shenzhen)Co.,Ltd.

Add: 2/F., Building 2, No.1–4, Chaxi Sanwei Technial Industrial Park, Gushu, Xixiang, Bao'an District, Shenzhen, Guangdong, China Tel: +86–755 2523 4088 E-mail: agc@agc-cert.com Service Hotline:400 089 2118





Line Conducted Emission Test Line 2-N

MEASUREMENT RESULT: "TEST_fin"

7/1/2019 11:5 Frequency MHz	8PM Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.470000 0.522000 0.882000 1.094000 1.146000 2.602000	44.00 45.30 38.00 34.50 35.70 30.30	11.0 11.1 11.1 11.5 11.5 11.5	57 56 56 56 56 56	12.5 10.7 18.0 21.5 20.3 25.7	QP QP QP QP QP QP QP	N N N N N	FLO FLO FLO FLO FLO FLO

MEASUREMENT RESULT: "TEST_fin2"

7/1/2019 11:58PM							
Frequency	Level	Transd	Limit	Margin	Detector	Line	PE
MHz	dBµV	dB	dBµV	dB			
0.470000	33.10	11.0	47	13.4	AV	N	FLO
0.522000	34.30	11.1	46	11.7	AV	N	FLO
0.886000	30.40	11.1	46	15.6	AV	N	FLO
1.094000	24.30	11.5	46	21.7	AV	N	FLO
1.146000	24.50	11.5	46	21.5	AV	Ν	FLO
2.550000	19.90	11.5	46	26.1	AV	N	FLO



7




Report No.:AGC03576190601FE04 Page 60 of 61

APPENDIX A: PHOTOGRAPHS OF TEST SETUP LINE CONDUCTED EMISSION TEST SETUP



RADIATED EMISSION TEST SETUP







Report No.:AGC03576190601FE04 Page 61 of 61



RADIATED EMISSION ABOVE 1G TEST SETUP

----END OF REPORT----



 $\label{eq:attestation} Attestation of Global Compliance (Shenzhen) Co., Ltd.$