



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ20190700561E-03

Applicant: MIGU Video Co., Ltd

Address of Applicant: No. 636 Qiaoyun Road, Shanghai, China.

Manufacturer: MIGU Video Co., Ltd

Address of Manufacturer: No. 636 Qiaoyun Road, Shanghai, China.

Factory: UNIONMAN TECHNOLOGY CO., LTD.

Address of Factory: No.5 Huitai Road, Huinan High-Tech Industrial Park, Huizhou City, Guangdong, China.

Equipment Under Test (EUT):

Product: Set-top box

Model No.: MGV2002

Brand Name: MIGU

FCC ID: 2ATTH-MGV2002

Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2019-06-17 to 2019-07-04

Date of Issue: 2019-07-04

Test Result : PASS*

Tested By:

Martin Lee

(Martin Lee)

Reviewed By:

Aaron Ma

(Aaron Ma)

Approved By:

Jack Ai
(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20190700561E-03	Rev.01	Initial report	2019-07-04

3 Contents

	Page
2 VERSION	2
3 CONTENTS	3
4 RF EXPOSURE EVALUATION	4
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	4
4.1.1 <i>Limits</i>	4
4.1.2 <i>Test Procedure</i>	4
4.2 EUT RF EXPOSURE EVALUATION	5

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 EUT RF Exposure Evaluation

Calculated Result and Limit (For 2.4G WIFI)

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
					(dBi)	(Linear)			
IEEE 802.11b (ANT 1)	2412	15.81	38.11	15±1	2	1.59	0.01255	1	Compiles
	2437	15.42	34.83	15±1	2	1.59	0.01255	1	Compiles
	2462	15.50	35.48	15±1	2	1.59	0.01255	1	Compiles
IEEE 802.11g (ANT 1)	2412	11.90	15.49	11±1	2	1.59	0.00500	1	Compiles
	2437	10.36	10.86	11±1	2	1.59	0.00500	1	Compiles
	2462	10.30	10.72	11±1	2	1.59	0.00500	1	Compiles
IEEE 802.11b (ANT 2)	2412	13.72	23.55	13±1	2	1.59	0.00792	1	Compiles
	2437	13.85	24.27	13±1	2	1.59	0.00792	1	Compiles
	2462	13.16	20.70	13±1	2	1.59	0.00792	1	Compiles
IEEE 802.11g (ANT 2)	2412	8.81	7.60	9±1	2	1.59	0.00315	1	Compiles
	2437	9.12	8.17	9±1	2	1.59	0.00315	1	Compiles
	2462	8.46	7.01	9±1	2	1.59	0.00315	1	Compiles
IEEE 802.11n HT20 (ANT 1)	2412	11.11	12.91	11±1	2	1.59	0.00500	1	Compiles
	2437	10.85	12.16	11±1	2	1.59	0.00500	1	Compiles
	2462	10.38	10.91	11±1	2	1.59	0.00500	1	Compiles
IEEE 802.11n HT20 (ANT 2)	2412	8.63	7.30	9±1	2	1.59	0.00315	1	Compiles
	2437	8.83	7.64	9±1	2	1.59	0.00315	1	Compiles
	2462	8.76	7.52	9±1	2	1.59	0.00315	1	Compiles
IEEE 802.11n HT40 (ANT 1)	2422	8.88	7.73	8±1	2	1.59	0.00251	1	Compiles
	2437	7.73	5.93	8±1	2	1.59	0.00251	1	Compiles
	2452	7.78	6.00	8±1	2	1.59	0.00251	1	Compiles
IEEE 802.11n HT40 (ANT 2)	2422	6.71	4.69	7±1	2	1.59	0.00199	1	Compiles
	2437	6.43	4.40	7±1	2	1.59	0.00199	1	Compiles
	2452	6.60	4.57	7±1	2	1.59	0.00199	1	Compiles

Mode	Frequency (MHz)	Power Density (S) (mW /cm ²)			Limited of Power Density (S) (mW /cm ²)	Test Result
		ANT 1	ANT 2	Sum		
IEEE 802.11n HT20 (ANT 1+2)	2412	0.00500	0.00315	0.00815	1	Compiles
	2437	0.00500	0.00315	0.00815	1	Compiles
	2462	0.00500	0.00315	0.00815	1	Compiles
IEEE 802.11n HT40 (ANT 1+2)	2422	0.00251	0.00199	0.00450	1	Compiles
	2437	0.00251	0.00199	0.00450	1	Compiles
	2452	0.00251	0.00199	0.00450	1	Compiles

Calculated Result and Limit (For 5G WIFI)

Antenna 1: 2dBi

Antenna 2: 3dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.59/1.99 in linear scale.

Output Power into Antenna & RF Exposure Evaluation Distance:

The worst case is IEEE 802.11N20 ANT1+ANT2

Mode	Frequency (MHz)	output power (dBm)	output power (mW)	Target power (dBm)	Antenna gain		Power Density (S) (mW /cm2)	Limited of Power Density (S) (mW /cm2)	Test Result
					(dBi)	(Linear)			
IEEE 802.11N20 (ANT 1)+	5610	21.50	141.25	20± 2	ANT1+ANT2	3.58	0.11288	1	Compiles
IEEE 802.11N20 (ANT 2)	5775	20.37	108.90	19± 1.5	ANT1+ANT2	3.58	0.07755	1	Compiles