

1. MAXIMUM PERMISSIBLE EXPOSURE (MPE)

1.1 General Information

Client Information

Applicant: AJS ELECTRONICS LIMITED
Address of applicant: 15/F, Liuchuang Building II, No. 29, South Ring Road, South Area Hi-Tech Zone, Nanshan District, Shenzhen, China

Manufacturer: Shenzhen Fudeyuan Digital Technology Co., Ltd.
Address of manufacturer: 1st Floor, No.3, Road 4 Dawei, Xinqiao Community, Xinqiao Street, Baoan District, Shenzhen, 518000, Guangdong, China

General Description of EUT:

Product Name: Soundbar with wireless subwoofer
Trade Name: AJS, SOUNDSTAGE, JVC
Model No.: Xbar 61HW 2.1.2
Adding Model(s): STAGE-AT212, TH-S560B
Rated Voltage: AC 110-240V, 50/60Hz
FCC ID: 2ATVN-AT212-560B
Equipment Type: Fixed

Technical Characteristics of EUT:

Bluetooth Version: V5.1 (BR/EDR mode)
Frequency Range: 2402-2480MHz
RF Output Power: -5.67dBm (Conducted)
Data Rate: 1Mbps, 2Mbps, 3Mbps
Modulation: GFSK, $\pi/4$ DQPSK, 8DPSK
Quantity of Channels: 79
Channel Separation: 1MHz
Type of Antenna: PCB Antenna
Antenna Gain: -0.58dBi

1.2 Standard Applicable

According to § 1.1307(b)(1) and KDB 447498 D01 General RF Exposure Guidance v06, system operating under the provisions of this section shall be operating in a manner that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure.

(a) Limits for Occupational / Controlled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500	/	/	F/300	6
1500-100000	/	/	5	6

(b) Limits for General Population / Uncontrolled Exposure

Frequency range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-100000	/	/	1	30

Note: f = frequency in MHz: * = Plane-wave equivalents power density

1.3 MPE Calculation Method

$$S = (30 * P * G) / (377 * R^2)$$

S = power density (in appropriate units, e.g., mw/cm²)

P = power input to the antenna (in appropriate units, e.g., mw)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor is normally numeric gain.

R = distance to the center of radiation of the antenna (in appropriate units, e.g., cm)

1.4 MPE Calculation Result

For Bluetooth

Maximum Tune-Up output power: -5(dBm)

Maximum peak output power at antenna input terminal: 0.32(mW)

Prediction distance: >20(cm)

Prediction frequency: 2402(MHz)

Antenna gain: -0.58 (dBi)

Directional gain (numeric gain): 0.87

The worst case is power density at prediction frequency at 20cm: 0.0001(mw/cm²)

MPE limit for general population exposure at prediction frequency: 1 (mw/cm²)

Result: Pass