



## Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640  
Fax: +86-755-26648637  
Website: [www.cqa-cert.com](http://www.cqa-cert.com)

Report Template Version: V04  
Report Template Revision Date: 2018-07-06

# RF Exposure Evaluation Report

**Report No. :** CQASZ20191101208E-02  
**Applicant:** Zhejiang PDW Industrial Co., Ltd.  
**Address of Applicant:** Quanxi Industrial Park, Wuyi County, Jinhua City, Zhejiang, P.R. China 321200  
**Equipment Under Test (EUT):**  
**EUT Name:** Truck TPMS External Sensor  
**Model No.:** 04.01.19, 04.01.50  
**Test Model No.:** 04.01.19  
**Brand Name:** PDW, PROCAST  
**FCC ID:** 2ATWD-040119  
**Standards:** 47 CFR Part 1.1307  
47 CFR Part 2.1093  
KDB447498D01 General RF Exposure Guidance v06  
**Date of Receipt:** 2019-11-28  
**Date of Test:** 2019-11-28 to 2019-12-06  
**Date of Issue:** 2019-12-06  
**Test Result :** **PASS\***

**\*In the configuration tested, the EUT complied with the standards specified above**

**Tested By:**

(Tom Chen)

**Reviewed By:**

(Aaron Ma)

**Approved By:**

( Jack Ai)



## 1 Version

### Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20191101208E-02	Rev.01	Initial report	2019-12-06

## 2 Contents

	Page
1 VERSION.....	2
2 CONTENTS.....	3
3 GENERAL INFORMATION.....	4
3.1 CLIENT INFORMATION.....	4
3.2 GENERAL DESCRIPTION OF EUT.....	4
4 SAR EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 <i>Standard Requirement</i> .....	5
4.1.2 <i>Limits</i> .....	5
4.1.3 <i>EUT RF Exposure</i> .....	6

### 3 General Information

#### 3.1 Client Information

Applicant:	Zhejiang PDW Industrial Co., Ltd.
Address of Applicant:	Quanxi Industrial Park, Wuyi County, Jinhua City, Zhejiang, P.R. China 321200
Manufacturer:	Zhejiang PDW Industrial Co., Ltd.
Address of Manufacturer:	Quanxi Industrial Park, Wuyi County, Jinhua City, Zhejiang, P.R. China 321200

#### 3.2 General Description of EUT

Product Name:	Truck TPMS External Sensor
Model No.:	04.01.19, 04.01.50
Test Model No.:	04.01.19
Trade Mark:	PDW, PROCAST
Hardware Version:	V03
Software Version:	V04
Sample Type:	Portable production
Operation Frequency:	433.92MHz
Channel Numbers:	1
Modulation Type:	FSK
Antenna Type:	integral antenna
Antenna Gain:	0dBi
Power Supply:	DC3.0V

Note:

Model: 04.01.19, 04.01.50

Only the model 04.01.19 was tested, since the electrical circuit design, layout, components used and internal wiring were identical for the above models, with difference being Trademarks and models.

## 4 SAR Evaluation

### 4.1 RF Exposure Compliance Requirement

#### 4.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

##### 4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

#### 4.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$\left[ \frac{\text{max. power of channel, including tune-up tolerance, mW}}{\text{min. test separation distance, mm}} \right] \cdot \sqrt{f(\text{GHz})} \leq 3.0$$
 for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion

#### 4.1.3 EUT RF Exposure

$$e_{\text{irp}} = p_t \times g_t = (E \times d)^2 / 30$$

where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m,  $10^{((\text{dB}\mu\text{V}/\text{m})/20)/10^6}$ ,

$d$  = measurement distance in meters (m)---3m,

$$\text{So } p_t = (E \times d)^2 / 30 / g_t$$

The worst case (refer to report CQASZ20191101208E-02) is below:

Antenna polarization: Horizontal		
Frequency (MHz)	Level (dBuV/m)	Polarization
433.92	83.86	Peak
433.92	66.34	Average

Antenna polarization: Vertical		
Frequency (MHz)	Level (dBuV/m)	Polarization
433.92	86.49	Peak
433.92	68.97	Average

For 433.92MHz wireless:

Field strength = 86.49dB $\mu$ V/m @3m

Ant. gain 0dBi; so Ant numeric gain=1.0

$$\text{So } p_t = \{ [10^{(86.49/20)} / 10^6 \times 3]^2 / 30 / 1.0 \} \times 1000\text{mW} = 0.134\text{mW}$$

$$\text{So } (0.134\text{mW}/5\text{mm}) \times \sqrt{0.43392\text{GHz}} = 0.0176,$$

0.0176 < 3.0 for 1-g SAR

So the SAR report is not required.