

TEST REPORT

Report No.: BCTC2104103319-1E

Applicant: Shenzhen Yuangu Technology Co., Ltd.

Product Name: TRUE WIRELESS SPORT EARBUDS

Model/Type Ref.: ET8

Tested Date: 2021-02-25 to 2021-04-26

Issued Date: 2021-04-26


Shenzhen BCTC Testing Co., Ltd.



FCC ID: 2ATWG-ET8C

Product Name: TRUE WIRELESS SPORT EARBUDS
Trademark: AXLOIE
Model/Type Ref.: ET8
Model/Type Ref.: ET12, ET13, ET14, ET15, ET16
Prepared For: Shenzhen Yuangu Technology Co., Ltd.
Address: No.101, 1st Factory Building, Hebei Industrial Park, Ma'antang Community, Hebeizhongxing Road, Bantian Sub-district, Longgang District, Shenzhen, China
Manufacturer: Shenzhen Yuangu Technology Co., Ltd.
Address: No.101, 1st Factory Building, Hebei Industrial Park, Ma'antang Community, Hebeizhongxing Road, Bantian Sub-district, Longgang District, Shenzhen, China
Prepared By: Shenzhen BCTC Testing Co., Ltd.
Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China
Sample Received Date: 2021-02-25
Sample tested Date: 2021-02-25 to 2021-04-26
Issue Date: 2021-04-26
Report No.: BCTC2104103319-1E
Test Standards: FCC Part15.209
ANSI C63.10-2013
Test Results: PASS

Tested by:



Willem Wang/Project Handler

Approved by:




Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

TABLE OF CONTENT


| Test Report Declaration | Page |
|--|------|
| 1. VERSION | 4 |
| 2. TEST SUMMARY | 5 |
| 3. MEASUREMENT UNCERTAINTY | 6 |
| 4. PRODUCT INFORMATION AND TEST SETUP | 7 |
| 4.1 Product Information | 7 |
| 4.2 Test Setup Configuration | 7 |
| 4.3 Support Equipment | 8 |
| 4.4 Test Mode | 8 |
| 5. TEST FACILITY AND TEST INSTRUMENT USED | 9 |
| 5.1 Test Facility | 9 |
| 5.2 Test Instrument Used | 9 |
| 6. CONDUCTED EMISSIONS | 11 |
| 6.1 Block Diagram Of Test Setup | 11 |
| 6.2 Limit | 11 |
| 6.3 Test procedure | 11 |
| 6.4 EUT operating Conditions | 11 |
| 6.5 Test Result | 12 |
| 7. RADIATED EMISSIONS | 14 |
| 7.1 Block Diagram Of Test Setup | 14 |
| 7.2 Limit | 15 |
| 7.3 Test procedure | 15 |
| 7.4 Test Result | 17 |
| 8. EUT PHOTOGRAPHS | 20 |
| 9. EUT TEST SETUP PHOTOGRAPHS | 21 |

(Note: N/A means not applicable)



1. VERSION


| Report No. | Issue Date | Description | Approved |
|-------------------|------------|-------------|----------|
| BCTC2104103319-1E | 2021-04-26 | Original | Valid |
| | | | |



2. TEST SUMMARY

The Product has been tested according to the following specifications:


| No. | Test Parameter | Clause No | Results |
|-----|---------------------|-----------|---------|
| 1 | Conducted Emission | 15.207 | PASS |
| 2 | Radiated Emission | 15.209 | PASS |
| 3 | Antenna Requirement | 15.203 | PASS |



3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

| No. | Item | Uncertainty |
|-----|---|-------------|
| 1 | 3m chamber Radiated spurious emission(9kHz-30MHz) | U=3.7dB |
| 2 | 3m chamber Radiated spurious emission(30MHz-1GHz) | U=4.3dB |
| 3 | 3m chamber Radiated spurious emission(1GHz-18GHz) | U=4.5dB |
| 4 | Conducted Emission (150kHz-30MHz) | U=3.2dB |
| 5 | humidity uncertainty | U=5.3% |
| 6 | Temperature uncertainty | U=0.59°C |
| 7 | Bandwidth | 0.9% |



4. PRODUCT INFORMATION AND TEST SETUP


4.1 Product Information

| | |
|-----------------------|---|
| Model/Type Ref.: | ET8 ET12, ET13, ET14, ET15, ET16 |
| Model differences: | All the model are the same circuit and RF module, except model names. |
| Operation Frequency: | 115kHz-205kHz |
| Antenna installation: | Inductive loop coil antenna |
| Ratings: | Input: DC 5V 2A Output: DC 5V 200Ma Wireless Charging: 5W Battery: DC 3.7V |



4.2 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.

Conducted Emission:



Radiated Spurious Emission:



4.3 Support Equipment

| No. | Device Type | Brand | Model | Series No. | Data Cable | Remark |
|-----|-----------------------------|--------|----------|------------|------------|--------|
| E-1 | TRUE WIRELESS SPORT EARBUDS | AXLOIE | ET8 | N/A | N/A | EUT |
| E-2 | Adapter | N/A | BCTC-002 | N/A | Auxiliary | EUT |
| E-3 | Dummy load | N/A | DL01 | N/A | Auxiliary | EUT |


Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

| | |
|--------------|-------------|
| Test Modes 1 | Wireless 5W |
|--------------|-------------|



5. TEST FACILITY AND TEST INSTRUMENT USED

5.1 Test Facility


All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

IC Registered No.: 23583

5.2 Test Instrument Used


| Conducted emissions Test | | | | | |
|--------------------------|--------------|----------|----------------|---------------|---------------|
| Equipment | Manufacturer | Model# | Serial# | Last Cal. | Next Cal. |
| Receiver | R&S | ESR3 | 102075 | Jun. 08, 2020 | Jun. 07, 2021 |
| LISN | R&S | ENV216 | 101375 | Jun. 04, 2020 | Jun. 03, 2021 |
| ISN | HPX | ISN T800 | S1509001 | Jun. 04, 2020 | Jun. 03, 2021 |
| Software | Frad | EZ-EMC | EMC-CON 3A1 | \ | \ |



| Radiated emissions Test (966 chamber) | | | | | |
|---------------------------------------|--------------|---------------|---------------|---------------|---------------|
| Equipment | Manufacturer | Model# | Serial# | Last Cal. | Next Cal. |
| 966 chamber | ChengYu | 966 Room | 966 | Jun. 06. 2020 | Jun. 05, 2023 |
| Receiver | R&S | ESR3 | 102075 | Jun. 08, 2020 | Jun. 07, 2021 |
| Receiver | R&S | ESRP | 101154 | Jun. 08, 2020 | Jun. 07, 2021 |
| Amplifier | Schwarzbeck | BBV9718 | 9718-309 | Jun. 04, 2020 | Jun. 03, 2021 |
| Amplifier | Schwarzbeck | BBV9744 | 9744-0037 | Jun. 04, 2020 | Jun. 03, 2021 |
| TRILOG Broadband Antenna | schwarzbeck | VULB 9163 | VULB9163-942 | Jun. 08, 2020 | Jun. 07, 2021 |
| Horn Antenna | SCHWARZBECK | BBHA9120D | 1201 | Jun. 10, 2020 | Jun. 09, 2021 |
| Horn Antenna (18GHz-40 GHz) | SCHWARZBECK | BBHA9170 | 822 | Jun. 10, 2020 | Jun. 09, 2021 |
| Amplifier (18GHz-40 GHz) | MITEQ | TTA1840-35-HG | 2034381 | Jun. 08, 2020 | Jun. 07, 2021 |
| Loop Antenna (9kHz-30MHz) | SCHWARZBECK | FMZB1519B | 014 | Jun. 08, 2020 | Jun. 07, 2021 |
| RF cables1 (9kHz-30MHz) | Huber+Suhnar | 9kHz-30MHz | B1702988-0008 | Jun. 08, 2020 | Jun. 07, 2021 |
| RF cables2 (30MHz-1GHz) | Huber+Suhnar | 30MHz-1GHz | 1486150 | Jun. 08, 2020 | Jun. 07, 2021 |
| RF cables3 (1GHz-40GHz) | Huber+Suhnar | 1GHz-40GHz | 1607106 | Jun. 08, 2020 | Jun. 07, 2021 |
| Power Metter | Keysight | E4419B | \ | Jun. 08, 2020 | Jun. 07, 2021 |
| Power Sensor (AV) | Keysight | E9 300A | \ | Jun. 08, 2020 | Jun. 07, 2021 |
| Signal Analyzer 20kHz-26.5 GHz | KEYSIGHT | N9020A | MY49100060 | Jun. 04, 2020 | Jun. 03, 2021 |
| Spectrum Analyzer 9kHz-40GHz | Agilent | FSP40 | 100363 | Jun. 08, 2020 | Jun. 07, 2021 |
| Software | Frad | EZ-EMC | FA-03A2RE | \ | \ |

6. CONDUCTED EMISSIONS

6.1 Block Diagram Of Test Setup



6.2 Limit

| FREQUENCY (MHz) | Limit (dBuV) | |
|-----------------|--------------|-----------|
| | Quas-peak | Average |
| 0.15 -0.5 | 66 - 56 * | 56 - 46 * |
| 0.50 -5.0 | 56.00 | 46.00 |
| 5.0 -30.0 | 60.00 | 50.00 |

Notes:
 1. *Decreasing linearly with logarithm of frequency.
 2. The lower limit shall apply at the transition frequencies.

6.3 Test procedure

| Receiver Parameters | Setting |
|---------------------|----------|
| Attenuation | 10 dB |
| Start Frequency | 0.15 MHz |
| Stop Frequency | 30 MHz |
| IF Bandwidth | 9 kHz |

a. The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).

b. The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.


c. For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

| | | | |
|----------------|--------------|---------------------|--------|
| Temperature : | 26 °C | Relative Humidity : | 54% |
| Pressure : | 101kPa | Phase : | L |
| Test Voltage : | AC 120V/60Hz | Test Mode : | Mode 1 |




Remark:

- All readings are Quasi-Peak and Average values.
- Factor = Insertion Loss + Cable Loss.

| No. | Mk. | Freq. MHz | Reading Level | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector |
|-----|-----|--------------|------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1 | | 0.1949 | 35.07 | 9.47 | 44.54 | 63.83 | -19.29 | QP |
| 2 | | 0.1949 | 24.05 | 9.47 | 33.52 | 53.83 | -20.31 | AVG |
| 3 | | 0.4785 | 31.62 | 9.57 | 41.19 | 56.37 | -15.18 | QP |
| 4 | | 0.4785 | 22.64 | 9.57 | 32.21 | 46.37 | -14.16 | AVG |
| 5 | * | 1.0005 | 34.52 | 9.57 | 44.09 | 56.00 | -11.91 | QP |
| 6 | | 1.0005 | 20.10 | 9.57 | 29.67 | 46.00 | -16.33 | AVG |
| 7 | | 3.2460 | 24.25 | 9.68 | 33.93 | 56.00 | -22.07 | QP |
| 8 | | 3.2460 | 14.17 | 9.68 | 23.85 | 46.00 | -22.15 | AVG |
| 9 | | 9.0105 | 28.71 | 9.70 | 38.41 | 60.00 | -21.59 | QP |
| 10 | | 9.0105 | 18.20 | 9.70 | 27.90 | 50.00 | -22.10 | AVG |
| 11 | | 14.6085 | 24.02 | 9.70 | 33.72 | 60.00 | -26.28 | QP |
| 12 | | 14.6085 | 18.46 | 9.70 | 28.16 | 50.00 | -21.84 | AVG |

| | | | |
|----------------|--------------|---------------------|--------|
| Temperature : | 26 °C | Relative Humidity : | 54% |
| Pressure : | 101kPa | Phase : | N |
| Test Voltage : | AC 120V/60Hz | Test Mode : | Mode 1 |



Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

| No. | Mk. | Freq. MHz | Reading Level | Correct Factor dB | Measure- ment dBuV | Limit dBuV | Over dB | Detector |
|-----|-----|--------------|------------------|-------------------------|--------------------------|---------------|------------|----------|
| 1 | | 0.1945 | 35.32 | 9.47 | 44.79 | 63.84 | -19.05 | QP |
| 2 | | 0.1945 | 21.61 | 9.47 | 31.08 | 53.84 | -22.76 | AVG |
| 3 | | 0.3832 | 31.39 | 9.51 | 40.90 | 58.21 | -17.31 | QP |
| 4 | | 0.3832 | 14.02 | 9.51 | 23.53 | 48.21 | -24.68 | AVG |
| 5 | * | 1.0997 | 34.41 | 9.57 | 43.98 | 56.00 | -12.02 | QP |
| 6 | | 1.0997 | 17.04 | 9.57 | 26.61 | 46.00 | -19.39 | AVG |
| 7 | | 3.3814 | 23.90 | 9.69 | 33.59 | 56.00 | -22.41 | QP |
| 8 | | 3.3814 | 12.17 | 9.69 | 21.86 | 46.00 | -24.14 | AVG |
| 9 | | 7.2903 | 25.56 | 9.72 | 35.28 | 60.00 | -24.72 | QP |
| 10 | | 7.2903 | 14.87 | 9.72 | 24.59 | 50.00 | -25.41 | AVG |
| 11 | | 18.2316 | 22.26 | 9.76 | 32.02 | 60.00 | -27.98 | QP |
| 12 | | 18.2316 | 15.39 | 9.76 | 25.15 | 50.00 | -24.85 | AVG |


7. RADIATED EMISSIONS

7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



7.2 Limit

FCC §15.209; §15.205.

| Test Standard | FCC Part15 C Section 15.209 and 15.205 | | | | |
|---------------|--|----------------------------------|----------------|------------|--------------------------|
| Test Limit | Frequency (MHz) | Field strength (microvolt/meter) | Limit (dBuV/m) | Remark | Measurement distance (m) |
| | 0.009MHz~0.490MHz | 2400/F(kHz) | - | - | 300 |
| | 0.490MHz~1.705MHz | 24000/F(kHz) | - | - | 30 |
| | 1.705MHz~30MHz | 30 | - | - | 30 |
| | 30MHz~88MHz | 100 | 40.0 | Quasi-peak | 3 |
| | 88MHz~216MHz | 150 | 43.5 | Quasi-peak | 3 |
| | 216MHz~960MHz | 200 | 46.0 | Quasi-peak | 3 |
| | 960MHz~1000MHz | 500 | 54.0 | Quasi-peak | 3 |
| | Above 1000MHz | 500 | 54.0 | Average | 3 |
| - | | 74.0 | Peak | 3 | |

7.3 Test procedure

| Receiver Parameter | Setting |
|--------------------|-------------------|
| Attenuation | Auto |
| 9kHz~150kHz | RBW 200Hz for QP |
| 150kHz~30MHz | RBW 9kHz for QP |
| 30MHz~1000MHz | RBW 120kHz for QP |

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).

h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.



7.4 Test Result

9kHz-30MHz

| | | | |
|--------------|---------|--------------------|---------|
| Temperature: | 26°C | Relative Humidity: | 24% |
| Pressure: | 101 kPa | Test Voltage : | DC 3.7V |
| Test Mode : | Mode 1 | Polarization : | -- |



| Frequency (kHz) | Meter Reading (dBμV) | Factor (dB) | Emission Level (dBμV/m) | Limits (dBμV/m) | Margin (dB) | Detector Type |
|-----------------|----------------------|-------------|-------------------------|-----------------|-------------|---------------|
| 102.9 | 23.96 | 19.76 | 43.72 | 127.36 | -83.64 | PK |
| 102.9 | 18.47 | 19.76 | 38.23 | 107.36 | -69.13 | AV |
| 132.7 | 56.21 | 19.75 | 75.96 | 125.15 | -49.19 | PK |
| 132.7 | 52.14 | 19.75 | 71.89 | 105.15 | -33.26 | AV |
| 452.5 | 19.94 | 19.79 | 39.73 | 114.49 | -74.76 | PK |
| 452.5 | 15.07 | 19.79 | 34.86 | 94.49 | -59.63 | AV |
| 776.5 | 17.74 | 19.88 | 37.62 | 69.8 | -32.18 | QP |
| 2341.8 | 11.65 | 19.91 | 31.56 | 69.54 | -37.98 | QP |
| 6899.7 | 6.97 | 20.08 | 27.05 | 69.54 | -42.49 | QP |

Note:


Pre-scan in the all of mode, the worst case in of was recorded.

Factor = antenna factor + cable loss – pre-amplifier.

Margin = Emission Level- Limit.

Between 30MHz – 1GHz

| | | | |
|--------------|---------|--------------------|------------|
| Temperature: | 26°C | Relative Humidity: | 54% |
| Pressure: | 101 kPa | Test Voltage : | DC 3.7V |
| Test Mode : | Mode 1 | Polarization : | Horizontal |




Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dB/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1 | ! | 69.8450 | 53.20 | -17.20 | 36.00 | 40.00 | -4.00 | QP |
| 2 | ! | 176.3086 | 56.48 | -16.89 | 39.59 | 43.50 | -3.91 | QP |
| 3 | * | 193.7728 | 56.74 | -15.69 | 41.05 | 43.50 | -2.45 | QP |
| 4 | | 243.3772 | 50.60 | -14.37 | 36.23 | 46.00 | -9.77 | QP |
| 5 | | 297.2241 | 43.30 | -12.50 | 30.80 | 46.00 | -15.20 | QP |
| 6 | | 397.6334 | 36.13 | -9.75 | 26.38 | 46.00 | -19.62 | QP |

| | | | |
|--------------|---------|--------------------|----------|
| Temperature: | 26°C | Relative Humidity: | 54% |
| Pressure: | 101 kpa | Test Voltage : | DC 3.7V |
| Test Mode : | Mode 1 | Polarization : | Vertical |



Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier.

| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measure- ment dBuV/m | Limit dB/m | Over dB | Detector |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|---------------|------------|----------|
| 1 | | 35.7490 | 36.55 | -15.44 | 21.11 | 40.00 | -18.89 | QP |
| 2 | | 52.9453 | 38.84 | -14.25 | 24.59 | 40.00 | -15.41 | QP |
| 3 | * | 69.8450 | 49.24 | -17.20 | 32.04 | 40.00 | -7.96 | QP |
| 4 | | 173.2051 | 49.22 | -17.11 | 32.11 | 43.50 | -11.39 | QP |
| 5 | | 197.8928 | 45.66 | -15.41 | 30.25 | 43.50 | -13.25 | QP |
| 6 | | 265.6757 | 39.46 | -13.66 | 25.80 | 46.00 | -20.20 | QP |

8. EUT PHOTOGRAPHS

EUT Photo 1




EUT Photo 2





9. EUT TEST SETUP PHOTOGRAPHS

Conducted emissions



Radiated Measurement Photos





STATEMENT

- 1.The equipment lists are traceable to the national reference standards.
- 2.The test report can not be partially copied unless prior written approval is issued from our lab.
- 3.The test report is invalid without stamp of laboratory.
- 4.The test report is invalid without signature of person(s) testing and authorizing.
- 5.The test process and test result is only related to the Unit Under Test.
- 6.The quality system of our laboratory is in accordance with ISO/IEC17025.
- 7.If there is any objection to report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Tangwei, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL : 400-788-9558

P.C.: 518103

FAX : 0755-33229357

Website : <http://www.bctc-lab.com>

E-Mail : bctc@bctc-lab.com.cn

***** END *****

