

# SulfiLogger™ A1-BCDE-F

Unisense A/S  
Tueager 1  
DK-8200 Aarhus N

**DTI 18ATEX0087X**

**CE 2804**



**II 1G Ex ia IIC T4 Ga**

**S/N: 1000000**

Tamb: -20°C to +60°C  
Power / 4-20 mA: Ui: 30 V, li: 100 mA, Ci: 1 nF, Li: 0 uH, Pi: 0.70 W  
RS-232: Ui: 20 V, li: 100 mA, Ci: 0 nF, Li: 0 uH, Pi: 0.30 W



---

Target gas:	H <sub>2</sub> S	Min. voltage (power):	20 V
Conc. range:	0-1000 ppm	FCC ID:	2ATWPSULFILOGGER1

**This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.**

**SulfiLogger™ X1-1220-1000ppm**

Unisense A/S  
Tueager 1  
DK-8200 Aarhus N

DTI 18ATEX0087X

CE 2804

S/N: 123456



II 1G Ex ia IIC T4 Ga



Tamb:	-20°C to +60°C
Power / 4-20 mA:	Ui: 30 V, Ii: 100 mA, Ci: 1 nF, Li: 0 uH, Pi: 0.70 W
RS-232:	Ui: 20 V, Ii: 100 mA, Ci: 0 nF, Li: 0 uH, Pi: 0.30 W

Target gas:	H <sub>2</sub> S	Min. voltage (power):	20 V
Conc. range:	0-1000 ppm	FCC ID:	2ATWPSULFILOGGER1

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.