



### FCC PART 15 SUBPART C TEST REPORT

**Report Reference No.....: CTL1904231031-WF**

Compiled by  
( position+printed name+signature)...: Happy Guo  
(File administrators)

*Happy Guo*

Name of the organization performing  
the tests  
( position+printed name+signature)...: Nice Nong  
(Test Engineer)

*Nice Nong*

Approved by  
( position+printed name+signature)...: Ivan Xie  
(Manager)

*Ivan Xie*

**Test Firm .....: Shenzhen CTL Testing Technology Co., Ltd.**

Address .....: Floor 1-A, Baisha Technology Park, No.3011, Shahehexi Road,  
Nanshan District, Shenzhen, China 518055

**Applicant's name.....: GCteq Wireless (Shenzhen) Co., Ltd.**

Address .....: Room 1316, Building 9B-2, Shenzhen Bay Technology and Ecology  
Park, Shenzhen, Guangdong, China.

**Test specification:**

Standard .....: FCC Part 15C

Master TRF.....: Dated 2011-01

**Test item description .....: Hidden wireless charging transmitter**

**FCC ID.....: 2ATX3GF-01**

Trade Mark .....: GCteq

Model/Type reference.....: GF-01

Transmit Frequency.....: 115~148KHz

Antenna type .....: Loop antenna

Date of receipt of test item .....: Jun. 18, 2019

Date of sampling.....: Jun. 18, 2019

Date of Test Date .....: Jun. 18, 2019–Jul. 01, 2019

Data of Issue .....: Jul. 02, 2019

Result.....: **Pass**

**Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**TEST REPORT**

<b>Test Report No. :</b>	<b>CTL1904231031-WF</b>	Jul. 02, 2019
		Date of issue

Equipment under Test : Hidden wireless charging transmitter

Type / Model(s) : GF-01

**Applicant** : **GCTeq Wireless (Shenzhen) Co., Ltd.**

Address : Room 1316, Building 9B-2, Shenzhen Bay Technology and Ecology Park, Shenzhen, Guangdong, China

**Manufacturer** : **TEN PAO ELECTRONICS(HUIZHOU) CO.,LTD.**

Address : dongjiang industrial Estate, shuikou Street, Huizhou City, guangdong Province, P.R.C

<b>Test Result</b> according to the standards on page 4:	<b>Positive</b>
--	-----------------

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

## Contents

FCC PART 15 SUBPART C TEST REPORT .....	1
<b><u>1. TEST STANDARDS .....</u></b>	<b><u>4</u></b>
<b><u>2. SUMMARY .....</u></b>	<b><u>5</u></b>
2.1. General Remarks	5
2.2. Equipment Under Test	5
2.3. Short description of the Equipment under Test (EUT)	5
2.4. EUT operation mode	5
2.5. EUT configuration	5
2.6. Related Submittal(s) / Grant (s)	5
2.7. Modifications	6
2.8. Summary of Test Results	7
<b><u>3. TEST ENVIRONMENT .....</u></b>	<b><u>8</u></b>
3.1. Address of the test laboratory	8
3.2. Test Facility	8
3.3. Environmental conditions	8
3.4. Statement of the measurement uncertainty	8
3.5. Equipments Used during the Test	9
<b><u>4. TEST CONDITIONS AND RESULTS .....</u></b>	<b><u>10</u></b>
4.1. AC Power Conducted Emission	10
4.2. Radiated Emission	13
4.3. 20dB Bandwidth/99% Bandwidth	18
<b><u>5. TEST SETUP PHOTOS OF THE EUT .....</u></b>	<b><u>19</u></b>
<b><u>6. EXTERNAL AND INTERNAL PHOTOS OF THE EUT .....</u></b>	<b><u>20</u></b>

## 1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.207,15.209, 15.215\(c\)](#)

[ANSI C63.10-2013](#)

## 2. SUMMARY

### 2.1. General Remarks

Date of receipt of test sample	:	Jun. 18, 2019
Testing commenced on	:	Jun. 18, 2019
Testing concluded on	:	Jul. 01, 2019

### 2.2. Equipment Under Test

#### Power supply system utilised

Power supply voltage	:	<input checked="" type="radio"/> 120V / 60 Hz	<input type="radio"/> 115V / 60Hz
		<input type="radio"/> 12 V DC	<input type="radio"/> 24 V DC
		<input type="radio"/> Other (specified in blank below)	

DC 5V from USB

### 2.3. Short description of the Equipment under Test (EUT)

A Hidden wireless charging transmitter work frequency range 115-148 KHz.  
For more details, refer to the user's manual of the EUT.  
Serial number:GF-01

### 2.4. EUT operation mode

About 7.5W with Apple mobile phone and 10W with Samsung mobile phone, this 2 modes all have been tested, only worse case 10W with Samsung mobile phone mode was reported.

### 2.5. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer
- supplied by the lab

Power adapter

Manufacturer: TEN PAO EIELECTRONICS(HUIZHOU)  
CO.,LTD.  
Model:S018BAV0900200  
Input: 100-240V~ 50/60Hz 500mA  
Output: 9.0V === 2000mA

Mobile phone

Manufacturer: SAMSUNG  
Model: S7 edge  
Manufacturer: Apple Inc.  
Model: iPhone XR

### 2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for **FCC ID: 2ATX3GF-01** filing to comply with FCC Part 15, Subpart C Rules.

## 2.7. Modifications

No modifications were implemented to meet testing criteria.

## 2.8. Summary of Test Results

The test summary of the EUT listed as below:

	Test Standards	Test Result
Electric Field Radiated Emissions	FCC Part 15 C (Section15.209)	PASS
20dB Bandwidth/99% Bandwidth	FCC Part 15 C (Section15.215(c))	PASS
Conducted Emissions	FCC Part 15 C (Section15.207)	PASS

Remark: The measurement uncertainty is not included in the test result.

### **3. TEST ENVIRONMENT**

#### **3.1. Address of the test laboratory**

Shenzhen CTL Testing Technology Co., Ltd.  
Floor 1-A, Baisha Technology Park, No. 3011, Shaheji Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

#### **3.2. Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

##### **CNAS-Lab Code: L7497**

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

##### **A2LA-Lab Cert. No. 4343.01**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

##### **IC Registration No.: 9518B**

##### **CAB identifier: CN0041**

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9518B on Jan. 22, 2019.

##### **FCC-Registration No.: 399832**

##### **Designation No.: CN1216**

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

#### **3.3. Environmental conditions**

During the measurement the environmental conditions were within the listed ranges:

Temperature:	<u>15-35 ° C</u>
Humidity:	<u>30-60 %</u>
Atmospheric pressure:	<u>950-1050mbar</u>

#### **3.4. Statement of the measurement uncertainty**

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested



may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	9KHz~30MHz	$\pm 3.70\text{dB}$	(1)
Radiated Emission	30~1000MHz	$\pm 4.10\text{dB}$	(1)
Radiated Emission	Above 1GHz	$\pm 4.32\text{dB}$	(1)
Conducted Disturbance	0.15~30MHz	$\pm 3.20\text{dB}$	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ .

### 3.5. Equipments Used during the Test


Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ENV216	3560.6550.12	2019/05/20	2020/05/19
LISN	R&S	ESH2-Z5	860014/010	2019/05/20	2020/05/19
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2019/05/20	2020/05/19
EMI Test Receiver	R&S	ESCI	1166.5950.03	2019/05/20	2020/05/19
Spectrum Analyzer	Agilent	E4407B	MY41440676	2019/05/20	2020/05/19
Spectrum Analyzer	Agilent	N9020	US46220290	2019/05/20	2020/05/19
Controller	EM Electronics	EM 1000	060859	2019/05/20	2020/05/19
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2019/05/20	2020/05/19
Active Loop Antenna	Da Ze	ZN30900A	/	2019/05/20	2020/05/19
Amplifier	Agilent	8449B	3008A02306	2019/05/20	2020/05/19
Amplifier	Agilent	8447D	2944A10176	2019/05/20	2020/05/19
Temperature/Humidity Meter	Gangxing	CTH-608	02	2019/05/20	2020/05/19
High-Pass Filter	micro-tranics	HPM50108	G174	2019/05/20	2020/05/19
High-Pass Filter	micro-tranics	HPM50111	G142	2019/05/20	2020/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-10M	10m	2019/05/20	2020/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2019/05/20	2020/05/19
Coaxial Cables	HUBER+SUHNER	SUCOFLEX 104PEA-3M	3m	2019/05/20	2020/05/19
RF Cable	Megalon	RF-A303	N/A	2019/05/20	2020/05/19

The calibration interval was one year

## 4. TEST CONDITIONS AND RESULTS

### 4.1. AC Power Conducted Emission

#### TEST CONFIGURATION



#### TEST PROCEDURE

- 1 The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10-2013.
- 2 Support equipment, if needed, was placed as per ANSI C63.10-2013
- 3 All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10-2013
- 4 The EUT received DC5V power from USB port of PC, PC received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5 All support equipments received AC power from a second LISN, if any.
- 6 The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7 Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- 8 During the above scans, the emissions were maximized by cable manipulation.  
Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

#### AC Power Conducted Emission Limit

For intentional device, according to § 15.207(a) AC Power Conducted Emission Limits is as following :

Frequency (MHz)	Maximum RF Line Voltage (dBµV)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56*	56-46*
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50


\* Decreasing linearly with the logarithm of the frequency

**TEST RESULTS**

Remark: The charger support DC 5V/2A input and DC9V/2A input two modes. Only the worst case DC9V/2A input was report.

**SCAN TABLE: "Voltage (9K-30M) FIN"**

Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "CTL190619418\_fin"**

2019-6-19 05:15??

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
1.076000	48.00	11.3	56	8.0	QP	L1	GND
1.430000	47.60	11.3	56	8.4	QP	L1	GND
1.790000	48.40	11.3	56	7.6	QP	L1	GND
2.150000	47.90	11.4	56	8.1	QP	L1	GND
2.510000	47.70	11.4	56	8.3	QP	L1	GND
7.160000	36.50	10.9	60	23.5	QP	L1	GND


**MEASUREMENT RESULT: "CTL190619418\_fin2"**

2019-6-19 05:15??

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.716000	42.20	11.2	46	3.8	AV	L1	GND
1.076000	42.80	11.3	46	3.2	AV	L1	GND
1.430000	43.80	11.3	46	2.2	AV	L1	GND
1.790000	44.80	11.3	46	1.2	AV	L1	GND
2.150000	42.00	11.4	46	4.0	AV	L1	GND
2.510000	36.40	11.4	46	9.6	AV	L1	GND

**SCAN TABLE: "Voltage (9K-30M) FIN"**

Short Description: 150K-30M Voltage



**MEASUREMENT RESULT: "CTL190619417\_fin"**

2019-6-19 05:12??

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.716000	40.40	11.2	56	15.6	QP	N	GND
1.076000	42.20	11.3	56	13.8	QP	N	GND
1.430000	42.80	11.3	56	13.2	QP	N	GND
1.790000	43.60	11.3	56	12.4	QP	N	GND
2.150000	42.60	11.4	56	13.4	QP	N	GND
2.504000	40.80	11.4	56	15.2	QP	N	GND

**MEASUREMENT RESULT: "CTL190619417\_fin2"**


2019-6-19 05:12??

Frequency MHz	Level dBµV	Transd dB	Limit dBµV	Margin dB	Detector	Line	PE
0.716000	36.10	11.2	46	9.9	AV	N	GND
1.076000	37.90	11.3	46	8.1	AV	N	GND
1.430000	38.20	11.3	46	7.8	AV	N	GND
1.790000	39.50	11.3	46	6.5	AV	N	GND
2.150000	37.20	11.4	46	8.8	AV	N	GND
2.504000	33.00	11.4	46	13.0	AV	N	GND


### 4.2. Radiated Emission

#### TEST CONFIGURATION

Radiated Emission Test Set-Up  
Frequency range 9KHz – 30MHz



Frequency range 30MHz – 1000MHz



**TEST PROCEDURE**

- 1 The EUT was placed on a turn table which is 0.8m above ground plane.
- 2 Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0 degree to 360 degrees to acquire the highest emissions from EUT
- 3 And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 4 Repeat above procedures until all frequency measurements have been completed.

**Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

For example

Frequency (MHz)	FS (dB $\mu$ V/m)	RA (dB $\mu$ V/m)	AF (dB)	CL (dB)	AG (dB)	Transd (dB)
300.00	40	58.1	12.2	1.6	31.90	-18.1

$$\text{Transd} = \text{AF} + \text{CL} - \text{AG}$$

**RADIATION LIMIT**

Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

**9k~30MHz:**

Frequency Range (MHz)	E-field Strength Limit @ 30m (mV/m)	E-field Strength Limit @ 3m (dB $\mu$ V/m)
0.009-0.490	2400/F(kHz)	129-94
0.490-1.705	24000/F(kHz)	74-63
1.705-30	30	70

Note: Where the limits have been defined at one distance, and a signal level measured at another, the limits have been extrapolated using the following formula:

$$\text{Extrapolation(dB)} = 40 \log_{10} (\text{Measurement Distance} / \text{Specification Distance})$$

Note:

- (1) The tighter limit shall apply at the edge between two frequency bands.
- (2) dBuV/m = 20\*log(uV/m)

**30M~1GHz:**

Frequency (MHz)	Distance (Meters)	Radiated (dB $\mu$ V/m)	Radiated ( $\mu$ V/m)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

**Note:**

- (1) The tighter limit shall apply at the edge between two frequency bands.
- (2) Distance refers to the distance in meters between the test instrument antenna and the closest point of any part of the E.U.T.

**TEST RESULTS**

Remark: The charger support DC 5V/2A input and DC9V/2A input two modes. Only the worst case DC9V/2A input was report.

**WORST-CASE RADIATED EMISSION BELOW 30 MHz**


Frequency (MHz)	Reading (dB $\mu$ V/m)	Polar Loop	Antenna Factor (dB/m)	Cable Loss (dB)	Emission Levels (dB $\mu$ V/m)	Limits at 3m (dB $\mu$ V/m)	Detector Mode
0.123(F)	56.40	Loop	23.64	0.01	80.05	105.81	PK
0.123(F)	50.86	Loop	23.64	0.01	74.51	85.81	AV
0.110	35.29	Loop	23.55	0.01	58.85	106.78	PK
0.110	33.88	Loop	23.55	0.01	57.44	86.78	AV
0.757	33.65	Loop	25.07	-0.17	58.55	70.02	QP
1.339	31.46	Loop	27.12	-0.25	58.33	65.07	QP
1.806	30.37	Loop	23.91	-0.24	54.04	70.00	QP

- Remark:
1. Data of measurement within this frequency range shown “-” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
  2. The test limit distance is 3m limit.
  3. PK means Peak Value, QP means Quasi Peak Value, AV means Average Value.
  4. F means Fundamental Frequency.

**Radiated Emission Test Data 30-1000MHz:**

***SWEEP TABLE: "test (30M-1G)"***

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	VULB9168



***MEASUREMENT RESULT: "CTL190618408\_red"***


2019-6-18 9:27

Frequency MHz	Level dB/m	Transd dB	Limit dB/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
33.880000	24.60	14.0	40.0	15.4	---	0.0	0.00	HORIZONTAL
57.160000	18.70	13.6	40.0	21.3	---	0.0	0.00	HORIZONTAL
109.540000	40.60	12.0	43.5	2.9	---	0.0	0.00	HORIZONTAL
191.020000	27.10	11.5	43.5	16.4	---	0.0	0.00	HORIZONTAL
538.280000	24.20	18.9	46.0	21.8	---	0.0	0.00	HORIZONTAL
827.340000	30.20	22.9	46.0	15.8	---	0.0	0.00	HORIZONTAL



**SWEEP TABLE: "test (30M-1G)"**

Short Description:		Field Strength			
Start	Stop	Detector	Meas. Time	IF Bandw.	Transducer
30.0 MHz	1.0 GHz	MaxPeak	300.0 ms	120 kHz	VULB9168




**MEASUREMENT RESULT: "CTL190618409\_red"**

2019-6-18 9:29

Frequency MHz	Level dB/m	Transd dB	Limit dB/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	33.20	13.9	40.0	6.8	---	0.0	0.00	VERTICAL
51.340000	32.10	14.1	40.0	7.9	---	0.0	0.00	VERTICAL
55.220000	24.00	13.8	40.0	16.0	---	0.0	0.00	VERTICAL
109.540000	42.20	12.0	43.5	1.3	---	0.0	0.00	VERTICAL
146.400000	29.90	15.0	43.5	13.6	---	0.0	0.00	VERTICAL
192.960000	28.90	11.4	43.5	14.6	---	0.0	0.00	VERTICAL

### 4.3. 20dB Bandwidth/99% Bandwidth

#### TEST CONFIGURATION



#### TEST PROCEDURE


The bandwidth of the fundamental frequency was measured by spectrum analyzer with 10Hz RBW and 30Hz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

#### LIMIT

The 20dB bandwidth shall be less than 80% of the permitted frequency band.

#### TEST RESULTS

PASS




### 5. Test Setup Photos of the EUT













Internal photos



Loop Antenna





.....End of Report.....