



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 1 of 27

**Applicant** : RMS International (USA) Inc.  
39 High Street, North Andover, Massachusetts, USA 01845

**Supplier / Manufacturer** : RMS International (USA) Inc.  
39 High Street, North Andover, Massachusetts, USA 01845

**Description of Sample(s)** : Submitted sample(s) said to be  
Product: Sonic Flyer  
Brand Name: N/A  
Model No.: US72-1292/MEN, SKU#2756219  
FCC ID: 2ATYAUS72-1292

**Date Samples Received** : 2023-11-10

**Date Tested** : 2023-11-10 to 2023-11-15

**Investigation Requested** : Perform ElectroMagnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 and ANSI C63.10: 2013 for FCC Certification.

**Conclusions** : The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.

**Remarks** : ---

  
  
Dr.CHAN Kwok Hung, Brian  
Authorized Signatory



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 2 of 27

### CONTENT:

Cover	Page 1 of 27	
Content	Page 2 of 27	
<b><u>1.0</u></b>	<b><u>General Details</u></b>	
1.1	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 27
1.2	RF Module Details	Page 3 of 27
1.3	Antenna Details	Page 3 of 27
1.4	Date of Order	Page 3 of 27
1.5	Submitted Sample(s)	Page 3 of 27
1.6	Test Duration	Page 3 of 27
1.7	Country of Origin	Page 3 of 27
1.8	Channel List	Page 4 of 27
<b><u>2.0</u></b>	<b><u>Technical Details</u></b>	
2.1	Investigations Requested	Page 5 of 27
2.2	Test Standards and Results Summary	Page 5 of 27
<b><u>3.0</u></b>	<b><u>Test Results</u></b>	
3.1	Emission	Page 6-26 of 27
<b><u>Appendix A</u></b>		
	List of Measurement Equipment	Page 24 of 27
<b><u>Appendix B</u></b>		
	Photograph(s) of Product	Page 25-27 of 27





## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 4 of 27

### 1.8 Channel List

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2408	27	2435	54	2462
1	2409	28	2436	55	2463
2	2410	29	2437	56	2464
3	2411	30	2438	57	2465
4	2412	31	2439	58	2466
5	2413	32	2440	59	2467
6	2414	33	2441	60	2468
7	2415	34	2442	61	2469
8	2416	35	2443	62	2470
9	2417	36	2444	63	2471
10	2418	37	2445	64	2472
11	2419	38	2446	65	2473
12	2420	39	2447	66	2474
13	2421	40	2448	67	2475
14	2422	41	2449		
15	2423	42	2450		
16	2424	43	2451		
17	2425	44	2452		
18	2426	45	2453		
19	2427	46	2454		
20	2428	47	2455		
21	2429	48	2456		
22	2430	49	2457		
23	2431	50	2458		
24	2432	51	2459		
25	2433	52	2460		
26	2434	53	2461		

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 5 of 27

### **2.0 Technical Details**

#### **2.1 Investigations Requested**

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15 Regulations and ANSI C63.10: 2013 for FCC Certification.  
The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level.

#### **2.2 Test Standards and Results Summary Tables**

EMISSION Results Summary						
Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Field Strength of Fundamental & Harmonics Emissions	FCC 47CFR 15.249	ANSI C63.10: 2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Radiated Emissions	FCC 47CFR 15.209 FCC 47CFR 15.205	ANSI C63.10: 2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.10: 2013	N/A	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
20dB Emission bandwidth	FCC 47CFR 15.215(c)	ANSI C63.10: 2013	N/A	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Note: N/A - Not Applicable



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 6 of 27

### **3.0 Test Results**

#### **3.1 Emission**

##### **3.1.1 Radiated Emissions**

Ambient temperature 25°C

Relative humidity 57%

Test Requirement: FCC 47CFR 15.249 & FCC 47CFR 15.209

Test Method: ANSI C63.10:2013

Test Date: 2023-11-10 to 2023-11-14

Mode of Operation: Tx mode

#### **Test Method:**

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber\*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber\*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

\* Semi-Anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd. with Registration Number: HK0001  
Test Firm Registration Number: 367672

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

## Test Report


Date : 2023-11-17  
No. : HMD23110011

Page 7 of 27

### Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW: 10kHz VBW: 30kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
30MHz – 1GHz (QP)	RBW: 120kHz VBW: 120kHz Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold
Above 1GHz (Pk & Av) (Other than Fundamental Emissions)	RBW: 1MHz VBW: 1MHz  Sweep: Auto Span: Fully capture the emissions being measured Trace: Max. hold

### Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 8 of 27

### Limits for Field Strength of Fundamental & Harmonics Emissions [FCC 47CFR 15.249]:

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [microvolts/meter]	Field Strength of Harmonics Emission [microvolts/meter]
902-928	50,000 [Quasi-Peak]	500 [Average]
2400-2483.5	50,000 [Average]	500 [Average]

#### Remarks:

No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz

Calculated measurement uncertainty  
(9kHz-30MHz): 2.0dB  
(30MHz -1GHz): 4.9dB  
(1GHz -6GHz): 4.02dB  
(6GHz -26.5GHz): 4.03dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.





## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 9 of 27

**Results of Tx mode (Lowest Frequency Channel-2408 MHz): Pass**

<b>Field Strength of Fundamental Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2408.00	91.4	-4.8	86.6	21,256.9	500,000	Vertical
2408.00	98.2	-4.7	93.5	47,315.1	500,000	Horizontal

<b>Field Strength of Fundamental Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2408.00	75.2	-4.8	70.4	3,322.8	50,000	Vertical
2408.00	81.5	-4.7	76.8	6,918.3	50,000	Horizontal

<b>Field Strength of Harmonics Emission</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4816.0	54.9	0.8	55.7	609.5	5,000	Vertical
4816.0	55.1	0.5	55.6	602.6	5,000	Horizontal
7224.0	48.5	7.0	55.5	595.7	5,000	Vertical
7224.0	48.7	6.5	55.2	575.4	5,000	Horizontal
9632.0	45.8	8.5	54.3	518.8	5,000	Vertical
9632.0	45.7	8.3	54.0	501.2	5,000	Horizontal
12040.0	45.2	10.9	56.1	638.3	5,000	Vertical
12040.0	44.9	10.8	55.7	609.5	5,000	Horizontal



## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 10 of 27

<b>Field Strength of Harmonics Emission</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4816.0	40.0	0.8	40.8	109.6	500	Vertical
4816.0	39.6	0.5	40.1	101.2	500	Horizontal
7224.0	33.7	7.0	40.7	108.4	500	Vertical
7224.0	33.1	6.5	39.6	95.5	500	Horizontal
9632.0	32.8	8.5	41.3	116.1	500	Vertical
9632.0	32.7	8.3	41.0	112.2	500	Horizontal
12040.0	30.9	10.9	41.8	123.0	500	Vertical
12040.0	30.8	10.8	41.6	120.2	500	Horizontal

**Results of Tx mode (Middle Frequency Channel- 2440MHz): Pass**

<b>Field Strength of Fundamental Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2440.00	95.0	-4.8	90.2	32,508.7	500,000	Vertical
2440.00	99.2	-4.7	94.5	53,088.4	500,000	Horizontal

<b>Field Strength of Fundamental Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2440.00	80.0	-4.8	75.2	5,754.4	50,000	Vertical
2440.00	84.3	-4.7	79.6	9,549.9	50,000	Horizontal



## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 11 of 27

<b>Field Strength of Harmonics Emission</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4880.0	54.8	0.8	55.6	605.3	5,000	Vertical
4880.0	55.6	0.5	56.1	638.3	5,000	Horizontal
7320.0	48.9	7.0	55.9	623.7	5,000	Vertical
7320.0	48.6	6.5	55.1	568.9	5,000	Horizontal
9760.0	46.3	8.5	54.8	549.5	5,000	Vertical
9760.0	46.8	8.3	55.1	568.9	5,000	Horizontal
12200.0	44.9	10.9	55.8	616.6	5,000	Vertical
12200.0	45.3	10.8	56.1	638.3	5,000	Horizontal

<b>Field Strength of Harmonics Emission</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4880.0	40.1	0.8	40.9	111.2	500	Vertical
4880.0	40.5	0.5	41.0	112.2	500	Horizontal
7320.0	33.6	7.0	40.6	107.2	500	Vertical
7320.0	32.9	6.5	39.4	93.3	500	Horizontal
9760.0	31.0	8.5	39.5	94.4	500	Vertical
9760.0	31.9	8.3	40.2	102.3	500	Horizontal
12200.0	30.9	10.9	41.8	123.0	500	Vertical
12200.0	30.7	10.8	41.5	118.9	500	Horizontal

**Results of Tx mode (Highest Frequency Channel – 2475MHz): Pass**

<b>Field Strength of Fundamental Emissions</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2475.00	95.1	-4.8	90.3	32,809.5	500,000	Vertical
2475.00	99.8	-4.7	95.1	56,754.5	500,000	Horizontal



## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 12 of 27

<b>Field Strength of Fundamental Emissions</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
2475.00	80.1	-4.8	75.3	5,821.0	50,000	Vertical
2475.00	85.3	-4.7	80.6	10,715.2	50,000	Horizontal

<b>Field Strength of Harmonics Emission</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4950.0	54.8	0.8	55.6	603.9	5,000	Vertical
4950.0	55.8	0.5	56.3	653.1	5,000	Horizontal
7425.0	48.2	7.0	55.2	575.4	5,000	Vertical
7425.0	49.1	6.5	55.6	602.6	5,000	Horizontal
9900.0	47.0	8.5	55.5	595.7	5,000	Vertical
9900.0	47.1	8.3	55.4	588.8	5,000	Horizontal
12735.0	44.9	10.9	55.8	616.6	5,000	Vertical
12735.0	45.1	10.8	55.9	623.7	5,000	Horizontal

<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V/m	Correction Factor dB $\mu$ V/m	Field Strength dB $\mu$ V/m	Field Strength $\mu$ V/m	Limit @3m $\mu$ V/m	E-Field Polarity
4950.0	40.1	0.8	40.9	111.2	500	Vertical
4950.0	39.6	0.5	40.1	101.2	500	Horizontal
7425.0	33.6	7.0	40.6	107.2	500	Vertical
7425.0	33.3	6.5	39.8	97.7	500	Horizontal
9900.0	31.2	8.5	39.7	96.6	500	Vertical
9900.0	31.1	8.3	39.4	93.3	500	Horizontal
12735.0	30.6	10.9	41.5	118.9	500	Vertical
12735.0	30.8	10.8	41.6	120.2	500	Horizontal



## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 13 of 27

**Radiated Emissions Measurement:**

**Limit :**

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

**Result: RF Radiated Emissions (1GHz-26GHz) (Lowest)**

<b>Field Strength of Band-edge Compliance</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
2400.0	59.6	-4.8	54.8	74.0	19.2	Vertical
2400.0	67.6	-4.7	62.9	74.0	11.1	Horizontal

<b>Field Strength of Band-edge Compliance</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
2400.0	51.4	-4.8	46.6	54.0	7.5	Vertical
2400.0	54.2	-4.7	49.5	54.0	4.5	Horizontal

**Result: RF Radiated Emissions (1GHz-26GHz) (Highest)**

<b>Field Strength of Band-edge Compliance</b>						
<b>Peak Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
2483.5	57.3	-4.8	52.5	74.0	21.5	Vertical
2483.5	65.3	-4.7	60.6	74.0	13.4	Horizontal


<b>Field Strength of Band-edge Compliance</b>						
<b>Average Value</b>						
Frequency MHz	Measured Level @3m dB $\mu$ V	Correction Factor dB/m	Field Strength dB $\mu$ V/m	Limit @3m dB $\mu$ V/m	Margin dB $\mu$ V/m	E-Field Polarity
2483.5	49.6	-4.8	44.8	54.0	9.2	Vertical
2483.5	51.8	-4.7	47.1	54.0	6.9	Horizontal

## Test Report


Date : 2023-11-17  
No. : HMD23110011

Page 14 of 27

Emissions radiated outside of the specified frequency bands (Lowest)  
Horizontal



Vertical




## Test Report

Date : 2023-11-17  
No. : HMD23110011


Page 15 of 27

### Emissions radiated outside of the specified frequency bands (Highest)

Horizontal



Vertical





## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 16 of 27

### Limits for Radiated Emissions [FCC 47 CFR 15.209 Class B]:

Frequency Range [MHz]	Quasi-Peak Limits [ $\mu$ V/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

#### Remarks:

Calculated measurement uncertainty (9kHz-30MHz): 2.0dB / (30MHz – 1GHz): 4.9dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

#### Results of TX mode (9kHz – 30MHz): PASS

Emissions detected are more than 20 dB below the FCC Limits

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.






## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 17 of 27

Results of TX mode (30MHz – 1GHz)(2402MHz worst case): PASS  
 Horizontal



Ambient Temperature: 26.3C  
 Relative Humidity : 54.7%  
 Air Pressure : 100.9kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	30.638	30.50	40.00	-9.50	Peak	Horizontal
2	32.179	29.08	40.00	-10.92	Peak	Horizontal
3	111.347	19.92	43.50	-23.58	Peak	Horizontal
4	210.786	23.91	43.50	-19.59	Peak	Horizontal
5	482.216	32.91	46.00	-13.09	Peak	Horizontal
6	661.151	36.93	46.00	-9.07	Peak	Horizontal




## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 18 of 27

**Results of TX mode (30MHz – 1GHz) (2402MHz worst case): PASS**

Vertical



Ambient Temperature: 26.3C  
 Relative Humidity : 54.7%  
 Air Pressure : 100.9kPa

	Freq	Level	Limit	Over	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB		
1	33.095	27.29	40.00	-12.71	Peak	Vertical
2	38.078	26.20	40.00	-13.80	Peak	Vertical
3	47.326	24.63	40.00	-15.37	Peak	Vertical
4	158.112	21.21	43.50	-22.29	Peak	Vertical
5	468.876	31.49	46.00	-14.51	Peak	Vertical
6	719.200	36.73	46.00	-9.27	Peak	Vertical



## Test Report

**Date : 2023-11-17**  
**No. : HMD23110011**

**Page 19 of 27**

### **3.1.2 Antenna Requirement**

Ambient temperature 25°C

Relative humidity 57%

**Test Requirements: § 15.203**

#### **Test Specification:**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### **Test Results:**

This is Linear antenna. There is no external antenna, the antenna gain =0dBi. User is unable to remove or changed the Antenna.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@stc.group](mailto:hkstc@stc.group) Website: [www.stc.group](http://www.stc.group)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 20 of 27

### 3.1.3 20dB Bandwidth of Fundamental Emission

Ambient temperature 25°C

Relative humidity 57%

Test Requirement: FCC 47 CFR 15.249  
Test Method: ANSI C63.10:2013  
Test Date: 2023-11-15  
Mode of Operation: Tx mode

#### **Test Method:**

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

The measurement bandwidth settings are RBW = 30 kHz  
VBW = 100 kHz

#### **Test Setup:**

As Test Setup of clause 3.1.1 in this test report.

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.




## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 21 of 27

**Limits for 20dB Bandwidth of Fundamental Emission (Low Frequency Channel):**

Frequency Range [MHz]	20dB Bandwidth [MHz]
2408.0	4.725






## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 22 of 27

**Limits for 20dB Bandwidth of Fundamental Emission (Middle Frequency Channel):**

Frequency Range [MHz]	20dB Bandwidth [MHz]
2440.0	4.800






## Test Report

Date : 2023-11-17  
 No. : HMD23110011

Page 23 of 27

**Limits for 20dB Bandwidth of Fundamental Emission (High Frequency Channel):**

Frequency Range [MHz]	20dB Bandwidth [MHz]
2475.0	3.953





## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 24 of 27

### Appendix A

#### List of Measurement Equipment

##### Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2019-04-16	2024-04-16
EM356	ANTENNA POSITIONING TOWER	ETS-LINDGREN	2171B	00150346	N/A	N/A
EM293	SPECTRUM ANALYZER	AGILENT TECHNOLOGIES	N9020A	MY50510152	2023-03-21	2024-03-21
EM299	BROADBAND HORN ANTENNA	ETS-LINDGREN	3115	00114120	2023-01-25	2025-01-25
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2023-01-16	2025-01-16
EM301	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-10	00130988	2023-02-15	2025-02-15
EM353	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2022-09-26	2024-09-26
EM355	BICONILOG ANTENNA	ETS-LINDGREN	3143B	00094856	2022-08-26	2024-08-26
EM200	DUAL CHANNEL POWER METER	R & S	NRVD	100592	2023-08-02	2025-08-02
EM012	PRE-AMPLIFIER	HP	HP8448B	3008A00262	2022-11-08	2025-11-08
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A

Remarks:-

N/A Not Applicable or Not Available

The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: hkstc@stc.group Website: www.stc.group

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.



## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 25 of 27

### Appendix B

#### Photographs of EUT

**View of the product**



**View of the product**




**Inside View of the product**




**Inner Circuit Top View**



**Inner Circuit Bottom View**



**Inner Circuit Top View**



## Test Report

Date : 2023-11-17  
No. : HMD23110011


Page 26 of 27

### Photographs of EUT

**Measurement of Radiated Emission Test Set Up(9kHz – 30MHz)**



**Measurement of Radiated Emission Test Set Up(30MHz to 1000MHz)**



The Hong Kong Standards and Testing Centre Limited

10 Dai Wang Street, Taipo Industrial Estate, Tai Po, N.T., Hong Kong

Tel: +852 2666 1888 Fax: +852 2664 4353 Email: [hkstc@stc.group](mailto:hkstc@stc.group) Website: [www.stc.group](http://www.stc.group)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.

For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.


## Test Report

Date : 2023-11-17  
No. : HMD23110011

Page 27 of 27

### Photographs of EUT

**Measurement of Radiated Emission Test Set Up(Above 1000MHz)**



\*\*\*\*\* End of Test Report \*\*\*\*\*

## Conditions of Issuance of Test Reports

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the “Company”) solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the “Clients”).
2. Any report issued by the Company as a result of this application for testing service (the “Report”) shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. Subject to clause 3, the Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.
3. The Company shall be at liberty to disclose the testing-related documents and/or files anytime to any third-party accreditation and/or recognition bodies for audit or other related purposes. No liabilities whatsoever shall attach to the Company's act of disclosure.
4. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.
5. The results in Report apply only to the sample as received and do not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.
6. When a statement of conformity to a specification or standard is provided, the ILAC-G8 Guidance document (and/or IEC Guide 115 in the electrotechnical sector) will be adopted as a decision rule for the determination of conformity unless it is inherent in the requested specification or standard, or otherwise specified in the Report.
7. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.
8. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.
9. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.
10. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.
11. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.
12. Issuance records of the Report are available on the internet at [www.stc.group](http://www.stc.group). Further enquiry of validity or verification of the Reports should be addressed to the Company.