



TEST REPORT

Applicant: Shenzhen Youmi Intelligent Technology Co., Ltd.

Address: 406-407 Jinqi Zhigu Building, 4/F, 1 Tangling Road, Nanshan District, Shenzhen City, China

FCC ID: 2ATZ4-G5TAB

IC: 26074-G5TAB

HVIN: T30-T616-G5TAB

Product Name: Smart Tablet Computer

Standard(s): 47 CFR Part 2, 47 CFR Part 22, Subpart H

47 CFR Part 24, Subpart E

47 CFR Part 27

RSS-130 Issue 2, February 2019

RSS-132 Issue 4, January 31, 2023

RSS-133 Issue 6, January 2018, Amendment

RSS-199 Issue 4, July 2023

RSS-Gen, Issue 5, February 2021 Amendment 2

ANSI C63.26-2015

The above equipment has been tested and found compliant with the requirement of the relative standards by China Certification ICT Co., Ltd (Dongguan)

Report Number: CR230846390-00E

Date Of Issue: 2023/10/17

Reviewed By: Calvin Chen

Calvin Chen

Title: RF Engineer

Approved By: Sun Zhong

Sun Zhong

Title: Manager

Test Laboratory: China Certification ICT Co., Ltd (Dongguan)

No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China

Tel: +86-769-82016888

Test Facility

The Test site used by China Certification ICT Co., Ltd (Dongguan) to collect test data is located on the No. 113, Pingkang Road, Dalang Town, Dongguan, Guangdong, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 442868, the FCC Designation No. : CN1314.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0123.

Declarations

China Certification ICT Co., Ltd (Dongguan) is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with a triangle symbol “▲”. Customer model name, addresses, names, trademarks etc. are not considered data.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

This report cannot be reproduced except in full, without prior written approval of the Company.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report may contain data that are not covered by the accreditation scope and shall be marked with an asterisk “★”.

CONTENTS

TEST FACILITY	2
DECLARATIONS.....	2
DOCUMENT REVISION HISTORY	6
1. GENERAL INFORMATION	7
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	7
1.2 DESCRIPTION OF TEST CONFIGURATION.....	8
1.2.2 Support Equipment List and Details	11
1.2.3 Support Cable List and Details	12
1.2.4 Block Diagram of Test Setup.....	13
1.3 MEASUREMENT UNCERTAINTY	14
2. SUMMARY OF TEST RESULTS	15
3. REQUIREMENTS AND TEST PROCEDURES	17
3.1 Applicable Standard For Part 22 Subpart H:.....	17
3.1.1 RF Output Power	17
3.1.2 Spurious Emissions.....	17
3.1.3 Frequency stability.....	17
3.2 Applicable Standard For Part 24 Subpart E:.....	19
3.2.1 RF Output Power	19
3.2.2 Spurious Emissions.....	19
3.2.3 Frequency stability.....	19
3.3 Applicable Standard For Part 27:.....	20
3.3.1 RF Output Power	20
3.3.2 Spurious Emissions.....	20
3.3.3 Frequency stability.....	22
3.4 APPLICABLE STANDARD FOR RSS-130 ISSUE 2, FEBRUARY 2019:	23
3.4.1 Types of modulation	23
3.4.1.1 Applicable Standard.....	23
3.4.1.2 Judgment.....	23
3.4.2 Frequency block.....	23
3.4.2.1 Applicable Standard.....	23
3.4.2.2 Judgment.....	23
3.4.3 Interoperability requirement	23
3.4.3.1 Applicable Standard.....	23
3.4.3.2 Judgment.....	23
3.4.4 Transmitter frequency stability	23
3.4.4.1 Applicable Standard.....	23
3.4.5 Transmitter output power and effective radiated power (e.r.p.).....	24
3.4.5.1 Applicable Standard.....	24
3.4.6 Transmitter unwanted emissions.....	24
3.4.5.1 Applicable Standard.....	24
3.5 APPLICABLE STANDARD FOR RSS-132 ISSUE 4, JANUARY 31, 2023:	25

3.5.1 Frequency Sub-bands.....	25
3.5.1.1 Applicable Standard.....	25
3.5.1.2 Judgment.....	25
3.5.2 Types of Modulation.....	25
3.5.2.1 Applicable Standard.....	25
3.5.2.2 Judgment.....	25
3.5.3 Frequency stability.....	25
3.5.3.1 Applicable Standard.....	25
3.5.4 Transmitter output power and effective radiated power (e.r.p.).....	26
3.5.4.1 Applicable Standard.....	26
3.5.5 Transmitter unwanted emissions.....	26
3.5.5.1 Applicable Standard.....	26
3.6 APPLICABLE STANDARD FOR RSS-133 ISSUE 6, JANUARY 2018 AMENDMENT:	27
3.6.1 Frequency Plan	27
3.6.1.1 Applicable Standard.....	27
3.6.1.2 Judgment.....	27
3.6.2 Types of Modulation.....	27
3.6.2.1 Applicable Standard.....	27
3.6.2.2 Judgment.....	27
3.6.3 Frequency stability.....	27
3.6.3.1 Applicable Standard.....	27
3.6.4 Transmitter Output Power and Equivalent Isotropically Radiated Power	27
3.6.4.1 Applicable Standard.....	27
3.6.5 Transmitter unwanted emissions.....	28
3.6.5.1 Applicable Standard.....	28
3.6.6 Receiver Spurious Emissions.....	28
3.6.6.1 Applicable Standard.....	28
3.7 APPLICABLE STANDARD FOR RSS-199 ISSUE 4 JULY 2023:	29
3.7.1 Types of Modulation.....	29
3.7.1.1 Applicable Standard.....	29
3.7.1.2 Judgment.....	29
3.7.2 Band plan	29
3.7.2.1 Applicable Standard.....	29
3.7.2.2 Judgment.....	29
3.7.3 Frequency stability.....	29
3.7.3.1 Applicable Standard.....	29
3.7.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.)	30
3.7.4.1 Applicable Standard.....	30
3.7.5 Transmitter unwanted emissions.....	30
3.7.5.1 Applicable Standard.....	30
3.8 Test Method:	31
3.8.1 Transmitter output power, e.r.p. and e.i.r.p.....	31
Test Setup Block:.....	31
3.8.2 Occupied Bandwidth.....	32
Test Setup Block:.....	32
3.8.3 Transmitter unwanted emissions-at antenna terminals	33
Test Setup Block:.....	33
3.8.4 Transmitter unwanted emissions-Out of band emission	34
Test Setup Block:.....	34
3.8.5 Frequency stability.....	35
Test Setup Block:.....	35
3.8.6 Transmitter unwanted emissions- Radiated Spurious emissions.....	36
4. Test DATA AND RESULTS	38
4.1 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 850 BAND:.....	38

4.2 ANTENNA PORT TEST DATA AND RESULTS FOR GSM 1900 BAND:	45
4.3 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 2:	52
4.4 ANTENNA PORT TEST DATA AND RESULTS FOR WCDMA BAND 5:	61
4.5 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 2.....	70
4.6 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 5.....	91
4.7 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 7.....	107
4.8 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 12.....	123
4.9 ANTENNA PORT TEST DATA AND RESULTS FOR LTE BAND 41.....	139
4.10 RADIATED SPURIOUS EMISSIONS.....	155
4.11 RECEIVER SPURIOUS EMISSIONS.....	165
5. EUT PHOTOGRAPHS	178
6. TEST SETUP PHOTOGRAPHS	179

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
1.0	CR230846390-00E	Original Report	2023/10/17

1. GENERAL INFORMATION

1.1 Product Description for Equipment under Test (EUT)

EUT Name:	Smart Tablet Computer
Trade Name:	UMIDIGI
EUT Model:	G5 Tab
Multiple Models:	G5 Tab Kids
Operation Bands and modes:	GSM/GPRS: 850/1900 WCDMA: Band 2/5 LTE: Band 2/5/7/12/41
Modulation Type:	GMSK, 8PSK, BPSK, QPSK, 16QAM
Rated Input Voltage:	DC 3.8V from battery or 5V from adapter
Serial Number:	29PD-1,29PD-2
EUT Received Date:	2023/8/1
EUT Received Status:	Good

Operation Voltage(V_{DC}) ▲:

Lowest:	3.45	Normal:	3.8	Highest:	4.4
---------	------	---------	-----	----------	-----

Transmission Antenna Information▲:

Antenna	Antenna Manufacturer	Antenna Type	Operation Bands	Antenna Frequency Range (MHz)	Antenna Gain (G _T) (dBi)	L _c (dB)
WWAN Main Antenna	ANWEI communication Equipment Co.,Ltd	FPC	GSM850	824-849	-6.8	0.1
			PCS1900	1850-1910	0.34	0.2
			WCDMA B2	1850-1910	0.34	0.2
			WCDMA B5	824-849	-6.8	0.1
			LTE B2	1850-1910	0.34	0.2
			LTE B5	824-849	-6.8	0.1
			LTE B7	2500-2570	2.24	0.2
			LTE B12	699-716	-9.2	0.1
			LTE B41	2535-2655	2.24	0.3

Note:

Lc= Signal Attenuation in the connecting cable between the transmitter and antenna, in dB.

1.2 Description of Test Configuration

1.2.1 EUT Operation Condition:

EUT Operation Mode:	The system was configured for testing in each operation mode.
Equipment Modifications:	No
EUT Exercise Software:	No
The maximum power was configured per 3GPP Standard for each operation modes as below setting:	
GSM/GPRS	
Function:	Menu select > GSM Mobile Station > GSM 850/1900
Press Connection control to choose the different menus	
Press RESET > choose all the reset all settings	
Connection	Press Signal Off to turn off the signal and change settings
Network Support	> GSM + GPRS or GSM + EGSM
Main Service	> Packet Data
Service selection	> Test Mode A – Auto Slot Config, off
MS Signal	Press Slot Config Bottom on the right twice to select and change the number of time slots and power setting
	> Slot configuration > Uplink/Gamma
	> 33 dBm for GPRS 850
	> 30 dBm for GPRS 1900
	> 27 dBm for EGPRS 850
	> 26 dBm for EGPRS 1900
BS Signal	Enter the same channel number for TCH channel (test channel) and BCCH channel
Frequency Offset >	+ 0 Hz
Mode >	BCCH and TCH
BCCH Level >	-85 dBm (May need to adjust if link is not stable)
BCCH Channel >	choose desire test channel [Enter the same channel number for TCH channel (test channel) and BCCH channel]
Channel Type >	Off
P0 >	4 dB
Slot Config >	Unchanged (if already set under MS signal)
TCH >	choose desired test channel
Hopping >	Off
Main Timeslot >	3
Network	Coding Scheme > CS4 (GPRS)
Bit Stream >	2E9-1 PSR Bit Stream
AF/RF Connection	Enter appropriate offsets for Ext. Att. Output and Ext. Att. Input Press Signal on to turn on the signal and change settings

WCDMA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2		4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/ 5	0
HSDPA Specific Settings	β_{ec}	209/225	12/15	30 15	2/15	5/ 5
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
	PR(dB)	0	2	1	2	0
	DACK	8				
	DNAK	8				
HSUPA Specific Settings	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
HSUPA Specific Settings	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate k_ps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCI	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		

LTE (FDD):

The following tests were conducted according to the test requirements in 3GPP TS36.101

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

UE Power Class: 3 (23 +/- 2dBm). The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (NRBs)	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
..					
NS_32	*	*	*	*	*

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

LTE(TDD):

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	6592· T_s	2192· T_s	2560· T_s	7680· T_s	2192· T_s	2560· T_s
1	19760· T_s			20480· T_s		
2	21952· T_s			23040· T_s		
3	24144· T_s			25600· T_s		
4	26336· T_s			7680· T_s		
5	6592· T_s			20480· T_s	4384· T_s	5120· T_s
6	19760· T_s			23040· T_s		
7	21952· T_s			12800· T_s		
8	24144· T_s			-		
9	13168· T_s			-		

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Calculated Duty Cycle

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-point Periodicity	Subframe Number										Calculated Duty Cycle (%)
		0	1	2	3	4	5	6	7	8	9	
0	5 ms	D	S	U	U	U	D	S	U	U	U	63.33
1	5 ms	D	S	U	U	D	D	S	U	U	D	43.33
2	5 ms	D	S	U	D	D	D	S	U	D	D	23.33
3	10 ms	D	S	U	U	U	D	D	D	D	D	31.67
4	10 ms	D	S	U	U	D	D	D	D	D	D	21.67
5	10 ms	D	S	U	D	D	D	D	D	D	D	11.67
6	5 ms	D	S	U	U	U	D	S	U	U	D	53.33

Calculated Duty Cycle = Extended cyclic prefix in uplink x (T_s) x # of S + # of U

Example for Calculated Duty Cycle for Uplink-Downlink Configuration 0:

Calculated Duty Cycle = 5120 x [1/(15000 x 2048)] x 2 + 6 ms = 63.33%

where

 $T_s = 1/(15000 x 2048)$ seconds**1.2.2 Support Equipment List and Details**


Manufacturer	Description	Model	Serial Number
UMIDIGI	Adapter	HF-0502000U	Unknown
UMIDIGI	Adapter	HJ-0502000W2-US	Unknown
IPRO	Earphone	Phonenix 5.0s	EP221126001
Unknown	Antenna	Unknown	Unknown
R&S	Wideband Radio Communication Tester	CMW500	143458

1.2.3 Support Cable List and Details

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
Power Cable	NO	NO	1	Adapter	EUT
Earphone Cable	NO	NO	1.2	EUT	Earphone
Antenna Cable	NO	NO	1.2	CMW500	Antenna

1.2.4 Block Diagram of Test Setup

Spurious emissions:



1.3 Measurement Uncertainty

Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty. The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

Parameter	Measurement Uncertainty
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±0.61dB
Power Spectral Density, conducted	±0.61 dB
Unwanted Emissions, radiated	30M~200MHz: 4.15 dB, 200M~1GHz: 5.61 dB, 1G~6GHz: 5.14 dB, 6G~18GHz: 5.93 dB, 18G~26.5G: 5.47 dB, 26.5G~40G: 5.63 dB
Unwanted Emissions, conducted	±1.26 dB
Temperature	±1°C
Humidity	±5%
DC and low frequency voltages	±0.4%
Duty Cycle	1%
RF Frequency	±0.082×10 ⁻⁶

2. SUMMARY OF TEST RESULTS

Cellular Band: GSM 850/WCDMA Band 5/LTE Band 5:

FCC Standard Rule(s)	ISEDC Standard Rule(s)	Description of Test	Result	Section
/	RSS-132 Clause 5.1	Frequency Sub-bands	Compliant	3.5.1.2
/	RSS-132 Clause 5.2	Types of Modulation	Compliant	3.5.2.2
§ 2.1055, § 22.355	RSS-132 Clause 5.3	Frequency stability	Compliant	4.1, 4.4, 4.6
§ 2.1046; § 22.913	RSS-132 Clause 5.4	Transmitter output power and effective radiated power (e.r.p.)	Compliant	4.1, 4.4, 4.6
§ 2.1051, § 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions-at Antenna Terminal	Compliant	4.1, 4.4, 4.6
§ 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions-Out of band emission	Compliant	4.1, 4.4, 4.6
§ 2.1053, § 22.917 (a)	RSS-132 Clause 5.5	Transmitter unwanted emissions-Radiated Spurious emissions	Compliant	4.10
§ 2.1049; § 22.905	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant	4.1, 4.4, 4.6

PCS Band: GSM 1900/WCDMA Band 2/LTE Band 2:

FCC Standard Rule(s)	ISEDC Standard Rule(s)	Description of Test	Result	Section
/	RSS-133 Clause 6.1	Frequency Plan	Compliant	3.6.1.2
/	RSS-133 Clause 6.2	Types of Modulation	Compliant	3.6.2.2
§ 2.1055, § 24.235	RSS-133 Clause 6.3	Frequency stability	Compliant	4.2, 4.3, 4.5
§ 2.1046, § 24.232	RSS-133 Clause 6.4	Transmitter Output Power and Equivalent Isotropically Radiated Power	Compliant	4.2, 4.3, 4.5
§ 2.1051, § 24.238 (a)	RSS-133 Clause 6.5	Transmitter unwanted emissions-at Antenna Terminal	Compliant	4.2, 4.3, 4.5
§ 24.238 (a)	RSS-133 Clause 6.5	Transmitter unwanted emissions-Out of band emission	Compliant	4.2, 4.3, 4.5
§ 2.1053, § 24.238 (a)	RSS-133 Clause 6.5	Transmitter unwanted emissions-Radiated Spurious emissions	Compliant	4.11
/	RSS-133 Clause 6.6	Receiver Spurious Emissions	Compliant	4.2, 4.3, 4.5
§ 2.1049, § 24.238	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant	4.2, 4.3, 4.5

Lower 700: LTE Band 12:

FCC Standard Rule(s)	ISEDC Standard Rule(s)	Description of Test	Result	Section
/	RSS-130 Clause 4.2	Types of modulation	Compliant	3.4.1.2
/	RSS-130 Clause 4.3	Frequency block	Compliant	3.4.2.2
/	RSS-130 Clause 4.4	Interoperability requirement	Compliant	3.4.3.2
§ 2.1055, §27.54	RSS-130 Clause 4.5	Transmitter frequency stability	Compliant	4.8
§2.1046, §27.50	RSS-130 Clause 4.6	Transmitter output power and effective radiated power (e.r.p.)	Compliant	4.8
§ 2.1051,§27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- at Antenna Terminal	Compliant	4.8
§27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- Out of band emission	Compliant	4.8
§ 2.1053, §27.53	RSS-130 Clause 4.7	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	4.10
§ 2.1049, §27.53	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant	4.8

BRS/EBS Band: LTE Band 7/41:

FCC Standard Rule(s)	ISEDC Standard Rule(s)	Description of Test	Result	Section
/	RSS-199 Clause 5.2	Frequency Plan	Compliant	3.7.2.2
	RSS-199 Clause 5.3	Types of Modulation	Compliant	3.7.1.2
§ 2.1055, §27.54	RSS-199 Clause 5.4	Frequency stability	Compliant	4.7, 4.9
FCC§2.1046, §27.50	RSS-199 Clause 5.5	Transmitter Output Power and Equivalent Isotropically Radiated Power	Compliant	4.7, 4.9
FCC§ 2.1051,§27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- at Antenna Terminal	Compliant	4.7, 4.9
§27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- Out of band emission	Compliant	4.7, 4.9
§ 2.1053, §27.53	RSS-199 Clause 5.6	Transmitter unwanted emissions- Radiated Spurious emissions	Compliant	4.10
§ 2.1049, §27.53	RSS-Gen Clause 6.7	Occupied Bandwidth	Compliant	4.7, 4.9

3. REQUIREMENTS AND TEST PROCEDURES

3.1 Applicable Standard For Part 22 Subpart H:

3.1.1 RF Output Power

FCC §22.913

(a)(5) The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7watts.

(d) *Power measurement.* Measurement of the ERP of Cellular base transmitters and repeaters must be made using an average power measurement technique. The peak-toaverage ratio (PAR) of the transmission must not exceed 13 dB. Power measurements for base transmitters and repeaters must be made in accordance with either of the following:

- (1) A Commission-approved average power technique (*see* FCC Laboratory's Knowledge Database); or
- (2) For purposes of this section, peak transmit power must be measured over an interval of continuous transmission using instrumentation calibrated in terms of an rmsequivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, *etc.*, so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

3.1.2 Spurious Emissions

FCC §22.917

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a reference bandwidth as follows:

- (1) In the spectrum below 1 GHz, instrumentation should employ a reference bandwidth of 100 kHz or greater. In the 1 MHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy, provided that the measured power is integrated over the full required reference bandwidth (i.e., 100 kHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.
- (2) In the spectrum above 1 GHz, instrumentation should employ a reference bandwidth of 1 MHz

3.1.3 Frequency stability

FCC §22.355

Except as otherwise provided in this part, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table C-1 of this section.

Table C-1 - Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency range (MHz)	Base, fixed (ppm)	Mobile >3 watts (ppm)	Mobile ≤3 watts (ppm)
25 to 50	20	20	50
50 to 450	5	5	50
450 to 512	2.5	5	5
821 to 896	1.5	2.5	2.5
928 to 929	5	n/a	n/a
929 to 960	1.5	n/a	n/a
2110 to 2220	10	n/a	n/a

3.2 Applicable Standard For Part 24 Subpart E:

3.2.1 RF Output Power

FCC §24.232

(c)Mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications.

(d)Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of § 24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.2.2 Spurious Emissions

FCC §24.238

The rules in this section govern the spectral characteristics of emissions in the Broadband Personal Communications Service.

(a) Out of band emissions. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

(b) Measurement procedure. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. A narrower resolution bandwidth is permitted in all cases to improve measurement accuracy provided the measured power is integrated over the full required measurement bandwidth (i.e. 1 MHz or 1 percent of emission bandwidth, as specified). The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

(c) Alternative out of band emission limit. Licensees in this service may establish an alternative out of band emission limit to be used at specified band edge(s) in specified geographical areas, in lieu of that set forth in this section, pursuant to a private contractual arrangement of all affected licensees and applicants. In this event, each party to such contract shall maintain a copy of the contract in their station files and disclose it to prospective assignees or transferees and, upon request, to the FCC.

(d) Interference caused by out of band emissions. If any emission from a transmitter operating in this service results in interference to users of another radio service, the FCC may require a greater attenuation of that emission than specified in this section.

3.2.3 Frequency stability

FCC §24.235

The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.3 Applicable Standard For Part 27:

3.3.1 RF Output Power

FCC §27.50

(a)(3) *Mobile and portable stations.*

(i) For mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band, the average EIRP must not exceed 50 milliwatts within any 1 megahertz of authorized bandwidth, *except that* for mobile and portable stations compliant with 3GPP LTE standards or another advanced mobile broadband protocol that avoids concentrating energy at the edge of the operating band the average EIRP must not exceed 250 milliwatts within any 5 megahertz of authorized bandwidth but may exceed 50 milliwatts within any 1 megahertz of authorized bandwidth. For mobile and portable stations using time division duplexing (TDD) technology, the duty cycle must not exceed 38 percent in the 2305-2315 MHz and 2350-2360 MHz bands. Mobile and portable stations using FDD technology are restricted to transmitting in the 2305-2315 MHz band. Power averaging shall not include intervals in which the transmitter is off.

(ii) Mobile and portable stations are not permitted to transmit in the 2315-2320 MHz and 2345-2350 MHz bands.

(iii) *Automatic transmit power control.* Mobile and portable stations transmitting in the 2305-2315 MHz band or in the 2350-2360 MHz band must employ automatic transmit power control when operating so the stations operate with the minimum power necessary for successful communications.

(iv) *Prohibition on external vehicle-mounted antennas.* The use of external vehicle-mounted antennas for mobile and portable stations transmitting in the 2305-2315 MHz band or the 2350-2360 MHz band is prohibited.

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c)(10) Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d)(4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP. Fixed stations operating in the 1710-1755 MHz band are limited to a maximum antenna height of 10 meters above ground. Mobile and portable stations operating in these bands must employ a means for limiting power to the minimum necessary for successful communications.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile and other user stations. Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

3.3.2 Spurious Emissions

FCC §27.53

(a) For operations in the 2305-2320 MHz band and the 2345-2360 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power P (with averaging performed only during periods of transmission) within the licensed band(s) of operation, in watts, by the following amounts:

(4) For mobile and portable stations operating in the 2305-2315 MHz and 2350-2360 MHz bands:

(i) By a factor of not less than: $43 + 10 \log (P)$ dB on all frequencies between 2305 and 2320 MHz and on all frequencies between 2345 and 2360 MHz that are outside the licensed band(s) of operation, not less than $55 + 10 \log (P)$ dB on all frequencies between 2320 and 2324 MHz and on all frequencies between 2341 and 2345 MHz, not less than $61 + 10 \log (P)$ dB on all frequencies between 2324 and 2328 MHz and on all frequencies between 2337 and 2341 MHz, and not less than $67 + 10 \log (P)$ dB on all frequencies between 2328 and 2337 MHz;

(ii) By a factor of not less than $43 + 10 \log_10(P)$ dB on all frequencies between 2300 and 2305 MHz, $55 + 10 \log_10(P)$ dB on all frequencies between 2296 and 2300 MHz, $61 + 10 \log_10(P)$ dB on all frequencies between 2292 and 2296 MHz, $67 + 10 \log_10(P)$ dB on all frequencies between 2288 and 2292 MHz, and $70 + 10 \log_10(P)$ dB below 2288 MHz;

(iii) By a factor of not less than $43 + 10 \log_10(P)$ dB on all frequencies between 2360 and 2365 MHz, and not less than $70 + 10 \log_10(P)$ dB above 2365 MHz.

(c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

(1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log_10(P)$ dB;

(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log_10(P)$ dB;

(3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log_10(P)$ dB in a 6.25 kHz band segment, for base and fixed stations;

(4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log_10(P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;

(5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

(6) Compliance with the provisions of paragraphs (c)(3) and (c)(4) of this section is based on the use of measurement instrumentation such that the reading taken with any resolution bandwidth setting should be adjusted to indicate spectral energy in a 6.25 kHz segment.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and - 80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log_10(P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

(h) AWS emission limits

(1) **General protection levels.** Except as otherwise specified below, for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ dB.

(m)(4) For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.3.3 Frequency stability

FCC §27.54

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

3.4 Applicable Standard For RSS-130 Issue 2, February 2019:**3.4.1 Types of modulation****3.4.1.1 Applicable Standard**

RSS-130 clause 4.2

Equipment certified under this standard shall employ digital modulation

3.4.1.2 Judgment

Compliant, the device employs digital modulation.

3.4.2 Frequency block**3.4.2.1 Applicable Standard**

RSS-130 clause 4.3

The frequency bands 617-652 MHz, 663-698 MHz, 698-756 MHz and 777-787 MHz are divided into small frequency blocks as per SRSP-518. Equipment shall operate according to the frequency plan given in the SRSP.

3.4.2.2 Judgment

Compliant, the device operates in the frequency bands 663-698 MHz, 698-756 MHz and 777-787 MHz are divided into small frequency blocks as per SRSP-518. Equipment shall operate according to the frequency plan given in the SRSP.

3.4.3 Interoperability requirement**3.4.3.1 Applicable Standard**

RSS-130 clause 4.4

Mobile and portable stations in the bands 617-652 MHz and 663-698 MHz must be capable of operating on all frequencies in these bands.

3.4.3.2 Judgment

Compliant, the device employs all the range of 663-698MHz for this band.

3.4.4 Transmitter frequency stability**3.4.4.1 Applicable Standard**

RSS-130 clause 4.5

For equipment that is capable of transmitting numerous channels simultaneously for different applications (e.g. LTE and narrowband – internet of things (IoT)), the occupied bandwidth shall be the bandwidth representing the sum of the occupied bandwidths of these channels.

The frequency stability shall be sufficient to ensure that the occupied bandwidth remains within each frequency block range when tested at the temperature and supply voltage variations specified in RSS-Gen.

3.4.5 Transmitter output power and effective radiated power (e.r.p.)

3.4.5.1 Applicable Standard

RSS-130 clause 4.6.1 General

The transmitter output power shall be measured in terms of average power. In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.

RSS-130 clause 4.6.2 Frequency bands 617-652 MHz and 663-698 MHz

The e.r.p. shall not exceed 3 watts for mobile equipment, fixed subscriber equipment and portable equipment.

For base and fixed equipment other than fixed subscriber equipment, refer to SRSP-518 for the equivalent isotropically radiated power (e.i.r.p.) limits.

RSS-130 clause 4.6.3 Frequency bands 698-756 MHz and 777-787 MHz

The e.r.p. shall not exceed 30 watts for mobile equipment and outdoor fixed subscriber equipment. The e.r.p. shall not exceed 3 watts for portable equipment and indoor fixed subscriber equipment.

For base and fixed equipment other than fixed subscriber equipment, refer to SRSP-518 for the e.i.r.p. limits.

3.4.6 Transmitter unwanted emissions

3.4.5.1 Applicable Standard

RSS-130 clause 4.7.1 General unwanted emissions limits

The unwanted emissions in any 100 kHz bandwidth on any frequency outside the low frequency edge and the high frequency edge of each frequency block range(s), shall be attenuated below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$ (watts), dB. However, in the 100 kHz band immediately outside of the equipment's frequency block range, a resolution bandwidth of 30 kHz may be employed.

RSS-130 clause 4.7.2 Additional unwanted emissions limits

In addition to the limit outlined in section 4.7.1 above, equipment operating in the frequency bands 746-756 MHz and 777-787 MHz shall also comply with the following restrictions:

- a) The power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least:
 - (i) $76 + 10 \log_{10} p$ (watts), dB, for base and fixed equipment, and
 - (ii) $65 + 10 \log_{10} p$ (watts), dB, for mobile and portable equipment.
- b) The e.i.r.p. in the band 1559-1610 MHz shall not exceed -70 dBW/MHz for wideband signal and -80 dBW for discrete emission with bandwidth less than 700 Hz.

3.5 Applicable Standard For RSS-132 Issue 4, January 31, 2023:

3.5.1 Frequency Sub-bands

3.5.1.1 Applicable Standard

RSS-132 clause 5.1

The frequency bands 824-849 MHz and 869-894 MHz are divided into sub-bands as described in SRSP-503. These sub-bands are:

824-835 MHz, 835-845 MHz, 845-846.5 MHz, and 846.5-849 MHz for mobile transmit; and

869-880 MHz, 880-890 MHz, 890-891.5 MHz, and 891.5-894 MHz for base transmit.

3.5.1.2 Judgment

Compliant, the device operates in this band is divided into sub-bands as described in SRSP-503.

3.5.2 Types of Modulation

3.5.2.1 Applicable Standard

RSS-132 clause 5.2

Digital modulation shall be used.

3.5.2.2 Judgment

Compliant, the device operates under this standard use digital modulation.

3.5.3 Frequency stability

3.5.3.1 Applicable Standard

RSS-132 clause 5.3

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within each of the sub-bands when tested at the temperature and supply voltage variations specified in [RSS-Gen](#).

3.5.4 Transmitter output power and effective radiated power (e.r.p.)

3.5.4.1 Applicable Standard

RSS-132 clause 5.4

The transmitter output power shall be measured in terms of average power. The equivalent radiated power (e.r.p.) shall not exceed 7 watts for mobile equipment and 3 watts for portable equipment. The effective isotropic radiated power (e.i.r.p.) shall not exceed the limits specified in [SRSP-503](#) for base station equipment.

In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

3.5.5 Transmitter unwanted emissions

3.5.5.1 Applicable Standard

RSS-132 clause 5.5

Mobile and base station equipment shall comply with the limits in (i) and (ii) below.

- (i) In the first 1.0 MHz band immediately outside and adjacent to each of the sub-bands specified in Section 5.1, the power of emissions per any 1% of the occupied bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts).
- (ii) After the first 1.0 MHz immediately outside and adjacent to each of the sub-bands, the power of emissions in any 100 kHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts). If the measurement is performed using 1% of the occupied bandwidth, power integration over 100 kHz is required.

3.6 Applicable Standard For RSS-133 Issue 6, January 2018 Amendment:

3.6.1 Frequency Plan

3.6.1.1 Applicable Standard

RSS-133 clause 6.1

The frequency plan is described in SRSP-510.

3.6.1.2 Judgment

Compliant, the device operates in this band is Compliant with SRSP-510.

3.6.2 Types of Modulation

3.6.2.1 Applicable Standard

RSS-133 clause 6.2

The devices shall employ digital modulation techniques.

3.6.2.2 Judgment

Compliant, the device operates under this standard use digital modulation.

3.6.3 Frequency stability

3.6.3.1 Applicable Standard

RSS-133 clause 6.3

The carrier frequency shall not depart from the reference frequency, in excess of ± 2.5 ppm for mobile stations and ± 1.0 ppm for base stations.

In lieu of meeting the above stability values, the test report may show that the frequency stability is sufficient to ensure that the emission bandwidth stays within the operating frequency block when tested to the temperature and supply voltage variations specified in RSS-Gen.

3.6.4 Transmitter Output Power and Equivalent Isotropically Radiated Power

3.6.4.1 Applicable Standard

RSS-133 clause 6.4

The equivalent isotropically radiated power (e.i.r.p.) for transmitters shall not exceed the limits given in SRSP-510.

In addition, the transmitter's peak-to-average power ratio (PAPR) shall not exceed 13 dB for more than 0.1% of the time using a signal corresponding to the highest PAPR during periods of continuous transmission.

3.6.5 Transmitter unwanted emissions

3.6.5.1 Applicable Standard

RSS-133 clause 6.5.1 Out-of-Block Emissions

Equipment shall comply with the limits in (i) and (ii) below.

(i) In the 1.0 MHz bands immediately outside and adjacent to the equipment's operating frequency block, the emission power per any 1% of the emission bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts).

(ii) After the first 1.0 MHz, the emission power in any 1 MHz bandwidth shall be attenuated (in dB) below the transmitter output power P (dBW) by at least $43 + 10 \log_{10} p$ (watts). If the measurement is performed using 1% of the emission bandwidth, power integration over 1.0 MHz is required.

3.6.6 Receiver Spurious Emissions

3.6.6.1 Applicable Standard

RSS-133 clause 6.6

Receiver spurious emissions shall comply with the limits specified in RSS-Gen.

3.7 Applicable Standard For RSS-199 Issue 4 July 2023:

3.7.1 Types of Modulation

3.7.1.1 Applicable Standard

RSS-199 clause 5.3

Equipment certified under this standard shall employ digital modulation.

3.7.1.2 Judgment

Compliant, the device operates under this standard use digital modulation.

3.7.2 Band plan

3.7.2.1 Applicable Standard

RSS-199 clause 5.2

The band 2500-2690 MHz is divided into 7 paired blocks and 2 unpaired blocks as shown in table 1 and 2. SRSP-517 contains the detailed band plan. Frequency blocks can be aggregated to form a frequency block group.

3.7.2.2 Judgment

Compliant, the device operates in this band is Compliant with SRSP-517.

3.7.3 Frequency stability

3.7.3.1 Applicable Standard

RSS-199 clause 5.4

The transmitter frequency stability limit shall be determined as follows:

The frequency stability shall be sufficient to ensure that the occupied bandwidth stays within the operating frequency block or frequency block group when tested to the temperature and supply voltage variations specified in RSS-Gen.

3.7.4 Transmitter output power and equivalent isotropically radiated power (e.i.r.p.)

3.7.4.1 Applicable Standard

RSS-199 clause 5.5

The transmitter output power shall be measured in terms of average value.

For base station equipment, refer to SRSP-517 for the maximum permissible e.i.r.p.

For mobile subscriber equipment, the e.i.r.p. shall not exceed 2 W. For fixed subscriber equipment, the transmitter output power shall not exceed 2 W and the e.i.r.p. shall be limited to 40 W.

In addition, the peak-to-average power ratio (PAPR) of the transmitter shall not exceed 13 dB for more than 0.1% of the time and shall use a signal corresponding to the highest PAPR during periods of continuous transmission.

For equipment with multiple antennas, the transmitter output power and e.i.r.p. shall be measured according to ANSI C63.26-2015.

3.7.5 Transmitter unwanted emissions

3.7.5.1 Applicable Standard

RSS-199 clause 5.6

In the 1 MHz band immediately outside and adjacent to the channel edge, the unwanted emission power shall be measured with a resolution bandwidth of at least 1% of the occupied bandwidth for base station and fixed subscriber equipment, and 2% for mobile subscriber equipment. Beyond the 1 MHz band, a resolution bandwidth of 1 MHz shall be used. A narrower resolution bandwidth can be used, provided that the measured power is integrated over the full required measurement bandwidth of 1 MHz, or 1% or 2% of the occupied bandwidth, as applicable.

Equipment shall comply with the following unwanted emission limits:

- (a) for base station and fixed subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least $43 + 10 \log_{10} p$.
- (b) for mobile subscriber equipment, the power of any unwanted emissions measured as above shall be attenuated (in dB) below the transmitter power, P (dBW), by at least:
 - (i) $40 + 10 \log_{10} p$ from the channel edges to 5 MHz away
 - (ii) $43 + 10 \log_{10} p$ between 5 MHz and X MHz from the channel edges, and
 - (iii) $55 + 10 \log_{10} p$ at X MHz and beyond from the channel edges

In addition, the attenuation shall not be less than $43 + 10 \log_{10} p$ on all frequencies between 2490.5 MHz and 2496 MHz, and $55 + 10 \log_{10} p$ at or below 2490.5 MHz.

In (a) and (b), p is the transmitter power measured in watts and X is 6 MHz or the equipment occupied bandwidth, whichever is greater.

3.8 Test Method:

3.8.1 Transmitter output power, e.r.p. and e.i.r.p

According to CFR Part 2.1046, ANSI C63.26-2015 Section 5.2.5.5:

The relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

where:


ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively (expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

Test Setup Block:



Note: The Insertion loss of the RF cable and coaxial Attenuator was offset into the Reading of CMW500.

3.8.2 Occupied Bandwidth


According to ANSI C63.26-2015 Section 5.4.4

The OBW is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission.

The following procedure shall be used for measuring (99%) power bandwidth:

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be set wide enough to capture all modulation products including the emission skirts (typically a span of $1.5 \times$ OBW is sufficient).
- b) The nominal IF filter 3 dB bandwidth (RBW) shall be in the range of 1% to 5% of the anticipated OBW, and the VBW shall be set $\geq 3 \times$ RBW.
- c) Set the reference level of the instrument as required to prevent the signal amplitude from exceeding the maximum spectrum analyzer input mixer level for linear operation. See guidance provided in 4.2.3.
NOTE—Step a), step b), and step c) may require iteration to adjust within the specified tolerances.
- d) Set the detection mode to peak, and the trace mode to max-hold.
- e) If the instrument does not have a 99% OBW function, recover the trace data points and sum directly in linear power terms. Place the recovered amplitude data points, beginning at the lowest frequency, in a running sum until 0.5% of the total is reached. Record that frequency as the lower OBW frequency. Repeat the process until 99.5% of the total is reached and record that frequency as the upper OBW frequency. The 99% power OBW can be determined by computing the difference these two frequencies.
- f) The OBW shall be reported and plot(s) of the measuring instrument display shall be provided with the test report. The frequency and amplitude axis and scale shall be clearly labeled. Tabular data can be reported in addition to the plot(s).

Test Setup Block:




3.8.3 Transmitter unwanted emissions-at antenna terminals

According to ANSI C63.26-2015 Section 5.7.4:

the applicable rule part specifies the reference bandwidth for measuring unwanted emission levels (typically, 100 kHz if the authorized frequency band/block is at or below 1 GHz and 1 MHz if the authorized frequency band/block is above 1 GHz),⁸ effectively depicting the unwanted emission limit in terms of a power spectral density. In those cases where no reference bandwidth is explicitly specified, the values in the preceding sentence should be used.

Test Setup Block:




3.8.4 Transmitter unwanted emissions-Out of band emission

According to ANSI C63.26-2015 Section 5.7.3:

Typically, a measurement (resolution) bandwidth smaller than the reference bandwidth is allowed for measurements within a specified frequency range at the edge of the authorized frequency block/band (e.g., within the first Y MHz outside of the authorized frequency band/block, where the value of Y is specified in the relevant rule part). Some FCC out-of-band emission rules permit the use of a narrower RBW (typically limited to a minimum RBW of 1 % of the OBW) for measuring the out-of-band emissions without a requirement to integrate the result over the full reference bandwidth. Beyond the specified frequency range in which this relaxation of the uniform reference bandwidth is permitted, it typically is also acceptable to use a narrower RBW (again limited to a minimum of 1 % of OBW) to increase accuracy, but the measurement result must subsequently be integrated over the full reference bandwidth.

Test Setup Block:



3.8.5 Frequency stability

According to ANSI C63.26-2015 Section 5.6:

Frequency stability is a measure of the frequency drift due to temperature and supply voltage variations, with reference to the frequency measured at +20 °C and rated supply voltage.


The operating carrier frequency shall be set up in accordance with the manufacturer's published operation and instruction manual prior to the commencement of these tests. No adjustment of any frequency determining circuit element shall be made subsequent to this initial set-up. Frequency stability is tested:

- a) At 10 °C intervals of temperatures between –30 °C and +50 °C at the manufacturer's rated supply voltage, and
- b) At +20 °C temperature and ±15% supply voltage variations. If a product is specified to operate over a range of input voltage then the –15% variation is applied to the lowermost voltage and the +15% is applied to the uppermost voltage.

During the test all necessary settings, adjustments and control of the EUT have to be performed without disturbing the test environment, i.e., without opening the environmental chamber. The frequency stabilities can be maintained to a lesser temperature range provided that the transmitter is automatically inhibited from operating outside the lesser temperature range. For handheld equipment that is only capable of operating from internal batteries and the supply voltage cannot be varied, the frequency stability tests shall be performed at the nominal battery voltage and the battery end point voltage specified by the manufacturer. An external supply voltage can be used and set at the internal battery nominal voltage, and again at the battery operating end point voltage which shall be specified by the equipment manufacturer.

If an unmodulated carrier is not available, the mean frequency of a modulated carrier can be obtained by using a frequency counter with gating time set to an appropriately large multiple of bit periods (gating time depending on the required accuracy). Full details on the choice of values shall be included in the test report.

Test Setup Block:



3.8.6 Transmitter unwanted emissions- Radiated Spurious emissions

According to ANSI C63.26-2015 Section 5.5.3:

Test setup:




Figure 6—Test site-up for radiated ERP and/or EIRP measurements




Figure 7—Substitution method set-up for radiated emission

Test Procedure:

- a) Place the EUT in the center of the turntable. The EUT shall be configured to transmit into the standard non-radiating load (for measuring radiated spurious emissions), connected with cables of minimal length unless specified otherwise. If the EUT uses an adjustable antenna, the antenna shall be positioned to the length that produces the worst case emission at the fundamental operating frequency.
- b) Each emission under consideration shall be evaluated:
 - 1) Raise and lower the measurement antenna in accordance 5.5.2, as necessary to enable detection of the maximum emission amplitude relative to measurement antenna height.
 - 2) Rotate the EUT through 360° to determine the maximum emission level relative to the axial position.
 - 3) Return the turntable to the azimuth where the highest emission amplitude level was observed.
 - 4) Vary the measurement antenna height again through 1 m to 4 m again to find the height associated with the maximum emission amplitude.
 - 5) Record the measured emission amplitude level and frequency using the appropriate RBW.
- c) Repeat step b) for each emission frequency with the measurement antenna oriented in both the horizontal and vertical polarizations to determine the orientation that gives the maximum emissions amplitude.
- d) Set-up the substitution measurement with the reference point of the substitution antenna located as near as possible to where the center of the EUT radiating element was located during the initial EUT measurement.
- e) Maintain the previous measurement instrument settings and test set-up, with the exception that the EUT is removed and replaced by the substitution antenna.
- f) Connect a signal generator to the substitution antenna; locate the signal generator so as to minimize any potential influences on the measurement results. Set the signal generator to the frequency where emissions are detected, and set an output power level such that the radiated signal can be detected by the measurement instrument, with sufficient dynamic range relative to the noise floor.
- g) For each emission that was detected and measured in the initial test [i.e., in step b) and step c)]:
 - 1) Vary the measurement antenna height between 1 m to 4 m to maximize the received (measured) signal amplitude.
 - 2) Adjust the signal generator output power level until the amplitude detected by the measurement instrument equals the amplitude level of the emission previously measured directly in step b) and step c).
 - 3) Record the output power level of the signal generator when equivalence is achieved in step 2).
- h) Repeat step e) through step g) with the measurement antenna oriented in the opposite polarization.
- i) Calculate the emission power in dBm referenced to a half-wave dipole using the following equation:
$$Pe = Ps(dBm) - \text{cable loss (dB)} + \text{antenna gain (dBD)}$$
where
 - Pe = equivalent emission power in dBm
 - Ps = source (signal generator) power in dBmNOTE—dBD refers to the measured antenna gain in decibels relative to a half-wave dipole.
- j) Correct the antenna gain of the substitution antenna if necessary to reference the emission power to a half-wave dipole. When using measurement antennas with the gain specified in dBi, the equivalent dipole-referenced gain can be determined from: gain (dBD) = gain (dBi) – 2.15 dB. If necessary, the antenna gain can be calculated from calibrated antenna factor information
- k) Provide the complete measurement results as a part of the test report.

4. Test DATA AND RESULTS

4.1 Antenna Port Test Data and Results for GSM 850 band:

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Panda Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	824.2	836.6	848.8
GPRS	824.2	836.6	848.8
EDGE	824.2	836.6	848.8

Test Data:

FCC§2.1046,§ 22.913 (a), RSS-132 Clause 5.4 :RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	29.9	29.7	29.6	20.85	38.45
GPRS 1 Slot	29.98	29.69	29.61	20.93	38.45
GPRS 2 Slots	27.73	27.39	27.03	18.68	38.45
GPRS 3 Slots	26	25.68	25.37	16.95	38.45
GPRS 4 Slots	23.94	23.63	23.35	14.89	38.45
EDGE 1 Slot	26.35	26.2	26.23	17.3	38.45
EDGE 2 Slots	24.66	24.7	24.59	15.65	38.45
EDGE 3 Slots	22.59	22.61	22.66	13.61	38.45
EDGE 4 Slots	20.78	20.97	21.27	12.22	38.45

Note:
ERP= Conducted Power(dBm) - L_C(dB) + G_T(dBd)
G_T(dBd)=G_T(dBi)-2.15

Result:	Pass
---------	------

FCC §2.1049, §22.917, §22.905, RSS-Gen Clause 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (kHz)			26 dB Occupied Bandwidth (kHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	242	244	243	308	314	315
EDGE	247	250	248	317	316	310

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, §22.917(a), RSS-132 Clause 5.5:Spurious Emissions at Antenna Terminal					
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.				


FCC §2.1051, §22.917(a), RSS-132 Clause 5.5:Out of band emission, Band Edge					
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.				


FCC §2.1055, §22.355, RSS-132 Clause 5.3: Frequency Stability					
Test Modulation:	GMSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.8	10.40	0.012	2.5
	-20	3.8	5.31	0.006	2.5
	-10	3.8	0.77	0.001	2.5
	0	3.8	5.83	0.007	2.5


	10	3.8	-2.71	-0.003	2.5
	20	3.8	-3.79	-0.005	2.5
	30	3.8	2.38	0.003	2.5
	40	3.8	0.70	0.001	2.5
	50	3.8	1.84	0.002	2.5
Frequency Stability vs. Voltage	20	3.45	2.50	0.003	2.5
	20	4.4	2.56	0.003	2.5
					Result: Pass


Test Modulation:	8PSK		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.8	2.75	0.003	2.5
	-20	3.8	-0.99	-0.001	2.5
	-10	3.8	-1.59	-0.002	2.5
	0	3.8	4.96	0.006	2.5
	10	3.8	0.49	0.001	2.5
	20	3.8	-4.52	-0.005	2.5
	30	3.8	1.47	0.002	2.5
	40	3.8	-4.21	-0.005	2.5
	50	3.8	3.90	0.005	2.5
Frequency Stability vs. Voltage	20	3.45	4.62	0.006	2.5
	20	4.4	4.75	0.006	2.5
					Result: Pass

Test Plots (Note: The 10dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):









4.2 Antenna Port Test Data and Results for GSM 1900 band:

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Panda Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
GSM	1850.2	1880	1909.8
GPRS	1850.2	1880	1909.8
EDGE	1850.2	1880	1909.8

Test Data:

FCC§2.1046,§ 24.232 (c), RSS-133 Clause 6.4 :RF Output Power					
Test Mode	Conducted Peak Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
GSM	27.8	27.6	27.7	27.94	33
GPRS 1 Slot	27.74	27.7	27.68	27.88	33
GPRS 2 Slots	25.59	25.58	25.54	25.73	33
GPRS 3 Slots	23.74	23.72	23.66	23.88	33
GPRS 4 Slots	21.72	21.69	21.62	21.86	33
EDGE 1 Slot	25.92	26.3	26.08	26.44	33
EDGE 2 Slots	24.85	25.41	25.15	25.55	33
EDGE 3 Slots	22.53	23.05	22.82	23.19	33
EDGE 4 Slots	20.37	20.79	20.53	20.93	33

Note: EIRP=Conducted Power(dBm) - L_C(dB) + G_T(dBi)

Result: Pass

FCC §2.1049, §24.238, RSS-Gen 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (kHz)			26 dB Occupied Bandwidth (kHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
GSM	242	243	242	316	321	314
EDGE	249	250	251	317	321	328

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Spurious Emissions at Antenna Terminal						
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.					


FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Out of band emission, Band Edge						
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.					


FCC §2.1055, §24.235, RSS-133 Clause 6.3: Frequency Stability						
Test Mode:	GMSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	1850.0132	1850.000	1909.9983	1910.000
	-20	3.8	1850.0181	1850.000	1909.9998	1910.000
	-10	3.8	1850.0116	1850.000	1909.9996	1910.000
	0	3.8	1850.0171	1850.000	1909.9969	1910.000
	10	3.8	1850.0138	1850.000	1909.9952	1910.000
	20	3.8	1850.0140	1850.000	1909.9987	1910.000


	30	3.8	1850.0174	1850.000	1909.9923	1910.000
	40	3.8	1850.0118	1850.000	1909.9976	1910.000
	50	3.8	1850.0130	1850.000	1909.9931	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.0130	1850.000	1909.9999	1910.000
	20	4.4	1850.0133	1850.000	1909.9970	1910.000
					Result:	Pass


Test Mode: 8PSK		Test Channel: Lowest for Lower Edge, Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	1850.0126	1850.000	1909.9854	1910.000
	-20	3.8	1850.0135	1850.000	1909.9833	1910.000
	-10	3.8	1850.0174	1850.000	1909.9839	1910.000
	0	3.8	1850.0144	1850.000	1909.9825	1910.000
	10	3.8	1850.0145	1850.000	1909.9812	1910.000
	20	3.8	1850.0187	1850.000	1909.9799	1910.000
	30	3.8	1850.0153	1850.000	1909.9822	1910.000
	40	3.8	1850.0193	1850.000	1909.9832	1910.000
	50	3.8	1850.0134	1850.000	1909.9811	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.0176	1850.000	1909.9807	1910.000
	20	4.4	1850.0137	1850.000	1909.9814	1910.000
					Result:	Pass

Test Plots(Note: The 10.5dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):









4.3 Antenna Port Test Data and Results for WCDMA Band 2:

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Panda Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	1852.4	1880	1907.6

Test Data:**FCC§2.1046;§ 24.232, RSS-133 Clause 6.4****RF Output Power:**

Test Mode	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	19.19	19.13	19.08	19.33	33
HSDPA Subtest 1	18.46	18.44	18.31	18.6	33
HSDPA Subtest 2	18.5	18.49	18.35	18.64	33
HSDPA Subtest 3	18.53	18.54	18.44	18.68	33
HSDPA Subtest 4	18.61	18.59	18.45	18.75	33
HSUPA Subtest 1	18.68	18.76	18.91	19.05	33
HSUPA Subtest 2	18.49	18.5	18.52	18.66	33
HSUPA Subtest 3	18.27	18.43	18.48	18.62	33
HSUPA Subtest 4	18.38	18.45	18.49	18.63	33
HSUPA Subtest 5	18.46	18.57	18.67	18.81	33
HSPA+ Subtest 1	18.68	18.68	18.49	18.82	33

Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gr(dBi)

Result: Pass

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	2.72	2.63	2.63	13
HSDPA	3.56	3.65	3.78	13
HSUPA	3.59	3.49	3.56	13

Result: Pass

FCC §2.1049, §24.238,RSS-Gen Clause 6.7:Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.170	4.155	4.155	4.710	4.695	4.695
HSDPA	4.155	4.140	4.155	4.710	4.710	4.710
HSUPA	4.155	4.140	4.155	4.710	4.710	4.695

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Spurious Emissions at Antenna Terminal


Result: Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Out of band emission, Band Edge


Result: Pass, Please refer to the test plots of Out of band emission, Band Edge.


FCC §2.1055, §24.235, RSS-133 Clause 6.3: Frequency Stability						
Test Mode:	WCDMA R99	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	1850.0109	1850.000	1909.9901	1910.000
	-20	3.8	1850.0152	1850.000	1909.9868	1910.000
	-10	3.8	1850.0143	1850.000	1909.9900	1910.000
	0	3.8	1850.0126	1850.000	1909.9918	1910.000
	10	3.8	1850.0168	1850.000	1909.9888	1910.000
	20	3.8	1850.0196	1850.000	1909.9916	1910.000
	30	3.8	1850.0139	1850.000	1909.9874	1910.000
	40	3.8	1850.0198	1850.000	1909.9926	1910.000
	50	3.8	1850.0190	1850.000	1909.9929	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.0151	1850.000	1909.9937	1910.000
	20	4.4	1850.0187	1850.000	1909.9880	1910.000
					Result:	Pass


Test Plots(Note: The 10.5dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):














4.4 Antenna Port Test Data and Results for WCDMA Band 5:

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Panda Sun	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency:

Operation Modes	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
WCDMA	826.4	836.6	846.6

Test Data:**FCC§2.1046;§ 22.913 (a) , RSS-132 Clause 5.4****RF Output Power:**

Test Mode	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
	Lowest Channel	Middle Channel	Highest Channel		
WCDMA R99	20.22	20.21	20.18	11.17	38.45
HSDPA Subtest 1	19.76	19.72	20.02	10.97	38.45
HSDPA Subtest 2	19.61	19.57	19.87	10.82	38.45
HSDPA Subtest 3	19.85	19.81	20.11	11.06	38.45
HSDPA Subtest 4	19.71	19.66	19.96	10.91	38.45
HSUPA Subtest 1	19.75	19.81	19.62	10.76	38.45
HSUPA Subtest 2	19.51	19.69	19.91	10.86	38.45
HSUPA Subtest 3	19.55	19.71	19.57	10.66	38.45
HSUPA Subtest 4	19.71	19.66	19.94	10.89	38.45
HSUPA Subtest 5	19.78	19.55	19.68	10.73	38.45
HSPA+ Subtest 1	19.31	19.28	19.41	10.36	38.45

Note:
ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd)
Gr(dBd)=Gr(dBi)-2.15

	Result:	Pass
--	----------------	-------------

Peak-to-average Ratio(PAR)

Test Mode	Peak-to-average Ratio(dB)			Limit (dB)
	Lowest Channel	Middle Channel	Highest Channel	
WCDMA R99	2.92	3.01	3.08	13
HSDPA	3.65	3.94	3.91	13
HSUPA	3.81	3.94	3.94	13

	Result:	Pass
--	----------------	-------------

FCC §2.1049, §22.917, §22.905.RSS-Gen Clause 6.7:Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
WCDMA R99	4.140	4.155	4.155	4.695	4.695	4.710
HSDPA	4.155	4.155	4.155	4.695	4.695	4.695
HSUPA	4.140	4.155	4.155	4.710	4.695	4.695

Note: The test plots please refer to the Plots of Occupied Bandwidth


FCC §2.1051, §22.917(a) , RSS-132 Clause 5.5:Spurious Emissions at Antenna Terminal


Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	---


FCC §2.1051, §22.917(a) , RSS-132 Clause 5.5:Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.


FCC §2.1055, §22.355, RSS-132 Clause 5.3: Frequency Stability					
Test Modulation:	WCDMA R99		Test Channel:	836.6	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error		Limit
			(Hz)	(ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.8	8.94	0.011	2.5
	-20	3.8	2.40	0.003	2.5
	-10	3.8	0.95	0.001	2.5
	0	3.8	3.97	0.005	2.5
	10	3.8	-0.20	0.000	2.5
	20	3.8	-2.11	-0.003	2.5
	30	3.8	7.26	0.009	2.5
	40	3.8	0.95	0.001	2.5
	50	3.8	2.52	0.003	2.5
Frequency Stability vs. Voltage	20	3.45	2.96	0.004	2.5
	20	4.4	3.57	0.004	2.5
				Result:	Pass


Test Plots(Note: The 10dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):














4.5 Antenna Port Test Data and Results for LTE Band 2

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Gary Ling	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	1850.7	1880	1909.3
3MHz	1851.5	1880	1908.5
5MHz	1852.5	1880	1907.5
10MHz	1855	1880	1905
15MHz	1857.5	1880	1902.5
20MHz	1860	1880	1900

Test Data:**FCC§2.1046;§ 24.232, RSS-133 Clause 6.4****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	18.69	18.85	18.83	19.11	33
	RB1#3	18.68	18.86	18.87		
	RB1#5	18.72	18.80	18.84		
	RB3#0	18.85	18.97	18.77		
	RB3#3	18.81	18.91	18.76		
	RB6#0	17.73	17.85	17.86		
1.4MHz 16QAM	RB1#0	18.31	18.14	17.36	18.51	33
	RB1#3	18.36	18.23	17.33		
	RB1#5	18.37	18.14	17.36		
	RB3#0	17.82	18.07	17.77		
	RB3#3	17.82	18.03	17.70		
	RB6#0	16.93	17.02	16.80		
3MHz QPSK	RB1#0	18.64	18.89	18.78	19.03	33
	RB1#8	18.69	18.85	18.75		
	RB1#14	18.76	18.85	18.75		
	RB6#0	17.73	17.82	17.73		
	RB6#9	17.80	17.86	17.74		
	RB15#0	17.71	17.90	17.72		
3MHz 16QAM	RB1#0	18.42	17.64	18.17	18.59	33
	RB1#8	18.45	17.55	18.08		
	RB1#14	18.42	17.58	18.12		
	RB6#0	16.92	16.82	17.05		
	RB6#9	16.93	16.79	17.06		
	RB15#0	16.81	16.96	17.01		
5MHz QPSK	RB1#0	18.91	18.73	18.78	19.07	33
	RB1#13	18.84	18.67	18.73		
	RB1#24	18.93	18.68	18.72		
	RB15#0	17.70	17.83	17.91		
	RB15#10	17.78	17.85	17.78		
	RB25#0	17.73	17.91	17.77		
5MHz 16QAM	RB1#0	17.90	18.01	17.19	18.15	33
	RB1#13	17.94	17.98	17.16		
	RB1#24	17.92	18.00	17.05		
	RB15#0	16.70	16.91	16.97		
	RB15#10	16.77	16.90	16.96		
	RB25#0	16.81	17.11	16.99		

10MHz QPSK	RB1#0	18.76	18.82	18.79	19.01	33
	RB1#25	18.79	18.87	18.78		
	RB1#49	18.79	18.84	18.72		
	RB25#0	17.71	17.85	17.82		
	RB25#25	17.76	17.85	17.79		
	RB50#0	17.73	17.79	17.80		
10MHz 16QAM	RB1#0	17.92	17.76	18.27	18.41	33
	RB1#25	17.90	17.81	18.25		
	RB1#49	17.89	17.70	18.19		
	RB25#0	16.93	17.12	17.00		
	RB25#25	16.96	17.10	16.86		
	RB50#0	16.94	17.05	16.93		
15MHz QPSK	RB1#0	18.78	18.59	18.69	18.94	33
	RB1#38	18.80	18.68	18.77		
	RB1#74	18.76	18.58	18.74		
	RB36#0	17.70	17.88	17.85		
	RB36#39	17.80	17.89	17.81		
	RB75#0	17.72	17.83	17.79		
15MHz 16QAM	RB1#0	17.93	17.96	18.27	18.43	33
	RB1#38	17.93	17.98	18.29		
	RB1#74	17.91	17.93	18.26		
	RB36#0	16.95	16.96	16.89		
	RB36#39	16.90	16.97	16.84		
	RB75#0	16.86	16.94	16.99		
20MHz QPSK	RB1#0	18.74	18.82	18.81	19.06	33
	RB1#50	18.70	18.89	18.92		
	RB1#99	18.66	18.85	18.82		
	RB50#0	17.72	17.86	17.81		
	RB50#50	17.75	17.71	17.88		
	RB100#0	17.65	17.86	17.79		
20MHz 16QAM	RB1#0	18.05	18.57	17.97	18.73	33
	RB1#50	18.09	18.51	17.96		
	RB1#99	18.08	18.59	17.89		
	RB50#0	16.89	16.87	16.98		
	RB50#50	17.00	16.85	16.99		
	RB100#0	16.93	16.99	16.98		

Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gr(dBi)

Result: Pass

Peak-to-average Ratio(PAR)		Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
Test Bandwidth & Modulation			Lowest Channel	Middle Channel	Highest Channel	

20MHz QPSK	RB1#0	2.92	3.3	3.78	13
	RB100#0	5.22	4.94	4.97	13
20MHz 16QAM	RB1#0	3.85	4.2	4.97	13
	RB100#0	6.09	5.8	5.77	13
				Result:	Pass

FCC §2.1049, §24.238,RSS-Gen Clause 6.7:Occupied Bandwidth

Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.12	1.11	1.11	1.30	1.34	1.27
1.4MHz 16QAM	1.12	1.10	1.11	1.27	1.31	1.26
3MHz QPSK	2.70	2.70	2.71	3.04	3.05	3.01
3MHz 16QAM	2.70	2.71	2.71	3.01	3.06	3.04
5MHz QPSK	4.52	4.52	4.54	5.00	5.00	5.00
5MHz 16QAM	4.54	4.56	4.54	5.04	5.18	5.02
10MHz QPSK	8.96	8.96	8.96	9.76	9.84	9.80
10MHz 16QAM	9.00	8.96	8.96	9.80	9.80	9.80
15MHz QPSK	13.56	13.50	13.50	15.12	15.18	15.06
15MHz 16QAM	13.62	13.56	13.50	15.18	14.94	14.94
20MHz QPSK	18.08	18.00	17.92	19.68	19.68	19.44
20MHz 16QAM	18.16	18.00	18.00	20.00	19.84	19.68

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Spurious Emissions at Antenna Terminal

Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.
----------------	--

FCC §2.1051, § 24.238 (a) , RSS-133 Clause 6.5:Out of band emission, Band Edge

Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.
----------------	---


FCC §2.1055, §24.235, RSS-133 Clause 6.3: Frequency Stability


Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	1850.0142	1850.000	1909.9931	1910.000
	-20	3.8	1850.0075	1850.000	1909.9957	1910.000
	-10	3.8	1850.0078	1850.000	1909.9919	1910.000
	0	3.8	1850.0146	1850.000	1909.9958	1910.000
	10	3.8	1850.0102	1850.000	1909.9925	1910.000
	20	3.8	1850.0133	1850.000	1909.9901	1910.000
	30	3.8	1850.0109	1850.000	1909.9912	1910.000


	40	3.8	1850.0139	1850.000	1909.9966	1910.000
	50	3.8	1850.0150	1850.000	1909.9945	1910.000
Frequency Stability vs. Voltage	20	3.45	1850.0141	1850.000	1909.9902	1910.000
	20	4.4	1850.0114	1850.000	1909.9935	1910.000
						Result: Pass


Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge					
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)		
			Result	Limit	Result	Limit	
Frequency Stability vs. Temperature	-30	3.8	1850.0169	1850.000	1909.9922	1910.000	
	-20	3.8	1850.0221	1850.000	1909.9869	1910.000	
	-10	3.8	1850.0216	1850.000	1909.9877	1910.000	
	0	3.8	1850.0202	1850.000	1909.9885	1910.000	
	10	3.8	1850.0188	1850.000	1909.9885	1910.000	
	20	3.8	1850.0184	1850.000	1909.9889	1910.000	
	30	3.8	1850.0189	1850.000	1909.9915	1910.000	
	40	3.8	1850.0179	1850.000	1909.9906	1910.000	
	50	3.8	1850.0162	1850.000	1909.9883	1910.000	
Frequency Stability vs. Voltage	20	3.45	1850.0231	1850.000	1909.9914	1910.000	
	20	4.4	1850.0186	1850.000	1909.9911	1910.000	
						Result:	Pass


Test Plots(Note: The 10.5dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):












































4.6 Antenna Port Test Data and Results for LTE Band 5

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Gary Ling	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	824.7	836.5	848.3
3MHz	825.5	836.5	847.5
5MHz	826.5	836.5	846.5
10MHz	829	836.5	844

Test Data:**FCC§2.1046;§ 22.913 (a) , RSS-132 Clause 5.4****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	19.44	19.39	19.39	10.54	38.45
	RB1#3	19.38	19.47	19.30		
	RB1#5	19.43	19.41	19.32		
	RB3#0	19.59	19.49	19.24		
	RB3#3	19.53	19.40	19.23		
	RB6#0	18.53	18.34	18.33		
1.4MHz 16QAM	RB1#0	18.25	18.82	19.27	10.26	38.45
	RB1#3	18.18	18.91	19.31		
	RB1#5	18.22	18.94	19.14		
	RB3#0	18.64	18.36	18.22		
	RB3#3	18.55	18.25	18.28		
	RB6#0	17.72	17.47	17.53		
3MHz QPSK	RB1#0	19.51	19.39	19.26	10.49	38.45
	RB1#8	19.54	19.35	19.27		
	RB1#14	19.53	19.39	19.22		
	RB6#0	18.40	18.32	18.28		
	RB6#9	18.47	18.41	18.31		
	RB15#0	18.50	18.40	18.33		
3MHz 16QAM	RB1#0	18.59	17.90	18.55	9.54	38.45
	RB1#8	18.54	17.91	18.48		
	RB1#14	18.54	17.89	18.51		
	RB6#0	17.72	17.52	17.47		
	RB6#9	17.73	17.57	17.54		
	RB15#0	17.55	17.56	17.42		
5MHz QPSK	RB1#0	19.60	19.20	19.23	10.55	38.45
	RB1#13	19.56	19.30	19.22		
	RB1#24	19.44	19.25	19.25		
	RB15#0	18.56	18.42	18.42		
	RB15#10	18.35	18.45	18.25		
	RB25#0	18.50	18.38	18.37		
5MHz 16QAM	RB1#0	18.52	18.42	17.51	9.47	38.45
	RB1#13	18.45	18.47	17.42		
	RB1#24	18.41	18.44	17.43		
	RB15#0	17.41	17.35	17.48		
	RB15#10	17.36	17.41	17.39		
	RB25#0	17.40	17.62	17.54		

10MHz QPSK	RB1#0	19.52	19.31	19.28	10.47	38.45
	RB1#25	19.40	19.23	19.33		
	RB1#49	19.47	19.22	19.23		
	RB25#0	18.51	18.37	18.41		
	RB25#25	18.43	18.40	18.36		
	RB50#0	18.48	18.47	18.38		
10MHz 16QAM	RB1#0	19.22	18.17	18.84	10.17	38.45
	RB1#25	19.14	18.22	18.82		
	RB1#49	19.18	18.05	18.76		
	RB25#0	17.58	17.62	17.48		
	RB25#25	17.52	17.63	17.40		
	RB50#0	17.55	17.55	17.43		
Note: ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd) Gr(dBd)=Gr(dBi)-2.15						
					Result:	Pass

Peak-to-average Ratio(PAR)					
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
10MHz QPSK	RB1#0	4.17	5.03	4.58	13
	RB50#0	5.42	5.64	5.54	13
10MHz 16QAM	RB1#0	5.13	6.35	5.58	13
	RB50#0	6.31	6.41	6.41	13
					Result:
					Pass

FCC §2.1049, §22.905, RSS-Gen Clause 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.10	1.10	1.10	1.26	1.26	1.25
1.4MHz 16QAM	1.12	1.11	1.10	1.26	1.26	1.27
3MHz QPSK	2.70	2.70	2.70	3.00	3.01	2.99
3MHz 16QAM	2.70	2.69	2.70	3.00	3.02	3.00
5MHz QPSK	4.52	4.50	4.54	5.00	4.98	4.98
5MHz 16QAM	4.54	4.52	4.52	5.00	5.00	4.98
10MHz QPSK	8.96	8.96	8.96	9.72	9.76	9.76
10MHz 16QAM	8.96	8.96	8.96	9.76	9.80	9.72
Note: The test plots please refer to the Plots of Occupied Bandwidth						


FCC §2.1051, §22.917(a) , RSS-132 Clause 5.5:Spurious Emissions at Antenna Terminal				
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.			


FCC §2.1051, §22.917(a) , RSS-132 Clause 5.5:Out of band emission, Band Edge				
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.			


FCC §2.1055, §22.355, RSS-132 Clause 5.3: Frequency Stability				
Test Modulation:	10 MHz QPSK		Test Channel:	836.5 MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error (Hz)	Limit (ppm)
Frequency Stability vs. Temperature	-30	3.8	4.60	0.005
	-20	3.8	-1.48	-0.002
	-10	3.8	-4.26	-0.005
	0	3.8	-3.73	-0.004
	10	3.8	-2.64	-0.003
	20	3.8	-10.02	-0.012
	30	3.8	-8.91	-0.011
	40	3.8	-5.54	-0.007
	50	3.8	-9.59	-0.011
Frequency Stability vs. Voltage	20	3.45	-9.23	-0.011
	20	4.4	-8.73	-0.010
				Result: Pass


Test Modulation:	10 MHz 16QAM		Test Channel:	836.5	MHz
Test Item	Temperature (°C)	Voltage (V _{DC})	Frequency Error (Hz)	Limit (ppm)	(ppm)
Frequency Stability vs. Temperature	-30	3.8	9.79	0.012	2.5
	-20	3.8	3.27	0.004	2.5
	-10	3.8	-2.63	-0.003	2.5
	0	3.8	-2.16	-0.003	2.5
	10	3.8	1.01	0.001	2.5
	20	3.8	-6.50	-0.008	2.5
	30	3.8	-5.98	-0.007	2.5
	40	3.8	-4.90	-0.006	2.5
	50	3.8	-4.38	-0.005	2.5
Frequency Stability vs. Voltage	20	3.45	-3.83	-0.005	2.5
	20	4.4	-3.34	-0.004	2.5
				Result: Pass	


Test Plots(Note: The 10dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):
































4.7 Antenna Port Test Data and Results for LTE Band 7

Serial Number:	29PD-2	Test Date:	2023/8/10~2023/8/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Gary Ling	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
5MHz	2502.5	2535	2567.5
10MHz	2505	2535	2565
15MHz	2507.5	2535	2562.5
20MHz	2510	2535	2560

Test Data:**FCC§2.1046;§ 27.50(h)(2) , RSS-199 Clause 5.5****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
5MHz QPSK	RB1#0	18.87	18.74	18.74	20.91	33
	RB1#13	18.73	18.62	18.85		
	RB1#24	18.82	18.60	18.69		
	RB15#0	17.63	17.75	17.90		
	RB15#10	17.72	17.73	17.82		
	RB25#0	17.71	17.71	17.82		
5MHz 16QAM	RB1#0	17.78	17.32	17.23	19.87	33
	RB1#13	17.83	17.33	17.25		
	RB1#24	17.77	17.33	17.24		
	RB15#0	16.82	16.84	17.01		
	RB15#10	16.78	16.82	16.99		
	RB25#0	16.85	16.73	17.01		
10MHz QPSK	RB1#0	18.76	18.79	18.66	20.83	33
	RB1#25	18.72	18.62	18.66		
	RB1#49	18.76	18.68	18.77		
	RB25#0	17.73	17.68	17.86		
	RB25#25	17.64	17.60	17.75		
	RB50#0	17.65	17.63	17.86		
10MHz 16QAM	RB1#0	17.80	17.15	18.12	20.16	33
	RB1#25	17.78	17.21	18.01		
	RB1#49	17.74	17.18	18.01		
	RB25#0	16.99	16.93	16.99		
	RB25#25	16.93	16.92	16.94		
	RB50#0	16.93	16.81	17.09		
15MHz QPSK	RB1#0	18.70	18.68	18.65	20.75	33
	RB1#38	18.67	18.62	18.68		
	RB1#74	18.70	18.65	18.71		
	RB36#0	17.59	17.62	17.81		
	RB36#39	17.71	17.67	17.79		
	RB75#0	17.68	17.72	17.82		
15MHz 16QAM	RB1#0	17.92	18.21	18.03	20.25	33
	RB1#38	17.86	18.12	18.09		
	RB1#74	17.79	18.16	18.14		
	RB36#0	16.93	16.85	17.02		
	RB36#39	16.90	16.84	17.05		
	RB75#0	16.81	16.89	17.02		

20MHz QPSK	RB1#0	18.85	18.51	18.78	20.91	33
	RB1#50	18.79	18.55	18.78		
	RB1#99	18.87	18.56	18.84		
	RB50#0	17.71	17.74	17.72		
	RB50#50	17.65	17.57	17.76		
	RB100#0	17.78	17.64	17.70		
20MHz 16QAM	RB1#0	18.04	18.69	17.71	20.73	33
	RB1#50	17.95	18.57	17.73		
	RB1#99	17.99	18.44	17.80		
	RB50#0	16.93	16.91	16.98		
	RB50#50	16.77	16.79	17.08		
	RB100#0	16.80	16.97	16.97		
Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gt(dBi)						
					Result:	Pass

Peak-to-average Ratio(PAR)						
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)	
		Lowest Channel	Middle Channel	Highest Channel		
20MHz QPSK	RB1#0	3.85	4.55	3.97	13	
	RB100#0	5.16	5.29	5.26	13	
20MHz 16QAM	RB1#0	4.62	5.48	4.87	13	
	RB100#0	5.96	6.09	6.03	13	
					Result:	Pass

FCC §2.1049, §27.53,RSS-Gen Clause 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
5MHz QPSK	4.52	4.50	4.54	5.02	4.98	4.98
5MHz 16QAM	4.54	4.54	4.52	5.00	5.04	5.04
10MHz QPSK	8.96	8.96	9.00	9.76	9.84	9.88
10MHz 16QAM	9.00	8.96	8.96	9.80	9.84	9.84
15MHz QPSK	13.50	13.56	13.62	15.00	15.18	15.12
15MHz 16QAM	13.62	13.56	13.62	15.00	15.18	15.06
20MHz QPSK	18.00	18.08	18.08	19.68	19.84	19.68
20MHz 16QAM	18.00	18.00	18.08	19.76	19.76	19.68

Note: The test plots please refer to the Plots of Occupied Bandwidth


FCC §2.1051, § 27.53, RSS-199 Clause 5.6:Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


FCC §2.1051, § 27.53, RSS-199 Clause 5.6:Out of band emission, Band Edge						
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.					


FCC §2.1055, §27.54, RSS-199 Clause 5.4: Frequency Stability						
Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	2500.0081	2500.00	2569.9941	2570
	-20	3.8	2500.0113	2500.00	2569.9950	2570
	-10	3.8	2500.0128	2500.00	2569.9872	2570
	0	3.8	2500.0110	2500.00	2569.9898	2570
	10	3.8	2500.0111	2500.00	2569.9901	2570
	20	3.8	2500.0097	2500.00	2569.9914	2570
	30	3.8	2500.0150	2500.00	2569.9894	2570
	40	3.8	2500.0141	2500.00	2569.9929	2570
	50	3.8	2500.0126	2500.00	2569.9890	2570
Frequency Stability vs. Voltage	20	3.45	2500.0127	2500.00	2569.9941	2570
	20	4.4	2500.0156	2500.00	2569.9923	2570
					Result:	Pass


Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	2500.0178	2500.00	2569.9848	2570
	-20	3.8	2500.0128	2500.00	2569.9894	2570
	-10	3.8	2500.0182	2500.00	2569.9897	2570
	0	3.8	2500.0122	2500.00	2569.9902	2570
	10	3.8	2500.0142	2500.00	2569.9875	2570
	20	3.8	2500.0134	2500.00	2569.9913	2570
	30	3.8	2500.0112	2500.00	2569.9853	2570
	40	3.8	2500.0175	2500.00	2569.9880	2570
	50	3.8	2500.0183	2500.00	2569.9852	2570
Frequency Stability vs. Voltage	20	3.45	2500.0141	2500.00	2569.9879	2570
	20	4.4	2500.0151	2500.00	2569.9900	2570
					Result:	Pass


Test Plots(Note: The 10.5dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):
































4.8 Antenna Port Test Data and Results for LTE Band 12

Serial Number:	29PD-2	Test Date:	2023/8/10
Test Site:	RF	Test Mode:	Transmitting
Tester:	Gary Ling	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
1.4MHz	699.7	707.5	715.3
3MHz	700.5	707.5	714.5
5MHz	701.5	707.5	713.5
10MHz	704	707.5	711

Test Data:**FCC§2.1046;§ 27.50(c) (10) , RSS-130 Clause 4.6****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum ERP (dBm)	ERP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
1.4MHz QPSK	RB1#0	19.86	19.83	19.82	8.5	34.77
	RB1#3	19.82	19.82	19.87		
	RB1#5	19.84	19.75	19.85		
	RB3#0	19.87	19.85	19.84		
	RB3#3	19.88	19.82	19.95		
	RB6#0	18.86	18.85	18.75		
1.4MHz 16QAM	RB1#0	18.93	18.37	18.91	7.53	34.77
	RB1#3	18.95	18.26	18.89		
	RB1#5	18.98	18.23	18.94		
	RB3#0	18.87	18.55	18.75		
	RB3#3	18.75	18.59	18.80		
	RB6#0	17.89	17.83	17.86		
3MHz QPSK	RB1#0	19.85	19.90	19.81	8.45	34.77
	RB1#8	19.84	19.79	19.79		
	RB1#14	19.87	19.78	19.81		
	RB6#0	18.84	18.91	18.87		
	RB6#9	18.91	18.86	18.88		
	RB15#0	18.77	18.83	18.74		
3MHz 16QAM	RB1#0	18.93	18.29	19.10	7.65	34.77
	RB1#8	18.96	18.23	19.03		
	RB1#14	19.05	18.25	19.01		
	RB6#0	18.03	17.93	17.72		
	RB6#9	18.08	17.84	17.92		
	RB15#0	17.93	17.80	17.89		
5MHz QPSK	RB1#0	19.89	19.71	19.73	8.51	34.77
	RB1#13	19.96	19.63	19.76		
	RB1#24	19.96	19.63	19.67		
	RB15#0	18.80	18.82	18.87		
	RB15#10	18.82	18.78	18.88		
	RB25#0	18.81	18.83	18.83		
5MHz 16QAM	RB1#0	18.78	18.82	18.11	7.39	34.77
	RB1#13	18.84	18.77	18.04		
	RB1#24	18.76	18.76	17.96		
	RB15#0	17.67	17.71	17.95		
	RB15#10	17.72	17.65	17.84		
	RB25#0	17.86	17.87	17.98		

10MHz QPSK	RB1#0	19.88	19.68	19.78	8.43	34.77
	RB1#25	19.82	19.74	19.76		
	RB1#49	19.75	19.76	19.76		
	RB25#0	18.84	18.81	18.78		
	RB25#25	18.76	18.82	18.76		
	RB50#0	18.79	18.74	18.80		
10MHz 16QAM	RB1#0	19.57	18.48	19.18	8.12	34.77
	RB1#25	19.50	18.44	19.16		
	RB1#49	19.46	18.38	19.11		
	RB25#0	17.93	18.04	17.83		
	RB25#25	17.94	18.03	17.80		
	RB50#0	17.83	17.85	17.81		

Note:

ERP= Conducted Power(dBm) - Lc(dB) + Gr(dBd)

Gr(dBd)=Gr(dBi)-2.15

Result: Pass

Peak-to-average Ratio(PAR)					
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)
		Lowest Channel	Middle Channel	Highest Channel	
10MHz QPSK	RB1#0	4.78	4.65	4.29	13
	RB50#0	5.51	5.61	5.54	13
10MHz 16QAM	RB1#0	6.19	5.1	5.26	13
	RB50#0	6.38	6.51	6.51	13

Result: Pass

FCC §2.1049, §27.53,RSS-Gen Clause 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
1.4MHz QPSK	1.10	1.10	1.10	1.26	1.26	1.26
1.4MHz 16QAM	1.10	1.10	1.12	1.25	1.25	1.26
3MHz QPSK	2.70	2.70	2.70	3.00	3.00	2.99
3MHz 16QAM	2.70	2.69	2.69	3.01	3.04	3.01
5MHz QPSK	4.54	4.52	4.52	4.98	4.94	4.96
5MHz 16QAM	4.54	4.56	4.52	5.00	5.02	4.98
10MHz QPSK	8.96	8.96	8.96	9.80	9.80	9.80
10MHz 16QAM	8.92	8.96	8.96	9.72	9.80	9.72

Note: The test plots please refer to the Plots of Occupied Bandwidth


FCC §2.1051, §27.53, RSS-130 Clause 4.7:Spurious Emissions at Antenna Terminal	
Result:	Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


FCC §2.1051, §27.53, RSS-130 Clause 4.7:Out of band emission, Band Edge	
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.


FCC §2.1055, §27.54, RSS-130 Clause 4.4: Frequency Stability						
Test Mode:	10M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	699.0192	699.00	715.9760	716.00
	-20	3.8	699.0199	699.00	715.9802	716.00
	-10	3.8	699.0167	699.00	715.9792	716.00
	0	3.8	699.0181	699.00	715.9783	716.00
	10	3.8	699.0188	699.00	715.9756	716.00
	20	3.8	699.0199	699.00	715.9750	716.00
	30	3.8	699.0195	699.00	715.9755	716.00
	40	3.8	699.0199	699.00	715.9776	716.00
	50	3.8	699.0174	699.00	715.9735	716.00
Frequency Stability vs. Voltage	20	3.45	699.0233	699.00	715.9793	716.00
	20	4.4	699.0225	699.00	715.9738	716.00
					Result:	Pass


Test Mode:	10M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	699.0102	699.00	715.9898	716.00
	-20	3.8	699.0102	699.00	715.9838	716.00
	-10	3.8	699.0138	699.00	715.9836	716.00
	0	3.8	699.0092	699.00	715.9850	716.00
	10	3.8	699.0107	699.00	715.9865	716.00
	20	3.8	699.0109	699.00	715.9898	716.00
	30	3.8	699.0115	699.00	715.9836	716.00
	40	3.8	699.0104	699.00	715.9911	716.00
	50	3.8	699.0146	699.00	715.9843	716.00
Frequency Stability vs. Voltage	20	3.45	699.0113	699.00	715.9842	716.00
	20	4.4	699.0152	699.00	715.9913	716.00
					Result:	Pass


Test Plots(Note: The 10dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):
































4.9 Antenna Port Test Data and Results for LTE Band 41

Serial Number:	29PD-2	Test Date:	2023/8/10~2023/8/11
Test Site:	RF	Test Mode:	Transmitting
Tester:	Gary Ling	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3	Relative Humidity: (%)	26	ATM Pressure: (kPa)	101
-------------------	------	------------------------	----	---------------------	-----

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSU26	200120	2023/4/18	2024/4/17
zhuoxiang	Coaxial Cable	SMA-178	211001	Each time	N/A
R&S	Wideband Radio Communication Tester	CMW500	143458	2023/3/31	2024/3/30
Weinschel	Power Splitter	1515	RA914	Each time	N/A
BACL	TEMP&HUMI Test Chamber	BTH-150-40	30174	2023/3/31	2024/3/30
UNI-T	Multimeter	UT39A+	C210582554	2022/9/29	2023/9/28
ZHAOXIN	DC Power Supply	RXN-6010D	21R6010D0912386	N/A	N/A

* Statement of Traceability: China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Frequency For Each Mode:

Operation Bandwidth	Lowest Frequency (MHz)	Middle Frequency (MHz)	Highest Frequency (MHz)
5MHz	2537.5	2595	2652.5
10MHz	2540	2595	2650
15MHz	2542.5	2595	2647.5
20MHz	2545	2595	2645

Test Data:**FCC§2.1046;§ 27.50(h)(2) , RSS-199 Clause 5.5****RF Output Power:**

Test Bandwidth & Modulation	Resource Block & RB offset	Conducted Average Output Power(dBm)			Maximum EIRP (dBm)	EIRP Limit (dBm)
		Lowest Channel	Middle Channel	Highest Channel		
5MHz QPSK	RB1#0	18.68	19.08	19.11	21.12	33
	RB1#13	18.62	19.09	19.17		
	RB1#24	18.71	19.11	19.18		
	RB15#0	17.81	18.08	18.06		
	RB15#10	17.83	18.07	18.17		
	RB25#0	17.79	18.05	17.98		
5MHz 16QAM	RB1#0	17.86	17.99	18.55	20.51	33
	RB1#13	17.92	17.99	18.57		
	RB1#24	17.69	17.96	18.54		
	RB15#0	17.17	17.20	17.36		
	RB15#10	17.10	17.21	17.41		
	RB25#0	16.85	17.24	17.44		
10MHz QPSK	RB1#0	18.62	19.13	19.11	21.14	33
	RB1#25	18.72	19.05	19.09		
	RB1#49	18.76	19.20	19.02		
	RB25#0	17.78	17.97	18.12		
	RB25#25	17.72	18.07	18.10		
	RB50#0	17.36	17.62	17.70		
10MHz 16QAM	RB1#0	17.79	18.48	18.09	20.42	33
	RB1#25	17.79	18.15	18.10		
	RB1#49	17.75	18.36	18.09		
	RB25#0	16.93	17.33	17.60		
	RB25#25	16.94	17.44	17.59		
	RB50#0	16.66	16.96	16.93		
15MHz QPSK	RB1#0	18.66	19.15	19.28	21.3	33
	RB1#38	18.47	19.08	19.31		
	RB1#74	18.54	19.04	19.36		
	RB36#0	17.81	18.11	18.11		
	RB36#39	17.74	18.07	18.04		
	RB75#0	17.43	17.61	17.75		
15MHz 16QAM	RB1#0	18.07	18.22	18.44	20.51	33
	RB1#38	18.06	18.27	18.57		
	RB1#74	17.97	18.18	18.51		
	RB36#0	16.89	17.24	17.25		
	RB36#39	16.88	17.20	17.14		
	RB75#0	16.66	16.72	16.95		

20MHz QPSK	RB1#0	18.88	18.96	19.24	21.22	33
	RB1#50	18.87	18.92	19.28		
	RB1#99	18.90	18.96	19.27		
	RB50#0	17.76	18.12	18.14		
	RB50#50	17.82	18.03	18.12		
	RB100#0	17.42	17.59	17.60		
20MHz 16QAM	RB1#0	18.19	17.92	18.99	21.04	33
	RB1#50	18.12	17.80	19.05		
	RB1#99	18.17	17.85	19.10		
	RB50#0	17.02	17.21	17.31		
	RB50#50	17.08	17.27	17.33		
	RB100#0	16.57	16.82	16.87		

Note: EIRP=Conducted Power(dBm) - Lc(dB) + Gt(dBi)

Result: Pass

Peak-to-average Ratio(PAR)						
Test Bandwidth & Modulation	Resource Block & RB offset	Peak-to-average Ratio(dB)			Limit (dB)	
		Lowest Channel	Middle Channel	Highest Channel		
20MHz QPSK	RB1#0	12.19	10.06	12.79	13	13
	RB100#0	12.43	12.44	9.74		
20MHz 16QAM	RB1#0	10.03	7.15	9.2	13	13
	RB100#0	12.08	8.04	12.79		

Result: Pass

FCC §2.1049, §27.53,RSS-Gen Clause 6.7:Occupied Bandwidth						
Operation Mode	99% Occupied Bandwidth (MHz)			26 dB Occupied Bandwidth (MHz)		
	Low Channel	Middle channel	High Channel	Low Channel	Middle Channel	High Channel
5MHz QPSK	4.52	4.52	4.52	5.08	5.22	5.00
5MHz 16QAM	4.52	4.54	4.54	5.28	5.12	5.16
10MHz QPSK	9.00	9.00	9.00	9.72	9.88	9.80
10MHz 16QAM	9.00	9.00	8.96	9.68	9.84	9.76
15MHz QPSK	13.56	13.56	13.62	16.32	16.26	15.36
15MHz 16QAM	13.62	13.68	13.62	15.96	16.74	15.60
20MHz QPSK	18.00	18.00	18.08	20.16	19.68	20.40
20MHz 16QAM	18.00	18.00	18.08	19.76	20.32	20.64

Note: The test plots please refer to the Plots of Occupied Bandwidth

FCC §2.1051, § 27.53, RSS-199 Clause 5.6:Spurious Emissions at Antenna Terminal


Result: Pass, Please refer to the test plots of Spurious Emissions at Antenna Terminal.


FCC §2.1051, § 27.53, RSS-199 Clause 5.6:Out of band emission, Band Edge						
Result:	Pass, Please refer to the test plots of Out of band emission, Band Edge.					


FCC §2.1055, §27.54, RSS-199 Clause 5.4: Frequency Stability						
Test Mode:	20M QPSK	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	2535.0082	2535.00	2654.9791	2655
	-20	3.8	2535.0112	2535.00	2654.9741	2655
	-10	3.8	2535.0099	2535.00	2654.9807	2655
	0	3.8	2535.0142	2535.00	2654.9775	2655
	10	3.8	2535.0195	2535.00	2654.9843	2655
	20	3.8	2535.0115	2535.00	2654.9812	2655
	30	3.8	2535.0096	2535.00	2654.9743	2655
	40	3.8	2535.0094	2535.00	2654.9748	2655
	50	3.8	2535.0078	2535.00	2654.9811	2655
Frequency Stability vs. Voltage	20	3.45	2535.0141	2535.00	2654.9789	2655
	20	4.4	2535.0078	2535.00	2654.9813	2655
					Result:	Pass


Test Mode:	20M 16QAM	Test Channel: Lowest for Lower Edge,Highest for Upper Edge				
Test Item	Temperature (°C)	Voltage (V _{DC})	Lower Edge (MHz)		Upper Edge (MHz)	
			Result	Limit	Result	Limit
Frequency Stability vs. Temperature	-30	3.8	2535.0047	2535.00	2654.9814	2655
	-20	3.8	2535.0051	2535.00	2654.9794	2655
	-10	3.8	2535.0043	2535.00	2654.9771	2655
	0	3.8	2535.0062	2535.00	2654.9769	2655
	10	3.8	2535.0012	2535.00	2654.9819	2655
	20	3.8	2535.0037	2535.00	2654.9810	2655
	30	3.8	2535.0002	2535.00	2654.9793	2655
	40	3.8	2535.0040	2535.00	2654.9746	2655
	50	3.8	2535.0003	2535.00	2654.9763	2655
Frequency Stability vs. Voltage	20	3.45	2535.0008	2535.00	2654.9739	2655
	20	4.4	2535.0002	2535.00	2654.9767	2655
					Result:	Pass


Test Plots(Note: The 10.5dB is the Insertion loss of the RF cable, Coaxial tee connector and DC Block, which was offset into the Spectrum Analyzer):
































4.10 Radiated Spurious Emissions

Serial Number:	29PD-1	Test Date:	2023/8/29~2023/9/8
Test Site:	966-2,966-1	Test Mode:	Transmitting
Tester:	Carl Xue, Coco Tian	Test Result:	Pass

Environmental Conditions:

Temperature: (°C)	25.3~26.1	Relative Humidity: (%)	63~65	ATM Pressure: (kPa)	99.7~100
-------------------	-----------	------------------------	-------	---------------------	----------

Test Equipment List and Details:

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
EMCO	Adjustable Dipole Antenna	3121C	9109-756	N/A	N/A
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/7/16	2024/7/15
ETS-Lindgren	Horn Antenna	3115	9912-5985	2020/10/13	2023/10/12
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
AH	Double Ridge Guide Horn Antenna	SAS-571	1396	2021/10/18	2024/10/17
MICRO-COAX	Coaxial Cable	UFA210B-0-0720-300300	99G1448	2022/7/16	2024/7/15
Agilent	Signal Generator	E8247C	MY43321352	2022/11/18	2023/11/17
PASTERNACK	Horn Antenna	PE9852/2F-20	112002	2021/2/5	2024/2/4
PASTERNACK	Horn Antenna	PE9852/2F-20	112001	2021/2/5	2024/2/4
Quinstar	Preamplifier	QLW-18405536-JO	15964001005	2022/9/16	2023/9/15
PASTERNACK	Horn Antenna	PE9850/2F-20	072001	2021/2/5	2024/2/4
PASTERNACK	Horn Antenna	PE9850/2F-20	072002	2021/2/5	2024/2/4
MICRO-COAX	Coaxial Cable	UFB142A-1-2362-200200	235772-001	2023/8/6	2024/8/5

* **Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:

Please refer to the below table.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.26 figure 5, the worst orientation was photographed and it's data was recorded.

Cellular Band**30 MHz-10 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 850 Frequency:824.2MHz								
723.95	H	21.15	-51.69	0.00	0.51	-52.20	-13.00	39.20
721.88	V	21.04	-48.40	0.00	0.50	-48.90	-13.00	35.90
1648.400	H	59.73	-44.60	8.68	0.80	-36.72	-13.00	23.72
1648.400	V	53.57	-50.84	8.68	0.80	-42.96	-13.00	29.96
2472.600	H	60.23	-40.55	9.38	1.00	-32.17	-13.00	19.17
2472.600	V	58.24	-42.49	9.38	1.00	-34.11	-13.00	21.11
3296.800	H	41.92	-54.76	10.32	1.15	-45.59	-13.00	32.59
3296.800	V	40.07	-56.37	10.32	1.15	-47.20	-13.00	34.20
GSM 850 Frequency:836.6MHz								
701.48	H	20.92	-52.37	0.00	0.55	-52.92	-13.00	39.92
663.67	V	20.89	-49.69	0.00	0.50	-50.19	-13.00	37.19
1673.200	H	58.39	-45.92	8.71	0.85	-38.06	-13.00	25.06
1673.200	V	49.77	-54.64	8.71	0.85	-46.78	-13.00	33.78
2509.800	H	60.11	-40.50	9.42	1.01	-32.09	-13.00	19.09
2509.800	V	54.41	-46.21	9.42	1.01	-37.80	-13.00	24.80
3346.400	H	45.24	-51.93	10.34	1.16	-42.75	-13.00	29.75
3346.400	V	44.02	-53.01	10.34	1.16	-43.83	-13.00	30.83
GSM 850 Frequency:848.8MHz								
472.17	H	21.08	-55.32	0.00	0.43	-55.75	-13.00	42.75
704.39	V	20.92	-48.90	0.00	0.55	-49.45	-13.00	36.45
1697.600	H	58.32	-45.97	8.74	0.90	-38.13	-13.00	25.13
1697.600	V	49.86	-54.56	8.74	0.90	-46.72	-13.00	33.72
2546.400	H	54.51	-45.82	9.47	1.01	-37.36	-13.00	24.36
2546.400	V	49.69	-50.59	9.47	1.01	-42.13	-13.00	29.13
3395.200	H	45.87	-51.82	10.36	1.19	-42.65	-13.00	29.65
3395.200	V	41.43	-56.23	10.36	1.19	-47.06	-13.00	34.06

PCS Band**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
GSM 1900 Frequency:1850.2MHz								
210.04	H	35.12	-77.57	0.00	0.26	-77.83	-13.00	64.83
45.21	V	41.40	-55.11	-19.59	0.12	-74.82	-13.00	61.82
3700.400	H	47.60	-49.72	10.60	1.25	-40.37	-13.00	27.37
3700.400	V	46.97	-50.33	10.60	1.25	-40.98	-13.00	27.98
5550.600	H	50.70	-42.56	11.44	1.49	-32.61	-13.00	19.61
5550.600	V	46.68	-46.42	11.44	1.49	-36.47	-13.00	23.47
GSM 1900 Frequency:1880MHz								
207.12	H	34.92	-77.83	0.00	0.26	-78.09	-13.00	65.09
43.81	V	41.36	-53.40	-21.37	0.12	-74.89	-13.00	61.89
3760.000	H	45.21	-51.20	10.66	1.24	-41.78	-13.00	28.78
3760.000	V	45.18	-51.11	10.66	1.24	-41.69	-13.00	28.69
5640.000	H	51.46	-41.99	11.33	1.54	-32.20	-13.00	19.20
5640.000	V	52.02	-41.31	11.33	1.54	-31.52	-13.00	18.52
GSM 1900 Frequency:1909.8MHz								
210.78	H	34.86	-77.82	0.00	0.26	-78.08	-13.00	65.08
43.81	V	41.30	-53.46	-21.37	0.12	-74.95	-13.00	61.95
3819.600	H	46.53	-49.33	10.72	1.29	-39.90	-13.00	26.90
3819.600	V	43.68	-52.04	10.72	1.29	-42.61	-13.00	29.61
5729.400	H	47.22	-46.26	11.22	1.59	-36.63	-13.00	23.63
5729.400	V	43.29	-50.07	11.22	1.59	-40.44	-13.00	27.44

WCDMA Band 2:**30 MHz-20 GHz:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band II, Frequency: 1852.4 MHz								
207.85	H	34.88	-77.85	0.00	0.26	-78.11	-13.00	65.11
43.81	V	41.37	-53.39	-21.37	0.12	-74.88	-13.00	61.88
3704.800	H	36.93	-60.33	10.60	1.25	-50.98	-13.00	37.98
3704.800	V	37.5	-59.73	10.60	1.25	-50.38	-13.00	37.38
5557.200	H	39.28	-54.00	11.43	1.49	-44.06	-13.00	31.06
5557.200	V	34.86	-58.27	11.43	1.49	-48.33	-13.00	35.33
WCDMA Band II, Frequency: 1880 MHz								
209.31	H	34.76	-77.95	0.00	0.26	-78.21	-13.00	65.21
45.21	V	41.20	-55.31	-19.59	0.12	-75.02	-13.00	62.02
3760.000	H	36.77	-59.64	10.66	1.24	-50.22	-13.00	37.22
3760.000	V	35.73	-60.56	10.66	1.24	-51.14	-13.00	38.14
5640.000	H	42.87	-50.58	11.33	1.54	-40.79	-13.00	27.79
5640.000	V	36.47	-56.86	11.33	1.54	-47.07	-13.00	34.07
WCDMA Band II, Frequency: 1907.6 MHz								
214.50	H	34.85	-77.75	0.00	0.27	-78.02	-13.00	65.02
43.65	V	41.43	-53.12	-21.58	0.12	-74.82	-13.00	61.82
3815.200	H	36.91	-58.94	10.72	1.29	-49.51	-13.00	36.51
3815.200	V	34.81	-60.88	10.72	1.29	-51.45	-13.00	38.45
5722.800	H	44.31	-49.18	11.23	1.58	-39.53	-13.00	26.53
5722.800	V	36.56	-56.79	11.23	1.58	-47.14	-13.00	34.14

30 MHz-10 GHz**WCDMA Band 5:**

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
WCDMA Band 5 Frequency:826.4 MHz								
699.47	H	20.80	-52.52	0.00	0.55	-53.07	-13.00	40.07
716.52	V	21.10	-48.46	0.00	0.50	-48.96	-13.00	35.96
1652.800	H	52.19	-52.14	8.68	0.81	-44.27	-13.00	31.27
1652.800	V	43.93	-60.48	8.68	0.81	-52.61	-13.00	39.61
2479.200	H	46.30	-54.46	9.39	1.01	-46.08	-13.00	33.08
2479.200	V	44.88	-55.85	9.39	1.01	-47.47	-13.00	34.47
3305.600	H	36.35	-60.38	10.32	1.15	-51.21	-13.00	38.21
3305.600	V	33.52	-62.98	10.32	1.15	-53.81	-13.00	40.81
WCDMA Band 5 Frequency:836.6MHz								
724.41	H	20.83	-52.00	0.00	0.51	-52.51	-13.00	39.51
724.09	V	20.86	-48.53	0.00	0.51	-49.04	-13.00	36.04
1673.200	H	54.10	-50.21	8.71	0.85	-42.35	-13.00	29.35
1673.200	V	45.17	-59.24	8.71	0.85	-51.38	-13.00	38.38
2509.800	H	47.13	-53.48	9.42	1.01	-45.07	-13.00	32.07
2509.800	V	50.29	-50.33	9.42	1.01	-41.92	-13.00	28.92
3346.400	H	44.01	-53.16	10.34	1.16	-43.98	-13.00	30.98
3346.400	V	40.86	-56.17	10.34	1.16	-46.99	-13.00	33.99
WCDMA Band 5 Frequency:846.6MHz								
647.59	H	20.75	-52.85	0.00	0.52	-53.37	-13.00	40.37
576.64	V	20.91	-50.78	0.00	0.46	-51.24	-13.00	38.24
1693.200	H	57.73	-46.57	8.73	0.89	-38.73	-13.00	25.73
1693.200	V	48.96	-55.46	8.73	0.89	-47.62	-13.00	34.62
2539.800	H	46.55	-53.83	9.46	1.01	-45.38	-13.00	32.38
2539.800	V	40.62	-59.72	9.46	1.01	-51.27	-13.00	38.27
3386.400	H	44.28	-53.31	10.35	1.18	-44.14	-13.00	31.14
3386.400	V	41.12	-56.42	10.35	1.18	-47.25	-13.00	34.25

LTE Bands:

(The Worst modulation and bandwidth was below)

LTE Band 2 (30MHz-20GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, 1.4MHz, Frequency:1850.7 MHz								
207.85	H	34.76	-77.97	0.00	0.26	-78.23	-13.00	65.23
43.66	V	41.29	-53.27	-21.57	0.12	-74.96	-13.00	61.96
3701.400	H	41	-56.31	10.60	1.25	-46.96	-13.00	33.96
3701.400	V	39.75	-57.54	10.60	1.25	-48.19	-13.00	35.19
5552.100	H	49.26	-44.01	11.44	1.49	-34.06	-13.00	21.06
5552.100	V	44.02	-49.08	11.44	1.49	-39.13	-13.00	26.13
QPSK, 1.4MHz, Frequency:1880 MHz								
206.39	H	34.80	-77.96	0.00	0.26	-78.22	-13.00	65.22
45.21	V	41.34	-55.17	-19.59	0.12	-74.88	-13.00	61.88
3760.000	H	37.32	-59.09	10.66	1.24	-49.67	-13.00	36.67
3760.000	V	38.01	-58.28	10.66	1.24	-48.86	-13.00	35.86
5640.000	H	56.01	-37.44	11.33	1.54	-27.65	-13.00	14.65
5640.000	V	48.66	-44.67	11.33	1.54	-34.88	-13.00	21.88
QPSK, 1.4MHz, Frequency:1909.3 MHz								
211.52	H	34.84	-77.82	0.00	0.26	-78.08	-13.00	65.08
45.21	V	41.38	-55.13	-19.59	0.12	-74.84	-13.00	61.84
3818.600	H	44.57	-51.29	10.72	1.29	-41.86	-13.00	28.86
3818.600	V	42.03	-53.68	10.72	1.29	-44.25	-13.00	31.25
5727.900	H	47.61	-45.87	11.23	1.59	-36.23	-13.00	23.23
5727.900	V	40.08	-53.28	11.23	1.59	-43.64	-13.00	30.64

LTE Band 5(30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, 1.4MHz, Frequency: 824.7 MHz								
631.75	H	20.88	-52.81	0.00	0.49	-53.30	-13.00	40.30
711.84	V	21.09	-48.57	0.00	0.51	-49.08	-13.00	36.08
1649.400	H	52.38	-51.95	8.68	0.80	-44.07	-13.00	31.07
1649.400	V	43	-61.41	8.68	0.80	-53.53	-13.00	40.53
2474.100	H	58.7	-42.08	9.38	1.00	-33.70	-13.00	20.70
2474.100	V	53.35	-47.38	9.38	1.00	-39.00	-13.00	26.00
3298.800	H	41.32	-55.36	10.32	1.15	-46.19	-13.00	33.19
3298.800	V	37.55	-58.89	10.32	1.15	-49.72	-13.00	36.72
QPSK, 1.4MHz, Frequency: 836.5 MHz								
721.70	H	20.98	-51.90	0.00	0.50	-52.40	-13.00	39.40
724.41	V	20.86	-48.53	0.00	0.51	-49.04	-13.00	36.04
1673.000	H	57.05	-47.26	8.71	0.85	-39.40	-13.00	26.40
1673.000	V	47.14	-57.27	8.71	0.85	-49.41	-13.00	36.41
2509.500	H	58.84	-41.77	9.42	1.01	-33.36	-13.00	20.36
2509.500	V	51.83	-48.79	9.42	1.01	-40.38	-13.00	27.38
3346.000	H	45.02	-52.14	10.34	1.16	-42.96	-13.00	29.96
3346.000	V	43.08	-53.94	10.34	1.16	-44.76	-13.00	31.76
QPSK, 1.4MHz, Frequency: 848.3 MHz								
696.85	H	21.15	-52.19	0.00	0.55	-52.74	-13.00	39.74
709.35	V	20.92	-48.80	0.00	0.52	-49.32	-13.00	36.32
1696.600	H	61.9	-42.39	8.74	0.89	-34.54	-13.00	21.54
1696.600	V	54.17	-50.25	8.74	0.89	-42.40	-13.00	29.40
2544.900	H	48.29	-52.05	9.47	1.01	-43.59	-13.00	30.59
2544.900	V	48.39	-51.91	9.47	1.01	-43.45	-13.00	30.45
3393.200	H	48.75	-48.92	10.36	1.19	-39.75	-13.00	26.75
3393.200	V	46.37	-51.26	10.36	1.19	-42.09	-13.00	29.09

LTE Band 7 (30MHz-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, 5MHz, Frequency: 2502.5 MHz								
205.93	H	34.83	-77.94	0.00	0.26	-78.20	-25.00	53.20
43.81	V	41.24	-53.52	-21.37	0.12	-75.01	-25.00	50.01
5005.000	H	52.83	-40.13	11.20	1.47	-30.40	-25.00	5.40
5005.000	V	52.08	-40.74	11.20	1.47	-31.01	-25.00	6.01
7507.500	H	52.01	-37.78	10.90	1.95	-28.83	-25.00	3.83
7507.500	V	52.33	-37.96	10.90	1.95	-29.01	-25.00	4.01
QPSK, 5MHz, Frequency: 2535 MHz								
209.56	H	35.05	-77.65	0.00	0.26	-77.91	-25.00	52.91
43.66	V	41.33	-53.23	-21.57	0.12	-74.92	-25.00	49.92
5070.000	H	52.23	-40.96	11.24	1.47	-31.19	-25.00	6.19
5070.000	V	50.56	-42.53	11.24	1.47	-32.76	-25.00	7.76
7605.000	H	51.2	-38.27	10.88	2.01	-29.40	-25.00	4.40
7605.000	V	52.38	-37.81	10.88	2.01	-28.94	-25.00	3.94
QPSK, 5MHz, Frequency: 2567.5 MHz								
210.30	H	34.73	-77.96	0.00	0.26	-78.22	-25.00	53.22
45.21	V	41.40	-55.11	-19.59	0.12	-74.82	-25.00	49.82
5135.000	H	54.12	-39.48	11.28	1.47	-29.67	-25.00	4.67
5135.000	V	52.87	-40.62	11.28	1.47	-30.81	-25.00	5.81
7702.500	H	51.85	-37.67	10.86	1.97	-28.78	-25.00	3.78
7702.500	V	52.2	-37.98	10.86	1.97	-29.09	-25.00	4.09

LTE Band 12 (30MHz-10GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, 1.4MHz, Frequency: 699.7 MHz								
532.12	H	20.60	-54.60	0.00	0.45	-55.05	-13.00	42.05
597.22	V	20.81	-50.92	0.00	0.51	-51.43	-13.00	38.43
1399.400	H	57.53	-46.17	8.22	0.71	-38.66	-13.00	25.66
1399.400	V	59.2	-44.55	8.22	0.71	-37.04	-13.00	24.04
2099.100	H	57.42	-44.46	9.16	0.91	-36.21	-13.00	23.21
2099.100	V	52.56	-49.27	9.16	0.91	-41.02	-13.00	28.02
2798.800	H	43.37	-56.56	9.88	1.04	-47.72	-13.00	34.72
2798.800	V	46.24	-53.56	9.88	1.04	-44.72	-13.00	31.72
QPSK, 1.4MHz, Frequency: 707.5 MHz								
578.79	H	20.65	-53.63	0.00	0.46	-54.09	-13.00	41.09
506.56	V	20.73	-50.86	0.00	0.45	-51.31	-13.00	38.31
1415.000	H	63.32	-40.35	8.26	0.72	-32.81	-13.00	19.81
1415.000	V	65.06	-38.66	8.26	0.72	-31.12	-13.00	18.12
2122.500	H	53.36	-48.63	9.17	0.92	-40.38	-13.00	27.38
2122.500	V	52.2	-49.77	9.17	0.92	-41.52	-13.00	28.52
2830.000	H	41.23	-58.57	9.93	1.06	-49.70	-13.00	36.70
2830.000	V	43.22	-56.51	9.93	1.06	-47.64	-13.00	34.64
QPSK, 1.4MHz, Frequency: 715.3 MHz								
452.93	H	20.71	-56.08	0.00	0.42	-56.50	-13.00	43.50
554.86	V	20.96	-50.70	0.00	0.49	-51.19	-13.00	38.19
1430.600	H	65.06	-38.57	8.31	0.73	-30.99	-13.00	17.99
1430.600	V	65.45	-38.24	8.31	0.73	-30.66	-13.00	17.66
2145.900	H	56.98	-45.12	9.19	0.93	-36.86	-13.00	23.86
2145.900	V	56.27	-45.84	9.19	0.93	-37.58	-13.00	24.58
2861.200	H	43.02	-56.63	9.98	1.07	-47.72	-13.00	34.72
2861.200	V	42.2	-57.47	9.98	1.07	-48.56	-13.00	35.56

LTE Band 41 (30MHz-27GHz):

Frequency (MHz)	Polar (H/V)	Receiver Reading (dB μ V)	Substituted Method			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Substituted Level (dBm)	Antenna Gain (dBd/dBi)	Cable Loss (dB)			
QPSK, 5MHz, Low Frequency: 2537.5 MHz								
208.83	H	34.87	-77.85	0.00	0.26	-78.11	-25.00	53.11
43.65	V	41.25	-53.30	-21.58	0.12	-75.00	-25.00	50.00
5075.000	H	54.72	-38.49	11.25	1.48	-28.72	-25.00	3.72
5075.000	V	54.32	-38.79	11.25	1.48	-29.02	-25.00	4.02
7612.500	H	43.9	-45.58	10.88	2.02	-36.72	-25.00	11.72
7612.500	V	51.64	-38.55	10.88	2.02	-29.69	-25.00	4.69
QPSK, 5MHz, Middle Frequency: 2595 MHz								
204.49	H	34.80	-78.00	0.00	0.26	-78.26	-25.00	53.26
45.21	V	41.31	-55.20	-19.59	0.12	-74.91	-25.00	49.91
5190.000	H	52.14	-41.93	11.31	1.44	-32.06	-25.00	7.06
5190.000	V	53.8	-40.12	11.31	1.44	-30.25	-25.00	5.25
7785.000	H	51.18	-38.31	10.84	1.99	-29.46	-25.00	4.46
7785.000	V	52.3	-37.62	10.84	1.99	-28.77	-25.00	3.77
QPSK, 5MHz, High Frequency: 2652.5 MHz								
211.78	H	34.94	-77.72	0.00	0.26	-77.98	-25.00	52.98
43.81	V	41.20	-53.56	-21.37	0.12	-75.05	-25.00	50.05
5305.000	H	55.51	-37.93	11.38	1.46	-28.01	-25.00	3.01
5305.000	V	53.79	-39.39	11.38	1.46	-29.47	-25.00	4.47
7957.500	H	50.07	-38.35	10.81	2.09	-29.63	-25.00	4.63
7957.500	V	52.03	-36.84	10.81	2.09	-28.12	-25.00	3.12

Note:

- 1) The unit of Antenna Gain is dBd for frequency below 1GHz, and the unit of Antenna Gain is dBi for frequency above 1GHz.
- 2) Absolute Level = Substituted Level - Cable loss + Antenna Gain
- 3) Margin = Limit-Absolute Level

4.11 Receiver Spurious Emissions

Serial Number:	29PD-1	Test Date:	2023/10/12~2023/10/16
Test Site:	966-2,966-1	Test Mode:	Receiver(Idle)
Tester:	Carl Xue, Mack Huang	Test Result:	Pass

Environmental Conditions:					
Temperature: (°C)	25.3~26.1	Relative Humidity: (%)	63~65	ATM Pressure: (kPa)	99.7~100

Test Equipment List and Details:


Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Antenna	JB6	A082520-5	2020/10/19	2023/10/18
R&S	EMI Test Receiver	ESR3	102724	2023/3/31	2024/3/30
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0470-02	2023/7/16	2024/7/15
TIMES MICROWAVE	Coaxial Cable	LMR-600-UltraFlex	C-0780-01	2023/7/16	2024/7/15
Sonoma	Amplifier	310N	186165	2023/7/16	2024/7/15
R&S	Spectrum Analyzer	FSV40	101591	2023/3/31	2024/3/30
MICRO-COAX	Coaxial Cable	UFA210A-1-1200-70U300	217423-008	2023/8/6	2024/8/5
MICRO-COAX	Coaxial Cable	UFA210A-1-2362-300300	235780-001	2023/8/6	2024/8/5
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2022/11/9	2023/11/8
ETS-Lindgren	Horn Antenna	3115	9912-5985	2021/10/14	2024/10/13
Audix	Test Software	E3	201021(V9)	N/A	N/A

* **Statement of Traceability:** China Certification ICT Co., Ltd (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data:


Please refer to the below table.

Note: The device can be mounted in multiple orientations, test was performed with X,Y, Z Axis according to C63.4, the worst orientation was photographed and it's data was recorded.



GSM 1900 Band

Project No.: CR230846390
Tester: Carl Xue
Polarization: vertical
Note: HJ-0502000W2-US




**30MHz-1GHz
Vertical**

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.962	37.63	-4.34	33.29	40.00	6.71	Peak
2	38.346	37.46	-10.00	27.46	40.00	12.54	Peak
3	71.080	43.21	-16.59	26.62	40.00	13.38	Peak
4	89.590	38.53	-16.96	21.57	43.50	21.93	Peak
5	146.888	31.73	-11.98	19.75	43.50	23.75	Peak
6	209.313	32.70	-12.46	20.24	43.50	23.26	Peak

GSM 1900 Band**1-18GHz
Horizontal**

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: horizontal
Note:

Date: 2023-10-16




No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	15106.020	20.73	25.46	46.19	54.00	7.81	Average
2	15106.020	32.91	25.46	58.37	74.00	15.63	Peak
3	15956.190	22.06	25.25	47.31	54.00	6.69	Average
4	15956.190	34.36	25.25	59.61	74.00	14.39	Peak
5	17517.100	17.29	30.06	47.35	54.00	6.65	Average
6	17517.100	29.63	30.06	59.69	74.00	14.31	Peak

GSM 1900 Band**1-18GHz
Vertical**

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: vertical
Note:

Date: 2023-10-16




No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	15694.340	22.25	24.78	47.03	54.00	6.97	Average
2	15694.340	34.28	24.78	59.06	74.00	14.94	Peak
3	16663.530	20.51	26.65	47.16	54.00	6.84	Average
4	16663.530	32.67	26.65	59.32	74.00	14.68	Peak
5	17459.290	17.41	29.84	47.25	54.00	6.75	Average
6	17459.290	29.66	29.84	59.50	74.00	14.50	Peak

WCDMA Band 2

Project No.: CR230846390
Tester: Carl Xue
Polarization: horizontal
Note: HJ-0502000W2-US

**30MHz-1GHz
Horizontal**




No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.105	27.83	-3.68	24.15	40.00	15.85	Peak
2	74.919	38.11	-16.92	21.19	40.00	18.81	Peak
3	89.590	41.32	-16.96	24.36	43.50	19.14	Peak
4	139.851	39.10	-11.86	27.24	43.50	16.26	Peak
5	206.398	36.10	-12.39	23.71	43.50	19.79	Peak
6	276.124	36.56	-11.84	24.72	46.00	21.28	Peak

WCDMA Band 2

Project No.: CR230846390
Tester: Carl Xue
Polarization: vertical
Note: HJ-0502000W2-US


**30MHz-1GHz
Vertical**



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	32.067	37.84	-5.17	32.67	40.00	7.33	Peak
2	44.275	39.03	-13.82	25.21	40.00	14.79	Peak
3	70.584	42.37	-16.53	25.84	40.00	14.16	Peak
4	90.855	36.96	-16.72	20.24	43.50	23.26	Peak
5	144.335	32.12	-11.96	20.16	43.50	23.34	Peak
6	204.238	32.66	-12.33	20.33	43.50	23.17	Peak

WCDMA Band 2

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: horizontal
Note:




**1-18GHz
Horizontal**

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	14925.790	21.56	25.45	47.01	54.00	6.99	Average
2	14925.790	33.57	25.45	59.02	74.00	14.98	Peak
3	16316.660	21.75	25.67	47.42	54.00	6.58	Average
4	16316.660	34.16	25.67	59.83	74.00	14.17	Peak
5	17030.810	18.81	28.22	47.03	54.00	6.97	Average
6	17030.810	31.83	28.22	60.05	74.00	13.95	Peak

WCDMA Band 2**1-18GHz
Vertical**

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: vertical
Note:

Date: 2023-10-16




No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	14772.750	20.51	25.62	46.13	54.00	7.87	Average
2	14772.750	32.64	25.62	58.26	74.00	15.74	Peak
3	15993.600	22.04	25.17	47.21	54.00	6.79	Average
4	15993.600	34.24	25.17	59.41	74.00	14.59	Peak
5	17173.630	18.58	28.57	47.15	54.00	6.85	Average
6	17173.630	30.73	28.57	59.30	74.00	14.70	Peak

LTE Band 2

Project No.: CR230846390
Tester: Carl Xue
Polarization: horizontal
Note: HJ-0502000W2-US

**30MHz-1GHz
Horizontal**




No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.962	28.21	-4.34	23.87	40.00	16.13	Peak
2	74.919	37.95	-16.92	21.03	40.00	18.97	Peak
3	89.590	40.53	-16.96	23.57	43.50	19.93	Peak
4	139.361	37.65	-11.83	25.82	43.50	17.68	Peak
5	207.123	36.31	-12.40	23.91	43.50	19.59	Peak
6	271.325	36.46	-12.04	24.42	46.00	21.58	Peak

LTE Band 2

Project No.: CR230846390
Tester: Carl Xue
Polarization: vertical
Note: HJ-0502000W2-US


**30MHz-1GHz
Vertical**



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	30.105	36.58	-3.68	32.90	40.00	7.10	Peak
2	37.812	37.60	-9.59	28.01	40.00	11.99	Peak
3	69.114	43.41	-16.59	26.82	40.00	13.18	Peak
4	89.590	37.52	-16.96	20.56	43.50	22.94	Peak
5	143.326	31.81	-11.93	19.88	43.50	23.62	Peak
6	202.100	32.59	-12.28	20.31	43.50	23.19	Peak

LTE Band 2

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: horizontal
Note:




**1-18GHz
Horizontal**

No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	15119.620	20.89	25.44	46.33	54.00	7.67	Average
2	15119.620	33.22	25.44	58.66	74.00	15.34	Peak
3	15701.140	22.26	24.78	47.04	54.00	6.96	Average
4	15701.140	34.29	24.78	59.07	74.00	14.93	Peak
5	17802.760	15.66	31.63	47.29	54.00	6.71	Average
6	17802.760	28.95	31.63	60.58	74.00	13.42	Peak

LTE Band 2**1-18GHz
Vertical**

Project No.: CR230846390-RF
Tester: Mack Huang
Polarization: vertical
Note:

Date: 2023-10-16



No.	Frequency (MHz)	Reading (dB μ V)	Factor (dB/m)	Result (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)	Detector
1	15680.740	22.58	24.77	47.35	54.00	6.65	Average
2	15680.740	34.93	24.77	59.70	74.00	14.30	Peak
3	16364.270	21.73	25.71	47.44	54.00	6.56	Average
4	16364.270	34.17	25.71	59.88	74.00	14.12	Peak
5	17469.490	17.59	29.87	47.46	54.00	6.54	Average
6	17469.490	30.04	29.87	59.91	74.00	14.09	Peak

5. EUT PHOTOGRAPHS

Please refer to the attachment CR230846390-EXP EUT EXTERNAL PHOTOGRAPHS and
CR230846390-INP EUT INTERNAL PHOTOGRAPHS

6. TEST SETUP PHOTOGRAPHS

Please refer to the attachment CR230846390-00E-TSP TEST SETUP PHOTOGRAPHS.

===== END OF REPORT =====