

FCC and ISED Test report for subparts 15C,  
sections 15.207 and 15.247;  
RSS-247, RSS-Gen

Product name : Motion sensor G3  
Applicant : in-lite  
FCC ID : 2AU26-SMARTMOVE  
IC ID : 25679-SMARTMOVE

Test report No. : 190800657 02 V1.00

## Laboratory information

### Accreditation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2005. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001.

Telefication is a Wireless Device Testing laboratory recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements. The Industry Canada registration number for the 3 meter test chamber of Telefication is: 4173A-1.

Telefication is a registered Conformity Assessment body (CAB) under the Japan-EC MRA (Agreement on Mutual Recognition between Japan and the European Community). The registration number is: 201.

### Documentation

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands.

### Testing Location

Test Site	Telefication BV
Test Site location	Edisonstraat 12a 6902 PK Zevenaar The Netherlands  Tel. +31316583180 Fax. +31316583189
Test Site FCC	NL0001

## Revision History

Version	Date	Remarks	By
v0.50	23-11-2019	First draft	PS
v1.00	26-11-2019	First issue	PS

## Table of Contents

Revision History .....	2
Summary of Test results.....	5
1 General Description.....	6
1.1 Applicant.....	6
1.2 Manufacturer .....	6
1.3 Tested Equipment Under Test (EUT) .....	6
1.4 Product specifications of Equipment under test .....	7
1.5 Environmental conditions.....	7
1.6 Measurement standards .....	7
1.7 Applicable standards .....	7
1.8 Observation and remarks .....	7
1.9 Conclusions.....	8
2 Test configuration of the Equipment Under Test .....	9
2.1 Test mode .....	9
2.2 Tested channels.....	9
2.3 Test setups.....	9
2.4 Equipment used in the test configuration .....	10
2.5 Sample calculations .....	10
3 Test results.....	11
3.1 Spurious emissions (incl. spurious emissions in the restricted bands).....	11
3.1.1 Limit.....	11
3.1.2 Measurement instruments .....	11
3.1.3 Test setup.....	11
3.1.4 Test procedure .....	11
3.1.5 Test results of the radiated spurious emission measurements .....	11
3.2 20 dB bandwidth Measurement.....	15
3.2.1 Limit.....	15
3.2.2 Measurement instruments .....	15
3.2.3 Test setup.....	15
3.2.4 Test procedure .....	15
3.2.5 Test Results of the 20 dB bandwidth Measurement.....	15
3.2.6 Plots of the 20 dB bandwidth measurement .....	15
3.3 99% Occupied Bandwidth.....	16
3.3.1 Limit.....	16
3.3.2 Measurement instruments .....	16
3.3.3 Test setup.....	16
3.3.4 Test procedure .....	16

3.3.5	Test results of the 99% occupied bandwidth measurement.....	16
3.3.6	Plots of the 99% occupied bandwidth measurement .....	16
3.4	Carrier frequency separation.....	17
3.4.1	Limit.....	17
3.4.2	Measurement instruments .....	17
3.4.3	Test setup.....	17
3.4.4	Test procedure .....	17
3.4.5	Measurement uncertainty .....	17
3.5	Number of hopping frequencies.....	18
3.5.1	Limit.....	18
3.5.2	Measurement instruments .....	18
3.5.3	Test setup.....	18
3.5.4	Test procedure .....	18
3.5.5	Measurement uncertainty .....	18
3.6	Average time of occupancy .....	19
3.6.1	Limit.....	19
3.6.2	Measurement instruments .....	19
3.6.3	Test setup.....	19
3.6.4	Test procedure .....	19
3.6.5	Measurement uncertainty .....	19
3.7	Output Power Measurement .....	20
3.7.1	Limit.....	20
3.7.2	Measurement instruments .....	20
3.7.3	Test setup.....	20
3.7.4	Test procedure .....	20
3.7.5	Test results of Output Power Measurement.....	20
3.8	Band edge Measurement .....	21
3.8.1	Limit.....	21
3.8.2	Measurement instruments .....	21
3.8.3	Test setup.....	21
3.8.4	Test procedure .....	21
3.8.5	Measurement Uncertainty.....	21
3.8.6	Results of the Band edge Measurements .....	21

## Summary of Test results

FCC	ISED	Description	Section in report	Verdict
15.247(d) 15.209 (a)	RSS-Gen §8.9	Radiated spurious emissions	3.1	Pass
15.205 (a)	RSS Gen §8.10	Spurious emissions in the restricted bands	3.1	Pass
15.247(a) (1)	RSS-247 §5.1(b)	Carrier frequency separation	3.4	Pass
15.247(a) (1) (iii)	RSS-247 §5.1(d)	Average time of occupancy	3.6	Pass
15.247(a) (1) (iii)	RSS-247 §5.1(d)	Number of hopping channels	3.5	Pass
15.247 (a)	RSS-247 §5.1(a)	20 dB bandwidth	3.2	Pass
--	RSS-Gen §6.7	99% bandwidth	3.3	Pass
15.247 (b)	RSS-247 §5.4 (d)	RF output power	3.7	Pass
15.247 (d)	RSS-247 §5.5	Band edge	3.8	Pass

## 1 General Description

### 1.1 Applicant

Client name: in-lite design bv  
Address: Stephensonweg 18  
Zip code: 4207 HB Gorinchem  
Telephone: +31 18 46 88 760  
E-mail: [wilbrand.menzo@in-lite.nl](mailto:wilbrand.menzo@in-lite.nl)  
Contact name: Wilbrand Menzo

### 1.2 Manufacturer

Manufacturer name: in-lite design bv  
Address: Stephensonweg 18  
Zip code: 4207 HB Gorinchem  
Telephone: +31 18 46 88 760  
E-mail: [wilbrand.menzo@in-lite.nl](mailto:wilbrand.menzo@in-lite.nl)  
Contact name: Wilbrand Menzo

### 1.3 Tested Equipment Under Test (EUT)

Product name: Motion sensor G3  
Brand name: SMART MOVE  
FCC ID: 2AU26-SMARTMOVE  
IC ID: 25679-SMARTMOVE  
Product type: Wideband data transmission equipment  
Model(s): SMART MOVE  
Batch and/or serial No. --  
Software version: --  
Hardware version: --  
Date of receipt: 4-09-2019  
Tests started: 4-09-2019  
Testing ended: 9-11-2019

#### 1.4 Product specifications of Equipment under test

Tx Frequency:	2400 – 2483.5 MHz
Rx frequency:	2400 – 2483.5 MHz
Antenna type	PIFA
Antenna gain	3.3 dBi (max)
Type of modulation:	GFSK
Emission designator	1M20G1D

#### 1.5 Environmental conditions

Test date	5-09-2019	9-11-2019
Ambient temperature	26.3 °C	19.9 °C
Humidity	43.4 %	44.3 %

#### 1.6 Measurement standards

- ANSI C63.4:2014
- ANSI C63.10:2013
- KDB 558074 D01 V05R02

#### 1.7 Applicable standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- RSS-Gen Issue 5
- RSS-247 Issue 2

#### 1.8 Observation and remarks

None.



## 1.9 Conclusions

The sample of the product showed NO NON-COMPLIANCES to the specifications stated in paragraph 1.7 of this report.

The results of the test as stated in this report, are exclusively applicable to the product items as identified in this report. Telefication accepts no responsibility for any properties of product items in this test report, which are not supported by the tests as specified in paragraph 1.7 "*Applicable standards*".

All conducted tests are performed by:

Name : ing P.A. Suringa

Review of test methods and report by:

Name : ing R. van Barneveld

The above conclusions have been verified by the following signatory:

Date : 10-01-2020

Name : P. van Wanrooij, BAsC

Function : Test Engineer

Signature :



## 2 Test configuration of the Equipment Under Test


### 2.1 Test mode

The applicant provided test mode firmware with which it was possible to configure the radio to transmit continuously.


### 2.2 Tested channels

Technology	Channels	Data rate	Frequency (MHz)
Bluetooth Low energy	37 (Low)	1 Mbps	2402
	17 (Mid)	1 Mbps	2440
	39 (High)	1 Mbps	2480

### 2.3 Test setups



## Radiated emissions test setup above 1 GHz



## 2.4 Equipment used in the test configuration

Description	Manufacturer	Model	ID	Used at Par.
Spectrum Analyzer	Rohde & Schwarz	FSP40	TE11125	3.1
Spectrum Analyzer	Rohde & Schwarz	ESR7	TE01220	3.1 – 3.9
Software	D.A.R.E Instruments	Radimation	2019.1.8	3.1
Biconilog Antenna	Chase	CBL6112A	TE00967	3.1
Horn Antenna	EMCO The Electro – Mechanics Co	3115	TE00531	3.1
Semi Anechoic Chamber	Comtest Engineering BV	-	TE00861	3.1
High pass filter	Wainwright instruments	WHK10-2520-3000-18000	TE01146	3.1

## 2.5 Sample calculations

Field Strength Measurement example(see chapter 3.3):

Frequency (MHz)	Polarization	Height(m)	Quasi-Peak (dB $\mu$ V/m)
135,6	Horizontal	1	40,4

The following relation applies:

$$E \text{ (dB}\mu\text{V/m)} = U \text{ (dB}\mu\text{V)} + AF \text{ (dB/m)} + CL \text{ (dB)}$$

Where:

E = Electric field strength

U = Measuring receiver voltage

AF = Antenna factor

CL = Cable loss

$$(40.4 = 27.23 + 11.8 + 1.37)$$

### 3 Test results

#### 3.1 Spurious emissions (incl. spurious emissions in the restricted bands)

##### 3.1.1 Limit

###### § 15.147(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the RF power shall be at least 20 dB attenuation below that in the 100 kHz bandwidth within the band that contains the highest level of desired power, based on either a conducted or radiated measurement.

###### §15.205(c)

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

##### 3.1.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

##### 3.1.3 Test setup

The test setup (cabinet radiation) is as shown in chapter 2.3 of this report.


##### 3.1.4 Test procedure

According to ANSI C63.10: 2013, sections 5.6, 6.6.

IRN 026\_14.1 Radiated electrical disturbance (V per m); methods 1, 2, 3


##### 3.1.5 Test results of the radiated spurious emission measurements

30 -1000 MHz



1 – 18 GHz

Vertical polarization




Channel 2440 MHz final measurements

Frequency	Peak	Peak Limit	Average	Average Limit	Height	Polarization
7,32 GHz	53,5 dBµV/m	74 dBµV/m	48,8 dBµV/m	54 dBµV/m	1 m	Vertical

Channel 2480 MHz final measurements

Frequency	Peak	Peak Limit	Average	Average Limit	Height	Polarization
7,441 GHz	55,3 dBµV/m	74 dBµV/m	48,2 dBµV/m	54 dBµV/m	1 m	Vertical

### Horizontal polarization




### Final measurements

Frequency	Peak	Peak Limit	Average	Average Limit	Height	Polarization
4,88 GHz	43,8 dBµV/m	74 dBµV/m	36,5 dBµV/m	54 dBµV/m	1,5 m	Horizontal
7,32 GHz	52,9 dBµV/m	74 dBµV/m	48,8 dBµV/m	54 dBµV/m	1 m	Horizontal

Frequency	Peak	Peak Limit	Average	Average Limit	Height	Polarization
7,441 GHz	54,1 dBµV/m	74 dBµV/m	47,8 dBµV/m	54 dBµV/m	2 m	Horizontal

18 – 26 GHz

Since no higher harmonics than the third harmonic are measured during the radiated emissions test, the frequency range 18 -26 GHz is covered by the conducted test only (middle channel only).



Bt, channel: 78 : Measure RX Spurious Emission 1 - 12.5 GHz  
Date: 15 OCT.2019 16:49:34

## 3.2 20 dB bandwidth Measurement

### 3.2.1 Limit

No limit applies.

### 3.2.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

### 3.2.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

### 3.2.4 Test procedure


According to ANSI C63.10: 2013, section 6.9.2

IRN 017 - Occupied bandwidth (Hz) Method 2 – Relative method.

### 3.2.5 Test Results of the 20 dB bandwidth Measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	20dB bandwidth (kHz)
Bluetooth Low energy	37	2402	1 Mbps	1225
	17	2440	1 Mbps	1225
	39	2480	1 Mbps	1238
Uncertainty	± 26 kHz			

### 3.2.6 Plots of the 20 dB bandwidth measurement





### 3.3 99% Occupied Bandwidth

#### 3.3.1 Limit

No limit, according to RSS-Gen §6.7

#### 3.3.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

#### 3.3.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

#### 3.3.4 Test procedure


RSS-GEN section 6.7

IRN 017 - Occupied bandwidth (Hz) Method 1 – XX % power bandwidth.

#### 3.3.5 Test results of the 99% occupied bandwidth measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	99% bandwidth (kHz)
Bluetooth Low energy	37	2402	1 Mbps	1063
	17	2440	1 Mbps	1067
	39	2480	1 Mbps	1071
Uncertainty	± 26 kHz			

#### 3.3.6 Plots of the 99% occupied bandwidth measurement



### 3.4 Carrier frequency separation

#### 3.4.1 Limit

Frequency hopping systems shall have hopping channel frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

#### 3.4.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

#### 3.4.3 Test setup


The test setup is as shown in chapter 2.3 of this report.

#### 3.4.4 Test procedure

According to ANSI C63.10: 2013, Section 7.8.2

IRN 005\_12.1 Frequency (Hz) – Method 4

##### 3.4.4.1 Plot of the carrier frequency separation measurement



Date: 17.OCT.2019 15:32:40

From the plot above:

Separation is:  $M2 - M1 = 2456 - 2454 = 2 \text{ MHz}$

#### 3.4.5 Measurement uncertainty

+/- 1 MHz

### 3.5 Number of hopping frequencies

#### 3.5.1 Limit

Frequency hopping systems in the 2400 – 2483.5 MHz band shall use at least 15 channels.

#### 3.5.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

#### 3.5.3 Test setup


The test setup is as shown in chapter 2.3 of this report.

#### 3.5.4 Test procedure

According to ANSI C63.10: 2013, Section 7.8.3

IRN 005\_12.1 Frequency (Hz) – Method 4

##### 3.5.4.1 Plot of the number of hopping frequencies



Date: 17.OCT.2019 15:32:40

The number of hopping frequencies is: 40

#### 3.5.5 Measurement uncertainty

Not applicable

### 3.6 Average time of occupancy

#### 3.6.1 Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of channels employed.

#### 3.6.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.


#### 3.6.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

#### 3.6.4 Test procedure

According to ANSI C63.10: 2013, Section 7.8.4

##### 3.6.4.1 Plots of the average time of occupancy measurement



From the plots above:

Each 10 seconds two 100 µsec pulses occur.

The average time of occupancy in 0.4x40 = 16 seconds:  $16/10 \times 0.1 \text{ msec} = 0.16 \text{ msec}$

#### 3.6.5 Measurement uncertainty

=/ - 0.1 %

## 3.7 Output Power Measurement

### 3.7.1 Limit

The maximum conducted output power of the intentional radiator shall not exceed 125 mW for frequency hopping systems in the 2400 – 2483.5 MHz band employing less than 75 non-overlapping channels.

If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point to point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

### 3.7.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

### 3.7.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

### 3.7.4 Test procedure

ANSI C63.10: 2013, section 6.6.4

IRN 014 - RF power (W) - Method 10

### 3.7.5 Test results of Output Power Measurement

Technology Std.	Channel	Frequency (MHz)	Data rate	Peak output power (dBm) <sup>*)</sup>
Bluetooth Low Energy	37	2402	1 Mbps	6.9
	18	2440	1 Mbps	7.7
	39	2480	1 Mbps	9.7
Uncertainty	± 3.8 dB			

<sup>\*)</sup> including antenna gain (3.3 dBi max)

### 3.8 Band edge Measurement

#### 3.8.1 Limit

Band edge:

At the edge of the authorized band the RF power shall be at least 20 dB down.

#### 3.8.2 Measurement instruments

The measurement instruments are listed in chapter 2.4 of this report.

#### 3.8.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

#### 3.8.4 Test procedure

According to ANSI C63.10, section 6.10

#### 3.8.5 Measurement Uncertainty

$\pm 2.7=5$  dB.

#### 3.8.6 Results of the Band edge Measurements

Band edge frequency (MHz)	Attenuation (dB)	Limit (dB)
2400	49.7	$\geq 20$
2483.5	54.9	$\geq 20$

##### 3.8.6.1 Plots

