



**Audix Technology (Shenzhen) Co., Ltd.**  
No. 6, Kefeng Road, Science & Technology Park,  
Nanshan District, Shenzhen, Guangdong, China

**Tel: 0755 26639496**  
**Fax: 0755 26632877**

## Maximum Permissive Exposure

FCC ID: 2AU3BU9W42  
EUT: WiFi module  
Model No.: U9W42

1. According to FCC CFR 47 §1.1310, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

Table 1 Limits for Maximum Permissible Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits for Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5.0	6
(B) Limits for General Population / Uncontrolled Exposures (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1.0	30

## 2. MPE Calculation

**Funai Electric R & D (Shenzhen) Co., Ltd.** declares that the product described above has been evaluated and found to comply with the RF exposure limits for humans, as specified based on ANSI/FCC recommendation.

RF Exposure Calculations:  $S = (P * G) / (4 * \pi * r^2)$  or  $r = \sqrt{(P * G) / (4 * \pi * S)}$

### 2.1. Estimation Result

#### Bluetooth MPE:

Mode	Frequency (MHz)	Output power (dBm)	Output power (mW)	antenna Gain (dBi)	antenna Gain (linear)	MPE (mW/cm <sup>2</sup> )
GFSK (DSS)	2402	10.066	10.15	-0.42	0.91	0.00183
	2441	10.356	10.85	-0.42	0.91	0.00196
	2480	9.912	9.80	-0.42	0.91	0.00177
8-DPSK (DSS)	2402	11.860	15.35	-0.42	0.91	0.00277
	2441	11.958	15.70	-0.42	0.91	<b>0.00284</b>
	2480	11.560	14.32	-0.42	0.91	0.00259
GFSK (DTS) (1Mbps)	2402	10.201	10.47	-0.42	0.91	0.00189
	2440	10.293	10.70	-0.42	0.91	0.00193
	2480	9.858	9.68	-0.42	0.91	0.00175
GFSK (DTS) (2Mbps)	2402	10.138	10.32	-0.42	0.91	0.00187
	2440	10.245	10.58	-0.42	0.91	0.00191
	2480	9.787	9.52	-0.42	0.91	0.00172

**DTS Band MPE:**

Mode	Frequency (MHz)	Output power (dBm)		Output power (mW)		antenna Gain (dBi)		antenna Gain (linear)		MPE (mW/cm <sup>2</sup> )	
		Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B
11b	2412	11.96	11.84	15.70	15.28	-2.3	-1	0.59	0.79	0.001841	0.002415
	2437	12.07	11.79	16.11	15.10	-2.3	-1	0.59	0.79	0.001888	0.002388
	2462	12.21	12.30	16.63	16.98	-2.3	-1	0.59	0.79	0.001950	0.002685
11g	2412	16.94		49.43		1.385		1.38		0.013535	
	2437	17.03		50.47		1.385		1.38		0.013818	
	2462	17.06		50.82		1.385		1.38		<b>0.013914</b>	
11n HT20	2412	16.62		45.92		1.385		1.38		0.012573	
	2437	16.68		46.56		1.385		1.38		0.012748	
	2462	16.76		47.42		1.385		1.38		0.012985	
11n HT40	2422	13.69		23.39		1.385		1.38		0.006404	
	2437	13.45		22.13		1.385		1.38		0.006060	
	2452	13.49		22.34		1.385		1.38		0.006116	

**U-NII-1 Band MPE:**

Mode	Frequency (MHz)	Output power (dBm)		Output power (mW)		antenna Gain (dBi)		antenna Gain (linear)		MPE (mW/cm <sup>2</sup> )	
		Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B
11a	5180	14.24	14.20	26.55	26.30	2.9	-3.8	1.95	0.42	0.010303	0.002182
	5200	14.12	14.35	25.82	27.23	2.9	-3.8	1.95	0.42	0.010022	0.002259
	5240	13.85	14.59	24.27	28.77	2.9	-3.8	1.95	0.42	0.009418	0.002388
11n HT20	5180	14.20		26.30		3.19		2.08		0.010913	
	5200	14.22		26.42		3.19		2.08		0.010964	
	5240	13.95		24.83		3.19		2.08		0.010303	
11n HT40	5190	16.47		44.36		3.19		2.08		<b>0.018406</b>	
	5230	16.37		43.35		3.19		2.08		0.017987	
11ac VHT20	5180	14.23		26.49		3.19		2.08		0.010989	
	5200	14.50		28.18		3.19		2.08		0.011694	
	5240	14.05		25.41		3.19		2.08		0.010543	
11ac VHT40	5190	16.20		41.69		3.19		2.08		0.017296	
	5230	15.82		38.19		3.19		2.08		0.015847	
11ac VHT80	5210	15.17		32.89		3.19		2.08		0.013644	



**Audix Technology (Shenzhen) Co., Ltd.**  
 No. 6, Kefeng Road, Science & Technology Park,  
 Nanshan District, Shenzhen, Guangdong, China

**Tel: 0755 26639496**  
**Fax: 0755 26632877**

**U-NII-3 Band MPE:**

Mode	Frequency (MHz)	Output power (dBm)		Output power (mW)		antenna Gain (dBi)		antenna Gain (linear)		MPE (mW/cm <sup>2</sup> )	
		Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B	Ant A	Ant B
11a	5745	15.60	15.83	36.31	38.28	-1.9	-4.5	0.65	0.35	0.004666	0.002704
	5785	15.47	15.73	35.24	37.41	-1.9	-4.5	0.65	0.35	0.004528	0.002642
	5825	15.27	15.75	33.65	37.58	-1.9	-4.5	0.65	0.35	0.004325	0.002654
11n HT20	5745	18.08		64.27		-0.093		0.98		0.012521	
	5785	18.02		63.39		-0.093		0.98		0.012350	
	5825	18.31		67.76		-0.093		0.98		0.013202	
11n HT40	5755	16.68		46.56		-0.093		0.98		0.009071	
	5795	17.05		50.70		-0.093		0.98		0.009878	
11ac VHT20	5745	18.09		64.42		-0.093		0.98		0.012550	
	5785	18.15		65.31		-0.093		0.98		0.012725	
	5825	18.31		67.76		-0.093		0.98		<b>0.013202</b>	
11ac VHT40	5755	16.63		46.03		-0.093		0.98		0.008967	
	5795	16.51		44.77		-0.093		0.98		0.008723	
11ac VHT80	5775	14.97		31.41		-0.093		0.98		0.006119	

Based on **safety** distance (r) **20cm**, the antenna gain (G) is **2.08 Numerical**, and the highest power output (P) is **44.36mW**, the power density (S) is **0.018406mW/cm<sup>2</sup>**.

**Bluetooth + WIFI MPE:**

Bluetooth MPE (mW/cm <sup>2</sup> )	WIFI MPE (mW/cm <sup>2</sup> )	Max MPE (mW/cm <sup>2</sup> )	Limit (mW/cm <sup>2</sup> )	Compliance or not
<b>0.00284</b>	<b>0.018406</b>	<b>0.021246</b>	<b>1</b>	<b>YES</b>