



Report No.: FCC 1911020 File Reference No.: 2019-11-12

Applicant: SHENZHEN LEAGEND OPTOELECTRONICS CO., LTD

Product: Wireless OBD Scanner and Adapter, Wireless Battery Tester

and Monitor, Wireless Battery Charger, Wireless Air Cleaner and Purifier, Wireless Safety Driving Reminder and Tracker

Model No.: N/A

Trademark: BM2(see the page 4 for additional models)

Test Standards: FCC Part 15.247

Test Result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.10, FCC Part 15.247 for

the evaluation of electromagnetic compatibility

Approved By

Jack Chung

Jack Chung

Manager

Dated: November 12, 2019

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TESTING LABORATORIES

Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le Village, Nanshan District, Shenzhen, China

Tel (755) 83448688, Fax (755) 83442996, E-Mail:info@timeway-lab.com

Report No.: FCC1911020 Page 2 of 46

Date: 2019-11-12



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2005 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 744189

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 744189.

Industry Canada (IC) — Registration No.:5205A

The EMC Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 5205A.

A2LA (Certification Number:5013.01)

The EMC Laboratory has been accredited by the American Association for Laboratory Accreditation (A2LA). Certification Number:5013.01

Page 3 of 46

Report No.: FCC1911020

Date: 2019-11-12



Test Report Conclusion

Content

1.0	General Details	4
1.1	Test Lab Details	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample.	4
1.5	Test Duration.	5
1.6	Test Uncertainty	5
1.7	Test By	5
2.0	List of Measurement Equipment	6
3.0	Technical Details	7
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT.	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT.	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
7.0	6dB Bandwidth Measurement Bandwidth	22
8.0	Maximum Peak Output Power	
9.0	Power Spectral Density Measurement.	
10.0	Out of Band Measurement.	34
11.0	Antenna Requirement	41
12.0	FCC ID Label	42
13.0	Photo of Test Setup and EUT View.	43

Date: 2019-11-12



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TESTING LABORATORIES.

Address: Zone C, 1st Floor, Block B, Jun Xiang Da Building, Zhongshan Park Road West, Tong Le

Village, Nanshan District, Shenzhen, China

Telephone: (755) 83448688 Fax: (755) 83442996

1.2 Applicant Details

Applicant: SHENZHEN LEAGEND OPTOELECTRONICS CO., LTD

Address: Room 401, Floor 4th, Building 3, Dacheng Industrial Park, Rd Jihua, Shenzhen, P.R. China

Telephone: (755)-82821859 Fax: (755)-82821866

1.3 Description of EUT

Product: Wireless OBD Scanner and Adapter, Wireless Battery Tester and Monitor,

Wireless Battery Charger, Wireless Air Cleaner and Purifier, Wireless

Safety Driving Reminder and Tracker

Manufacturer: SHENZHEN LEAGEND OPTOELECTRONICS CO., LTD

Address: Room 401, Floor 4th, Building 3, Dacheng Industrial Park, Rd Jihua,

Shenzhen, P.R. China

Brand Name: N/A
Additional Brand Name: N/A
Model Number: BM2

Additional Model Number: BLE327, ELM327, GSM327, OBD327, Cblackbox, Cblackbox-BT, BM1, BM3, BM4, BM5, BM6, BM7, BM8, BM9, BA200, BA300, BA400, BA500, BA600, BA700, BA800, BA900, BT1000, BT2000, BT3000, BT4000, BT5000, BT6000, BT7000, BT8000, BT9000, FA40, FA45, FA46, FA47, FA48, FA49, FA51, FA55, FA61, FA65, FA69, FA70, FA71, FA75, FA79, FA80, FA81, FA85, FA86, FA89, AM1, AM2, AM3, AM4, AM5, AM6, AM7, AM8, AM9, IC1, IC2, IC3, IC4, IC5, IC6, IC7, IC8, IC9MT1, MT2, MT3, MT4, MT5, MT6, MT7, MT8, MT9,TK1, TK2, TK3, TK4, TK5, TK6, TK7, TK8, TK9,AC1, AC2, AC3, AC4, AC5, AC6, AC7, AC8, AC9, SP1, SP2, SP3, SP4, SP5, SP6, SP7, SP8, SP9, SD1, SD2, SD3, SD4, SD5, SD6, SD7, SD8, SD9,BK1, BK2, BK3, BK4, BK5, BK6, BK7, BK8, BK9, CARREC, DRIVEREC, T40+, T49+.

Type of Modulation GFSK (Bluetooth BLE)

Frequency range 2402-2480MHz
Frequency Selection By software

Channel Number 40

Rating: Input: DC6-20V

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1911020 Page 5 of 46

Date: 2019-11-12



1.4 Submitted Sample: 1 Samples

1.5 Test Duration 2019-11-04 to 2019-11-12

1.6 Test Uncertainty

Conducted Emissions Uncertainty =3.6dB
Radiated Emissions below 1GHz Uncertainty =4.7dB
Radiated Emissions above 1GHz Uncertainty =6.0dB
Conducted Power Uncertainty =6.0dB
Occupied Channel Bandwidth Uncertainty =5%

1.7 Test Engineer

Terry Tang

The sample tested by

Print Name: Terry Tang

Page 6 of 46 Report No.: FCC1911020

Date: 2019-11-12



2.0 Test Equipment					
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	R&S	ESPI 3	100379	2019-06-21	2020-06-20
TWO Line-V-NETW			100294	2019-06-21	2020-06-20
TWO Line-V-NETW	R&S	EZH3-Z5	100253	2019-06-21	2020-06-20
Impuls-Begrenzer	R&S	ESH3-Z2	100281	2019-06-21	2020-06-20
Loop Antenna	EMCO	6507	00078608	2019-06-20	2020-06-20
Spectrum	R&S	FSIQ26	100292	2019-06-21	2020-06-20
Horn Antenna	A-INFO	LB-180400-KF	J211060660	2019-06-21	2020-06-20
Horn Antenna	R&S	BBHA 9120D	9120D-631	2018-07-09	2021-07-08
Power meter	Anritsu	ML2487A	6K00003613	2019-08-22	2020-08-21
Power sensor	Anritsu	MA2491A	32263	2019-08-22	2020-08-21
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2018-07-04	2021-07-03
9*6*6 Anechoic			N/A	2018-02-07	2021-02-06
EMI Test Receiver	RS	ESVB	826156/011	2019-06-21	2020-06-20
EMI Test Receiver	RS	ESH3	860904/006	2019-06-21	2020-06-20
Spectrum	HP/Agilent	ESA-L1500A	US37451154	2019-06-21	2020-06-20
Spectrum	HP/Agilent	E4407B	MY50441392	2019-06-21	2020-06-20
Spectrum	RS	FSP	1164.4391.38	2019-01-20	2020-01-19
RF Cable	Zhengdi	ZT26-NJ-NJ-8 M/FA		2019-06-21	2020-06-20
RF Cable	Zhengdi	7m		2019-06-21	2020-06-20
RF Switch	EM	EMSW18	060391	2019-06-21	2020-06-20
Pre-Amplifier	Schwarebeck	BBV9743	#218	2019-06-21	2020-06-20
Pre-Amplifier	HP/Agilent	8449B	3008A00160	2019-06-21	2020-06-20
LISN	SCHAFFNER	NNB42	00012	2019-01-08	2020-01-07

Date: 2019-11-12



3.0 **Technical Details**

3.1 **Summary of test results**

Standard	Test Type	Result	Notes
CCC Part 15, Paragraph 15.107 & 15.207	Conducted Emission Test	PASS	N/A
FCC Part 15 Subpart C Paragraph 15.247(a)(2) Limit	Spectrum bandwidth of a Orthogonal Frequency Division Multiplex System Limit: 6dB bandwidth>500kHz	PASS	Complies
FCC Part 15, Paragraph 15.247(b)	Maximum peak output power Limit: max. 30dBm	PASS	Complies
FCC Part 15, Paragraph 15.109,15.205 & 15.209	Transmitter Radiated Emission Limit: Table 15.209	PASS	Complies
FCC Part 15, Paragraph 15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Complies
FCC Part 15, Paragraph 15.247(d)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band limit:	PASS	Complies

3.2 **Test Standards**

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

EUT Modification 4.0

No modification by SHENZHEN TIMEWAY TESTING LABORATORIES.

Page 8 of 46


Report No.: FCC1911020

Date: 2019-11-12



5.Power Line Conducted Emission Test

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.10-2013. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.10 –2013.

Test Voltage: 120V~, 60Hz Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.10-2013. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device		Manufacturer	Model	FCC ID
Wire	eless OBD	SHENZHEN LEAGEND	DM2	241144 101114
Scanner and Adapter		OPTOELECTRONICS CO., LTD	BM2	2AU4A-191114

Report No.: FCC1911020 Page 9 of 46

Date: 2019-11-12



B. Internal Device

Device	Manufacturer	Model	Rating

C. Peripherals

Device	Manufacturer	Model	Rating	
		-		

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.10-2013.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

Frequency	Class A Lim	its (dB μ V)	Class B Limits (dB µ V)		
(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average L vel	
$0.15 \sim 0.50$	79.0	6.0	66.0~56.0*	56.0~46.0*	
$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: EUT powered by battery, this test item not applicable.


Date: 2019-11-12



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.10-2013. The radiated test was performed at Timeway EMC Laboratory. This site is on file with the FCC laboratory division, Registration No.744189
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.10-2013.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=1MHz VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT
 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

The report refers only to the sample tested and does not apply to the bulk.

Report No.: FCC1911020 Page 11 of 46

Date: 2019-11-12



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

Frequency Range (MHz)	Distance (m)	Field strength (dB μ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Abov 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT
- 4. This is a handhold device. The radiated emissions should be tested under 3-axes position (Lying, Side, and Stand), After pre-test. It was found that the worse radiated emission was get at the lying position.

Page 12 of 46

Report No.: FCC1911020

Date: 2019-11-12



Test result


General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Bluetooth Transmitting

Results: Pass

Test Figure:



No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
1	103.702	16.34	-13.35	43.5	-27.16	Peak	94.00	100	Н	Pass

Page 13 of 46

Date: 2019-11-12

Report No.: FCC1911020



Test result General Radiated Emission Data and Harmonics Radiated Emission Data


Radiated Emission In Vertical (30MHz----1000MHz)

EUT set Condition: **Keep Transmitting**

Results: Pass

Test Figure:

FCC_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	108.065	16.68	-13.42	43.5	-26.82	Peak	208.00	100	V	Pass

Report No.: FCC1911020 Page 14 of 46

Date: 2019-11-12




Test Figures above 1GHz:

Please refer to the following test plots for details:

Low Channel: Vertical

FCC_FCC Part 15B Class B 1GHz-18GHz - 2




No.	Frequency	Results	Factor (dB)	Limit	Over Limit	Detector	Table	Height	ANT	Verdict
	(MHz)	(dBuV/m)		(dBuV/m)	(dB)		(o)	(cm)		
2**	4802.799	48.33	3.12	54.0	-5.67	AV	136.00	100	V	Pass
2	4802.799	56.21	3.12	74.0	-17.79	Peak	136.00	100	V	Pass

Report No.: FCC1911020 Page 15 of 46

Date: 2019-11-12



Low Channel: Horizontal



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2**	4802.799	49.12	3.12	54.0	-4.88	AV	45.00	100	Н	Pass
2	4802.799	57.05	3.12	74.0	-16.95	Peak	45.00	100	Н	Pass


Page 16 of 46

Report No.: FCC1911020

Date: 2019-11-12



Middle Channel: Vertical




Note: The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Report No.: FCC1911020 Page 17 of 46

Date: 2019-11-12



Middle Channel: Horizontal



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2**	4879.280	46.89	3.20	54.0	-7.11	AV	26.00	100	Н	Pass
2	4879.280	54.61	3.20	74.0	-19.39	Peak	26.00	100	Н	Pass


Report No.: FCC1911020 Page 18 of 46

Date: 2019-11-12



High Channel: Vertical

FCC_FCC Part 15B Class B 1GHz-18GHz - 2




No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2**	4960.010	46.65	3.36	54.0	-7.35	AV	151.00	100	V	Pass
2	4960.010	54.32	3.36	74.0	-19.68	Peak	151.00	100	V	Pass

Report No.: FCC1911020 Page 19 of 46

Date: 2019-11-12



High Channel: Horizontal



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
2**	4960.010	47.70	3.36	54.0	-6.30	AV	22.00	100	Н	Pass
2	4960.010	55.30	3.36	74.0	-18.70	Peak	22.00	100	Н	Pass

Note: 1. Level = Reading + AF + Cable - Preamp

- 2. For the radiated emissions above 18G, it is the floor noise.
- 3. The measured PK value less than the AV limit, no necessary to take down the AV measurement result.

Page 20 of 46


Report No.: FCC1911020

Date: 2019-11-12



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500 kHz

7.3 Test Procedure

- 1. Set resolution bandwidth (RBW) = 100 kHz
- 2. Set the video bandwidth (VBW) \geq 3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = \max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 Test Result

Page 21 of 46 Report No.: FCC1911020

Date: 2019-11-12



6dB BW

EUT		Wireless OBD	Scanner and	Model			BM2
	Adap		ter				
Mode		Keep Trans	smitting	Input Voltage	e		DC12V
Temperat	ure	24 deg	. C,	Humidity 56% RH		56% RH	
Channel	Cł			andwidth Hz)	M	inimum Limit (MHz)	Pass/ Fail
Low		2402	6	689		0.5	Pass
Middle		2440	6	89		0.5	Pass
High		2480	6	81		0.5	Pass

Page 22 of 46


Report No.: FCC1911020

Date: 2019-11-12



Test Figure:

1. Condition: Low Channel



Date: 8.NOV.2019 08:26:31


Page 23 of 46

Report No.: FCC1911020

Date: 2019-11-12



2. Condition: Middle Channel




Date: 8.NOV.2019 08:27:51

Report No.: FCC1911020 Page 24 of 46

Date: 2019-11-12



3. High Channel



Date: 8.NOV.2019 08:29:26


Report No.: FCC1911020 Page 25 of 46

Date: 2019-11-12



8. Maximum Output Power

8.1 Test Setup



8.2 Limits of Maximum Output Power

The Maximum Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the Peak power were measured.

Report No.: FCC1911020 Page 26 of 46

Date: 2019-11-12



8.4Test Results

EUT		Wireless OBD So	anner and	Model		BM2	
	Adapter		- :				
Mode	Mode Keep Transmitting Input Voltage		DC12V				
Temperatu	re	24 deg. (Ξ,	Humidity		56% RH	
Channel	Channel Frequency		Мах	Max. Power Output (dBm)			Pass/ Fail
Chamici		(MHz)		Peak		Limit (dBm)	
Low		2402		-5.40		30	Pass
Middle		2440		-6.45		30	Pass
High		2480		-8.05		30	Pass

Note: 1. the result basic equation calculation as follow:

Max. Power Output = Power Reading + Cable loss + Attenuator


Report No.: FCC1911020 Page 27 of 46

Date: 2019-11-12



9. Power Spectral Density Measurement

9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

- 1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
- 2. Set the RBW = 10 kHz.
- 3. Set the VBW \geq 30 kHz.
- 4. Set the span to 1.5 times the DTS channel bandwidth.
- 5. Detector = peak.
- 6. Sweep time = auto couple.
- 7. Trace mode = max hold.
- 8. Allow trace to fully stabilize.
- 9. Use the peak marker function to determine the maximum amplitude level.
- 10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.
- 11. The resulting peak PSD level must be ≤ 8 dBm.

Report No.: FCC1911020 Page 28 of 46

Date: 2019-11-12



9.4Test Result

EUT		Wirele	Wireless OBD Scanner and Adapter]	BM2	
Mode		Keep Transmitting			Input Voltage	•		
Temperat	ure		24 deg. C,		Humidity	56% RH		
Channel	Re	k Power Cable Final Power Loss Density		wer Spectral ty (dBm)	Maximum Limit (dBm)	Pass/ Fail		
Low	-1	2.55	0.2	-	12.35	8	Pass	
Middle	-1	4.28	0.2	-	14.08	8	Pass	
High	-1	5.43	0.2		15.23	8	Pass	

Note: The result basic equation calculation as follow:

Peak Power Output = Peak Power Reading + Cable loss

Page 29 of 46


Report No.: FCC1911020

Date: 2019-11-12



Test Figure:

1. Condition: Low Channel




Date: 8.NOV.2019 08:38:12

Report No.: FCC1911020 Page 30 of 46

Date: 2019-11-12



2. Condition: Middle Channel




Date: 8.NOV.2019 08:39:40

Report No.: FCC1911020 Page 31 of 46

Date: 2019-11-12



3. High Channel




Date: 8.NOV.2019 08:41:25

Report No.: FCC1911020 Page 32 of 46

Date: 2019-11-12



10 Out of Band Measurement 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of Radiated emission test. (Peak values with RBW=1MHz, VBW=3MHz and PK detector. AV value with RBW=1MHz, VBW=3MHz and RMS detector)

For bandage test, the spectrum set as follows: RBW=100 kHz, VBW=300 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Note: 1. For band-edge measurement, the frequency from 30MHz-25GHz was tested. And It met the FCC rule.

Page 33 of 46

Report No.: FCC1911020


Date: 2019-11-12



10.4 Band-edge Measurement

EUT	Wireless OBD Scanner and	Model	BM2
	Adapter		
Mode	LCH Keep Transmitting	Input Voltage	DC12V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 8.NOV.2019 08:32:06

Page 34 of 46

Report No.: FCC1911020


Date: 2019-11-12



10.4 Band-edge Measurement

EUT	Wireless OBD Scanner and	Model	BM2
	Adapter		
Mode	HCH Keeping Transmitting	Input Voltage	DC12V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 8.NOV.2019 08:30:40


Page 35 of 46 Report No.: FCC1911020

Date: 2019-11-12



10.4 Restrict Band Measurement

EUT	Wireless OBD Scanner and	Model	BM2
	Adapter		
Mode	LCH Keep Transmitting	Input Voltage	DC12V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1	2390	53.59	-3.53	74.0	-20.41	Peak	81.00	100	Н	Pass
1*	2390	46.12	-3.53	54.0	-7.88	AV	81.00	100	Н	Pass

Page 36 of 46

Report No.: FCC1911020

Date: 2019-11-12



10.4 Restrict Band Measurement

EUT		EUT	Wirele	ess OBD	Scanner and	d l	Model			BM2			
				Adap	oter								
	N	Mode	L	СН Кеер	Transmittii	ng In	put Voltage	;	DC12V				
-	Гет	perature		24 deg	g. C,		Humidity			56% RH			
	Test	t Result:		Pas	SS								
	art 15B 0E+2-r	Class B 1GHz-18GH:	z - 2										
1.	06+2-												
	90-												
									/	\bigcap			
	80-												
	70-												
(m//													
level (dBuV/m)	60-								and the second	/_			
<u>e</u>	50-								stracture.				
					A STANSON OF THE PERSON OF THE	COLUMN TO STREET	A CONTRACTOR OF THE PERSON ASSESSED.	A STATE OF THE STA					
	40-	يوليانيا ويبارين والمالي	Anida da d	A STATE OF THE PARTY OF THE PAR	大学の中国の大学の大学の大学	Charles Charles							
	30-	Anna de participa de la companya de participa de la companya de la											
	23	60				Frequency (MHz)				2410		
No).	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict		
		(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)				
		2390	46.86	-3.53	54.0	-7.14	Peak	319.00	100	V	Pass		

Note: The measured PK value less than the AV limit, no necessary to take down the AV measurement result.


Page 37 of 46 Report No.: FCC1911020

Date: 2019-11-12



10.4 Restrict Band Measurement

EUT	Wireless OBD Scanner and	Model	BM2
	Adapter		
Mode	HCH Keep Transmitting	Input Voltage	120V~
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1**	2483.5	49.79	-3.57	54.0	-4.21	AV	123.00	100	Н	Pass
1	2483.5	57.34	-3.57	74.0	-16.66	Peak	123.00	100	Н	Pass


Page 38 of 46 Report No.: FCC1911020

Date: 2019-11-12



10.4 Restrict Band Measurement

EUT	Wireless OBD Scanner and	Model	BM2
	Adapter		
Mode HCH Keep Transmitting		Input Voltage	DC12V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass		



No.	Frequency	Results	Factor	Limit	Over Limit	Detector	Table (o)	Height	ANT	Verdict
	(MHz)	(dBuV/m)	(dB)	(dBuV/m)	(dB)			(cm)		
1**	2483.5	44.74	-3.57	54.0	-9.26	AV	12.00	100	V	Pass
1	2483.5	52.27	-3.57	74.0	-21.73	Peak	12.00	100	V	Pass

Date: 2019-11-12



Page 39 of 46

11.0 Antenna Requirement

11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

PCB antenna used. The maximum gain of the antennas is 2.0dBi.

Report No.: FCC1911020 Page 40 of 46

Date: 2019-11-12



12.0 FCC ID Label

FCC ID: 2AU4A-191114

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:





Date: 2019-11-12



13.0 Photo of testing

Radiated Emission Test Setup:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Date: 2019-11-12



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Date: 2019-11-12



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to


adopt any other remedies which may be appropriate.

Date: 2019-11-12



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES. reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Date: 2019-11-12



Photographs - EUT





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the SHENZHEN TIMEWAY TESTING LABORATORIES. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the SHENZHEN TIMEWAY TESTING LABORATORIES. to his customer. Supplier or others persons directly concerned. SHENZHEN TIMEWAY TESTING LABORATORIES. will not, without the consent of the client enter into any

discussion of correspondence with any third party concerning the contents of the report.


In the event of the improper use of the report. The SHENZHEN TIMEWAY TESTING LABORATORIES, reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No.: FCC1911020 Page 46 of 46

Date: 2019-11-12



Photographs - EUT



End of the report