FCC ID: 2AU4M-VS1800

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR+EDR:

Antenna Type: PCB Antenna Antenna Gain: 1.21dBi

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)	Conducte d power (mW)	Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)		1g SAR Exclusion threshold	SAR test exclusion
BLE(1M)	2.40	-2.06	0.622	-2±1	-1.0	0.794	<5	0.24622	3.00	YES
	2.44	-2.71	0.536	-2±1	-1.0	0.794	<5	0.24816	3.00	YES
	2.48	-3.29	0.469	-3±1	-2.0	0.631	<5	0.19873	3.00	YES
BLE(2M)	2.40	-2.04	0.625	-2±1	-1.0	0.794	<5	0.24622	3.00	YES
	2.44	-2.72	0.535	-2±1	-1.0	0.794	<5	0.24816	3.00	YES
	2.48	-3.31	0.467	-3±1	-2.0	0.631	<5	0.19873	3.00	YES

Conclusion:

Signature: Alex Li

For the max result: 0.24816≤ 3.0 for 1-g SAR, No SAR is required.

NAME AND TITLE (Please print or type): Alex /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen 518126 P.R. China

Date: 2024-06-14