

FCC REPORT

Applicant: ShenZhen Lanshuo Communication Equipment Co., Ltd.

Address of Applicant: No.12, Yumin Road, Shajing Town, Bao'an District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: GSM Fixed Wireless Phone

Model No.: LS931

Trade mark: lancotel

FCC ID: 2AU55-LS931

Applicable standards: FCC CFR Title 47 Part 15 Subpart B

Date of sample receipt: 12 Nov., 2019

Date of Test: 13 Nov., to 21 Nov., 2019

Date of report issued: 27 Nov., 2019

Test Result: PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Bruce Zhang

Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the CCIS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

2 Version

Version No.	Date	Description
00	27 Nov., 2019	Original

Tested by:

Janet Wei
Test Engineer

Date:

27 Nov., 2019

Reviewed by:

Winner Zhang
Project Engineer

Date:

27 Nov., 2019

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION.....	2
3 CONTENTS.....	3
4 TEST SUMMARY.....	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 TEST MODE.....	5
5.4 MEASUREMENT UNCERTAINTY.....	5
5.5 DESCRIPTION OF SUPPORT UNITS	6
5.6 RELATED SUBMITTAL(S) / GRANT (s).....	6
5.7 DESCRIPTION OF CABLE USED	6
5.8 ADDITIONS TO, DEVIATIONS, OR EXCLUSIONS FROM THE METHOD	6
5.9 LABORATORY FACILITY.....	6
5.10 LABORATORY LOCATION.....	6
5.11 TEST INSTRUMENTS LIST.....	7
6 TEST RESULTS AND MEASUREMENT DATA.....	8
6.1 CONDUCTED EMISSION.....	8
6.2 RADIATED EMISSION	11
7 TEST SETUP PHOTO	17
8 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part 15.107	Pass
Radiated Emission	Part 15.109	Pass
Remark:		
1. Pass: The EUT complies with the essential requirements in the standard. 2. N/A: The EUT not applicable of the test item.		
Test Method:	ANSI C63.4:2014	

5 General Information

5.1 Client Information

Applicant:	ShenZhen Lanshuo Communication Equipment Co., Ltd.
Address:	No.12, Yumin Road, Shajing Town, Bao'an District, Shenzhen, China
Manufacturer/Factory:	ShenZhen Lanshuo Communication Equipment Co., Ltd.
Address:	No.12, Yumin Road, Shajing Town, Bao'an District, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	GSM Fixed Wireless Phone
Model No.:	LS931
Power supply:	Rechargeable Li-ion Battery DC3.7V-1800mAh
AC adapter :	Model: SW-0018 Input: AC100-240V, 50/60Hz, 0.2A Output: DC 5.0V, 1.0A
Test Sample Condition:	The test samples were provided in good working order with no visible defects.

5.3 Test Mode

Operating mode	Detail description
PC mode	Keep the EUT in Downloading mode(Worst case)
Charging+Recording mode	Keep the EUT in Charging+Recording mode
Charging+Playing mode	Keep the EUT in Charging+Playing mode
FM mode	Keep the EUT in FM receiver mode

The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

5.4 Measurement Uncertainty

Parameters	Expanded Uncertainty
Conducted Emission (9kHz ~ 30MHz)	±1.60 dB (k=2)
Radiated Emission (9kHz ~ 30MHz)	±3.12 dB (k=2)
Radiated Emission (30MHz ~ 1000MHz)	±4.32 dB (k=2)
Radiated Emission (1GHz ~ 18GHz)	±5.38 dB (k=2)
Radiated Emission (18GHz ~ 40GHz)	±3.36 dB (k=2)

5.5 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
DELL	PC	OPTIPLEX745	N/A	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC
LENOVO	Laptop	SL510	2847A65	DoC

5.6 Related Submittal(s) / Grant (s)

This is an original grant, no related submittals and grants.

5.7 Description of Cable Used

Cable Type	Description	Length	From	To
Detached USB Cable	Shielding	1.5m	EUT	PC/Adapter

5.8 Additions to, deviations, or exclusions from the method

No

5.9 Laboratory Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC - Designation No.: CN1211**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been accredited as a testing laboratory by FCC(Federal Communications Commission). The test firm Registration No. is 727551.

● **ISED – CAB identifier.: CN0021**

The 3m Semi-anechoic chamber of Shenzhen Zhongjian Nanfang Testing Co., Ltd. has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 10106A-1.

● **CNAS - Registration No.: CNAS L6048**

Shenzhen Zhongjian Nanfang Testing Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6048.

● **A2LA - Registration No.: 4346.01**

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 General requirements for the competence of testing and calibration laboratories. The test scope can be found as below link: <https://portal.a2la.org/scopepdf/4346-01.pdf>

5.10 Laboratory Location

Shenzhen Zhongjian Nanfang Testing Co., Ltd.

Address: No. B-C, 1/F., Building 2, Laodong No.2 Industrial Park, Xixiang Road,

Bao'an District, Shenzhen, Guangdong, China

Tel: +86-755-23118282, Fax: +86-755-23116366

Email: info@ccis-cb.com, Website: http://www.ccis-cb.com

5.11 Test Instruments list

Radiated Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
3m SAC	SAEMC	9m*6m*6m	966	07-22-2017	07-21-2020
Loop Antenna	SCHWARZBECK	FMZB1519B	00044	03-18-2019	03-17-2020
BiConiLog Antenna	SCHWARZBECK	VULB9163	497	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	916	03-18-2019	03-17-2020
Horn Antenna	SCHWARZBECK	BBHA9120D	1805	06-22-2017	06-21-2020
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170582	11-21-2018	11-20-2019
				11-21-2019	11-20-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		
Pre-amplifier	HP	8447D	2944A09358	03-18-2019	03-17-2020
Pre-amplifier	CD	PAP-1G18	11804	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP30	101454	03-18-2019	03-17-2020
Spectrum analyzer	Rohde & Schwarz	FSP40	100363	11-21-2018	11-20-2019
				11-21-2019	11-20-2020
EMI Test Receiver	Rohde & Schwarz	ESRP7	101070	03-18-2019	03-17-2020
Cable	ZDECL	Z108-NJ-NJ-81	1608458	03-18-2019	03-17-2020
Cable	MICRO-COAX	MFR64639	K10742-5	03-18-2019	03-17-2020
Cable	SUHNER	SUCOFLEX100	58193/4PE	03-18-2019	03-17-2020

Conducted Emission:					
Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (mm-dd-yy)	Cal. Due date (mm-dd-yy)
EMI Test Receiver	Rohde & Schwarz	ESCI	101189	03-18-2019	03-17-2020
Pulse Limiter	SCHWARZBECK	OSRAM 2306	9731	03-18-2019	03-17-2020
LISN	CHASE	MN2050D	1447	03-18-2019	03-17-2020
LISN	Rohde & Schwarz	ESH3-Z5	8438621/010	07-21-2018	07-20-2019
				07-21-2019	07-20-2020
Cable	HP	10503A	N/A	03-18-2019	03-17-2020
EMI Test Software	AUDIX	E3	Version: 6.110919b		


6 Test results and Measurement Data

6.1 Conducted Emission

Test Requirement:	FCC Part 15 B Section 15.107		
Test Frequency Range:	150kHz to 30MHz		
Class / Severity:	Class B		
Receiver setup:	RBW=9kHz, VBW=30kHz		
Limit:	Frequency range (MHz)		Limit (dB μ V)
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	0.5-30	60	50
* Decreases with the logarithm of the frequency.			
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>80cm</p> <p>40cm</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>		
Test procedure	<ol style="list-style-type: none"> The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs). Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement. 		
Test Instruments:	Refer to section 5.11 for details		
Test mode:	Refer to section 5.3 for details		
Test results:	Pass		

Measurement data:

Product name:	GSM Fixed Wireless Phone	Product model:	LS931
Test by:	Janet	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Line
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%




Freq MHz	Read Level dBuV	LISN Factor dB	Cable Loss dB	Aux Factor dB	Level dBuV	Limit Line dBuV	Over Line Limit dB	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB	
1	0.154	30.43	-0.45	10.78	-0.06	40.70	55.78	-15.08 Average
2	0.166	45.59	-0.44	10.77	-0.09	55.83	65.16	-9.33 QP
3	0.194	42.89	-0.41	10.76	-0.15	53.09	63.84	-10.75 QP
4	0.442	37.89	-0.38	10.74	0.08	48.33	57.02	-8.69 QP
5	0.442	29.57	-0.38	10.74	0.08	40.01	47.02	-7.01 Average
6	0.608	22.65	-0.38	10.77	-0.38	32.66	46.00	-13.34 Average
7	0.614	35.49	-0.38	10.77	-0.38	45.50	56.00	-10.50 QP
8	0.697	33.84	-0.38	10.77	-0.40	43.83	56.00	-12.17 QP
9	0.880	17.76	-0.38	10.83	0.15	28.36	46.00	-17.64 Average
10	2.567	18.19	-0.43	10.94	-0.25	28.45	46.00	-17.55 Average
11	2.678	30.03	-0.43	10.93	-0.24	40.29	56.00	-15.71 QP
12	2.678	18.75	-0.43	10.93	-0.24	29.01	46.00	-16.99 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level =Receiver Read level + LISN Factor + Cable Loss.

Product name:	GSM Fixed Wireless Phone	Product model:	LS931
Test by:	Janet	Test mode:	PC mode
Test frequency:	150 kHz ~ 30 MHz	Phase:	Neutral
Test voltage:	AC 120 V/60 Hz	Environment:	Temp: 22.5°C Huni: 55%



Freq MHz	Read Level dBuV	LISN Factor	Cable Loss dB	Aux Factor	Level dBuV	Limit Line dBuV	Over Limit dB	Over Limit Remark
1	0.166	47.30	-0.68	10.77	0.01	57.40	65.16	-7.76 QP
2	0.170	26.62	-0.68	10.77	0.01	36.72	54.94	-18.22 Average
3	0.194	44.50	-0.69	10.76	0.00	54.57	63.84	-9.27 QP
4	0.222	42.04	-0.67	10.76	0.00	52.13	62.74	-10.61 QP
5	0.437	37.39	-0.64	10.74	-0.02	47.47	57.11	-9.64 QP
6	0.442	29.36	-0.64	10.74	-0.02	39.44	47.02	-7.58 Average
7	0.535	22.13	-0.65	10.76	0.03	32.27	46.00	-13.73 Average
8	0.555	35.88	-0.65	10.76	0.03	46.02	56.00	-9.98 QP
9	0.665	18.97	-0.64	10.77	0.04	29.14	46.00	-16.86 Average
10	0.675	32.77	-0.64	10.77	0.04	42.94	56.00	-13.06 QP
11	0.720	18.38	-0.64	10.78	0.04	28.56	46.00	-17.44 Average
12	1.734	16.19	-0.66	10.94	0.15	26.62	46.00	-19.38 Average

Notes:

- An initial pre-scan was performed on the line and neutral lines with peak detector.
- Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- Final Level = Receiver Read level + LISN Factor + Cable Loss.


6.2 Radiated Emission

Test Requirement:	FCC Part 15 B Section 15.109													
Test Frequency Range:	30MHz to 6000MHz													
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)													
Receiver setup:	Frequency	Detector	RBW	VBW	Remark									
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value									
	Above 1GHz	Peak	1MHz	3MHz	Peak Value									
Limit:	RMS	1MHz	3MHz	Average	Value									
	Frequency	Limit (dBuV/m @3m)		Remark										
	30MHz-88MHz	40.0		Quasi-peak Value										
	88MHz-216MHz	43.5		Quasi-peak Value										
	216MHz-960MHz	46.0		Quasi-peak Value										
	960MHz-1GHz	54.0		Quasi-peak Value										
Test setup:	Above 1GHz													
	Below 1GHz													
Test Procedure:	<ol style="list-style-type: none"> The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 													

	<ol style="list-style-type: none">4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test Instruments:	Refer to section 5.11 for details
Test mode:	Refer to section 5.3 for details
Test results:	Passed
Remark:	All of the observed value above 6GHz were the noise floor , which were not recorded

Measurement Data:**Below 1GHz:**

Product Name:	GSM Fixed Wireless Phone	Product Model:	LS931
Test By:	Janet	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Vertical
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq MHz	ReadAntenna Level Factor		Cable Loss Factor		Preamp Level	Limit Line dBm/m	Over Limit dB	Remark
	MHz	dBm	dB/m	dB				
1	40.135	51.64	12.40	1.22	29.90	35.36	40.00	-4.64 QP
2	46.016	51.40	12.26	1.28	29.85	35.09	40.00	-4.91 QP
3	53.318	53.69	11.76	1.32	29.81	36.96	40.00	-3.04 QP
4	60.918	51.28	11.02	1.38	29.77	33.91	40.00	-6.09 QP
5	143.326	42.60	9.31	2.44	29.25	25.10	43.50	-18.40 QP
6	169.599	40.76	9.61	2.66	29.05	23.98	43.50	-19.52 QP

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	GSM Fixed Wireless Phone	Product Model:	LS931
Test By:	Janet	Test mode:	PC mode
Test Frequency:	30 MHz ~ 1 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%




Freq	ReadAntenna		Cable Preamp		Limit Line	Over Limit	Remark
	Freq MHz	Level dBm	Factor dB/m	Loss Factor dB			
1	54.643	43.43	11.62	1.34	29.80	26.59	40.00 -13.41 QP
2	61.562	44.12	10.83	1.38	29.77	26.56	40.00 -13.44 QP
3	128.563	44.78	10.25	2.27	29.34	27.96	43.50 -15.54 QP
4	175.037	40.15	9.81	2.69	29.01	23.64	43.50 -19.86 QP
5	187.753	38.24	10.23	2.78	28.92	22.33	43.50 -21.17 QP
6	942.131	36.02	22.67	4.13	27.75	35.07	46.00 -10.93 QP

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Above 1GHz:

Product Name:	GSM Fixed Wireless Phone		Product Model:	LS931	
Test By:	Janet		Test mode:	PC mode	
Test Frequency:	1 GHz ~ 6 GHz		Polarization:	Vertical	
Test Voltage:	AC 120/60Hz		Environment:	Temp: 24°C Huni: 57%	




Freq	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Line Level	Limit Line	Over Limit	Remark
MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m	dB	
1	3239.420	48.14	28.75	5.47	41.40	40.96	74.00	-33.04 Peak
2	3239.420	39.48	28.75	5.47	41.40	32.30	54.00	-21.70 Average
3	4448.361	48.41	31.01	6.75	42.00	44.17	74.00	-29.83 Peak
4	4448.361	39.67	31.01	6.75	42.00	35.43	54.00	-18.57 Average
5	5716.644	49.37	32.80	7.64	41.92	47.89	74.00	-26.11 Peak
6	5716.644	40.56	32.80	7.64	41.92	39.08	54.00	-14.92 Average

Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
- The emission levels of other frequencies are very lower than the limit and not show in test report.

Product Name:	GSM Fixed Wireless Phone	Product Model:	LS931
Test By:	Janet	Test mode:	PC mode
Test Frequency:	1 GHz ~ 6 GHz	Polarization:	Horizontal
Test Voltage:	AC 120/60Hz	Environment:	Temp: 24°C Huni: 57%



Freq	Read	Antenna	Cable	Preamp	Limit	Over	Over	
	Freq	Level	Factor	Loss				Remark
	MHz	dBm	dB/m	dB	dB	dBm/m	dBm/m	dB
1	3381.760	48.95	28.83	5.61	41.35	42.04	74.00	-31.96 Peak
2	3381.760	39.71	28.83	5.61	41.35	32.80	54.00	-21.20 Average
3	4694.016	49.37	31.42	6.85	41.99	45.65	74.00	-28.35 Peak
4	4694.016	40.56	31.42	6.85	41.99	36.84	54.00	-17.16 Average
5	5914.609	48.76	33.15	7.91	42.04	47.78	74.00	-26.22 Peak
6	5914.609	39.63	33.15	7.91	42.04	38.65	54.00	-15.35 Average

Remark:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor.
2. The emission levels of other frequencies are very lower than the limit and not show in test report.